Menpo Documentation

Release 0.5.1+0.g0888b60.dirty

Joan Alabort-i-Medina, Epameinondas Antonakos, James Booth,

July 16, 2015

Contents

1 User Guide **3**
1.1 Quick Start . . . 3
1.2 Introduction . . . 4
1.3 Menpo's Data Types . . . 4
1.4 Working with Images and PointClouds . . . 6
1.5 Vectorizing Objects . . . 7
1.6 Visualizing Objects . . . 9
1.7 Changelog . . . 10

2 The Menpo API **19**
2.1 `menpo.base` . . . 19
2.2 `menpo.io` . . . 21
2.3 `menpo.image` . . . 27
2.4 `menpo.feature` . . . 73
2.5 `menpo.landmark` . . . 79
2.6 `menpo.math` . . . 94
2.7 `menpo.model` . . . 98
2.8 `menpo.shape` . . . 117
2.9 `menpo.transform` . . . 207
2.10 `menpo.visualize` . . . 270

Welcome to the Menpo documentation!

Menpo is a Python package designed to make manipulating annotated data more simple. In particular, sparse locations on either images or meshes, referred to as **landmarks** within Menpo, are tightly coupled with their reference objects. For areas such as Computer Vision that involve learning models based on prior knowledge of object location (such as object detection and landmark localisation), Menpo is a very powerful toolkit.

A short example is often more illustrative than a verbose explanation. Let's assume that you want to load a set of images that have been annotated with bounding boxes, and that these bounding box locations live in text files next to the images. Here's how we would load the images and extract the areas within the bounding boxes using Menpo:

```
import menpo.io as mio

images = []
for image in mio.import_images('./images_folder'):
    image.crop_to_landmarks_inplace()
    images.append(image)
```

Where `import_images` yields a generator to keep memory usage low.

Although the above is a very simple example, we believe that being able to easily manipulate and couple landmarks with images *and* meshes, is an important problem for building powerful models in areas such as facial point localisation.

To get started, check out the User Guide for instructions on installation and some of the core concepts within Menpo.

CHAPTER 1

User Guide

The User Guide is designed to give you an overview of the key concepts within Menpo. In particular, we want to try and explain some of the design decisions that we made and demonstrate why we think they are powerful concepts for exploring visual data.

1.1 Quick Start

Here we give a very quick rundown of the basic links and information sources for the project.

1.1.1 Basic Installation

Menpo should be installable via pip on all major platforms:

```
$ pip install menpo
```

However, in the menpo team, we **strongly** advocate the usage of conda for scientific Python, as it makes installation of compiled binaries much more simple. In particular, if you wish to use any of the related Menpo projects such as *menpofit*, *menpo3d* or *menpodetect*, you will not be able to easily do so without using conda.

```
$ conda install -c menpo menpo
```

To install using conda, please see the thorough instructions for each platform on the Menpo website.

1.1.2 API Documentation

Visit API Documentation

Menpo is extensively documented on a per-method/class level and much of this documentation is reflected in the API Documentation. If any functions or classes are missing, please bring it to the attention of the developers on Github.

1.1.3 Notebooks

Explore the Menpo Notebooks

For a more thorough set of examples, we provide a set of IPython notebooks that demonstrate common use cases of Menpo. This concentrates on an overview of the functionality of the major classes and ideas behind Menpo.

1.1.4 User Group and Issues

If you wish to get in contact with the Menpo developers, you can do so via various channels. If you have found a bug, or if any part of Menpo behaves in a way you do not expect, please raise an issue on Github.

If you want to ask a theoretical question, or are having problems installing or setting up Menpo, please visit the user group.

1.2 Introduction

This user guide is a general introduction to Menpo, aiming to provide a bird's eye of Menpo's design. After reading this guide you should be able to go explore Menpo's extensive Notebooks and not be too suprised by what you see.

1.2.1 Core Interfaces

Menpo is an object oriented framework built around a set of core abstract interfaces, each one governing a single facet of Menpo's design. Menpo's key interfaces are:

- `Shape` - spatial data containers
- *`Vectorizable`* - efficient bi-directional conversion of types to a vector representation
- *`Targetable`* - objects that generate some spatial data
- *`Transform`* - flexible spatial transformations
- *`Landmarkable`* - objects that can be annotated with spatial labelled landmarks

1.2.2 Data containers

Most numerical data in Menpo is passed around in one of our core data containers. The features of each of the data containers is explained in great detail in the notebooks - here we just list them to give you a feel for what to expect:

- *`Image`* - n-dimensional image with k-channels of data
- *`MaskedImage`* - As *`Image`*, but with a boolean mask
- *`BooleanImage`* - As boolean image that is used for masking images.
- *`PointCloud`* - n-dimensional ordered point collection
- *`PointUndirectedGraph`* - n-dimensional ordered point collection with undirected connectivity
- *`PointDirectedGraph`* - n-dimensional ordered point collection with directed connectivity
- *`TriMesh`* - As *`PointCloud`*, but with a triangulation

1.3 Menpo's Data Types

Menpo is a high level software package. It is not a replacement for scikit-image, scikit-learn, or opencv - it ties all these types of packages together in to a unified framework for building and fitting deformable models. As a result, most of our algorithms take as input a higher level representation of data than simple numpy arrays.

1.3.1 Why have data types - what's wrong with numpy arrays?

Menpo's data types are thin wrappers around numpy arrays. They give semantic meaning to the underlying array through providing clearly named and consistent properties. As an example let's take a look at `PointCloud`, Menpo's workhorse for spatial data. Construction requires a numpy array:

```
x = np.random.rand(3, 2)
pc = PointCloud(x)
```

It's natural to ask the question:

> *Is this a collection of three 2D points, or two 3D points?*

In Menpo, you never do this - just look at the properties on the pointcloud:

```
pc.n_points  # 3
pc.n_dims    # 2
```

If we take a look at the properties we can see they are trivial:

```
@property
def n_points(self):
    return self.points.shape[0]

@property
def n_dims(self):
    return self.points.shape[1]
```

Using these properties makes code much more readable in algorithms accepting Menpo's types. Let's imagine a routine that does some operation on an image and a related point cloud. If it accepted numpy arrays, we might see something like this on the top line:

```
def foo_arrays(x, img):
    # preallocate the result
    y = np.zeros(x.shape[1],
                 x.shape[2],
                 img.shape[-1])
    ...
```

On first glance it is not at all apparent what `y`'s shape is semantically. Now let's take a look at the equivalent code using Menpo's types:

```
def foo_menpo(pc, img):
    # preallocate the result
    y = np.zeros(pc.n_dims,
                 pc.n_points,
                 img.n_channels)
    ...
```

This time it's immediately apparent what `y`'s shape is. Although this is a somewhat contrived example, you will find this pattern applied consistently across Menpo, and it aids greatly in keeping the code readable.

1.3.2 Key points

1. **Containers store the underlying numpy array in an easy to access attribute.** For the `PointCloud` family see the `.points` attribute. On `Image` and subclasses, the actual data array is stored at `.pixels`.

2. **Importing assets though *menpo.io* will result in our data containers, not numpy arrays**. This means in a lot of situations you never need to remember the Menpo conventions for ordering of array data - just ask for an image and you will get an `Image` object.

3. **All containers copy data by default**. Look for the `copy=False` keyword argument if you want to avoid copying a large numpy array for performance.

4. **Containers perform sanity checks**. This helps catch obvious bugs like misshaping an array. You can sometimes suppress them for extra performance with the `skip_checks=True` keyword argument.

1.4 Working with Images and PointClouds

Menpo takes an opinionated stance on certain issues - one of which is establishing sensible rules for how to work with spatial data and image data in the same framework.

Let's start with a quiz - which of the following is correct?



?	x	y
a	30	50
b	50	30
c	50	160
d	160	50

Most would answer **b** - images are indexed from the top left, with `x` going across and `y` going down.

Now another question - how do I access that pixel in the pixels array?

```
a: lenna[30, 50]
b: lenna[50, 30]
```

The correct answer is **b** - pixels get stored in a *y, x* order so we have to flip the points to access the array.

As Menpo blends together use of PointClouds and Images frequently this can cause a lot of confusion. You might create a *`Translation`* of `5` in the `y` direction as the following:

```
t = menpo.transform.Translation([0, 5])
```

And then expect to use it to warp an image:

```
img.warp_to(reference_shape, t)
```

and then some spatial data related to the image:

```
t.apply(some_data)
```

Unfortunately the meaning of `y` in these two domains is different - some code would have to flip the order of applying the translation of the transform to an image, a potential cause of confusion.

The *worst* part about this is that once we go to voxel data (which `Image` largely supports, and will fully support in the future), a z-axis is added.

There is one important caveat, unfortunately. The **first axis of an image represents the channels**. Unlike in other software, such as Matlab, which follows the fortran convention of being column major, Python and other C-like languages generally conform to a row major order. Practically this means that if you want to iterate over each channel of an image, you need the memory layout to reflect this. This means you want the pixel data of each channel to be contiguous in memory. **For row major memory, this implies that the first axis should represent an iteration over the channel data.**

Now, as was mentioned, we want to drop all the swapping business. Therefore, forgiving that the **first axis indexes the channel data**, the following axes always match the spatial data. For example, The zeroth axis of the spatial data once more corresponds with the first axis (the first axis is *after the zeroth axis representing the channel data*) of the image data. Trying to keep track of these rules muddies an otherwise very simple concept.

1.4.1 Menpo's approach

Menpo's solution to this problem is simple - **drop the insistence of calling axes x, y, and z**. Skipping the channel data, which represents the zeroth axis, the first axis of the pixel data is simply that - the first axis. It corresponds exactly with the zeroth axis on the point cloud. If you have an image with annotations provided the zeroth axis of the *PointCloud* representing the annotations will correspond with the first axis of the image. This rule makes working with images and spatial data simple - short you should never have to think about flipping axes in Menpo.

It's natural to be concerned at this point that establishing such rules must make it really difficult ingest data which follows different conventions. This is incorrect - one of the biggest strengths of the *menpo.io* module is that each asset importer normalizes the format of the data to format Menpo's rules.

1.4.2 Key Points

- **Menpo is n-dimensional**. We try and avoid speaking of `x` and `y`, because there are many different conventions in use.
- **The IO module ensures that different data formats are normalized** upon loading into Menpo. For example, `Image` types are imported as 64-bit floating point numbers normalised between [0, 1], by default.
- **axis 0 of landmarks corresponds to axis 0 of the container it is an annotation of**.
- **The first axis of image types is always the channel data. The remaining axes map exactly to the other spatial axes.** Therefore, the first image axis maps exactly to the zeroth axis of a PointCloud.

1.5 Vectorizing Objects

Computer Vision algorithms are frequently formulated as linear algebra problems in a high dimensional space, where each asset is stripped into a vector. In this high dimensional space we may perform any number of operations, but normally we can't stay in this space for the whole algorithm - we normally have to recast the vector back into it's original domain in order to perform other operations.



Fig. 1.1: **Figure 1:** *Vectorizing allows Menpo to have rich data types whilst simultaneously providing efficient linear algebra routines. Here an image is vectorized, and an arbitrary process* `f()` *is performed on it's vector representation. Afterwards the vector is converted the back into an image. The vector operation is completely general, and could have equally been performed on some spatial data.*

An example of this might be seen with images, where the gradient of the intensity values of an image needs to be taken. This is a complex problem to solve in a vector space representation of the image, but trivial to solve in the image domain.

Menpo bridges the gap by naively supporting bi-directional vectorisation of it's types through the `Vectorizable` interface. Through this, any type can be safely and efficiently converted to a vector form and back again. You'll find the key methods of `Vectorizable` are extensively used in Menpo. They are

- `as_vector` - generate a vector from one of our types.
- `from_vector` - rebuild one of our types from a vector
- `from_vector_inplace` - alter an object inplace to take on the new state

1.5.1 Key points

1. **Each type defines it's own form of vectorization**. Calling `as_vector` on a `Image` returns all of the pixels in a single strip, whilst on a `MaskedImage` only the true pixels are returned. This distinction means that much of Menpo's image algorithms work equally well with masked or unmasked data - it's the `Vectorizable` interface that abstracts away the difference between the two.

2. **Lots of things are vectorizable, not just images.** Pointclouds and lots of transforms are too.

3. **The length of the resulting vector of a type can be found by querying the ''n_parameters'' property.**

4. **The vectorized form of an object does not have to be 'complete'.** `from_vector` and `from_vector_inplace` can use the object they are called on to rebuild a complete state. Think of vectorization more as a `parametrization` of the object, not a complete serialization.

1.6 Visualizing Objects

In Menpo, we take an opinionated stance that data exploration is a key part of working with visual data. Therefore, we tried to make the mental overhead of visualizing objects as low as possible. Therefore, we made visualization a key concept directly on our data containers, rather than requiring extra imports in order to view your data.

We also took a strong step towards simple visualization of data collections by integrating some of our core types such as `Image` with visualization widgets for the IPython notebook.

1.6.1 Visualizing 2D Images

Without further ado, a quick example of viewing a 2D image:

```
%matplotlib inline  # This is only needed if viewing in an IPython notebook
import menpo.io as mio

bb = mio.import_builtin_asset.breakingbad_jpg()
bb.view()
```

Viewing the image landmarks:

```
%matplotlib inline  # This is only needed if viewing in an IPython notebook
import menpo.io as mio

bb = mio.import_builtin_asset.breakingbad_jpg()
bb.view_landmarks()
```

Viewing the image with a native IPython widget:

```
%matplotlib inline  # This is only needed if viewing in an IPython notebook
import menpo.io as mio

bb = mio.import_builtin_asset.breakingbad_jpg()
bb.view_widget()
```

1.6.2 Visualizing A List Of 2D Images

Visualizing lists of images is also incredibly simple if you are using the IPython notebook:

```
%matplotlib inline
import menpo.io as mio
from menpo.visualize import visualize_images

# import_images is a generator, so we must exhaust the generator before
# we can visualize the list. This is because the widget allows you to
# jump arbitrarily around the list, which cannot be done with generators.
images = list(mio.import_images('./path/to/images/*.jpg'))
visualize_images(images)
```

1.6.3 Visualizing A 2D PointCloud

Visualizing `PointCloud` objects and subclasses is a very familiar experience:

```
%matplotlib inline
from menpo.shape import PointCloud
import numpy as np

pcloud = PointCloud(np.array([[0, 0], [1, 0], [1, 1], [0, 1]]))
pcloud.view()
```

1.6.4 Visualizing In 3D

Menpo natively supports 3D objects, such as triangulated meshes, as our base classes are n-dimensional. However, as viewing in 3D is a much more complicated experience, we have segregated the 3D viewing package into one of our sub-packages: Menpo3D.

If you try to view a 3D `PointCloud` without having Menpo3D installed, you will receive an exception asking you to install it.

Menpo3D also comes with many other complicated pieces of functionality for 3D meshes such as a rasterizer. We recommend you look at Menpo3D if you want to use Menpo for 3D mesh manipulation.

1.7 Changelog

1.7.1 0.5.0 (2015/06/25)

This release of Menpo makes a number of very important **BREAKING** changes to the format of Menpo's core data types. Most importantly is #524 which swaps the position of the channels on an image from the last axis to the first. This is to maintain row-major ordering and make iterating over the pixels of a channel efficient. This made a huge

improvement in speed in other packages such as MenpoFit. It also makes common operations such as iterating over the pixels in an image much simpler:

```
for channels in image.pixels:
    print(channels.shape)  # This will be a (height x width) ndarray
```

Other important changes include:

- Updating all widgets to work with IPython 3
- Incremental PCA was added.
- non-inplace cropping methods
- Dense SIFT features provided by vlfeat
- The implementation of graphs was changed to use sparse matrices by default. **This may cause breaking changes.**
- Many other improvements detailed in the pull requests below!

If you have serialized data using Menpo, you will likely find you have trouble reimporting it. If this is the case, please visit the user group for advice.

Github Pull Requests

- #598 Visualize sum of channels in widgets (@nontas, @patricksnape)
- #597 test new dev tag behavior on condaci (@jabooth)
- #591 Scale around centre (@patricksnape)
- #596 Update to versioneer v0.15 (@jabooth, @patricksnape)
- #495 SIFT features (@nontas, @patricksnape, @jabooth, @jalabort)
- #595 Update mean_pointcloud (@patricksnape, @jalabort)
- #541 Add triangulation labels for ibug_face_(66/51/49) (@jalabort)
- #590 Fix centre and diagonal being properties on Images (@patricksnape)
- #592 Refactor out bounding_box method (@patricksnape)
- #566 TriMesh utilities (@jabooth)
- #593 Minor bugfix on AnimationOptionsWidget (@nontas)
- #587 promote non-inplace crop methods, crop performance improvements (@jabooth, @patricksnape)
- #586 fix as_matrix where the iterator finished early (@jabooth)
- #574 Widgets for IPython3 (@nontas, @patricksnape, @jabooth)
- #588 test condaci 0.2.1, less noisy slack notifications (@jabooth)
- #568 rescale_pixels() for rescaling the range of pixels (@jabooth)
- #585 Hotfix: suffix change led to double path resolution. (@patricksnape)
- #581 Fix the landmark importer in case the landmark file has a '.' in its filename. (@grigorisg9gr)
- #584 new print_progress visualization function (@jabooth)
- #580 export_pickle now ensures pathlib.Path save as PurePath (@jabooth)
- #582 New readers for Middlebury FLO and FRGC ABS files (@patricksnape)

- #579 Fix the image importer in case of upper case letters in the suffix (@grigorisg9gr)
- #575 Allowing expanding user paths in exporting pickle (@patricksnape)
- #577 Change to using run_test.py (@patricksnape)
- #570 Zoom (@jabooth, @patricksnape)
- #569 Add new point_in_pointcloud kwarg to constrain (@patricksnape)
- #563 TPS Updates (@patricksnape)
- #567 Optional cmaps (@jalabort)
- #559 Graphs with isolated vertices (@nontas)
- #564 Bugfix: PCAModel print (@nontas)
- #565 fixed minor typo in introduction.rst (@evanjbowling)
- #562 IPython3 widgets (@patricksnape, @jalabort)
- #558 Channel roll (@patricksnape)
- #524 BREAKING CHANGE: Channels flip (@patricksnape, @jabooth, @jalabort)
- #512 WIP: remove_all_landmarks convienience method, quick lm filter (@jabooth)
- #554 Bugfix:visualize_images (@nontas)
- #553 Transform docs fixes (@nontas)
- #533 LandmarkGroup.init_with_all_label, init_* convenience constructors (@jabooth, @patricksnape)
- #552 Many fixes for Python 3 support (@patricksnape)
- #532 Incremental PCA (@patricksnape, @jabooth, @jalabort)
- #528 New as_matrix and from_matrix methods (@patricksnape)

1.7.2 0.4.4 (2015/03/05)

A hotfix release for properly handling nan values in the landmark formats. Also, a few other bug fixes crept in:

- Fix 3D Ljson importing
- Fix trim_components on PCA
- Fix setting None key on the landmark manager
- Making mean_pointcloud faster

Also makes an important change to the build configuration that syncs this version of Menpo to IPython 2.x.

Github Pull Requests

- #560 Assorted fixes (@patricksnape)
- #557 Ljson nan fix (@patricksnape)

1.7.3 0.4.3 (2015/02/19)

Adds the concept of nan values to the landmarker format for labelling missing landmarks.

Github Pull Requests

- #556 [0.4.x] Ljson nan/null fixes (@patricksnape)

1.7.4 0.4.2 (2015/02/19)

A hotfix release for landmark groups that have no connectivity.

Github Pull Requests

- #555 don't try and build a Graph with no connectivity (@jabooth)

1.7.5 0.4.1 (2015/02/07)

A hotfix release to enable compatibility with landmarker.io.

Github Pull Requests

- #551 HOTFIX: remove incorrect tojson() methods (@jabooth)

1.7.6 0.4.0 (2015/02/04)

The 0.4.0 release (pending any currently unknown bugs), represents a very significant overhaul of Menpo from v0.3.0. In particular, Menpo has been broken into four distinct packages: Menpo, MenpoFit, Menpo3D and MenpoDetect.

Visualization has had major improvements for 2D viewing, in particular through the use of IPython widgets and explicit options on the viewing methods for common tasks (like changing the landmark marker color). This final release is a much smaller set of changes over the alpha releases, so please check the full changelog for the alphas to see all changes from v0.3.0 to v0.4.0.

Summary of changes since v0.4.0a2:

- Lots of documentation rendering fixes and style fixes including this changelog.
- Move the LJSON format to V2. V1 is now being deprecated over the next version.
- More visualization customization fixes including multiple marker colors for landmark groups.

Github Pull Requests

- #546 IO doc fixes (@jabooth)
- #545 Different marker colour per label (@nontas)
- #543 Bug fix for importing an image, case of a dot in image name. (@grigorisg9gr)
- #544 Move docs to Sphinx 1.3b2 (@patricksnape)
- #536 Docs fixes (@patricksnape)
- #530 Visualization and Widgets upgrade (@patricksnape, @nontas)
- #540 LJSON v2 (@jabooth)
- #537 fix BU3DFE connectivity, pretty JSON files (@jabooth)

- #529 BU3D-FE labeller added (@jabooth)
- #527 fixes paths for pickle importing (@jabooth)
- #525 Fix .rst doc files, auto-generation script (@jabooth)

1.7.7 v0.4.0a2 (2014/12/03)

Alpha 2 moves towards extending the graphing API so that visualization is more dependable.

Summary:

- Add graph classes, `PointUndirectedGraph`, `PointDirectedGraph`, `PointTree`. This makes visualization of landmarks much nicer looking.
- Better support of pickling menpo objects
- Add a bounding box method to `PointCloud` for calculating the correctly oriented bounding box of point clouds.
- Allow PCA to operate in place for large data matrices.

Github Pull Requests

- #522 Add bounding box method to pointclouds (@patricksnape)
- #523 HOTFIX: fix export_pickle bug, add path support (@jabooth)
- #521 menpo.io add pickle support, move to pathlib (@jabooth)
- #520 Documentation fixes (@patricksnape, @jabooth)
- #518 PCA memory improvements, inplace dot product (@jabooth)
- #519 replace wrapt with functools.wraps - we can pickle (@jabooth)
- #517 (@jabooth)
- #514 Remove the use of triplot (@patricksnape)
- #516 Fix how images are converted to PIL (@patricksnape)
- #515 Show the path in the image widgets (@patricksnape)
- #511 2D Rotation convenience constructor, Image.rotate_ccw_about_centre (@jabooth)
- #510 all menpo io glob operations are now always sorted (@jabooth)
- #508 visualize image on MaskedImage reports Mask proportion (@jabooth)
- #509 path is now preserved on image warping (@jabooth)
- #507 fix rounding issue in n_components (@jabooth)
- #506 is_tree update in Graph (@nontas)
- #505 (@nontas)
- #504 explicitly have kwarg in IO for landmark extensions (@jabooth)
- #503 Update the README (@patricksnape)

1.7.8 v0.4.0a1 (2014/10/31)

This first alpha release makes a number of large, breaking changes to Menpo from v0.3.0. The biggest change is that Menpo3D and MenpoFit were created and thus all AAM and 3D visualization/rasterization code has been moved out of the main Menpo repository. This is working towards Menpo being pip installable.

Summary:

- Fixes memory leak whereby weak references were being kept between landmarks and their host objects. The Landmark manager now no longer keeps references to its host object. This also helps with serialization.
- Use pathlib instead of strings for paths in the `io` module.
- Importing of builtin assets from a simple function
- Improve support for image importing (including ability to import without normalising)
- Add fast methods for image warping, `warp_to_mask` and `warp_to_shape` instead of `warp_to`
- Allow masking of triangle meshes
- Add IPython visualization widgets for our core types
- All expensive properties (properties that would be worth caching in a variable and are not merely a lookup) are changed to methods.

Github Pull Requests

- #502 Fixes pseudoinverse for Alignment Transforms (@jalabort, @patricksnape)
- #501 Remove menpofit widgets (@nontas)
- #500 Shapes widget (@nontas)
- #499 spin out AAM, CLM, SDM, ATM and related code to menpofit (@jabooth)
- #498 Minimum spanning tree bug fix (@nontas)
- #492 Some fixes for PIL image importing (@patricksnape)
- #494 Widgets bug fix and Active Template Model widget (@nontas)
- #491 Widgets fixes (@nontas)
- #489 remove _view, fix up color_list -> colour_list (@jabooth)
- #486 Image visualisation improvements (@patricksnape)
- #488 Move expensive image properties to methods (@jabooth)
- #487 Change expensive PCA properties to methods (@jabooth)
- #485 MeanInstanceLinearModel.mean is now a method (@jabooth)
- #452 Advanced widgets (@patricksnape, @nontas)
- #481 Remove 3D (@patricksnape)
- #480 Graphs functionality (@nontas)
- #479 Extract patches on image (@patricksnape)
- #469 Active Template Models (@nontas)
- #478 Fix residuals for AAMs (@patricksnape, @jabooth)
- #474 remove HDF5able making room for h5it (@jabooth)

- #475 Normalize norm and std of Image object (@nontas)
- #472 Daisy features (@nontas)
- #473 Fix from_mask for Trimesh subclasses (@patricksnape)
- #470 expensive properties should really be methods (@jabooth)
- #467 get a progress bar on top level feature computation (@jabooth)
- #466 Spin out rasterization and related methods to menpo3d (@jabooth)
- #465 'me_norm' error type in tests (@nontas)
- #463 goodbye ioinfo, hello path (@jabooth)
- #464 make mayavi an optional dependency (@jabooth)
- #447 Displacements in fitting result (@nontas)
- #451 AppVeyor Windows continuous builds from condaci (@jabooth)
- #445 Serialize fit results (@patricksnape)
- #444 remove pyramid_on_features from Menpo (@jabooth)
- #443 create_pyramid now applies features even if pyramid_on_features=False, SDM uses it too (@jabooth)
- #369 warp_to_mask, warp_to_shape, fast resizing of images (@nontas, @patricksnape, @jabooth)
- #442 add rescale_to_diagonal, diagonal property to Image (@jabooth)
- #441 adds constrain_to_landmarks on BooleanImage (@jabooth)
- #440 pathlib.Path can no be used in menpo.io (@jabooth)
- #439 Labelling fixes (@jabooth, @patricksnape)
- #438 extract_channels (@jabooth)
- #437 GLRasterizer becomes HDF5able (@jabooth)
- #435 import_builtin_asset.ASSET_NAME (@jabooth)
- #434 check_regression_features unified with check_features, classmethods removed from SDM (@jabooth)
- #433 tidy classifiers (@jabooth)
- #432 aam.fitter, clm.fitter, sdm.trainer packages (@jabooth)
- #431 More fitmultilevel tidying (@jabooth)
- #430 Remove classmethods from DeformableModelBuilder (@jabooth)
- #412 First visualization widgets (@jalabort, @nontas)
- #429 Masked image fixes (@patricksnape)
- #426 rename 'feature_type' to 'features throughout Menpo (@jabooth)
- #427 Adds HDF5able serialization support to Menpo (@jabooth)
- #425 Faster cached piecewise affine, Cython varient demoted (@jabooth)
- #424 (@nontas)
- #378 Fitting result fixes (@jabooth, @nontas, @jalabort)
- #423 name now displays on constrained features (@jabooth)
- #421 Travis CI now makes builds, Linux/OS X Python 2.7/3.4 (@jabooth, @patricksnape)

- #400 Features as functions (@nontas, @patricksnape, @jabooth)
- #420 move IOInfo to use pathlib (@jabooth)
- #405 import menpo is now twice as fast (@jabooth)
- #416 waffle.io Badge (@waffle-iron)
- #415 export_mesh with .OBJ exporter (@jabooth, @patricksnape)
- #410 Fix the render_labels logic (@patricksnape)
- #407 Exporters (@patricksnape)
- #406 Fix greyscale PIL images (@patricksnape)
- #404 LandmarkGroup tojson method and PointGraph (@patricksnape)
- #403 Fixes a couple of viewing problems in fitting results (@patricksnape)
- #402 Landmarks fixes (@jabooth, @patricksnape)
- #401 Dogfood landmark_resolver in menpo.io (@jabooth)
- #399 bunch of Python 3 compatibility fixes (@jabooth)
- #398 throughout Menpo. (@jabooth)
- #397 Performance improvements for Similarity family (@jabooth)
- #396 More efficient initialisations of Menpo types (@jabooth)
- #395 remove cyclic target reference from landmarks (@jabooth)
- #393 Groundwork for dense correspondence pipeline (@jabooth)
- #394 weakref to break cyclic references (@jabooth)
- #389 assorted fixes (@jabooth)
- #390 (@jabooth)
- #387 Adds landmark label for tongues (@nontas)
- #386 Adds labels for the ibug eye annotation scheme (@jalabort)
- #382 BUG fixed: block element not reset if norm=0 (@dubzzz)
- #381 Recursive globbing (@jabooth)
- #384 Adds support for odd patch shapes in function extract_local_patches_fast (@jalabort)
- #379 imported textures have ioinfo, docs improvements (@jabooth)

1.7.9 v0.3.0 (2014/05/27)

First public release of Menpo, this release coincided with submission to the ACM Multimedia Open Source Software Competition 2014. This provides the basic scaffolding for Menpo, but it is not advised to use this version over the improvements in 0.4.0.

Github Pull Requests

- #377 Simple fixes (@patricksnape)
- #375 improvements to importing multiple assets (@jabooth)

- #374 Menpo's User guide (@jabooth)

CHAPTER 2

The Menpo API

This section attempts to provide a simple browsing experience for the Menpo documentation. In Menpo, we use legible docstrings, and therefore, all documentation should be easily accessible in any sensible IDE (or IPython) via tab completion. However, this section should make most of the core classes available for viewing online.

2.1 menpo.base

2.1.1 Core

Core interfaces of Menpo.

Copyable

class menpo.base.**Copyable**

Bases: object

Efficient copying of classes containing numpy arrays.

Interface that provides a single method for copying classes very efficiently.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns type(self) – A copy of this object

Vectorizable

class menpo.base.**Vectorizable**

Bases: *Copyable*

Flattening of rich objects to vectors and rebuilding them back.

Interface that provides methods for 'flattening' an object into a vector, and restoring from the same vectorized form. Useful for statistical analysis of objects, which commonly requires the data to be provided as a single vector.

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returnsvector (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other `Copyable` objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns`type(self)` – A copy of this object

from_vector(*vector*)

Build a new instance of the object from it's vectorized state.

`self` is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is which is a `deepcopy` of the object followed by a call to `from_vector_inplace()`. This method can be overridden for a performance benefit if desired.

Parametersvector (`(n_parameters,)` *ndarray*) – Flattened representation of the object.

Returnsobject (`type(self)`) – An new instance of this class.

from_vector_inplace(*vector*)

Update the state of this object from a vector form.

Parametersvector (`(n_parameters,)` *ndarray*) – Flattened representation of this object

has_nan_values()

Tests if the vectorized form of the object contains `nan` values or not. This is particularly useful for objects with unknown values that have been mapped to `nan` values.

Returnshas_nan_values (*bool*) – If the vectorized object contains `nan` values.

n_parameters

The length of the vector that this object produces.

Type*int*

Targetable

class `menpo.base.`**Targetable**

Bases: `Copyable`

Interface for objects that can produce a target `PointCloud`.

This could for instance be the result of an alignment or a generation of a `PointCloud` instance from a shape model.

Implementations must define sensible behavior for:

- what a target is: see `target`
- how to set a target: see `set_target()`
- how to update the object after a target is set: see `_sync_state_from_target()`
- how to produce a new target after the changes: see `_new_target_from_state()`

Note that `_sync_target_from_state()` needs to be triggered as appropriate by subclasses e.g. when *from_vector_inplace* is called. This will in turn trigger `_new_target_from_state()`, which each subclass must implement.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns `type(self)` – A copy of this object

set_target(*new_target*)

Update this object so that it attempts to recreate the `new_target`.

Parameters **new_target** (*PointCloud*) – The new target that this object should try and regenerate.

n_dims

The number of dimensions of the *target*.

Type *int*

n_points

The number of points on the *target*.

Type *int*

target

The current *PointCloud* that this object produces.

Type *PointCloud*

2.1.2 Convenience

menpo_src_dir_path

menpo.base.**menpo_src_dir_path**()

The path to the top of the menpo Python package.

Useful for locating where the data folder is stored.

Returns **path** (`pathlib.Path`) – The full path to the top of the Menpo package

2.2 menpo.io

2.2.1 Input

import_image

menpo.io.**import_image**(*filepath*, *landmark_resolver=<function same_name>*, *normalise=True*)

Single image (and associated landmarks) importer.

If an image file is found at *filepath*, returns an *Image* or subclass representing it. By default, landmark files sharing the same filename stem will be imported and attached with a group name based on the extension of the

landmark file, although this behavior can be customised (see *landmark_resolver*). If the image defines a mask, this mask will be imported.

Parameters

- **filepath** (*pathlib.Path* or *str*) – A relative or absolute filepath to an image file.
- **landmark_resolver** (*function*, optional) – This function will be used to find landmarks for the image. The function should take one argument (the image itself) and return a dictionary of the form `{'group_name': 'landmark_filepath'}` Default finds landmarks with the same name as the image file.
- **normalise** (*bool*, optional) – If `True`, normalise the image pixels between 0 and 1 and convert to floating point. If false, the native datatype of the image will be maintained (commonly *uint8*). Note that in general Menpo assumes `Image` instances contain floating point data - if you disable this flag you will have to manually convert the images you import to floating point before doing most Menpo operations. This however can be useful to save on memory usage if you only wish to view or crop images.

Returnsimages (`Image` or list of) – An instantiated `Image` or subclass thereof or a list of images.

import_images

`menpo.io.`**`import_images`**(*pattern*, *max_images=None*, *landmark_resolver=<function same_name>*, *normalise=True*, *verbose=False*)

Multiple image (and associated landmarks) importer.

For each image found yields an `Image` or subclass representing it. By default, landmark files sharing the same filename stem will be imported and attached with a group name based on the extension of the landmark file, although this behavior can be customised (see *landmark_resolver*). If the image defines a mask, this mask will be imported.

Note that this is a generator function. This allows for pre-processing of data to take place as data is imported (e.g. cropping images to landmarks as they are imported for memory efficiency).

Parameters

- **pattern** (*str*) – A glob path pattern to search for images. Every image found to match the glob will be imported one by one. See `image_paths` for more details of what images will be found.
- **max_images** (positive *int*, optional) – If not `None`, only import the first `max_images` found. Else, import all.
- **landmark_resolver** (*function*, optional) – This function will be used to find landmarks for the image. The function should take one argument (the image itself) and return a dictionary of the form `{'group_name': 'landmark_filepath'}` Default finds landmarks with the same name as the image file.
- **normalise** (*bool*, optional) – If `True`, normalise the image pixels between 0 and 1 and convert to floating point. If false, the native datatype of the image will be maintained (commonly *uint8*). Note that in general Menpo assumes `Image` instances contain floating point data - if you disable this flag you will have to manually convert the images you import to floating point before doing most Menpo operations. This however can be useful to save on memory usage if you only wish to view or crop images.
- **verbose** (*bool*, optional) – If `True` progress of the importing will be dynamically reported with a progress bar.

Returnsgenerator (*generator* yielding `Image` or list of) – Generator yielding `Image` instances found to match the glob pattern provided.

Raises`ValueError` – If no images are found at the provided glob.

Examples

Import images at 20% scale from a huge collection:

```
>>> images = []
>>> for img in menpo.io.import_images('./massive_image_db/*'):
>>>     # rescale to a sensible size as we go
>>>     images.append(img.rescale(0.2))
```

import_landmark_file

`menpo.io.`**`import_landmark_file`**(*filepath*, *asset=None*)

Single landmark group importer.

If a landmark file is found at `filepath`, returns a `LandmarkGroup` representing it.

Parameters`filepath` (*pathlib.Path* or *str*) – A relative or absolute filepath to an landmark file.

Returnslandmark_group (`LandmarkGroup`) – The `LandmarkGroup` that the file format represents.

import_landmark_files

`menpo.io.`**`import_landmark_files`**(*pattern*, *max_landmarks=None*, *verbose=False*)

Multiple landmark file import generator.

Note that this is a generator function.

Parameters

- **`pattern`** (*str*) – A glob path pattern to search for landmark files. Every landmark file found to match the glob will be imported one by one. See `landmark_file_paths` for more details of what landmark files will be found.
- **`max_landmark_files`** (positive *int*, optional) – If not `None`, only import the first `max_landmark_files` found. Else, import all.
- **`verbose`** (*bool*, optional) – If `True` progress of the importing will be dynamically reported.

Returnsgenerator (*generator* yielding `LandmarkGroup`) – Generator yielding `LandmarkGroup` instances found to match the glob pattern provided.

Raises`ValueError` – If no landmarks are found at the provided glob.

import_pickle

`menpo.io.`**`import_pickle`**(*filepath*)

Import a pickle file of arbitrary Python objects.

Menpo unambiguously uses `.pkl` as it's choice of extension for Pickle files. Menpo also supports automatic importing and exporting of gzip compressed pickle files - just choose a `filepath` ending `pkl.gz` and gzip

compression will automatically be applied. Compression can massively reduce the filesize of a pickle file at the cost of longer import and export times.

Parameters **filepath** (*pathlib.Path* or *str*) – A relative or absolute filepath to a `.pkl` or `.pkl.gz` file.

Returns **object** (*object*) – Whatever Python objects are present in the Pickle file

import_pickles

`menpo.io.`**`import_pickles`**(*pattern*, *max_pickles=None*, *verbose=False*)

Multiple pickle file import generator.

Note that this is a generator function.

Menpo unambiguously uses `.pkl` as it's choice of extension for pickle files. Menpo also supports automatic importing of gzip compressed pickle files - matching files with extension `pkl.gz` will be automatically ungzipped and imported.

Parameters

- **pattern** (*str*) – The glob path pattern to search for pickles. Every pickle file found to match the glob will be imported one by one.
- **max_pickles** (positive *int*, optional) – If not `None`, only import the first `max_pickles` found. Else, import all.
- **verbose** (*bool*, optional) – If `True` progress of the importing will be dynamically reported.

Returns **generator** (generator yielding *object*) – Generator yielding whatever Python object is present in the pickle files that match the glob pattern provided.

Raises `ValueError` – If no pickles are found at the provided glob.

import_builtin_asset

`menpo.io.`**`import_builtin_asset`**()

This is a dynamically generated method. This method is designed to automatically generate import methods for each data file in the `data` folder. This method it designed to be tab completed, so you do not need to call this method explicitly. It should be treated more like a property that will dynamically generate functions that will import the shipped data. For example:

```
>>> import menpo
>>> bb_image = menpo.io.import_builtin_asset.breakingbad_jpg()
```

2.2.2 Output

export_image

`menpo.io.`**`export_image`**(*image*, *fp*, *extension=None*, *overwrite=False*)

Exports a given image. The `fp` argument can be either a *str* or any Python type that acts like a file. If a file is provided, the `extension` kwarg **must** be provided. If no `extension` is provided and a *str* filepath is provided, then the export type is calculated based on the filepath extension.

Due to the mix of string and file types, an explicit overwrite argument is used which is `False` by default.

Parameters

- **image** (*Image*) – The image to export.
- **fp** (*str* or *file*-like object) – The string path or file-like object to save the object at/into.
- **extension** (*str* or None, optional) – The extension to use, this must match the file path if the file path is a string. Determines the type of exporter that is used.
- **overwrite** (*bool*, optional) – Whether or not to overwrite a file if it already exists.

Raises

- `ValueError` – File already exists and `overwrite` != `True`
- `ValueError` – `fp` is a *str* and the `extension` is not `None` and the two extensions do not match
- `ValueError` – `fp` is a *file*-like object and `extension` is `None`
- `ValueError` – The provided extension does not match to an existing exporter type (the output type is not supported).

export_landmark_file

`menpo.io.`**`export_landmark_file`**(*landmark_group*, *fp*, *extension=None*, *overwrite=False*)

Exports a given landmark group. The `fp` argument can be either or a *str* or any Python type that acts like a file. If a file is provided, the `extension` kwarg **must** be provided. If no `extension` is provided and a *str* filepath is provided, then the export type is calculated based on the filepath extension.

Due to the mix in string and file types, an explicit overwrite argument is used which is `False` by default.

Parameters

- **landmark_group** (*LandmarkGroup*) – The landmark group to export.
- **fp** (*str* or *file*-like object) – The string path or file-like object to save the object at/into.
- **extension** (*str* or None, optional) – The extension to use, this must match the file path if the file path is a string. Determines the type of exporter that is used.
- **overwrite** (*bool*, optional) – Whether or not to overwrite a file if it already exists.

Raises

- `ValueError` – File already exists and `overwrite` != `True`
- `ValueError` – `fp` is a *str* and the `extension` is not `None` and the two extensions do not match
- `ValueError` – `fp` is a *file*-like object and `extension` is `None`
- `ValueError` – The provided extension does not match to an existing exporter type (the output type is not supported).

export_pickle

`menpo.io.`**`export_pickle`**(*obj*, *fp*, *overwrite=False*)

Exports a given collection of Python objects with Pickle.

The `fp` argument can be either a *str* or any Python type that acts like a file. If `fp` is a path, it must have the suffix *.pkl* or *.pkl.gz*. If *.pkl*, the object will be pickled using Pickle protocol 2 without compression. If *.pkl.gz* the object will be pickled using Pickle protocol 2 with gzip compression (at a fixed compression level of 3).

Note that a special exception is made for *pathlib.Path* objects - they are pickled down as a *pathlib.PurePath* so that pickles can be easily moved between different platforms.

Parameters

- **obj** (`object`) – The object to export.
- **fp** (*str* or *file*-like object) – The string path or file-like object to save the object at/into.
- **overwrite** (*bool*, optional) – Whether or not to overwrite a file if it already exists.

Raises

- `ValueError` – File already exists and `overwrite` != `True`
- `ValueError` – `fp` is a *file*-like object and `extension` is `None`
- `ValueError` – The provided extension does not match to an existing exporter type (the output type is not supported).

2.2.3 Path Operations

image_paths

`menpo.io.`**`image_paths`**(*pattern*)

Return image filepaths that Menpo can import that match the glob pattern.

landmark_file_paths

`menpo.io.`**`landmark_file_paths`**(*pattern*)

Return landmark file filepaths that Menpo can import that match the glob pattern.

data_path_to

`menpo.io.`**`data_path_to`**(*asset_filename*)

The path to a builtin asset in the ./data folder on this machine.

Parameters **asset_filename** (*str*) – The filename (with extension) of a file builtin to Menpo. The full set of allowed names is given by `ls_builtin_assets()`

Returns **data_path** (*pathlib.Path*) – The path to a given asset in the ./data folder

Raises `ValueError` – If the asset_filename doesn't exist in the *data* folder.

data_dir_path

`menpo.io.`**`data_dir_path`**()

A path to the Menpo built in ./data folder on this machine.

Returns `pathlib.Path` – The path to the local Menpo ./data folder

ls_builtin_assets

`menpo.io.`**`ls_builtin_assets`**()

List all the builtin asset examples provided in Menpo.

Returns *list of strings* – Filenames of all assets in the data directory shipped with Menpo

2.3 menpo.image

2.3.1 Image Types

Image

class menpo.image.**Image**(*image_data*, *copy=True*)

Bases: *Vectorizable*, Landmarkable, Viewable, LandmarkableViewable

An n-dimensional image.

Images are n-dimensional homogeneous regular arrays of data. Each spatially distinct location in the array is referred to as a *pixel*. At a pixel, k distinct pieces of information can be stored. Each datum at a pixel is refereed to as being in a *channel*. All pixels in the image have the same number of channels, and all channels have the same data-type (*float64*).

Parameters

- **image_data** ((C, M, N ..., Q) *ndarray*) – Array representing the image pixels, with the first axis being channels.
- **copy** (*bool*, optional) – If False, the image_data will not be copied on assignment. Note that this will miss out on additional checks. Further note that we still demand that the array is C-contiguous - if it isn't, a copy will be generated anyway. In general, this should only be used if you know what you are doing.

Raises

- Warning – If copy=False cannot be honoured
- ValueError – If the pixel array is malformed

_view_2d(*figure_id=None*, *new_figure=False*, *channels=None*, *interpolation='bilinear'*, *cmap_name=None*, *alpha=1.0*, *render_axes=False*, *axes_font_name='sans-serif'*, *axes_font_size=10*, *axes_font_style='normal'*, *axes_font_weight='normal'*, *axes_x_limits=None*, *axes_y_limits=None*, *figure_size=(10, 8)*)

View the image using the default image viewer. This method will appear on the Image as view if the Image is 2D.

Returns

- **figure_id** (*object*, optional) – The id of the figure to be used.
- **new_figure** (*bool*, optional) – If True, a new figure is created.
- **channels** (*int* or *list* of *int* or all or None) – If *int* or *list* of *int*, the specified channel(s) will be rendered. If all, all the channels will be rendered in subplots. If None and the image is RGB, it will be rendered in RGB mode. If None and the image is not RGB, it is equivalent to all.
- **interpolation** (*See Below, optional*) – The interpolation used to render the image. For example, if bilinear, the image will be smooth and if nearest, the image will be pixelated. Example options

```
{none, nearest, bilinear, bicubic, spline16, spline36,
hanning, hamming, hermite, kaiser, quadric, catrom, gaussian,
bessel, mitchell, sinc, lanczos}
```

- **cmap_name** (*str*, optional,) – If None, single channel and three channel images default to greyscale and rgb colormaps respectively.

- **alpha** (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.
- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** ({`normal`, `italic`, `oblique`}, optional) – The font style of the axes.
- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **axes_x_limits** ((*float*, *float*) *tuple* or `None`, optional) – The limits of the x axis.
- **axes_y_limits** ((*float*, *float*) *tuple* or `None`, optional) – The limits of the y axis.
- **figure_size** ((*float*, *float*) *tuple* or `None`, optional) – The size of the figure in inches.

Returns **viewer** (*ImageViewer*) – The image viewing object.

_view_landmarks_2d(*channels=None*, *group=None*, *with_labels=None*, *without_labels=None*, *figure_id=None*, *new_figure=False*, *interpolation='bilinear'*, *cmap_name=None*, *alpha=1.0*, *render_lines=True*, *line_colour=None*, *line_style='-'*, *line_width=1*, *render_markers=True*, *marker_style='o'*, *marker_size=20*, *marker_face_colour=None*, *marker_edge_colour=None*, *marker_edge_width=1.0*, *render_numbering=False*, *numbers_horizontal_align='center'*, *numbers_vertical_align='bottom'*, *numbers_font_name='sans-serif'*, *numbers_font_size=10*, *numbers_font_style='normal'*, *numbers_font_weight='normal'*, *numbers_font_colour='k'*, *render_legend=False*, *legend_title=''*, *legend_font_name='sans-serif'*, *legend_font_style='normal'*, *legend_font_size=10*, *legend_font_weight='normal'*, *legend_marker_scale=None*, *legend_location=2*, *legend_bbox_to_anchor=(1.05, 1.0)*, *legend_border_axes_pad=None*, *legend_n_columns=1*, *legend_horizontal_spacing=None*, *legend_vertical_spacing=None*, *legend_border=True*, *legend_border_padding=None*, *legend_shadow=False*, *legend_rounded_corners=False*, *render_axes=False*, *axes_font_name='sans-serif'*, *axes_font_size=10*, *axes_font_style='normal'*, *axes_font_weight='normal'*, *axes_x_limits=None*, *axes_y_limits=None*, *figure_size=(10, 8)*)

Visualize the landmarks. This method will appear on the Image as `view_landmarks` if the Image is 2D.

Parameters

- **channels** (*int* or *list* of *int* or `all` or `None`) – If *int* or *list* of *int*, the specified channel(s) will be rendered. If `all`, all the channels will be rendered in subplots. If `None` and the image is RGB, it will be rendered in RGB mode. If `None` and the image is not RGB, it is equivalent to `all`.
- **group** (*str* or''None'' optional) – The landmark group to be visualized. If `None` and there are more than one landmark groups, an error is raised.
- **with_labels** (`None` or *str* or *list* of *str*, optional) – If not `None`, only show the given label(s). Should **not** be used with the `without_labels` kwarg.
- **without_labels** (`None` or *str* or *list* of *str*, optional) – If not `None`, show all except the given label(s). Should **not** be used with the `with_labels` kwarg.
- **figure_id** (*object*, optional) – The id of the figure to be used.
- **new_figure** (*bool*, optional) – If `True`, a new figure is created.

- **interpolation** (*See Below, optional*) – The interpolation used to render the image. For example, if `bilinear`, the image will be smooth and if `nearest`, the image will be pixelated. Example options

```
{none, nearest, bilinear, bicubic, spline16, spline36, hanning,
hamming, hermite, kaiser, quadric, catrom, gaussian, bessel,
mitchell, sinc, lanczos}
```

- **cmap_name** (*str*, optional,) – If `None`, single channel and three channel images default to greyscale and rgb colormaps respectively.
- **alpha** (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).
- **render_lines** (*bool*, optional) – If `True`, the edges will be rendered.
- **line_colour** (*See Below, optional*) – The colour of the lines. Example options:

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **line_style** (`{-, --, -., :}`, optional) – The style of the lines.
- **line_width** (*float*, optional) – The width of the lines.
- **render_markers** (*bool*, optional) – If `True`, the markers will be rendered.
- **marker_style** (*See Below, optional*) – The style of the markers. Example options

```
{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}
```

- **marker_size** (*int*, optional) – The size of the markers in points^2.
- **marker_face_colour** (*See Below, optional*) – The face (filling) colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_colour** (*See Below, optional*) – The edge colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_width** (*float*, optional) – The width of the markers' edge.
- **render_numbering** (*bool*, optional) – If `True`, the landmarks will be numbered.
- **numbers_horizontal_align** (`{center, right, left}`, optional) – The horizontal alignment of the numbers' texts.
- **numbers_vertical_align** (`{center, top, bottom, baseline}`, optional) – The vertical alignment of the numbers' texts.
- **numbers_font_name** (*See Below, optional*) – The font of the numbers. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **numbers_font_size** (*int*, optional) – The font size of the numbers.
- **numbers_font_style** (`{normal, italic, oblique}`, optional) – The font style of the numbers.
- **numbers_font_weight** (*See Below, optional*) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **numbers_font_colour** (*See Below, optional*) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **render_legend** (*bool*, optional) – If `True`, the legend will be rendered.
- **legend_title** (*str*, optional) – The title of the legend.
- **legend_font_name** (*See below, optional*) – The font of the legend. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **legend_font_style** (`{normal, italic, oblique}`, optional) – The font style of the legend.
- **legend_font_size** (*int*, optional) – The font size of the legend.
- **legend_font_weight** (*See Below, optional*) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **legend_marker_scale** (*float*, optional) – The relative size of the legend markers with respect to the original
- **legend_location** (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

- **legend_bbox_to_anchor** ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.
- **legend_border_axes_pad** (*float*, optional) – The pad between the axes and legend border.
- **legend_n_columns** (*int*, optional) – The number of the legend's columns.
- **legend_horizontal_spacing** (*float*, optional) – The spacing between the columns.
- **legend_vertical_spacing** (*float*, optional) – The vertical space between the legend entries.
- **legend_border** (*bool*, optional) – If `True`, a frame will be drawn around the legend.
- **legend_border_padding** (*float*, optional) – The fractional whitespace inside the legend border.
- **legend_shadow** (*bool*, optional) – If `True`, a shadow will be drawn behind legend.
- **legend_rounded_corners** (*bool*, optional) – If `True`, the frame's corners will be rounded (fancybox).
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.
- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** (`{normal, italic, oblique}`, optional) – The font style of the axes.

- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold,demibold, demi, bold, heavy, extra bold, black}
```

- **axes_x_limits** ((*float*, *float*) *tuple* or `None` optional) – The limits of the x axis.
- **axes_y_limits** ((*float*, *float*) *tuple* or `None` optional) – The limits of the y axis.
- **figure_size** ((*float*, *float*) *tuple* or `None` optional) – The size of the figure in inches.

Raises

- `ValueError` – If both `with_labels` and `without_labels` are passed.
- `ValueError` – If the landmark manager doesn't contain the provided group label.

as_PILImage()

Return a PIL copy of the image. Depending on the image data type, different operations are performed:

dtype	Processing
uint8	No processing, directly converted to PIL
bool	Scale by 255, convert to uint8
float32	Scale by 255, convert to uint8
float64	Scale by 255, convert to uint8
OTHER	Raise ValueError

Image must only have 1 or 3 channels and be 2 dimensional. Non *uint8* images must be in the rage `[0, 1]` to be converted.

Returnspil_image (*PILImage*) – PIL copy of image

Raises

- `ValueError` – If image is not 2D and 1 channel or 3 channels.
- `ValueError` – If pixels data type is not *float32*, *float64*, *bool* or *uint8*
- `ValueError` – If pixels data type is *float32* or *float64* and the pixel range is outside of `[0, 1]`

as_greyscale(*mode='luminosity'*, *channel=None*)

Returns a greyscale version of the image. If the image does *not* represent a 2D RGB image, then the `luminosity` mode will fail.

Parameters

- **mode** (`{average, luminosity, channel}`, optional) –

mode	Greyscale Algorithm
average	Equal average of all channels
luminosity	Calculates the luminance using the CCIR 601 formula:
	$Y' = 0.2989R' + 0.5870G' + 0.1140B'$
channel	A specific channel is chosen as the intensity value.

- **channel** (*int*, optional) – The channel to be taken. Only used if mode is `channel`.

Returnsgreyscale_image (`MaskedImage`) – A copy of this image in greyscale.

as_histogram(*keep_channels=True*, *bins='unique'*)

Histogram binning of the values of this image.

Parameters

- **keep_channels** (*bool*, optional) – If set to `False`, it returns a single histogram for all the channels of the image. If set to `True`, it returns a *list* of histograms, one for each channel.

- **bins** ({unique}, positive *int* or sequence of scalars, optional) – If set equal to 'unique', the bins of the histograms are centred on the unique values of each channel. If set equal to a positive *int*, then this is the number of bins. If set equal to a sequence of scalars, these will be used as bins centres.

Returns

- **hist** (*ndarray* or *list* with n_channels *ndarrays* inside) – The histogram(s). If keep_channels=False, then hist is an *ndarray*. If keep_channels=True, then hist is a *list* with len(hist)=n_channels.
- **bin_edges** (*ndarray* or *list* with *n_channels ndarrays* inside) – An array or a list of arrays corresponding to the above histograms that store the bins' edges.

Raises ValueError – Bins can be either 'unique', positive int or a sequence of scalars.

Examples

Visualizing the histogram when a list of array bin edges is provided:

```
>>> hist, bin_edges = image.as_histogram()
>>> for k in range(len(hist)):
>>>     plt.subplot(1,len(hist),k)
>>>     width = 0.7 * (bin_edges[k][1] - bin_edges[k][0])
>>>     centre = (bin_edges[k][:-1] + bin_edges[k][1:]) / 2
>>>     plt.bar(centre, hist[k], align='center', width=width)
```

as_masked(*mask=None*, *copy=True*)

Return a copy of this image with an attached mask behavior.

A custom mask may be provided, or None. See the *MaskedImage* constructor for details of how the kwargs will be handled.

Parameters

- **mask** ((self.shape) *ndarray* or *BooleanImage*) – A mask to attach to the newly generated masked image.
- **copy** (*bool*, optional) – If False, the produced *MaskedImage* will share pixels with self. Only suggested to be used for performance.

Returns **masked_image** (*MaskedImage*) – An image with the same pixels and landmarks as this one, but with a mask.

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returns **vector** (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

centre()

The geometric centre of the Image - the subpixel that is in the middle.

Useful for aligning shapes and images.

Type (n_dims,) *ndarray*

constrain_landmarks_to_bounds()

Move landmarks that are located outside the image bounds on the bounds.

constrain_points_to_bounds(*points*)

Constrains the points provided to be within the bounds of this image.

Parameters **points** ((d,) *ndarray*) – Points to be snapped to the image boundaries.

Returns **bounded_points** ((d,) *ndarray*) – Points snapped to not stray outside the image edges.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other `Copyable` objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns `type(self)` – A copy of this object

crop(*min_indices*, *max_indices*, *constrain_to_boundary=False*)

Return a cropped copy of this image using the given minimum and maximum indices. Landmarks are correctly adjusted so they maintain their position relative to the newly cropped image.

Parameters

- **min_indices** (`(n_dims,)` *ndarray*) – The minimum index over each dimension.
- **max_indices** (`(n_dims,)` *ndarray*) – The maximum index over each dimension.
- **constrain_to_boundary** (*bool*, optional) – If `True` the crop will be snapped to not go beyond this images boundary. If `False`, an `ImageBoundaryError` will be raised if an attempt is made to go beyond the edge of the image.

Returns **cropped_image** (*type(self)*) – A new instance of self, but cropped.

Raises

- `ValueError` – `min_indices` and `max_indices` both have to be of length `n_dims`. All `max_indices` must be greater than `min_indices`.
- `ImageBoundaryError` – Raised if `constrain_to_boundary=False`, and an attempt is made to crop the image in a way that violates the image bounds.

crop_inplace(**args*, ***kwargs*)

Deprecated: please use `crop()` instead.

crop_to_landmarks(*group=None*, *label=None*, *boundary=0*, *constrain_to_boundary=True*)

Return a copy of this image cropped so that it is bounded around a set of landmarks with an optional `n_pixel` boundary

Parameters

- **group** (*str*, optional) – The key of the landmark set that should be used. If `None` and if there is only one set of landmarks, this set will be used.
- **label** (*str*, optional) – The label of of the landmark manager that you wish to use. If `None` all landmarks in the group are used.
- **boundary** (*int*, optional) – An extra padding to be added all around the landmarks bounds.
- **constrain_to_boundary** (*bool*, optional) – If `True` the crop will be snapped to not go beyond this images boundary. If `False`, an :map'ImageBoundaryError' will be raised if an attempt is made to go beyond the edge of the image.

Returns **image** (`Image`) – A copy of this image cropped to its landmarks.

Raises `ImageBoundaryError` – Raised if `constrain_to_boundary=False`, and an attempt is made to crop the image in a way that violates the image bounds.

crop_to_landmarks_inplace(**args*, ***kwargs*)

Deprecated: please use `crop_to_landmarks()` instead.

crop_to_landmarks_proportion(*boundary_proportion*, *group=None*, *label=None*, *minimum=True*, *constrain_to_boundary=True*)

Crop this image to be bounded around a set of landmarks with a border proportional to the landmark spread or range.

Parameters

- **boundary_proportion** (*float*) – Additional padding to be added all around the landmarks bounds defined as a proportion of the landmarks range. See the

minimum parameter for a definition of how the range is calculated.

- **group** (*str*, optional) – The key of the landmark set that should be used. If `None` and if there is only one set of landmarks, this set will be used.
- **label** (*str*, optional) – The label of of the landmark manager that you wish to use. If `None` all landmarks in the group are used.
- **minimum** (*bool*, optional) – If `True` the specified proportion is relative to the minimum value of the landmarks' per-dimension range; if `False` w.r.t. the maximum value of the landmarks' per-dimension range.
- **constrain_to_boundary** (*bool*, optional) – If `True`, the crop will be snapped to not go beyond this images boundary. If `False`, an `ImageBoundaryError` will be raised if an attempt is made to go beyond the edge of the image.

Returns **image** (`Image`) – This image, cropped to its landmarks with a border proportional to the landmark spread or range.

Raises `ImageBoundaryError` – Raised if `constrain_to_boundary=False`, and an attempt is made to crop the image in a way that violates the image bounds.

crop_to_landmarks_proportion_inplace(**args*, ***kwargs*)

Deprecated: please use `crop_to_landmarks_proportion()` instead.

diagonal()

The diagonal size of this image

Type *float*

extract_channels(*channels*)

A copy of this image with only the specified channels.

Parameters **channels** (*int* or *[int]*) – The channel index or *list* of channel indices to retain.

Returns **image** (*type(self)*) – A copy of this image with only the channels requested.

extract_patches(*patch_centers*, *patch_size=(16, 16)*, *sample_offsets=None*, *as_single_array=False*)

Extract a set of patches from an image. Given a set of patch centers and a patch size, patches are extracted from within the image, centred on the given coordinates. Sample offsets denote a set of offsets to extract from within a patch. This is very useful if you want to extract a dense set of features around a set of landmarks and simply sample the same grid of patches around the landmarks.

If sample offsets are used, to access the offsets for each patch you need to slice the resulting list. So for 2 offsets, the first centers offset patches would be `patches[:2]`.

Currently only 2D images are supported.

Parameters

- **patch_centers** (`PointCloud`) – The centers to extract patches around.
- **patch_size** (*tuple* or *ndarray*, optional) – The size of the patch to extract
- **sample_offsets** (`PointCloud`, optional) – The offsets to sample from within a patch. So (0, 0) is the centre of the patch (no offset) and (1, 0) would be sampling the patch from 1 pixel up the first axis away from the centre.
- **as_single_array** (*bool*, optional) – If `True`, an `(n_center * n_offset, self.shape...)` *ndarray*, thus a single numpy array is returned containing each patch. If `False`, a *list* of `Image` objects is returned representing each patch.

Returns **patches** (*list* or *ndarray*) – Returns the extracted patches. Returns a list if `as_single_array=True` and an *ndarray* if `as_single_array=False`.

Raises `ValueError` – If image is not 2D

extract_patches_around_landmarks(*group=None*, *label=None*, *patch_size=(16, 16)*, *sample_offsets=None*, *as_single_array=False*)

Extract patches around landmarks existing on this image. Provided the group label and optionally the landmark label extract a set of patches.

See *extract_patches* for more information.

Currently only 2D images are supported.

Parameters

- **group** (*str* or `None` optional) – The landmark group to use as patch centres.
- **label** (*str* or `None` optional) – The landmark label within the group to use as centres.
- **patch_size** (*tuple* or *ndarray*, optional) – The size of the patch to extract
- **sample_offsets** (`PointCloud`, optional) – The offsets to sample from within a patch. So (0,0) is the centre of the patch (no offset) and (1, 0) would be sampling the patch from 1 pixel up the first axis away from the centre.
- **as_single_array** (*bool*, optional) – If `True`, an `(n_center * n_offset, self.shape...)` *ndarray*, thus a single numpy array is returned containing each patch. If `False`, a *list* of `Image` objects is returned representing each patch.

Returns **patches** (*list* or *ndarray*) – Returns the extracted patches. Returns a list if `as_single_array=True` and an *ndarray* if `as_single_array=False`.

Raises `ValueError` – If image is not 2D

from_vector(*vector*, *n_channels=None*, *copy=True*)

Takes a flattened vector and returns a new image formed by reshaping the vector to the correct pixels and channels.

The *n_channels* argument is useful for when we want to add an extra channel to an image but maintain the shape. For example, when calculating the gradient.

Note that landmarks are transferred in the process.

Parameters

- **vector** (`(n_parameters,)` *ndarray*) – A flattened vector of all pixels and channels of an image.
- **n_channels** (*int*, optional) – If given, will assume that vector is the same shape as this image, but with a possibly different number of channels.
- **copy** (*bool*, optional) – If `False`, the vector will not be copied in creating the new image.

Returns **image** (`Image`) – New image of same shape as this image and the number of specified channels.

Raises `Warning` – If the `copy=False` flag cannot be honored

from_vector_inplace(*vector*, *copy=True*)

Takes a flattened vector and update this image by reshaping the vector to the correct dimensions.

Parameters

- **vector** (`(n_pixels,)` *bool ndarray*) – A vector vector of all the pixels of a `BooleanImage`.
- **copy** (*bool*, optional) – If `False`, the vector will be set as the pixels. If `True`, a copy of the vector is taken.

Raises `Warning` – If `copy=False` flag cannot be honored

Note: For `BooleanImage` this is rebuilding a boolean image **itself** from boolean values. The mask is in no way interpreted in performing the operation, in contrast to `MaskedImage`, where only the masked region is used in `from_vector_inplace()` and `as_vector()`.

---

gaussian_pyramid(*n_levels=3*, *downscale=2*, *sigma=None*)

Return the gaussian pyramid of this image. The first image of the pyramid will be the original, unmodified, image, and counts as level 1.

Parameters

- **n_levels** (*int*, optional) – Total number of levels in the pyramid, including the original unmodified image

- **downscale** (*float*, optional) – Downscale factor.
- **sigma** (*float*, optional) – Sigma for gaussian filter. Default is `downscale / 3.` which corresponds to a filter mask twice the size of the scale factor that covers more than 99% of the gaussian distribution.

Yieldsimage_pyramid (*generator*) – Generator yielding pyramid layers as `Image` objects.

gradient(***kwargs*)

Returns an `Image` which is the gradient of this one. In the case of multiple channels, it returns the gradient over each axis over each channel as a flat *list*. Take care to note the ordering of the returned gradient (the gradient over each spatial dimension is taken over each channel).

The first axis of the gradient of a 2D, 3-channel image, will have length *6*, the ordering being `I[:, 0, 0] = [R0_y, G0_y, B0_y, R0_x, G0_x, B0_x]`. To be clear, all the `y`-gradients are returned over each channel, then all the `x`-gradients.

Returnsgradient (`Image`) – The gradient over each axis over each channel. Therefore, the gradient of a 2D, single channel image, will have length *2*. The length of a 2D, 3-channel image, will have length *6*.

has_nan_values()

Tests if the vectorized form of the object contains `nan` values or not. This is particularly useful for objects with unknown values that have been mapped to `nan` values.

Returnshas_nan_values (*bool*) – If the vectorized object contains `nan` values.

indices()

Return the indices of all pixels in this image.

Type(`n_dims`, `n_pixels`) ndarray

classmethod init_blank(*shape*, *n_channels=1*, *fill=0*, *dtype=<Mock object>*)

Returns a blank image.

Parameters

- **shape** (*tuple* or *list*) – The shape of the image. Any floating point values are rounded up to the nearest integer.
- **n_channels** (*int*, optional) – The number of channels to create the image with.
- **fill** (*int*, optional) – The value to fill all pixels with.
- **dtype** (*numpy data type, optional*) – The data type of the image.

Returnsblank_image (`Image`) – A new image of the requested size.

normalize_norm_inplace(*mode='all'*, ***kwargs*)

Normalizes this image such that its pixel values have zero mean and its norm equals 1.

Parametersmode (`{all, per_channel}`, optional) – If `all`, the normalization is over all channels. If `per_channel`, each channel individually is mean centred and normalized in variance.

normalize_std_inplace(*mode='all'*, ***kwargs*)

Normalizes this image such that its pixel values have zero mean and unit variance.

Parametersmode (`{all, per_channel}`, optional) – If `all`, the normalization is over all channels. If `per_channel`, each channel individually is mean centred and normalized in variance.

pyramid(*n_levels=3*, *downscale=2*)

Return a rescaled pyramid of this image. The first image of the pyramid will be the original, unmodified, image, and counts as level 1.

Parameters

- **n_levels** (*int*, optional) – Total number of levels in the pyramid, including the original unmodified image
- **downscale** (*float*, optional) – Downscale factor.

Yieldsimage_pyramid (*generator*) – Generator yielding pyramid layers as `Image` objects.

rescale(*scale*, *round='ceil'*, *order=1*)

Return a copy of this image, rescaled by a given factor. Landmarks are rescaled appropriately.

Parameters

- **scale** (*float* or *tuple* of *floats*) – The scale factor. If a tuple, the scale to apply to each dimension. If a single *float*, the scale will be applied uniformly across each dimension.
- **round** (`{ceil, floor, round}`, optional) – Rounding function to be applied to floating point shapes.
- **order** (*int*, optional) – The order of interpolation. The order has to be in the range [0,5]

Order	Interpolation
0	Nearest-neighbor
1	Bi-linear *(default)*
2	Bi-quadratic
3	Bi-cubic
4	Bi-quartic
5	Bi-quintic

Returns **rescaled_image** (`type(self)`) – A copy of this image, rescaled.

Raises `ValueError` – If less scales than dimensions are provided. If any scale is less than or equal to 0.

rescale_landmarks_to_diagonal_range(*diagonal_range*, *group=None*, *label=None*, *round='ceil'*, *order=1*)

Return a copy of this image, rescaled so that the diagonal_range of the bounding box containing its landmarks matches the specified diagonal_range range.

Parameters

- **diagonal_range** (`(n_dims,)` *ndarray*) – The diagonal_range range that we want the landmarks of the returned image to have.
- **group** (*str*, optional) – The key of the landmark set that should be used. If `None` and if there is only one set of landmarks, this set will be used.
- **label** (*str*, optional) – The label of of the landmark manager that you wish to use. If `None` all landmarks in the group are used.
- **round** (`{ceil, floor, round}`, optional) – Rounding function to be applied to floating point shapes.
- **order** (*int*, optional) – The order of interpolation. The order has to be in the range [0,5]

Order	Interpolation
0	Nearest-neighbor
1	Bi-linear *(default)*
2	Bi-quadratic
3	Bi-cubic
4	Bi-quartic
5	Bi-quintic

Returns **rescaled_image** (`type(self)`) – A copy of this image, rescaled.

rescale_pixels(*minimum*, *maximum*, *per_channel=True*)

A copy of this image with pixels linearly rescaled to fit a range.

Note that the only pixels that will considered and rescaled are those that feature in the vectorized form of this image. If you want to use this routine on all the pixels in a `MaskedImage`, consider using *as_unmasked()* prior to this call.

Parameters

- **minimum** (*float*) – The minimal value of the rescaled pixels
- **maximum** (*float*) – The maximal value of the rescaled pixels

- **per_channel** (*boolean*, optional) – If `True`, each channel will be rescaled independently. If `False`, the scaling will be over all channels.

Returnsrescaled_image (`type(self)`) – A copy of this image with pixels linearly rescaled to fit in the range provided.

rescale_to_diagonal(*diagonal*, *round='ceil'*)

Return a copy of this image, rescaled so that the it's diagonal is a new size.

Parameters

- **diagonal** (*int*) – The diagonal size of the new image.
- **round** (`{ceil, floor, round}`, optional) – Rounding function to be applied to floating point shapes.

Returnsrescaled_image (*type(self)*) – A copy of this image, rescaled.

rescale_to_reference_shape(*reference_shape*, *group=None*, *label=None*, *round='ceil'*, *order=1*)

Return a copy of this image, rescaled so that the scale of a particular group of landmarks matches the scale of the passed reference landmarks.

Parameters

- **reference_shape** (`PointCloud`) – The reference shape to which the landmarks scale will be matched against.
- **group** (*str*, optional) – The key of the landmark set that should be used. If `None`, and if there is only one set of landmarks, this set will be used.
- **label** (*str*, optional) – The label of of the landmark manager that you wish to use. If `None` all landmarks in the group are used.
- **round** (`{ceil, floor, round}`, optional) – Rounding function to be applied to floating point shapes.
- **order** (*int*, optional) – The order of interpolation. The order has to be in the range [0,5]

Order	Interpolation
0	Nearest-neighbor
1	Bi-linear *(default)*
2	Bi-quadratic
3	Bi-cubic
4	Bi-quartic
5	Bi-quintic

Returnsrescaled_image (`type(self)`) – A copy of this image, rescaled.

resize(*shape*, *order=1*)

Return a copy of this image, resized to a particular shape. All image information (landmarks, and mask in the case of `MaskedImage`) is resized appropriately.

Parameters

- **shape** (*tuple*) – The new shape to resize to.
- **order** (*int*, optional) – The order of interpolation. The order has to be in the range [0,5]

Order	Interpolation
0	Nearest-neighbor
1	Bi-linear *(default)*
2	Bi-quadratic
3	Bi-cubic
4	Bi-quartic
5	Bi-quintic

Returnsresized_image (`type(self)`) – A copy of this image, resized.

Raises`ValueError` – If the number of dimensions of the new shape does not match the number of dimensions of the image.

rolled_channels()

Returns the pixels matrix, with the channels rolled to the back axis. This may be required for interacting with external code bases that require images to have channels as the last axis, rather than the menpo convention of channels as the first axis.

Returnsrolled_channels (*ndarray*) – Pixels with channels as the back (last) axis.

rotate_ccw_about_centre(*theta*, *degrees=True*, *cval=0.0*)

Return a rotation of this image clockwise about its centre.

Parameters

- **theta** (*float*) – The angle of rotation about the origin.
- **degrees** (*bool*, optional) – If `True`, *theta* is interpreted as a degree. If `False`, `theta` is interpreted as radians.
- **cval** (`float`, optional) – The value to be set outside the rotated image boundaries.

Returnsrotated_image (`type(self)`) – The rotated image.

sample(*points_to_sample*, *order=1*, *mode='constant'*, *cval=0.0*)

Sample this image at the given sub-pixel accurate points. The input PointCloud should have the same number of dimensions as the image e.g. a 2D PointCloud for a 2D multi-channel image. A numpy array will be returned the has the values for every given point across each channel of the image.

Parameters

- **points_to_sample** (*PointCloud*) – Array of points to sample from the image. Should be *(n_points, n_dims)*
- **order** (*int*, optional) – The order of interpolation. The order has to be in the range [0,5]. See warp_to_shape for more information.
- **mode** (`{constant, nearest, reflect, wrap}`, optional) – Points outside the boundaries of the input are filled according to the given mode.
- **cval** (*float*, optional) – Used in conjunction with mode `constant`, the value outside the image boundaries.

Returnssampled_pixels ((*n_points*, *n_channels*) *ndarray*) – The interpolated values taken across every channel of the image.

view_widget(*browser_style='buttons'*, *figure_size=(10, 8)*, *style='coloured'*)

Visualizes the image object using the *visualize_images* widget. Currently only supports the rendering of 2D images.

Parameters

- **browser_style** (`{'buttons','slider'}`, optional) – It defines whether the selector of the images will have the form of plus/minus buttons or a slider.
- **figure_size** ((*int*, *int*), optional) – The initial size of the rendered figure.
- **style** (`{'coloured','minimal'}`, optional) – If `'coloured'`, then the style of the widget will be coloured. If `minimal`, then the style is simple using black and white colours.

warp_to_mask(*template_mask*, *transform*, *warp_landmarks=False*, *order=1*, *mode='constant'*, *cval=0.0*, *batch_size=None*)

Return a copy of this image warped into a different reference space.

Note that warping into a mask is slower than warping into a full image. If you don't need a non-linear mask, consider :meth:`warp_to_shape` instead.

Parameters

- **template_mask** (*BooleanImage*) – Defines the shape of the result, and what pixels should be sampled.
- **transform** (*Transform*) – Transform **from the template space back to this image**. Defines, for each pixel location on the template, which pixel location should be sampled from on this image.
- **warp_landmarks** (*bool*, optional) – If `True`, result will have the same landmark dictionary as `self`, but with each landmark updated to the warped posi-

tion.

- **order** (*int*, optional) – The order of interpolation. The order has to be in the range [0,5]

Order	Interpolation
0	Nearest-neighbor
1	Bi-linear *(default)*
2	Bi-quadratic
3	Bi-cubic
4	Bi-quartic
5	Bi-quintic

- **mode** (`{constant, nearest, reflect, wrap}`, optional) – Points outside the boundaries of the input are filled according to the given mode.
- **cval** (*float*, optional) – Used in conjunction with mode `constant`, the value outside the image boundaries.
- **batch_size** (*int* or `None`, optional) – This should only be considered for large images. Setting this value can cause warping to become much slower, particular for cached warps such as Piecewise Affine. This size indicates how many points in the image should be warped at a time, which keeps memory usage low. If `None`, no batching is used and all points are warped at once.

Returns **warped_image** (`MaskedImage`) – A copy of this image, warped.

warp_to_shape(*template_shape*, *transform*, *warp_landmarks=False*, *order=1*, *mode='constant'*, *cval=0.0*, *batch_size=None*)

Return a copy of this image warped into a different reference space.

Parameters

- **template_shape** (*tuple* or *ndarray*) – Defines the shape of the result, and what pixel indices should be sampled (all of them).
- **transform** (`Transform`) – Transform **from the template_shape space back to this image**. Defines, for each index on template_shape, which pixel location should be sampled from on this image.
- **warp_landmarks** (*bool*, optional) – If `True`, result will have the same landmark dictionary as self, but with each landmark updated to the warped position.
- **order** (*int*, optional) – The order of interpolation. The order has to be in the range [0,5]

Order	Interpolation
0	Nearest-neighbor
1	Bi-linear *(default)*
2	Bi-quadratic
3	Bi-cubic
4	Bi-quartic
5	Bi-quintic

- **mode** (`{constant, nearest, reflect, wrap}`, optional) – Points outside the boundaries of the input are filled according to the given mode.
- **cval** (*float*, optional) – Used in conjunction with mode `constant`, the value outside the image boundaries.
- **batch_size** (*int* or `None`, optional) – This should only be considered for large images. Setting this value can cause warping to become much slower, particular for cached warps such as Piecewise Affine. This size indicates how many points in the image should be warped at a time, which keeps memory usage low. If `None`, no batching is used and all points are warped at once.

Returns **warped_image** (*type(self)*) – A copy of this image, warped.

zoom(*scale*, *cval=0.0*)

Zoom this image about the centre point. `scale` values greater than 1.0 denote zooming **in** to the image

and values less than 1.0 denote zooming **out** of the image. The size of the image will not change, if you wish to scale an image, please see `rescale()`.

Parameters

- **scale** (*float*) – `scale > 1.0` denotes zooming in. Thus the image will appear larger and areas at the edge of the zoom will be 'cropped' out. `scale < 1.0` denotes zooming out. The image will be padded by the value of `cval`.
- **cval** (`float`, optional) – The value to be set outside the rotated image boundaries.

has_landmarks

Whether the object has landmarks.

Type *bool*

has_landmarks_outside_bounds

Indicates whether there are landmarks located outside the image bounds.

Type *bool*

height

The height of the image.

This is the height according to image semantics, and is thus the size of the **second to last** dimension.

Type *int*

landmarks

The landmarks object.

Type `LandmarkManager`

n_channels

The number of channels on each pixel in the image.

Type *int*

n_dims

The number of dimensions in the image. The minimum possible `n_dims` is 2.

Type *int*

n_elements

Total number of data points in the image `(prod(shape), n_channels)`

Type *int*

n_landmark_groups

The number of landmark groups on this object.

Type *int*

n_parameters

The length of the vector that this object produces.

Type *int*

n_pixels

Total number of pixels in the image `(prod(shape),)`

Type *int*

shape

The shape of the image (with `n_channel` values at each point).

Type *tuple*

width

The width of the image.

This is the width according to image semantics, and is thus the size of the **last** dimension.

Type *int*

BooleanImage

class `menpo.image.`**`BooleanImage`**(*mask_data*, *copy=True*)

Bases: `Image`

A mask image made from binary pixels. The region of the image that is left exposed by the mask is referred to as the 'masked region'. The set of 'masked' pixels is those pixels corresponding to a `True` value in the mask.

Parameters

- **`mask_data`** (`(M, N, ..., L)` *ndarray*) – The binary mask data. Note that there is no channel axis - a 2D Mask Image is built from just a 2D numpy array of mask_data. Automatically coerced in to boolean values.
- **`copy`** (*bool*, optional) – If `False`, the image_data will not be copied on assignment. Note that if the array you provide is not boolean, there **will still be copy**. In general this should only be used if you know what you are doing.

`all_true`()

`True` iff every element of the mask is `True`.

Type*bool*

`as_PILImage`()

Return a PIL copy of the image. Depending on the image data type, different operations are performed:

dtype	Processing
uint8	No processing, directly converted to PIL
bool	Scale by 255, convert to uint8
float32	Scale by 255, convert to uint8
float64	Scale by 255, convert to uint8
OTHER	Raise ValueError

Image must only have 1 or 3 channels and be 2 dimensional. Non *uint8* images must be in the rage `[0, 1]` to be converted.

Returnspil_image (*PILImage*) – PIL copy of image

Raises

- `ValueError` – If image is not 2D and 1 channel or 3 channels.
- `ValueError` – If pixels data type is not *float32*, *float64*, *bool* or *uint8*
- `ValueError` – If pixels data type is *float32* or *float64* and the pixel range is outside of `[0, 1]`

`as_greyscale`(*mode='luminosity'*, *channel=None*)

Returns a greyscale version of the image. If the image does *not* represent a 2D RGB image, then the `luminosity` mode will fail.

Parameters

- **`mode`** (`{average, luminosity, channel}`, optional) –

mode	Greyscale Algorithm
average	Equal average of all channels
luminosity	Calculates the luminance using the CCIR 601 formula:
	$Y' = 0.2989R' + 0.5870G' + 0.1140B'$
channel	A specific channel is chosen as the intensity value.

- **`channel`** (*int*, optional) – The channel to be taken. Only used if mode is `channel`.

Returnsgreyscale_image (`MaskedImage`) – A copy of this image in greyscale.

as_histogram(*keep_channels=True*, *bins='unique'*)

Histogram binning of the values of this image.

Parameters

- **keep_channels** (*bool*, optional) – If set to `False`, it returns a single histogram for all the channels of the image. If set to `True`, it returns a *list* of histograms, one for each channel.
- **bins** (`{unique}`, positive *int* or sequence of scalars, optional) – If set equal to `'unique'`, the bins of the histograms are centred on the unique values of each channel. If set equal to a positive *int*, then this is the number of bins. If set equal to a sequence of scalars, these will be used as bins centres.

Returns

- **hist** (*ndarray* or *list* with `n_channels` *ndarrays* inside) – The histogram(s). If `keep_channels=False`, then hist is an *ndarray*. If `keep_channels=True`, then hist is a *list* with `len(hist)=n_channels`.
- **bin_edges** (*ndarray* or *list* with *n_channels ndarrays* inside) – An array or a list of arrays corresponding to the above histograms that store the bins' edges.

Raises `ValueError` – Bins can be either 'unique', positive int or a sequence of scalars.

Examples

Visualizing the histogram when a list of array bin edges is provided:

```
>>> hist, bin_edges = image.as_histogram()
>>> for k in range(len(hist)):
>>>     plt.subplot(1,len(hist),k)
>>>     width = 0.7 * (bin_edges[k][1] - bin_edges[k][0])
>>>     centre = (bin_edges[k][:-1] + bin_edges[k][1:]) / 2
>>>     plt.bar(centre, hist[k], align='center', width=width)
```

---

as_masked(*mask=None*, *copy=True*)

Impossible for a `BooleanImage` to be transformed to a `MaskedImage`.

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returns **vector** (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

bounds_false(*boundary=0*, *constrain_to_bounds=True*)

Returns the minimum to maximum indices along all dimensions that the mask includes which fully surround the False mask values. In the case of a 2D Image for instance, the min and max define two corners of a rectangle bounding the False pixel values.

Parameters

- **boundary** (*int* >= 0, optional) – A number of pixels that should be added to the extent. A negative value can be used to shrink the bounds in.
- **constrain_to_bounds** (*bool*, optional) – If `True`, the bounding extent is snapped to not go beyond the edge of the image. If `False`, the bounds are left unchanged.

Returns

- **min_b** (`(D,)` *ndarray*) – The minimum extent of the `True` mask region with the boundary along each dimension. If `constrain_to_bounds=True`, is clipped to legal image bounds.
- **max_b** (`(D,)` *ndarray*) – The maximum extent of the `True` mask region with the boundary along each dimension. If `constrain_to_bounds=True`, is clipped to legal image bounds.

bounds_true(*boundary=0*, *constrain_to_bounds=True*)

Returns the minimum to maximum indices along all dimensions that the mask includes which fully surround the `True` mask values. In the case of a 2D Image for instance, the min and max define two corners of a rectangle bounding the True pixel values.

Parameters

- **boundary** (*int*, optional) – A number of pixels that should be added to the extent. A negative value can be used to shrink the bounds in.
- **constrain_to_bounds** (*bool*, optional) – If `True`, the bounding extent is snapped to not go beyond the edge of the image. If `False`, the bounds are left unchanged.
- **Returns** –
- **--------** –
- **min_b** (`(D,)` *ndarray*) – The minimum extent of the `True` mask region with the boundary along each dimension. If `constrain_to_bounds=True`, is clipped to legal image bounds.
- **max_b** (`(D,)` *ndarray*) – The maximum extent of the `True` mask region with the boundary along each dimension. If `constrain_to_bounds=True`, is clipped to legal image bounds.

centre()

The geometric centre of the Image - the subpixel that is in the middle.

Useful for aligning shapes and images.

Type(`n_dims`,) *ndarray*

constrain_landmarks_to_bounds()

Move landmarks that are located outside the image bounds on the bounds.

constrain_points_to_bounds(*points*)

Constrains the points provided to be within the bounds of this image.

Parameterspoints (`(d,)` *ndarray*) – Points to be snapped to the image boundaries.

Returnsbounded_points (`(d,)` *ndarray*) – Points snapped to not stray outside the image edges.

constrain_to_landmarks(*group=None*, *label=None*, *trilist=None*, *batch_size=None*)

Restricts this mask to be equal to the convex hull around the landmarks chosen. This is not a per-pixel convex hull, but instead relies on a triangulated approximation.

Parameters

- **group** (*str*, optional) – The key of the landmark set that should be used. If `None`, and if there is only one set of landmarks, this set will be used.
- **label** (*str*, optional) – The label of of the landmark manager that you wish to use. If no label is passed, the convex hull of all landmarks is used.
- **trilist** (`(t, 3)` *ndarray*, optional) – Triangle list to be used on the landmarked points in selecting the mask region. If `None`, defaults to performing Delaunay triangulation on the points.
- **batch_size** (*int* or `None`, optional) – This should only be considered for large images. Setting this value will cause constraining to become much slower. This size indicates how many points in the image should be checked at a time, which keeps memory usage low. If `None`, no batching is used and all points are checked at once.

constrain_to_pointcloud(*pointcloud*, *batch_size=None*, *point_in_pointcloud='pwa'*, *trilist=None*)

Restricts this mask to be equal to the convex hull around a pointcloud. The choice of whether a pixel is inside or outside of the pointcloud is determined by the `point_in_pointcloud` parameter. By default a Piecewise Affine transform is used to test for containment, which is useful when building efficiently aligning images. For large images, a faster and pixel-accurate method can be used ('convex_hull'). Alternatively, a callable can be provided to override the test. By default, the provided implementations

are only valid for 2D images.

Parameters

- **pointcloud** (*PointCloud*) – The pointcloud of points that should be constrained to.
- **batch_size** (*int* or `None`, optional) – This should only be considered for large images. Setting this value will cause constraining to become much slower. This size indicates how many points in the image should be checked at a time, which keeps memory usage low. If `None`, no batching is used and all points are checked at once. By default, this is only used for the 'pwa' point_in_pointcloud choice.
- **point_in_pointcloud** ({'pwa', 'convex_hull'} or *callable*) – The method used to check if pixels in the image fall inside the pointcloud or not. Can be accurate to a Piecewise Affine transform, a pixel accurate convex hull or any arbitrary callable. If a callable is passed, it should take two parameters, the *PointCloud* to constrain with and the pixel locations ((d, n_dims) ndarray) to test and should return a (d, 1) boolean ndarray of whether the pixels were inside (True) or outside (False) of the *PointCloud*.
- **trilist** (`(t, 3)` *ndarray*, optional) – Deprecated. Please provide a Trimesh instead of relying on this parameter.

Raises

- `ValueError` – If the image is not 2D and a default implementation is chosen.
- `ValueError` – If the chosen `point_in_pointcloud` is unknown.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns `type(self)` – A copy of this object

crop(*min_indices*, *max_indices*, *constrain_to_boundary=False*)

Return a cropped copy of this image using the given minimum and maximum indices. Landmarks are correctly adjusted so they maintain their position relative to the newly cropped image.

Parameters

- **min_indices** (`(n_dims,)` *ndarray*) – The minimum index over each dimension.
- **max_indices** (`(n_dims,)` *ndarray*) – The maximum index over each dimension.
- **constrain_to_boundary** (*bool*, optional) – If `True` the crop will be snapped to not go beyond this images boundary. If `False`, an *ImageBoundaryError* will be raised if an attempt is made to go beyond the edge of the image.

Returns **cropped_image** (*type(self)*) – A new instance of self, but cropped.

Raises

- `ValueError` – `min_indices` and `max_indices` both have to be of length `n_dims`. All `max_indices` must be greater than `min_indices`.
- *ImageBoundaryError* – Raised if `constrain_to_boundary=False`, and an attempt is made to crop the image in a way that violates the image bounds.

crop_inplace(**args*, ***kwargs*)

Deprecated: please use *crop()* instead.

crop_to_landmarks(*group=None*, *label=None*, *boundary=0*, *constrain_to_boundary=True*)

Return a copy of this image cropped so that it is bounded around a set of landmarks with an optional

`n_pixel` boundary

Parameters

- **group** (*str*, optional) – The key of the landmark set that should be used. If `None` and if there is only one set of landmarks, this set will be used.
- **label** (*str*, optional) – The label of of the landmark manager that you wish to use. If `None` all landmarks in the group are used.
- **boundary** (*int*, optional) – An extra padding to be added all around the landmarks bounds.
- **constrain_to_boundary** (*bool*, optional) – If `True` the crop will be snapped to not go beyond this images boundary. If `False`, an :map'ImageBoundaryError' will be raised if an attempt is made to go beyond the edge of the image.

Returns **image** (*Image*) – A copy of this image cropped to its landmarks.

Raises *ImageBoundaryError* – Raised if `constrain_to_boundary=False`, and an attempt is made to crop the image in a way that violates the image bounds.

crop_to_landmarks_inplace(**args*, ***kwargs*)

Deprecated: please use *crop_to_landmarks()* instead.

crop_to_landmarks_proportion(*boundary_proportion*, *group=None*, *label=None*, *minimum=True*, *constrain_to_boundary=True*)

Crop this image to be bounded around a set of landmarks with a border proportional to the landmark spread or range.

Parameters

- **boundary_proportion** (*float*) – Additional padding to be added all around the landmarks bounds defined as a proportion of the landmarks range. See the minimum parameter for a definition of how the range is calculated.
- **group** (*str*, optional) – The key of the landmark set that should be used. If `None` and if there is only one set of landmarks, this set will be used.
- **label** (*str*, optional) – The label of of the landmark manager that you wish to use. If `None` all landmarks in the group are used.
- **minimum** (*bool*, optional) – If `True` the specified proportion is relative to the minimum value of the landmarks' per-dimension range; if `False` w.r.t. the maximum value of the landmarks' per-dimension range.
- **constrain_to_boundary** (*bool*, optional) – If `True`, the crop will be snapped to not go beyond this images boundary. If `False`, an *ImageBoundaryError* will be raised if an attempt is made to go beyond the edge of the image.

Returns **image** (*Image*) – This image, cropped to its landmarks with a border proportional to the landmark spread or range.

Raises *ImageBoundaryError* – Raised if `constrain_to_boundary=False`, and an attempt is made to crop the image in a way that violates the image bounds.

crop_to_landmarks_proportion_inplace(**args*, ***kwargs*)

Deprecated: please use *crop_to_landmarks_proportion()* instead.

diagonal()

The diagonal size of this image

Type *float*

extract_channels(*channels*)

A copy of this image with only the specified channels.

Parameters **channels** (*int* or *[int]*) – The channel index or *list* of channel indices to retain.

Returns **image** (*type(self)*) – A copy of this image with only the channels requested.

extract_patches(*patch_centers*, *patch_size=(16, 16)*, *sample_offsets=None*, *as_single_array=False*)

Extract a set of patches from an image. Given a set of patch centers and a patch size, patches are extracted from within the image, centred on the given coordinates. Sample offsets denote a set of offsets to extract from within a patch. This is very useful if you want to extract a dense set of features around a set of landmarks and simply sample the same grid of patches around the landmarks.

If sample offsets are used, to access the offsets for each patch you need to slice the resulting list. So for 2 offsets, the first centers offset patches would be `patches[:2]`.

Currently only 2D images are supported.

Parameters

- **patch_centers** (*PointCloud*) – The centers to extract patches around.
- **patch_size** (*tuple* or *ndarray*, optional) – The size of the patch to extract
- **sample_offsets** (*PointCloud*, optional) – The offsets to sample from within a patch. So (0, 0) is the centre of the patch (no offset) and (1, 0) would be sampling the patch from 1 pixel up the first axis away from the centre.
- **as_single_array** (*bool*, optional) – If `True`, an `(n_center * n_offset, self.shape...)` *ndarray*, thus a single numpy array is returned containing each patch. If `False`, a *list* of *Image* objects is returned representing each patch.

Returns **patches** (*list* or *ndarray*) – Returns the extracted patches. Returns a list if `as_single_array=True` and an *ndarray* if `as_single_array=False`.

Raises `ValueError` – If image is not 2D

extract_patches_around_landmarks(*group=None*, *label=None*, *patch_size=(16, 16)*, *sample_offsets=None*, *as_single_array=False*)

Extract patches around landmarks existing on this image. Provided the group label and optionally the landmark label extract a set of patches.

See *extract_patches* for more information.

Currently only 2D images are supported.

Parameters

- **group** (*str* or `None` optional) – The landmark group to use as patch centres.
- **label** (*str* or `None` optional) – The landmark label within the group to use as centres.
- **patch_size** (*tuple* or *ndarray*, optional) – The size of the patch to extract
- **sample_offsets** (*PointCloud*, optional) – The offsets to sample from within a patch. So (0,0) is the centre of the patch (no offset) and (1, 0) would be sampling the patch from 1 pixel up the first axis away from the centre.
- **as_single_array** (*bool*, optional) – If `True`, an `(n_center * n_offset, self.shape...)` *ndarray*, thus a single numpy array is returned containing each patch. If `False`, a *list* of *Image* objects is returned representing each patch.

Returns **patches** (*list* or *ndarray*) – Returns the extracted patches. Returns a list if `as_single_array=True` and an *ndarray* if `as_single_array=False`.

Raises `ValueError` – If image is not 2D

false_indices()

The indices of pixels that are `Flase`.

Type `(n_dims, n_false)` *ndarray*

from_vector(*vector*, *copy=True*)

Takes a flattened vector and returns a new *BooleanImage* formed by reshaping the vector to the correct dimensions. Note that this is rebuilding a boolean image **itself** from boolean values. The mask is in no way interpreted in performing the operation, in contrast to *MaskedImage*, where only the masked region is used in *from_vector()* and :meth'as_vector'. Any image landmarks are transferred in the process.

Parameters

- **vector** ((n_pixels,) *bool ndarray*) – A flattened vector of all the pixels of a `BooleanImage`.
- **copy** (*bool*, optional) – If `False`, no copy of the vector will be taken.

Returns **image** (`BooleanImage`) – New BooleanImage of same shape as this image

Raises `Warning` – If `copy=False` cannot be honored.

from_vector_inplace(*vector*, *copy=True*)

Takes a flattened vector and update this image by reshaping the vector to the correct dimensions.

Parameters

- **vector** ((n_pixels,) *bool ndarray*) – A vector vector of all the pixels of a `BooleanImage`.
- **copy** (*bool*, optional) – If `False`, the vector will be set as the pixels. If `True`, a copy of the vector is taken.

Raises `Warning` – If `copy=False` flag cannot be honored

Note: For `BooleanImage` this is rebuilding a boolean image **itself** from boolean values. The mask is in no way interpreted in performing the operation, in contrast to `MaskedImage`, where only the masked region is used in `from_vector_inplace()` and `as_vector()`.

---

gaussian_pyramid(*n_levels=3*, *downscale=2*, *sigma=None*)

Return the gaussian pyramid of this image. The first image of the pyramid will be the original, unmodified, image, and counts as level 1.

Parameters

- **n_levels** (*int*, optional) – Total number of levels in the pyramid, including the original unmodified image
- **downscale** (*float*, optional) – Downscale factor.
- **sigma** (*float*, optional) – Sigma for gaussian filter. Default is `downscale / 3.` which corresponds to a filter mask twice the size of the scale factor that covers more than 99% of the gaussian distribution.

Yields **image_pyramid** (*generator*) – Generator yielding pyramid layers as `Image` objects.

gradient(***kwargs*)

Returns an `Image` which is the gradient of this one. In the case of multiple channels, it returns the gradient over each axis over each channel as a flat *list*. Take care to note the ordering of the returned gradient (the gradient over each spatial dimension is taken over each channel).

The first axis of the gradient of a 2D, 3-channel image, will have length *6*, the ordering being `I[:, 0, 0] = [R0_y, G0_y, B0_y, R0_x, G0_x, B0_x]`. To be clear, all the `y`-gradients are returned over each channel, then all the `x`-gradients.

Returns **gradient** (`Image`) – The gradient over each axis over each channel. Therefore, the gradient of a 2D, single channel image, will have length *2*. The length of a 2D, 3-channel image, will have length *6*.

has_nan_values()

Tests if the vectorized form of the object contains `nan` values or not. This is particularly useful for objects with unknown values that have been mapped to `nan` values.

Returns **has_nan_values** (*bool*) – If the vectorized object contains `nan` values.

indices()

Return the indices of all pixels in this image.

Type(`n_dims`, `n_pixels`) ndarray

classmethod init_blank(*shape*, *fill=True*, *round='ceil'*, ***kwargs*)

Returns a blank `BooleanImage` of the requested shape

Parameters

- **shape** (*tuple* or *list*) – The shape of the image. Any floating point values are rounded according to the `round` kwarg.

- **fill** (*bool*, optional) – The mask value to be set everywhere.
- **round** ({ceil, floor, round}, optional) – Rounding function to be applied to floating point shapes.

Returnsblank_image (*BooleanImage*) – A blank mask of the requested size

invert()

Returns a copy of this boolean image, which is inverted.

Returnsinverted (*BooleanImage*) – A copy of this boolean mask, where all `True` values are `False` and all `False` values are `True`.

invert_inplace()

Inverts this Boolean Image inplace.

n_false()

The number of `False` values in the mask.

Type*int*

n_true()

The number of `True` values in the mask.

Type*int*

normalize_norm_inplace(*mode='all'*, ***kwargs*)

Normalizes this image such that its pixel values have zero mean and its norm equals 1.

Parametersmode ({all, per_channel}, optional) – If `all`, the normalization is over all channels. If `per_channel`, each channel individually is mean centred and normalized in variance.

normalize_std_inplace(*mode='all'*, ***kwargs*)

Normalizes this image such that its pixel values have zero mean and unit variance.

Parametersmode ({all, per_channel}, optional) – If `all`, the normalization is over all channels. If `per_channel`, each channel individually is mean centred and normalized in variance.

proportion_false()

The proportion of the mask which is `False`

Type*float*

proportion_true()

The proportion of the mask which is `True`.

Type*float*

pyramid(*n_levels=3*, *downscale=2*)

Return a rescaled pyramid of this image. The first image of the pyramid will be the original, unmodified, image, and counts as level 1.

Parameters

- **n_levels** (*int*, optional) – Total number of levels in the pyramid, including the original unmodified image
- **downscale** (*float*, optional) – Downscale factor.

Yieldsimage_pyramid (*generator*) – Generator yielding pyramid layers as *Image* objects.

rescale(*scale*, *round='ceil'*, *order=1*)

Return a copy of this image, rescaled by a given factor. Landmarks are rescaled appropriately.

Parameters

- **scale** (*float* or *tuple* of *floats*) – The scale factor. If a tuple, the scale to apply to each dimension. If a single *float*, the scale will be applied uniformly across each dimension.
- **round** ({ceil, floor, round}, optional) – Rounding function to be applied to floating point shapes.

- **order** (*int*, optional) – The order of interpolation. The order has to be in the range [0,5]

Order	Interpolation
0	Nearest-neighbor
1	Bi-linear *(default)*
2	Bi-quadratic
3	Bi-cubic
4	Bi-quartic
5	Bi-quintic

Returns **rescaled_image** (`type(self)`) – A copy of this image, rescaled.

Raises `ValueError` – If less scales than dimensions are provided. If any scale is less than or equal to 0.

rescale_landmarks_to_diagonal_range(*diagonal_range*, *group=None*, *label=None*, *round='ceil'*, *order=1*)

Return a copy of this image, rescaled so that the diagonal_range of the bounding box containing its landmarks matches the specified diagonal_range range.

Parameters

- **diagonal_range** (`(n_dims,)` *ndarray*) – The diagonal_range range that we want the landmarks of the returned image to have.
- **group** (*str*, optional) – The key of the landmark set that should be used. If `None` and if there is only one set of landmarks, this set will be used.
- **label** (*str*, optional) – The label of of the landmark manager that you wish to use. If `None` all landmarks in the group are used.
- **round** (`{ceil, floor, round}`, optional) – Rounding function to be applied to floating point shapes.
- **order** (*int*, optional) – The order of interpolation. The order has to be in the range [0,5]

Order	Interpolation
0	Nearest-neighbor
1	Bi-linear *(default)*
2	Bi-quadratic
3	Bi-cubic
4	Bi-quartic
5	Bi-quintic

Returns **rescaled_image** (`type(self)`) – A copy of this image, rescaled.

rescale_pixels(*minimum*, *maximum*, *per_channel=True*)

A copy of this image with pixels linearly rescaled to fit a range.

Note that the only pixels that will considered and rescaled are those that feature in the vectorized form of this image. If you want to use this routine on all the pixels in a `MaskedImage`, consider using *as_unmasked()* prior to this call.

Parameters

- **minimum** (*float*) – The minimal value of the rescaled pixels
- **maximum** (*float*) – The maximal value of the rescaled pixels
- **per_channel** (*boolean*, optional) – If `True`, each channel will be rescaled independently. If `False`, the scaling will be over all channels.

Returns **rescaled_image** (`type(self)`) – A copy of this image with pixels linearly rescaled to fit in the range provided.

rescale_to_diagonal(*diagonal*, *round='ceil'*)

Return a copy of this image, rescaled so that the it's diagonal is a new size.

Parameters

- **diagonal** (*int*) – The diagonal size of the new image.

- **round** (`{ceil, floor, round}`, optional) – Rounding function to be applied to floating point shapes.

Returns **rescaled_image** (*type(self)*) – A copy of this image, rescaled.

rescale_to_reference_shape(*reference_shape*, *group=None*, *label=None*, *round='ceil'*, *order=1*)

Return a copy of this image, rescaled so that the scale of a particular group of landmarks matches the scale of the passed reference landmarks.

Parameters

- **reference_shape** (`PointCloud`) – The reference shape to which the landmarks scale will be matched against.
- **group** (*str*, optional) – The key of the landmark set that should be used. If `None`, and if there is only one set of landmarks, this set will be used.
- **label** (*str*, optional) – The label of of the landmark manager that you wish to use. If `None` all landmarks in the group are used.
- **round** (`{ceil, floor, round}`, optional) – Rounding function to be applied to floating point shapes.
- **order** (*int*, optional) – The order of interpolation. The order has to be in the range [0,5]

Order	Interpolation
0	Nearest-neighbor
1	Bi-linear *(default)*
2	Bi-quadratic
3	Bi-cubic
4	Bi-quartic
5	Bi-quintic

Returns **rescaled_image** (`type(self)`) – A copy of this image, rescaled.

resize(*shape*, *order=1*)

Return a copy of this image, resized to a particular shape. All image information (landmarks, and mask in the case of `MaskedImage`) is resized appropriately.

Parameters

- **shape** (*tuple*) – The new shape to resize to.
- **order** (*int*, optional) – The order of interpolation. The order has to be in the range [0,5]

Order	Interpolation
0	Nearest-neighbor
1	Bi-linear *(default)*
2	Bi-quadratic
3	Bi-cubic
4	Bi-quartic
5	Bi-quintic

Returns **resized_image** (`type(self)`) – A copy of this image, resized.

Raises `ValueError` – If the number of dimensions of the new shape does not match the number of dimensions of the image.

rolled_channels()

Returns the pixels matrix, with the channels rolled to the back axis. This may be required for interacting with external code bases that require images to have channels as the last axis, rather than the menpo convention of channels as the first axis.

Returns **rolled_channels** (*ndarray*) – Pixels with channels as the back (last) axis.

rotate_ccw_about_centre(*theta*, *degrees=True*, *cval=0.0*)

Return a rotation of this image clockwise about its centre.

Parameters

- **theta** (*float*) – The angle of rotation about the origin.
- **degrees** (*bool*, optional) – If `True`, *theta* is interpreted as a degree. If `False`, `theta` is interpreted as radians.
- **cval** (`float`, optional) – The value to be set outside the rotated image boundaries.

Returnsrotated_image (`type(self)`) – The rotated image.

sample(*points_to_sample*, *mode='constant'*, *cval=False*, ***kwargs*)

Sample this image at the given sub-pixel accurate points. The input PointCloud should have the same number of dimensions as the image e.g. a 2D PointCloud for a 2D multi-channel image. A numpy array will be returned the has the values for every given point across each channel of the image.

Parameters

- **points_to_sample** (*PointCloud*) – Array of points to sample from the image. Should be *(n_points, n_dims)*
- **mode** (`{constant, nearest, reflect, wrap}`, optional) – Points outside the boundaries of the input are filled according to the given mode.
- **cval** (*float*, optional) – Used in conjunction with mode `constant`, the value outside the image boundaries.

Returnssampled_pixels ((*n_points*, *n_channels*) *bool ndarray*) – The interpolated values taken across every channel of the image.

true_indices()

The indices of pixels that are `True`.

Type (`n_dims, n_true`) *ndarray*

view_widget(*browser_style='buttons'*, *figure_size=(10, 8)*, *style='coloured'*)

Visualizes the image object using the *visualize_images* widget. Currently only supports the rendering of 2D images.

Parameters

- **browser_style** (`{'buttons','slider'}`, optional) – It defines whether the selector of the images will have the form of plus/minus buttons or a slider.
- **figure_size** ((*int*, *int*), optional) – The initial size of the rendered figure.
- **style** (`{'coloured','minimal'}`, optional) – If `'coloured'`, then the style of the widget will be coloured. If `minimal`, then the style is simple using black and white colours.

warp_to_mask(*template_mask*, *transform*, *warp_landmarks=True*, *mode='constant'*, *cval=False*, *batch_size=None*)

Return a copy of this *BooleanImage* warped into a different reference space.

Note that warping into a mask is slower than warping into a full image. If you don't need a non-linear mask, consider warp_to_shape instead.

Parameters

- **template_mask** (*BooleanImage*) – Defines the shape of the result, and what pixels should be sampled.
- **transform** (*Transform*) – Transform **from the template space back to this image**. Defines, for each pixel location on the template, which pixel location should be sampled from on this image.
- **warp_landmarks** (*bool*, optional) – If `True`, result will have the same landmark dictionary as self, but with each landmark updated to the warped position.
- **mode** (`{constant, nearest, reflect or wrap}`, optional) – Points outside the boundaries of the input are filled according to the given mode.
- **cval** (*float*, optional) – Used in conjunction with mode `constant`, the value outside the image boundaries.
- **batch_size** (*int* or `None`, optional) – This should only be considered for large images. Setting this value can cause warping to become much slower, particular for cached warps such as Piecewise Affine. This size indicates how many points

in the image should be warped at a time, which keeps memory usage low. If `None`, no batching is used and all points are warped at once.

Returns **warped_image** (`BooleanImage`) – A copy of this image, warped.

warp_to_shape(*template_shape*, *transform*, *warp_landmarks=True*, *mode='constant'*, *cval=False*, *order=None*, *batch_size=None*)

Return a copy of this `BooleanImage` warped into a different reference space.

Note that the order keyword argument is in fact ignored, as any order other than 0 makes no sense on a binary image. The keyword argument is present only for compatibility with the `Image` warp_to_shape API.

Parameters

- **template_shape** (`(n_dims, )` *tuple* or *ndarray*) – Defines the shape of the result, and what pixel indices should be sampled (all of them).
- **transform** (`Transform`) – Transform **from the template_shape space back to this image**. Defines, for each index on template_shape, which pixel location should be sampled from on this image.
- **warp_landmarks** (*bool*, optional) – If `True`, result will have the same landmark dictionary as self, but with each landmark updated to the warped position.
- **mode** (`{constant, nearest, reflect or wrap}`, optional) – Points outside the boundaries of the input are filled according to the given mode.
- **cval** (*float*, optional) – Used in conjunction with mode `constant`, the value outside the image boundaries.
- **batch_size** (*int* or `None`, optional) – This should only be considered for large images. Setting this value can cause warping to become much slower, particular for cached warps such as Piecewise Affine. This size indicates how many points in the image should be warped at a time, which keeps memory usage low. If `None`, no batching is used and all points are warped at once.

Returns **warped_image** (`BooleanImage`) – A copy of this image, warped.

zoom(*scale*, *cval=0.0*)

Zoom this image about the centre point. `scale` values greater than 1.0 denote zooming **in** to the image and values less than 1.0 denote zooming **out** of the image. The size of the image will not change, if you wish to scale an image, please see `rescale()`.

Parameters

- **scale** (*float*) – `scale > 1.0` denotes zooming in. Thus the image will appear larger and areas at the edge of the zoom will be 'cropped' out. `scale < 1.0` denotes zooming out. The image will be padded by the value of `cval`.
- **cval** (`float`, optional) – The value to be set outside the rotated image boundaries.

has_landmarks

Whether the object has landmarks.

Type *bool*

has_landmarks_outside_bounds

Indicates whether there are landmarks located outside the image bounds.

Type *bool*

height

The height of the image.

This is the height according to image semantics, and is thus the size of the **second to last** dimension.

Type *int*

landmarks

The landmarks object.

Type `LandmarkManager`

mask
Returns the pixels of the mask with no channel axis. This is what should be used to mask any k-dimensional image.
Type `(M, N, ..., L)`, *bool ndarray*

n_channels
The number of channels on each pixel in the image.
Type *int*

n_dims
The number of dimensions in the image. The minimum possible `n_dims` is 2.
Type *int*

n_elements
Total number of data points in the image `(prod(shape), n_channels)`
Type *int*

n_landmark_groups
The number of landmark groups on this object.
Type *int*

n_parameters
The length of the vector that this object produces.
Type *int*

n_pixels
Total number of pixels in the image `(prod(shape),)`
Type *int*

shape
The shape of the image (with `n_channel` values at each point).
Type *tuple*

width
The width of the image.

This is the width according to image semantics, and is thus the size of the **last** dimension.
Type *int*

MaskedImage

class `menpo.image.`**`MaskedImage`**(*image_data*, *mask=None*, *copy=True*)
Bases: `Image`

Represents an *n*-dimensional *k*-channel image, which has a mask. Images can be masked in order to identify a region of interest. All images implicitly have a mask that is defined as the the entire image. The mask is an instance of `BooleanImage`.

Parameters
- **`image_data`** (`(C, M, N ..., Q)` *ndarray*) – The pixel data for the image, where the first axis represents the number of channels.
- **`mask`** (`(M, N)` *bool ndarray* or `BooleanImage`, optional) – A binary array representing the mask. Must be the same shape as the image. Only one mask is supported for an image (so the mask is applied to every channel equally).
- **`copy`** (*bool*, optional) – If `False`, the `image_data` will not be copied on assignment. If a mask is provided, this also won't be copied. In general this should only be used if you know what you are doing.

Raises `ValueError` – Mask is not the same shape as the image

_view_2d(*figure_id=None*, *new_figure=False*, *channels=None*, *masked=True*, *interpolation='bilinear'*, *cmap_name=None*, *alpha=1.0*, *render_axes=False*, *axes_font_name='sans-serif'*, *axes_font_size=10*, *axes_font_style='normal'*, *axes_font_weight='normal'*, *axes_x_limits=None*, *axes_y_limits=None*, *figure_size=(10, 8)*)

View the image using the default image viewer. This method will appear on the Image as `view` if the Image is 2D.

Returns

- **figure_id** (*object*, optional) – The id of the figure to be used.
- **new_figure** (*bool*, optional) – If `True`, a new figure is created.
- **channels** (*int* or *list* of *int* or `all` or `None`) – If *int* or *list* of *int*, the specified channel(s) will be rendered. If `all`, all the channels will be rendered in subplots. If `None` and the image is RGB, it will be rendered in RGB mode. If `None` and the image is not RGB, it is equivalent to `all`.
- **masked** (*bool*, optional) – If `True`, only the masked pixels will be rendered.
- **interpolation** (*See Below, optional*) – The interpolation used to render the image. For example, if `bilinear`, the image will be smooth and if `nearest`, the image will be pixelated. Example options

```
{none, nearest, bilinear, bicubic, spline16, spline36,
hanning, hamming, hermite, kaiser, quadric, catrom, gaussian,
bessel, mitchell, sinc, lanczos}
```

- **cmap_name** (*str*, optional,) – If `None`, single channel and three channel images default to greyscale and rgb colormaps respectively.
- **alpha** (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.
- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** ({`normal`, `italic`, `oblique`}, optional) – The font style of the axes.
- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **axes_x_limits** ((*float*, *float*) *tuple* or `None`, optional) – The limits of the x axis.
- **axes_y_limits** ((*float*, *float*) *tuple* or `None`, optional) – The limits of the y axis.
- **figure_size** ((*float*, *float*) *tuple* or `None`, optional) – The size of the figure in inches.

Raises `ValueError` – If Image is not 2D

_view_landmarks_2d(*channels=None*, *masked=True*, *group=None*, *with_labels=None*, *without_labels=None*, *figure_id=None*, *new_figure=False*, *interpolation='bilinear'*, *cmap_name=None*, *alpha=1.0*, *render_lines=True*, *line_colour=None*, *line_style='-'*, *line_width=1*, *render_markers=True*, *marker_style='o'*, *marker_size=20*, *marker_face_colour=None*, *marker_edge_colour=None*, *marker_edge_width=1.0*, *render_numbering=False*, *numbers_horizontal_align='center'*, *numbers_vertical_align='bottom'*, *numbers_font_name='sans-serif'*, *numbers_font_size=10*, *numbers_font_style='normal'*, *numbers_font_weight='normal'*, *numbers_font_colour='k'*, *render_legend=False*, *legend_title=''*, *legend_font_name='sans-serif'*, *legend_font_style='normal'*, *legend_font_size=10*, *legend_font_weight='normal'*, *legend_marker_scale=None*, *legend_location=2*, *legend_bbox_to_anchor=(1.05, 1.0)*, *legend_border_axes_pad=None*, *legend_n_columns=1*, *legend_horizontal_spacing=None*, *legend_vertical_spacing=None*, *legend_border=True*, *legend_border_padding=None*, *legend_shadow=False*, *legend_rounded_corners=False*, *render_axes=False*, *axes_font_name='sans-serif'*, *axes_font_size=10*, *axes_font_style='normal'*, *axes_font_weight='normal'*, *axes_x_limits=None*, *axes_y_limits=None*, *figure_size=(10, 8)*)

Visualize the landmarks. This method will appear on the Image as `view_landmarks` if the Image is 2D.

Parameters

- **channels** (*int* or *list* of *int* or `all` or `None`) – If *int* or *list* of *int*, the specified channel(s) will be rendered. If `all`, all the channels will be rendered in subplots. If `None` and the image is RGB, it will be rendered in RGB mode. If `None` and the image is not RGB, it is equivalent to `all`.
- **masked** (*bool*, optional) – If `True`, only the masked pixels will be rendered.
- **group** (*str* or''None'' optionals) – The landmark group to be visualized. If `None` and there are more than one landmark groups, an error is raised.
- **with_labels** (`None` or *str* or *list* of *str*, optional) – If not `None`, only show the given label(s). Should **not** be used with the `without_labels` kwarg.
- **without_labels** (`None` or *str* or *list* of *str*, optional) – If not `None`, show all except the given label(s). Should **not** be used with the `with_labels` kwarg.
- **figure_id** (*object*, optional) – The id of the figure to be used.
- **new_figure** (*bool*, optional) – If `True`, a new figure is created.
- **interpolation** (*See Below, optional*) – The interpolation used to render the image. For example, if `bilinear`, the image will be smooth and if `nearest`, the image will be pixelated. Example options

```
{none, nearest, bilinear, bicubic, spline16, spline36, hanning,
hamming, hermite, kaiser, quadric, catrom, gaussian, bessel,
mitchell, sinc, lanczos}
```

- **cmap_name** (*str*, optional,) – If `None`, single channel and three channel images default to greyscale and rgb colormaps respectively.
- **alpha** (*float*, optional) – The alpha blending value, between 0 (transparent) and 1 (opaque).
- **render_lines** (*bool*, optional) – If `True`, the edges will be rendered.
- **line_colour** (*See Below, optional*) – The colour of the lines. Example options:

```
{r, g, b, c, m, k, w}
or
```

```
(3, ) ndarray
```

- **line_style** ({-, --, -., :}, optional) – The style of the lines.
- **line_width** (*float*, optional) – The width of the lines.
- **render_markers** (*bool*, optional) – If True, the markers will be rendered.
- **marker_style** (*See Below, optional*) – The style of the markers. Example options

```
{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}
```

- **marker_size** (*int*, optional) – The size of the markers in points^2.
- **marker_face_colour** (*See Below, optional*) – The face (filling) colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_colour** (*See Below, optional*) – The edge colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_width** (*float*, optional) – The width of the markers' edge.
- **render_numbering** (*bool*, optional) – If True, the landmarks will be numbered.
- **numbers_horizontal_align** ({center, right, left}, optional) – The horizontal alignment of the numbers' texts.
- **numbers_vertical_align** ({center, top, bottom, baseline}, optional) – The vertical alignment of the numbers' texts.
- **numbers_font_name** (*See Below, optional*) – The font of the numbers. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **numbers_font_size** (*int*, optional) – The font size of the numbers.
- **numbers_font_style** ({normal, italic, oblique}, optional) – The font style of the numbers.
- **numbers_font_weight** (*See Below, optional*) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **numbers_font_colour** (*See Below, optional*) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **render_legend** (*bool*, optional) – If True, the legend will be rendered.
- **legend_title** (*str*, optional) – The title of the legend.
- **legend_font_name** (*See below, optional*) – The font of the legend. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **legend_font_style** ({normal, italic, oblique}, optional) – The font style of the legend.
- **legend_font_size** (*int*, optional) – The font size of the legend.
- **legend_font_weight** (*See Below, optional*) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **legend_marker_scale** (*float*, optional) – The relative size of the legend markers with respect to the original
- **legend_location** (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

- **legend_bbox_to_anchor** ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.
- **legend_border_axes_pad** (*float*, optional) – The pad between the axes and legend border.
- **legend_n_columns** (*int*, optional) – The number of the legend's columns.
- **legend_horizontal_spacing** (*float*, optional) – The spacing between the columns.
- **legend_vertical_spacing** (*float*, optional) – The vertical space between the legend entries.
- **legend_border** (*bool*, optional) – If `True`, a frame will be drawn around the legend.
- **legend_border_padding** (*float*, optional) – The fractional whitespace inside the legend border.
- **legend_shadow** (*bool*, optional) – If `True`, a shadow will be drawn behind legend.
- **legend_rounded_corners** (*bool*, optional) – If `True`, the frame's corners will be rounded (fancybox).
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.
- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** ({normal, italic, oblique}, optional) – The font style of the axes.
- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold,demibold, demi, bold, heavy, extra bold, black}
```

- **axes_x_limits** ((*float*, *float*) *tuple* or `None` optional) – The limits of the x axis.
- **axes_y_limits** ((*float*, *float*) *tuple* or `None` optional) – The limits of the y axis.
- **figure_size** ((*float*, *float*) *tuple* or `None` optional) – The size of the figure in inches.

Raises

- `ValueError` – If both `with_labels` and `without_labels` are passed.
- `ValueError` – If the landmark manager doesn't contain the provided group label.

as_PILImage()

Return a PIL copy of the image. Depending on the image data type, different operations are performed:

dtype	Processing
uint8	No processing, directly converted to PIL
bool	Scale by 255, convert to uint8
float32	Scale by 255, convert to uint8
float64	Scale by 255, convert to uint8
OTHER	Raise ValueError

Image must only have 1 or 3 channels and be 2 dimensional. Non *uint8* images must be in the rage `[0, 1]` to be converted.

Returnspil_image (*PILImage*) – PIL copy of image

Raises

- `ValueError` – If image is not 2D and 1 channel or 3 channels.
- `ValueError` – If pixels data type is not *float32*, *float64*, *bool* or *uint8*
- `ValueError` – If pixels data type is *float32* or *float64* and the pixel range is outside of `[0, 1]`

as_greyscale(*mode='luminosity'*, *channel=None*)

Returns a greyscale version of the image. If the image does *not* represent a 2D RGB image, then the `luminosity` mode will fail.

Parameters

- **mode** (`{average, luminosity, channel}`, optional) –

mode	Greyscale Algorithm
average	Equal average of all channels
luminosity	Calculates the luminance using the CCIR 601 formula:
	$Y' = 0.2989R' + 0.5870G' + 0.1140B'$
channel	A specific channel is chosen as the intensity value.

- **channel** (*int*, optional) – The channel to be taken. Only used if mode is `channel`.

Returnsgreyscale_image (`MaskedImage`) – A copy of this image in greyscale.

as_histogram(*keep_channels=True*, *bins='unique'*)

Histogram binning of the values of this image.

Parameters

- **keep_channels** (*bool*, optional) – If set to `False`, it returns a single histogram for all the channels of the image. If set to `True`, it returns a *list* of histograms, one for each channel.
- **bins** (`{unique}`, positive *int* or sequence of scalars, optional) – If set equal to `'unique'`, the bins of the histograms are centred on the unique values of each channel. If set equal to a positive *int*, then this is the number of bins. If set equal to a sequence of scalars, these will be used as bins centres.

Returns

- **hist** (*ndarray* or *list* with `n_channels` *ndarrays* inside) – The histogram(s). If `keep_channels=False`, then hist is an *ndarray*. If `keep_channels=True`, then hist is a *list* with `len(hist)=n_channels`.
- **bin_edges** (*ndarray* or *list* with *n_channels ndarrays* inside) – An array or a list of arrays corresponding to the above histograms that store the bins' edges.

Raises `ValueError` – Bins can be either 'unique', positive int or a sequence of scalars.

Examples

Visualizing the histogram when a list of array bin edges is provided:

```
>>> hist, bin_edges = image.as_histogram()
>>> for k in range(len(hist)):
>>>     plt.subplot(1,len(hist),k)
>>>     width = 0.7 * (bin_edges[k][1] - bin_edges[k][0])
>>>     centre = (bin_edges[k][:-1] + bin_edges[k][1:]) / 2
>>>     plt.bar(centre, hist[k], align='center', width=width)
```

as_masked(*mask=None*, *copy=True*)

Return a copy of this image with an attached mask behavior.

A custom mask may be provided, or `None`. See the `MaskedImage` constructor for details of how the kwargs will be handled.

Parameters

- **mask** (`(self.shape)` *ndarray* or `BooleanImage`) – A mask to attach to the newly generated masked image.
- **copy** (*bool*, optional) – If `False`, the produced `MaskedImage` will share pixels with `self`. Only suggested to be used for performance.

Returns **masked_image** (`MaskedImage`) – An image with the same pixels and landmarks as this one, but with a mask.

as_unmasked(*copy=True*, *fill=None*)

Return a copy of this image without the masking behavior.

By default the mask is simply discarded. However, there is an optional kwarg, `fill`, that can be set which will fill the **non-masked** areas with the given value.

Parameters

- **copy** (*bool*, optional) – If `False`, the produced `Image` will share pixels with `self`. Only suggested to be used for performance.
- **fill** (*float* or `None`, optional) – If `None` the mask is simply discarded. If a number, the *unmasked* regions are filled with the given value.

Returns **image** (`Image`) – An image with the same pixels and landmarks as this one, but with no mask.

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returns **vector** (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

build_mask_around_landmarks(*patch_size*, *group=None*, *label=None*)

Restricts this images mask to be patches around each landmark in the chosen landmark group. This is useful for visualizing patch based methods.

Parameters

- **patch_shape** (*tuple*) – The size of the patch. Any floating point values are rounded up to the nearest integer.
- **group** (*str*, optional) – The key of the landmark set that should be used. If `None`, and if there is only one set of landmarks, this set will be used.
- **label** (*str*, optional) – The label of of the landmark manager that you wish to use. If no label is passed, the convex hull of all landmarks is used.

centre()

The geometric centre of the Image - the subpixel that is in the middle.

Useful for aligning shapes and images.

Type(`n_dims`,) *ndarray*

constrain_landmarks_to_bounds()

Move landmarks that are located outside the image bounds on the bounds.

constrain_mask_to_landmarks(*group=None*, *label=None*, *batch_size=None*, *point_in_pointcloud='pwa'*, *trilist=None*)

Restricts this mask to be equal to the convex hull around the chosen landmarks.

The choice of whether a pixel is inside or outside of the pointcloud is determined by the `point_in_pointcloud` parameter. By default a Piecewise Affine transform is used to test for containment, which is useful when building efficiently aligning images. For large images, a faster and pixel-accurate method can be used ('convex_hull'). Alternatively, a callable can be provided to override the test. By default, the provided implementations are only valid for 2D images.

Parameters

- **group** (*str*, optional) – The key of the landmark set that should be used. If `None`, and if there is only one set of landmarks, this set will be used.
- **label** (*str*, optional) – The label of of the landmark manager that you wish to use. If no label is passed, the convex hull of all landmarks is used.
- **batch_size** (*int* or `None`, optional) – This should only be considered for large images. Setting this value will cause constraining to become much slower. This size indicates how many points in the image should be checked at a time, which keeps memory usage low. If `None`, no batching is used and all points are checked at once. By default, this is only used for the 'pwa' point_in_pointcloud choice.
- **point_in_pointcloud** ({'pwa', 'convex_hull'} or *callable*) – The method used to check if pixels in the image fall inside the pointcloud or not. Can be accurate to a Piecewise Affine transform, a pixel accurate convex hull or any arbitrary callable. If a callable is passed, it should take two parameters, the `PointCloud` to constrain with and the pixel locations ((d, n_dims) ndarray) to test and should return a (d, 1) boolean ndarray of whether the pixels were inside (True) or outside (False) of the `PointCloud`.
- **trilist** (`(t, 3)` *ndarray*, optional) – Deprecated. Please provide a Trimesh instead of relying on this parameter.

constrain_points_to_bounds(*points*)

Constrains the points provided to be within the bounds of this image.

Parameterspoints (`(d,)` *ndarray*) – Points to be snapped to the image boundaries.

Returnsbounded_points (`(d,)` *ndarray*) – Points snapped to not stray outside the image edges.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other `Copyable` objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns `type(self)` – A copy of this object

crop(*min_indices*, *max_indices*, *constrain_to_boundary=False*)

Return a cropped copy of this image using the given minimum and maximum indices. Landmarks are correctly adjusted so they maintain their position relative to the newly cropped image.

Parameters

- **min_indices** (`(n_dims,)` *ndarray*) – The minimum index over each dimension.
- **max_indices** (`(n_dims,)` *ndarray*) – The maximum index over each dimension.
- **constrain_to_boundary** (*bool*, optional) – If `True` the crop will be snapped to not go beyond this images boundary. If `False`, an `ImageBoundaryError` will be raised if an attempt is made to go beyond the edge of the image.

Returns **cropped_image** (*type(self)*) – A new instance of self, but cropped.

Raises

- `ValueError` – `min_indices` and `max_indices` both have to be of length `n_dims`. All `max_indices` must be greater than `min_indices`.
- `ImageBoundaryError` – Raised if `constrain_to_boundary=False`, and an attempt is made to crop the image in a way that violates the image bounds.

crop_inplace(**args*, ***kwargs*)

Deprecated: please use `crop()` instead.

crop_to_landmarks(*group=None*, *label=None*, *boundary=0*, *constrain_to_boundary=True*)

Return a copy of this image cropped so that it is bounded around a set of landmarks with an optional `n_pixel` boundary

Parameters

- **group** (*str*, optional) – The key of the landmark set that should be used. If `None` and if there is only one set of landmarks, this set will be used.
- **label** (*str*, optional) – The label of of the landmark manager that you wish to use. If `None` all landmarks in the group are used.
- **boundary** (*int*, optional) – An extra padding to be added all around the landmarks bounds.
- **constrain_to_boundary** (*bool*, optional) – If `True` the crop will be snapped to not go beyond this images boundary. If `False`, an :map'ImageBoundaryError' will be raised if an attempt is made to go beyond the edge of the image.

Returns **image** (`Image`) – A copy of this image cropped to its landmarks.

Raises `ImageBoundaryError` – Raised if `constrain_to_boundary=False`, and an attempt is made to crop the image in a way that violates the image bounds.

crop_to_landmarks_inplace(**args*, ***kwargs*)

Deprecated: please use `crop_to_landmarks()` instead.

crop_to_landmarks_proportion(*boundary_proportion*, *group=None*, *label=None*, *minimum=True*, *constrain_to_boundary=True*)

Crop this image to be bounded around a set of landmarks with a border proportional to the landmark spread or range.

Parameters

- **boundary_proportion** (*float*) – Additional padding to be added all around the landmarks bounds defined as a proportion of the landmarks range. See the

minimum parameter for a definition of how the range is calculated.

- **group** (*str*, optional) – The key of the landmark set that should be used. If `None` and if there is only one set of landmarks, this set will be used.
- **label** (*str*, optional) – The label of of the landmark manager that you wish to use. If `None` all landmarks in the group are used.
- **minimum** (*bool*, optional) – If `True` the specified proportion is relative to the minimum value of the landmarks' per-dimension range; if `False` w.r.t. the maximum value of the landmarks' per-dimension range.
- **constrain_to_boundary** (*bool*, optional) – If `True`, the crop will be snapped to not go beyond this images boundary. If `False`, an `ImageBoundaryError` will be raised if an attempt is made to go beyond the edge of the image.

Returnsimage (`Image`) – This image, cropped to its landmarks with a border proportional to the landmark spread or range.

Raises`ImageBoundaryError` – Raised if `constrain_to_boundary=False`, and an attempt is made to crop the image in a way that violates the image bounds.

crop_to_landmarks_proportion_inplace(**args*, ***kwargs*)

Deprecated: please use `crop_to_landmarks_proportion()` instead.

crop_to_true_mask(*boundary=0*, *constrain_to_boundary=True*)

Crop this image to be bounded just the *True* values of it's mask.

Parameters

- **boundary** (*int*, optional) – An extra padding to be added all around the true mask region.
- **constrain_to_boundary** (*bool*, optional) – If `True` the crop will be snapped to not go beyond this images boundary. If `False`, an `ImageBoundaryError` will be raised if an attempt is made to go beyond the edge of the image. Note that is only possible if `boundary != 0`.

Returnscropped_image (`type(self)`) – A copy of this image, cropped to the true mask.

Raises`ImageBoundaryError` – Raised if 11constrain_to_boundary=False'1, and an attempt is made to crop the image in a way that violates the image bounds.

diagonal()

The diagonal size of this image

Type*float*

dilate(*n_pixels=1*)

Returns a copy of this `MaskedImage` in which its mask has been expanded by n pixels along its boundary.

Parametersn_pixels (*int, optional*) – The number of pixels by which we want to expand the mask along its own boundary.

Returns`MaskedImage` – The copy of the masked image in which the mask has been expanded by n pixels along its boundary.

erode(*n_pixels=1*)

Returns a copy of this `MaskedImage` in which the mask has been shrunk by n pixels along its boundary.

Parametersn_pixels (*int, optional*) – The number of pixels by which we want to shrink the mask along its own boundary.

Returns`MaskedImage` – The copy of the masked image in which the mask has been shrunk by n pixels along its boundary.

extract_channels(*channels*)

A copy of this image with only the specified channels.

Parameterschannels (*int* or *[int]*) – The channel index or *list* of channel indices to retain.

Returnsimage (*type(self)*) – A copy of this image with only the channels requested.

extract_patches(*patch_centers*, *patch_size=(16, 16)*, *sample_offsets=None*, *as_single_array=False*)

Extract a set of patches from an image. Given a set of patch centers and a patch size, patches are extracted from within the image, centred on the given coordinates. Sample offsets denote a set of offsets to extract from within a patch. This is very useful if you want to extract a dense set of features around a set of landmarks and simply sample the same grid of patches around the landmarks.

If sample offsets are used, to access the offsets for each patch you need to slice the resulting list. So for 2 offsets, the first centers offset patches would be `patches[:2]`.

Currently only 2D images are supported.

Parameters

- **patch_centers** (*PointCloud*) – The centers to extract patches around.
- **patch_size** (*tuple* or *ndarray*, optional) – The size of the patch to extract
- **sample_offsets** (*PointCloud*, optional) – The offsets to sample from within a patch. So (0, 0) is the centre of the patch (no offset) and (1, 0) would be sampling the patch from 1 pixel up the first axis away from the centre.
- **as_single_array** (*bool*, optional) – If `True`, an `(n_center * n_offset, self.shape...)` *ndarray*, thus a single numpy array is returned containing each patch. If `False`, a *list* of *Image* objects is returned representing each patch.

Returns **patches** (*list* or *ndarray*) – Returns the extracted patches. Returns a list if `as_single_array=True` and an *ndarray* if `as_single_array=False`.

Raises `ValueError` – If image is not 2D

extract_patches_around_landmarks(*group=None*, *label=None*, *patch_size=(16, 16)*, *sample_offsets=None*, *as_single_array=False*)

Extract patches around landmarks existing on this image. Provided the group label and optionally the landmark label extract a set of patches.

See *extract_patches* for more information.

Currently only 2D images are supported.

Parameters

- **group** (*str* or `None` optional) – The landmark group to use as patch centres.
- **label** (*str* or `None` optional) – The landmark label within the group to use as centres.
- **patch_size** (*tuple* or *ndarray*, optional) – The size of the patch to extract
- **sample_offsets** (*PointCloud*, optional) – The offsets to sample from within a patch. So (0,0) is the centre of the patch (no offset) and (1, 0) would be sampling the patch from 1 pixel up the first axis away from the centre.
- **as_single_array** (*bool*, optional) – If `True`, an `(n_center * n_offset, self.shape...)` *ndarray*, thus a single numpy array is returned containing each patch. If `False`, a *list* of *Image* objects is returned representing each patch.

Returns **patches** (*list* or *ndarray*) – Returns the extracted patches. Returns a list if `as_single_array=True` and an *ndarray* if `as_single_array=False`.

Raises `ValueError` – If image is not 2D

from_vector(*vector*, *n_channels=None*)

Takes a flattened vector and returns a new image formed by reshaping the vector to the correct pixels and channels. Note that the only region of the image that will be filled is the masked region.

On masked images, the vector is always copied.

The `n_channels` argument is useful for when we want to add an extra channel to an image but maintain the shape. For example, when calculating the gradient.

Note that landmarks are transferred in the process.

Parameters

- **vector** ((n_pixels,)) – A flattened vector of all pixels and channels of an image.
- **n_channels** (*int*, optional) – If given, will assume that vector is the same shape as this image, but with a possibly different number of channels.

Returnsimage (MaskedImage) – New image of same shape as this image and the number of specified channels.

from_vector_inplace(*vector*, *copy=True*)

Takes a flattened vector and updates this image by reshaping the vector to the correct pixels and channels. Note that the only region of the image that will be filled is the masked region.

Parameters

- **vector** ((n_parameters,)) – A flattened vector of all pixels and channels of an image.
- **copy** (*bool*, optional) – If False, the vector will be set as the pixels with no copy made. If True a copy of the vector is taken.

RaisesWarning – If copy=False cannot be honored.

gaussian_pyramid(*n_levels=3*, *downscale=2*, *sigma=None*)

Return the gaussian pyramid of this image. The first image of the pyramid will be the original, unmodified, image, and counts as level 1.

Parameters

- **n_levels** (*int*, optional) – Total number of levels in the pyramid, including the original unmodified image
- **downscale** (*float*, optional) – Downscale factor.
- **sigma** (*float*, optional) – Sigma for gaussian filter. Default is downscale / 3. which corresponds to a filter mask twice the size of the scale factor that covers more than 99% of the gaussian distribution.

Yieldsimage_pyramid (*generator*) – Generator yielding pyramid layers as Image objects.

gradient(***kwargs*)

Returns an Image which is the gradient of this one. In the case of multiple channels, it returns the gradient over each axis over each channel as a flat *list*. Take care to note the ordering of the returned gradient (the gradient over each spatial dimension is taken over each channel).

The first axis of the gradient of a 2D, 3-channel image, will have length *6*, the ordering being I[:, 0, 0] = [R0_y, G0_y, B0_y, R0_x, G0_x, B0_x]. To be clear, all the y-gradients are returned over each channel, then all the x-gradients.

Returnsgradient (Image) – The gradient over each axis over each channel. Therefore, the gradient of a 2D, single channel image, will have length *2*. The length of a 2D, 3-channel image, will have length *6*.

has_nan_values()

Tests if the vectorized form of the object contains nan values or not. This is particularly useful for objects with unknown values that have been mapped to nan values.

Returnshas_nan_values (*bool*) – If the vectorized object contains nan values.

indices()

Return the indices of all true pixels in this image.

Type (n_dims, n_true_pixels) *ndarray*

classmethod init_blank(*shape*, *n_channels=1*, *fill=0*, *dtype=<Mock object>*, *mask=None*)

Generate a blank masked image

Parameters

- **shape** (*tuple* or *list*) – The shape of the image. Any floating point values are rounded up to the nearest integer.
- **n_channels** (*int*, optional) – The number of channels to create the image with.

- **fill** (*int*, optional) – The value to fill all pixels with.
- **dtype** (*numpy datatype*, optional) – The datatype of the image.
- **mask** (`(M, N)` *bool ndarray* or `BooleanImage`) – An optional mask that can be applied to the image. Has to have a shape equal to that of the image.

Notes

Subclasses of `MaskedImage` need to overwrite this method and explicitly call this superclass method

```
super(SubClass, cls).init_blank(shape,**kwargs)
```

in order to appropriately propagate the subclass type to `cls`.

Returnsblank_image (`MaskedImage`) – A new masked image of the requested size.

masked_pixels()

Get the pixels covered by the *True* values in the mask.

Type `(n_channels, mask.n_true)` *ndarray*

n_false_elements()

The number of `False` elements of the image over all the channels.

Type*int*

n_false_pixels()

The number of `False` values in the mask.

Type*int*

n_true_elements()

The number of `True` elements of the image over all the channels.

Type*int*

n_true_pixels()

The number of `True` values in the mask.

Type*int*

normalize_norm_inplace(*mode='all'*, *limit_to_mask=True*, ***kwargs*)

Normalizes this image such that it's pixel values have zero mean and its norm equals 1.

Parameters

- **mode** (`{all, per_channel}`, optional) – If `all`, the normalization is over all channels. If `per_channel`, each channel individually is mean centred and normalized in variance.
- **limit_to_mask** (*bool*, optional) – If `True`, the normalization is only performed wrt the masked pixels. If `False`, the normalization is wrt all pixels, regardless of their masking value.

normalize_std_inplace(*mode='all'*, *limit_to_mask=True*)

Normalizes this image such that it's pixel values have zero mean and unit variance.

Parameters

- **mode** (`{all, per_channel}`, optional) – If `all`, the normalization is over all channels. If `per_channel`, each channel individually is mean centred and normalized in variance.
- **limit_to_mask** (*bool*, optional) – If `True`, the normalization is only performed wrt the masked pixels. If `False`, the normalization is wrt all pixels, regardless of their masking value.

pyramid(*n_levels=3*, *downscale=2*)

Return a rescaled pyramid of this image. The first image of the pyramid will be the original, unmodified, image, and counts as level 1.

Parameters

- **n_levels** (*int*, optional) – Total number of levels in the pyramid, including the original unmodified image
- **downscale** (*float*, optional) – Downscale factor.

Yieldsimage_pyramid (*generator*) – Generator yielding pyramid layers as `Image` objects.

rescale(*scale*, *round='ceil'*, *order=1*)

Return a copy of this image, rescaled by a given factor. Landmarks are rescaled appropriately.

Parameters

- **scale** (*float* or *tuple* of *floats*) – The scale factor. If a tuple, the scale to apply to each dimension. If a single *float*, the scale will be applied uniformly across each dimension.
- **round** (`{ceil, floor, round}`, optional) – Rounding function to be applied to floating point shapes.
- **order** (*int*, optional) – The order of interpolation. The order has to be in the range [0,5]

Order	Interpolation
0	Nearest-neighbor
1	Bi-linear *(default)*
2	Bi-quadratic
3	Bi-cubic
4	Bi-quartic
5	Bi-quintic

Returnsrescaled_image (`type(self)`) – A copy of this image, rescaled.

Raises`ValueError` – If less scales than dimensions are provided. If any scale is less than or equal to 0.

rescale_landmarks_to_diagonal_range(*diagonal_range*, *group=None*, *label=None*, *round='ceil'*, *order=1*)

Return a copy of this image, rescaled so that the diagonal_range of the bounding box containing its landmarks matches the specified diagonal_range range.

Parameters

- **diagonal_range** (`(n_dims,)` *ndarray*) – The diagonal_range range that we want the landmarks of the returned image to have.
- **group** (*str*, optional) – The key of the landmark set that should be used. If `None` and if there is only one set of landmarks, this set will be used.
- **label** (*str*, optional) – The label of of the landmark manager that you wish to use. If `None` all landmarks in the group are used.
- **round** (`{ceil, floor, round}`, optional) – Rounding function to be applied to floating point shapes.
- **order** (*int*, optional) – The order of interpolation. The order has to be in the range [0,5]

Order	Interpolation
0	Nearest-neighbor
1	Bi-linear *(default)*
2	Bi-quadratic
3	Bi-cubic
4	Bi-quartic
5	Bi-quintic

Returnsrescaled_image (`type(self)`) – A copy of this image, rescaled.

rescale_pixels(*minimum*, *maximum*, *per_channel=True*)

A copy of this image with pixels linearly rescaled to fit a range.

Note that the only pixels that will considered and rescaled are those that feature in the vectorized form of this image. If you want to use this routine on all the pixels in a `MaskedImage`, consider using

as_unmasked() prior to this call.

Parameters

- **minimum** (*float*) – The minimal value of the rescaled pixels
- **maximum** (*float*) – The maximal value of the rescaled pixels
- **per_channel** (*boolean*, optional) – If `True`, each channel will be rescaled independently. If `False`, the scaling will be over all channels.

Returnsrescaled_image (`type(self)`) – A copy of this image with pixels linearly rescaled to fit in the range provided.

rescale_to_diagonal(*diagonal*, *round='ceil'*)

Return a copy of this image, rescaled so that the it's diagonal is a new size.

Parameters

- **diagonal** (*int*) – The diagonal size of the new image.
- **round** (`{ceil, floor, round}`, optional) – Rounding function to be applied to floating point shapes.

Returnsrescaled_image (*type(self)*) – A copy of this image, rescaled.

rescale_to_reference_shape(*reference_shape*, *group=None*, *label=None*, *round='ceil'*, *order=1*)

Return a copy of this image, rescaled so that the scale of a particular group of landmarks matches the scale of the passed reference landmarks.

Parameters

- **reference_shape** (`PointCloud`) – The reference shape to which the landmarks scale will be matched against.
- **group** (*str*, optional) – The key of the landmark set that should be used. If `None`, and if there is only one set of landmarks, this set will be used.
- **label** (*str*, optional) – The label of of the landmark manager that you wish to use. If `None` all landmarks in the group are used.
- **round** (`{ceil, floor, round}`, optional) – Rounding function to be applied to floating point shapes.
- **order** (*int*, optional) – The order of interpolation. The order has to be in the range [0,5]

Order	Interpolation
0	Nearest-neighbor
1	Bi-linear *(default)*
2	Bi-quadratic
3	Bi-cubic
4	Bi-quartic
5	Bi-quintic

Returnsrescaled_image (`type(self)`) – A copy of this image, rescaled.

resize(*shape*, *order=1*)

Return a copy of this image, resized to a particular shape. All image information (landmarks, and mask in the case of `MaskedImage`) is resized appropriately.

Parameters

- **shape** (*tuple*) – The new shape to resize to.
- **order** (*int*, optional) – The order of interpolation. The order has to be in the range [0,5]

Order	Interpolation
0	Nearest-neighbor
1	Bi-linear *(default)*
2	Bi-quadratic
3	Bi-cubic
4	Bi-quartic
5	Bi-quintic

Returnsresized_image (`type(self)`) – A copy of this image, resized.

Raises`ValueError` – If the number of dimensions of the new shape does not match the number of dimensions of the image.

rolled_channels()

Returns the pixels matrix, with the channels rolled to the back axis. This may be required for interacting with external code bases that require images to have channels as the last axis, rather than the menpo convention of channels as the first axis.

Returnsrolled_channels (*ndarray*) – Pixels with channels as the back (last) axis.

rotate_ccw_about_centre(*theta*, *degrees=True*, *cval=0.0*)

Return a rotation of this image clockwise about its centre.

Parameters

- **theta** (*float*) – The angle of rotation about the origin.
- **degrees** (*bool*, optional) – If `True`, *theta* is interpreted as a degree. If `False`, `theta` is interpreted as radians.
- **cval** (`float`, optional) – The value to be set outside the rotated image boundaries.

Returnsrotated_image (`type(self)`) – The rotated image.

sample(*points_to_sample*, *order=1*, *mode='constant'*, *cval=0.0*)

Sample this image at the given sub-pixel accurate points. The input PointCloud should have the same number of dimensions as the image e.g. a 2D PointCloud for a 2D multi-channel image. A numpy array will be returned the has the values for every given point across each channel of the image.

If the points to sample are *outside* of the mask (fall on a `False` value in the mask), an exception is raised. This exception contains the information of which points were outside of the mask (`False`) and *also* returns the sampled points.

Parameters

- **points_to_sample** (`PointCloud`) – Array of points to sample from the image. Should be *(n_points, n_dims)*
- **order** (*int*, optional) – The order of interpolation. The order has to be in the range [0,5]. See warp_to_shape for more information.
- **mode** (`{constant, nearest, reflect, wrap}`, optional) – Points outside the boundaries of the input are filled according to the given mode.
- **cval** (*float*, optional) – Used in conjunction with mode `constant`, the value outside the image boundaries.

Returnssampled_pixels ((*n_points*, *n_channels*) *ndarray*) – The interpolated values taken across every channel of the image.

Raises`OutOfMaskSampleError` – One of the points to sample was outside of the valid area of the mask (`False` in the mask). This exception contains both the mask of valid sample points, **as well as** the sampled points themselves, in case you want to ignore the error.

set_boundary_pixels(*value=0.0*, *n_pixels=1*)

Returns a copy of this `MaskedImage` for which n pixels along the its mask boundary have been set to a particular value. This is useful in situations where there is absent data in the image which can cause, for example, erroneous computations of gradient or features.

Parameters

- **value** (*float or (n_channels, 1) ndarray*) –
- **n_pixels** (*int, optional*) – The number of pixels along the mask boundary that will be set to 0.

Returns `MaskedImage` – The copy of the image for which the n pixels along its mask boundary have been set to a particular value.

set_masked_pixels(*pixels*, *copy=True*)

Update the masked pixels only to new values.

Parameters

- **pixels** (*ndarray*) – The new pixels to set.
- **copy** (*bool*, optional) – If `False` a copy will be avoided in assignment. This can only happen if the mask is all `True` - in all other cases it will raise a warning.

Raises `Warning` – If the `copy=False` flag cannot be honored.

view_widget(*browser_style='buttons'*, *figure_size=(10, 8)*, *style='coloured'*)

Visualizes the image object using the `visualize_images` widget. Currently only supports the rendering of 2D images.

Parameters

- **browser_style** (`{'buttons', 'slider'}`, optional) – It defines whether the selector of the images will have the form of plus/minus buttons or a slider.
- **figure_size** ((*int*, *int*), optional) – The initial size of the rendered figure.
- **style** (`{'coloured', 'minimal'}`, optional) – If `'coloured'`, then the style of the widget will be coloured. If `minimal`, then the style is simple using black and white colours.

warp_to_mask(*template_mask*, *transform*, *warp_landmarks=False*, *order=1*, *mode='constant'*, *cval=0.0*, *batch_size=None*)

Warps this image into a different reference space.

Parameters

- **template_mask** (`BooleanImage`) – Defines the shape of the result, and what pixels should be sampled.
- **transform** (`Transform`) – Transform **from the template space back to this image**. Defines, for each pixel location on the template, which pixel location should be sampled from on this image.
- **warp_landmarks** (*bool*, optional) – If `True`, result will have the same landmark dictionary as `self`, but with each landmark updated to the warped position.
- **order** (*int*, optional) – The order of interpolation. The order has to be in the range [0,5]

Order	Interpolation
0	Nearest-neighbor
1	Bi-linear *(default)*
2	Bi-quadratic
3	Bi-cubic
4	Bi-quartic
5	Bi-quintic

- **mode** (`{constant, nearest, reflect, wrap}`, optional) – Points outside the boundaries of the input are filled according to the given mode.
- **cval** (*float*, optional) – Used in conjunction with mode `constant`, the value outside the image boundaries.
- **batch_size** (*int* or `None`, optional) – This should only be considered for large images. Setting this value can cause warping to become much slower, particular for cached warps such as Piecewise Affine. This size indicates how many points in the image should be warped at a time, which keeps memory usage low. If `None`, no batching is used and all points are warped at once.

Returnswarped_image (`type(self)`) – A copy of this image, warped.

warp_to_shape(*template_shape*, *transform*, *warp_landmarks=False*, *order=1*, *mode='constant'*, *cval=0.0*, *batch_size=None*)

Return a copy of this `MaskedImage` warped into a different reference space.

Parameters

- **template_shape** (*tuple* or *ndarray*) – Defines the shape of the result, and what pixel indices should be sampled (all of them).
- **transform** (`Transform`) – Transform **from the template_shape space back to this image**. Defines, for each index on template_shape, which pixel location should be sampled from on this image.
- **warp_landmarks** (*bool*, optional) – If `True`, result will have the same landmark dictionary as self, but with each landmark updated to the warped position.
- **order** (*int*, optional) – The order of interpolation. The order has to be in the range [0,5]

Order	Interpolation
0	Nearest-neighbor
1	Bi-linear *(default)*
2	Bi-quadratic
3	Bi-cubic
4	Bi-quartic
5	Bi-quintic

- **mode** (`{constant, nearest, reflect, wrap}`, optional) – Points outside the boundaries of the input are filled according to the given mode.
- **cval** (*float*, optional) – Used in conjunction with mode `constant`, the value outside the image boundaries.
- **batch_size** (*int* or `None`, optional) – This should only be considered for large images. Setting this value can cause warping to become much slower, particular for cached warps such as Piecewise Affine. This size indicates how many points in the image should be warped at a time, which keeps memory usage low. If `None`, no batching is used and all points are warped at once.

Returnswarped_image (`MaskedImage`) – A copy of this image, warped.

zoom(*scale*, *cval=0.0*)

Zoom this image about the centre point. `scale` values greater than 1.0 denote zooming **in** to the image and values less than 1.0 denote zooming **out** of the image. The size of the image will not change, if you wish to scale an image, please see `rescale()`.

Parameters

- **scale** (*float*) – `scale > 1.0` denotes zooming in. Thus the image will appear larger and areas at the edge of the zoom will be 'cropped' out. `scale < 1.0` denotes zooming out. The image will be padded by the value of `cval`.
- **cval** (`float`, optional) – The value to be set outside the rotated image boundaries.

has_landmarks

Whether the object has landmarks.

Type*bool*

has_landmarks_outside_bounds

Indicates whether there are landmarks located outside the image bounds.

Type*bool*

height

The height of the image.

This is the height according to image semantics, and is thus the size of the **second to last** dimension.

Type*int*

landmarks
The landmarks object.
Type*LandmarkManager*

n_channels
The number of channels on each pixel in the image.
Type*int*

n_dims
The number of dimensions in the image. The minimum possible `n_dims` is 2.
Type*int*

n_elements
Total number of data points in the image `(prod(shape), n_channels)`
Type*int*

n_landmark_groups
The number of landmark groups on this object.
Type*int*

n_parameters
The length of the vector that this object produces.
Type*int*

n_pixels
Total number of pixels in the image `(prod(shape),)`
Type*int*

shape
The shape of the image (with `n_channel` values at each point).
Type*tuple*

width
The width of the image.

This is the width according to image semantics, and is thus the size of the **last** dimension.
Type*int*

2.3.2 Exceptions

ImageBoundaryError

class `menpo.image.`**`ImageBoundaryError`**(*requested_min*, *requested_max*, *snapped_min*, *snapped_max*)

Bases: `ValueError`

Exception that is thrown when an attempt is made to crop an image beyond the edge of it's boundary.

Parameters

- **requested_min** (`(d,)` *ndarray*) – The per-dimension minimum index requested for the crop
- **requested_max** (`(d,)` *ndarray*) – The per-dimension maximum index requested for the crop
- **snapped_min** (`(d,)` *ndarray*) – The per-dimension minimum index that could be used if the crop was constrained to the image boundaries.
- **requested_max** – The per-dimension maximum index that could be used if the crop was constrained to the image boundaries.

2.4 menpo.feature

2.4.1 Features

no_op

`menpo.feature.no_op`(*image*, **args*, ***kwargs*)

A no operation feature - does nothing but return a copy of the pixels passed in.

Parameters **pixels** (*Image* or subclass or `(C, X, Y, ..., Z)` *ndarray*) – Either the image object itself or an array with the pixels. The first dimension is interpreted as channels. This means an N-dimensional image is represented by an N+1 dimensional array.

Returns **pixels** (*Image* or subclass or `(X, Y, ..., Z, C)` *ndarray*) – A copy of the image that was passed in.

gradient

`menpo.feature.gradient`(*image*, **args*, ***kwargs*)

Calculates the gradient of an input image. The image is assumed to have channel information on the first axis. In the case of multiple channels, it returns the gradient over each axis over each channel as the first axis.

The gradient is computed using second order accurate central differences in the interior and first order accurate one-side (forward or backwards) differences at the boundaries.

Parameters **pixels** (*Image* or subclass or `(C, X, Y, ..., Z)` *ndarray*) – Either the image object itself or an array where the first dimension is interpreted as channels. This means an N-dimensional image is represented by an N+1 dimensional array.

Returns **gradient** (*ndarray*) – The gradient over each axis over each channel. Therefore, the first axis of the gradient of a 2D, single channel image, will have length *2*. The first axis of the gradient of a 2D, 3-channel image, will have length *6*, the ordering being `I[:, 0, 0] = [R0_y, G0_y, B0_y, R0_x, G0_x, B0_x]`. To be clear, all the `y`-gradients are returned over each channel, then all the `x`-gradients.

gaussian_filter

`menpo.feature.gaussian_filter`(*image*, **args*, ***kwargs*)

Calculates the convolution of the input image with a multidimensional Gaussian filter.

Parameters

- **pixels** (*Image* or subclass or `(C, X, Y, ..., Z)` *ndarray*) – Either the image object itself or an array with the pixels. The first dimension is interpreted as channels. This means an N-dimensional image is represented by an N+1 dimensional array.
- **sigma** (*float* or *list* of *float*) – The standard deviation for Gaussian kernel. The standard deviations of the Gaussian filter are given for each axis as a *list*, or as a single *float*, in which case it is equal for all axes.

Returns **output_image** (*Image* or subclass or `(X, Y, ..., Z, C)` *ndarray*) – The filtered image has the same type and size as the input `pixels`.

igo

`menpo.feature.igo`(*image*, **args*, ***kwargs*)

Extracts Image Gradient Orientation (IGO) features from the input image. The output image has `N * C` number of channels, where `N` is the number of channels of the original image and `C = 2` or `C = 4` depending on whether double angles are used.

Parameters

- **pixels** (*Image* or subclass or `(C, X, Y, ..., Z)` *ndarray*) – Either the image object itself or an array with the pixels. The first dimension is interpreted as channels. This means an N-dimensional image is represented by an N+1 dimensional array.
- **double_angles** (*bool*, optional) – Assume that `phi` represents the gradient orientations.

  If this flag is `False`, the features image is the concatenation of `cos(phi)` and `sin(phi)`, thus 2 channels.

  If `True`, the features image is the concatenation of `cos(phi)`, `sin(phi)`, `cos(2 * phi)`, `sin(2 * phi)`, thus 4 channels.
- **verbose** (*bool*, optional) – Flag to print IGO related information.

Returnsigo (*Image* or subclass or `(X, Y, ..., Z, C)` *ndarray*) – The IGO features image. It has the same type and shape as the input `pixels`. The output number of channels depends on the `double_angles` flag.

Raises`ValueError` – Image has to be 2D in order to extract IGOs.

References

es

`menpo.feature.`**`es`**(*image*, **args*, ***kwargs*)

Extracts Edge Structure (ES) features from the input image. The output image has `N * C` number of channels, where `N` is the number of channels of the original image and `C = 2`.

Parameters

- **pixels** (*Image* or subclass or `(C, X, Y, ..., Z)` *ndarray*) – Either an image object itself or an array where the first axis represents the number of channels. This means an N-dimensional image is represented by an N+1 dimensional array.
- **verbose** (*bool*, optional) – Flag to print ES related information.

Returnses (*Image* or subclass or `(X, Y, ..., Z, C)` *ndarray*) – The ES features image. It has the same type and shape as the input `pixels`. The output number of channels is `C = 2`.

Raises`ValueError` – Image has to be 2D in order to extract ES features.

References

lbp

`menpo.feature.`**`lbp`**(*image*, **args*, ***kwargs*)

Extracts Local Binary Pattern (LBP) features from the input image. The output image has `N * C` number of channels, where `N` is the number of channels of the original image and `C` is the number of radius/samples values combinations that are used in the LBP computation.

Parameters

- **pixels** (*Image* or subclass or `(C, X, Y, ..., Z)` *ndarray*) – Either the image object itself or an array with the pixels. The first dimension is interpreted as channels. This means an N-dimensional image is represented by an N+1 dimensional array.
- **radius** (*int* or *list* of *int* or `None`, optional) – It defines the radius of the circle (or circles) at which the sampling points will be extracted. The radius (or radii) values must be greater than zero. There must be a radius value for each samples value, thus they both need to have the same length. If `None`, then `[1, 2, 3, 4]` is used.
- **samples** (*int* or *list* of *int* or `None`, optional) – It defines the number of sampling points that will be extracted at each circle. The samples value (or values) must be

greater than zero. There must be a samples value for each radius value, thus they both need to have the same length. If `None`, then `[8, 8, 8, 8]` is used.

- **mapping_type** ({`u2`, `ri`, `riu2`, `none`}, optional) – It defines the mapping type of the LBP codes. Select `u2` for uniform-2 mapping, `ri` for rotation-invariant mapping, `riu2` for uniform-2 and rotation-invariant mapping and `none` to use no mapping and only the decimal values instead.
- **window_step_vertical** (*float*, optional) – Defines the vertical step by which the window is moved, thus it controls the features density. The metric unit is defined by *window_step_unit*.
- **window_step_horizontal** (*float*, optional) – Defines the horizontal step by which the window is moved, thus it controls the features density. The metric unit is defined by *window_step_unit*.
- **window_step_unit** ({`pixels`, `window`}, optional) – Defines the metric unit of the *window_step_vertical* and *window_step_horizontal* parameters.
- **padding** (*bool*, optional) – If `True`, the output image is padded with zeros to match the input image's size.
- **verbose** (*bool*, optional) – Flag to print LBP related information.
- **skip_checks** (*bool*, optional) – If `True`, do not perform any validation of the parameters.

Returns

lbp (`Image` or subclass or `(X, Y, ..., Z, C)` *ndarray*) – The ES features image. It has the same type and shape as the input `pixels`. The output number of channels is `C = len(radius) * len(samples)`.

Raises

- `ValueError` – Radius and samples must both be either integers or lists
- `ValueError` – Radius and samples must have the same length
- `ValueError` – Radius must be > 0
- `ValueError` – Radii must be > 0
- `ValueError` – Samples must be > 0
- `ValueError` – Mapping type must be u2, ri, riu2 or none
- `ValueError` – Horizontal window step must be > 0
- `ValueError` – Vertical window step must be > 0
- `ValueError` – Window step unit must be either pixels or window

References

hog

`menpo.feature.hog`(*image*, **args*, ***kwargs*)

Extracts Histograms of Oriented Gradients (HOG) features from the input image.

Parameters

- **pixels** (`Image` or subclass or `(C, X, Y, ..., Z)` *ndarray*) – Either the image object itself or an array with the pixels. The first dimension is interpreted as channels. This means an N-dimensional image is represented by an N+1 dimensional array.
- **mode** ({`dense`, `sparse`}, optional) – The `sparse` case refers to the traditional usage of HOGs, so predefined parameters values are used.

  The `sparse` case of `dalaltriggs` algorithm sets `window_height = window_width = block_size` and `window_step_horizontal = window_step_vertical = cell_size`.

  The `sparse` case of `zhuramanan` algorithm sets `window_height = window_width = 3 * cell_size` and `window_step_horizontal = window_step_vertical = cell_size`.

  In the `dense` case, the user can choose values for *window_height*, *window_width*,

window_unit, *window_step_vertical*, *window_step_horizontal*, *window_step_unit* and *padding* to customize the HOG calculation.

- **window_height** (*float*, optional) – Defines the height of the window. The metric unit is defined by *window_unit*.
- **window_width** (*float*, optional) – Defines the width of the window. The metric unit is defined by *window_unit*.
- **window_unit** (`{blocks, pixels}`, optional) – Defines the metric unit of the *window_height* and *window_width* parameters.
- **window_step_vertical** (*float*, optional) – Defines the vertical step by which the window is moved, thus it controls the features' density. The metric unit is defined by *window_step_unit*.
- **window_step_horizontal** (*float*, optional) – Defines the horizontal step by which the window is moved, thus it controls the features' density. The metric unit is defined by *window_step_unit*.
- **window_step_unit** (`{pixels, cells}`, optional) – Defines the metric unit of the *window_step_vertical* and *window_step_horizontal* parameters.
- **padding** (*bool*, optional) – If `True`, the output image is padded with zeros to match the input image's size.
- **algorithm** (`{dalaltriggs, zhuramanan}`, optional) – Specifies the algorithm used to compute HOGs. `dalaltriggs` is the implementation of [1] and `zhuramanan` is the implementation of [2].
- **cell_size** (*float*, optional) – Defines the cell size in pixels. This value is set to both the width and height of the cell. This option is valid for both algorithms.
- **block_size** (*float*, optional) – Defines the block size in cells. This value is set to both the width and height of the block. This option is valid only for the `dalaltriggs` algorithm.
- **num_bins** (*float*, optional) – Defines the number of orientation histogram bins. This option is valid only for the `dalaltriggs` algorithm.
- **signed_gradient** (*bool*, optional) – Flag that defines whether we use signed or unsigned gradient angles. This option is valid only for the `dalaltriggs` algorithm.
- **l2_norm_clip** (*float*, optional) – Defines the clipping value of the gradients' L2-norm. This option is valid only for the `dalaltriggs` algorithm.
- **verbose** (*bool*, optional) – Flag to print HOG related information.

Returns **hog** (`Image` or subclass or `(X, Y, ..., Z, K)` *ndarray*) – The HOG features image. It has the same type as the input `pixels`. The output number of channels in the case of `dalaltriggs` is `K = num_bins * block_size *block_size` and `K = 31` in the case of `zhuramanan`.

Raises

- `ValueError` – HOG features mode must be either dense or sparse
- `ValueError` – Algorithm must be either dalaltriggs or zhuramanan
- `ValueError` – Number of orientation bins must be > 0
- `ValueError` – Cell size (in pixels) must be > 0
- `ValueError` – Block size (in cells) must be > 0
- `ValueError` – Value for L2-norm clipping must be > 0.0
- `ValueError` – Window height must be >= block size and <= image height
- `ValueError` – Window width must be >= block size and <= image width
- `ValueError` – Window unit must be either pixels or blocks
- `ValueError` – Horizontal window step must be > 0
- `ValueError` – Vertical window step must be > 0
- `ValueError` – Window step unit must be either pixels or cells

References

dsift

daisy

`menpo.feature.`**`daisy`**(*image*, **args*, ***kwargs*)

Extracts Daisy features from the input image. The output image has `N * C` number of channels, where `N` is the number of channels of the original image and `C` is the feature channels determined by the input options. Specifically, `C = (rings * histograms + 1) * orientations`.

Parameters

- **`pixels`** (*`Image`* or subclass or `(C, X, Y, ..., Z)` *ndarray*) – Either the image object itself or an array with the pixels. The first dimension is interpreted as channels. This means an N-dimensional image is represented by an N+1 dimensional array.
- **`step`** (*int*, optional) – The sampling step that defines the density of the output image.
- **`radius`** (*int*, optional) – The radius (in pixels) of the outermost ring.
- **`rings`** (*int*, optional) – The number of rings to be used.
- **`histograms`** (*int*, optional) – The number of histograms sampled per ring.
- **`orientations`** (*int*, optional) – The number of orientations (bins) per histogram.
- **`normalization`** (*['l1', 'l2', 'daisy', None], optional*) – It defines how to normalize the descriptors If 'l1' then L1-normalization is applied at each descriptor. If 'l2' then L2-normalization is applied at each descriptor. If 'daisy' then L2-normalization is applied at individual histograms. If None then no normalization is employed.
- **`sigmas`** (*list* of *float* or `None`, optional) – Standard deviation of spatial Gaussian smoothing for the centre histogram and for each ring of histograms. The *list* of sigmas should be sorted from the centre and out. I.e. the first sigma value defines the spatial smoothing of the centre histogram and the last sigma value defines the spatial smoothing of the outermost ring. Specifying sigmas overrides the *rings* parameter by setting `rings = len(sigmas) - 1`.
- **`ring_radii`** (*list* of *float* or `None`, optional) – Radius (in pixels) for each ring. Specifying *ring_radii* overrides the *rings* and *radius* parameters by setting `rings = len(ring_radii)` and `radius = ring_radii[-1]`.

  If both sigmas and ring_radii are given, they must satisfy

```
len(ring_radii) == len(sigmas) + 1
```

  since no radius is needed for the centre histogram.
- **`verbose`** (*bool*) – Flag to print Daisy related information.

Returns **daisy** (*`Image`* or subclass or `(X, Y, ..., Z, C)` *ndarray*) – The ES features image. It has the same type and shape as the input `pixels`. The output number of channels is `C = (rings * histograms + 1) * orientations`.

Raises

- `ValueError` – len(sigmas)-1 != len(ring_radii)
- `ValueError` – Invalid normalization method.

References

2.4.2 Visualization

glyph

`menpo.feature.visualize.`**`glyph`**(*image*, **args*, ***kwargs*)

Create the glyph of a feature image that can be used for visualization. If *pixels* have negative values, the

use_negative flag controls whether there will be created a glyph of both positive and negative values concatenated the one on top of the other.

Parameters

- **pixels** (*Image* or subclass or `(C, X, Y, ..., Z)` *ndarray*) – Either the image object itself or an array with the pixels. The first dimension is interpreted as channels.
- **vectors_block_size** (*int*) – Defines the size of each block with vectors of the glyph image.
- **use_negative** (*bool*) – Defines whether to take into account possible negative values of feature_data.
- **channels** (*list* of *int* or `None`) – The list of channels to be used. If `None`, then all the channels are employed.

sum_channels

`menpo.feature.visualize.`**`sum_channels`**`(`*image*, **args*, ***kwargs*`)`

Create the sum of the channels of an image that can be used for visualization.

Parameters

- **pixels** (*Image* or subclass or `(C, X, Y, ..., Z)` *ndarray*) – Either the image object itself or an array with the pixels. The first dimension is interpreted as channels.
- **channels** (*list* of *int* or `None`) – The list of channels to be used. If `None`, then all the channels are employed.

2.4.3 Widget

features_selection_widget

`menpo.feature.`**`features_selection_widget`**`()`

Widget that allows for easy selection of a features function and its options. It also has a 'preview' tab for visual inspection. It returns a *list* of length 1 with the selected features function closure.

Returns

features_function (*list* of length `1`) – The function closure of the features function using *functools.partial*. So the function can be called as:

```
features_image = features_function[0](image)
```

Examples

The widget can be invoked as

```
from menpo.feature import features_selection_widget
features_fun = features_selection_widget()
```

And the returned function can be used as

```
import menpo.io as mio
image = mio.import_builtin_asset.lenna_png()
features_image = features_fun[0](image)
```

2.5 menpo.landmark

2.5.1 Abstract Classes

Landmarkable

class menpo.landmark.**Landmarkable**

Bases: *Copyable*

Abstract interface for object that can have landmarks attached to them. Landmarkable objects have a public dictionary of landmarks which are managed by a *LandmarkManager*. This means that different sets of landmarks can be attached to the same object. Landmarks can be N-dimensional and are expected to be some subclass of *PointCloud*. These landmarks are wrapped inside a *LandmarkGroup* object that performs useful tasks like label filtering and viewing.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns `type(self)` – A copy of this object

n_dims()

The total number of dimensions.

Type *int*

has_landmarks

Whether the object has landmarks.

Type *bool*

landmarks

The landmarks object.

Type *LandmarkManager*

n_landmark_groups

The number of landmark groups on this object.

Type *int*

LabellingError

class menpo.landmark.**LabellingError**

Bases: `Exception`

Raised when labelling a landmark manager and the set of landmarks does not match the expected semantic layout.

2.5.2 Landmarks & Labeller

LandmarkManager

class menpo.landmark.**LandmarkManager**

Bases: `MutableMapping`, *Transformable*

Store for `LandmarkGroup` instances associated with an object

Every `Landmarkable` instance has an instance of this class available at the `.landmarks` property. It is through this class that all access to landmarks attached to instances is handled. In general the `LandmarkManager` provides a dictionary-like interface for storing landmarks. `LandmarkGroup` instances are stored under string keys - these keys are refereed to as the **group name**. A special case is where there is a single unambiguous `LandmarkGroup` attached to a `LandmarkManager` - in this case `None` can be used as a key to access the sole group.

Note that all landmarks stored on a `Landmarkable` in it's attached `LandmarkManager` are automatically transformed and copied with their parent object.

clear() → None. Remove all items from D.

copy()

Generate an efficient copy of this `LandmarkManager`.

Returns `type(self)` – A copy of this object

get(*k*[, *d*]) → D[k] if k in D, else d. d defaults to None.

items() → list of D's (key, value) pairs, as 2-tuples

items_matching(*glob_pattern*)

Yield only items `(group, LandmarkGroup)` where the key matches a given glob.

Parameters **glob_pattern** (*str*) – A glob pattern e.g. 'frontal_face_*'

Yields **item** (`(group, LandmarkGroup)`) – Tuple of group, LandmarkGroup where the group matches the glob

iteritems() → an iterator over the (key, value) items of D

iterkeys() → an iterator over the keys of D

itervalues() → an iterator over the values of D

keys() → list of D's keys

keys_matching(*glob_pattern*)

Yield only landmark group names (keys) matching a given glob.

Parameters **glob_pattern** (*str*) – A glob pattern e.g. 'frontal_face_*'

Yields **keys** (*group labels that match the glob pattern*)

pop(*k*[, *d*]) → v, remove specified key and return the corresponding value.

If key is not found, d is returned if given, otherwise KeyError is raised.

popitem() → (k, v), remove and return some (key, value) pair

as a 2-tuple; but raise KeyError if D is empty.

setdefault(*k*[, *d*]) → D.get(k,d), also set D[k]=d if k not in D

update([*E*], **F) → None. Update D from mapping/iterable E and F.

If E present and has a .keys() method, does: for k in E: D[k] = E[k] If E present and lacks .keys() method, does: for (k, v) in E: D[k] = v In either case, this is followed by: for k, v in F.items(): D[k] = v

values() → list of D's values

view_widget(*browser_style='buttons'*, *figure_size=(10, 8)*, *style='coloured'*)

Visualizes the landmark manager object using the `visualize_landmarks` widget.

Parameters

- **browser_style** (`{'buttons', 'slider'}`, optional) – It defines whether the selector of the landmark managers will have the form of plus/minus buttons or a slider.
- **figure_size** ((*int*, *int*), optional) – The initial size of the rendered figure.

- **style** ({'coloured', 'minimal'}, optional) – If 'coloured', then the style of the widget will be coloured. If minimal, then the style is simple using black and white colours.

group_labels
All the labels for the landmark set.
Type *list* of *str*

has_landmarks
Whether the object has landmarks or not
Type *int*

n_dims
The total number of dimensions.
Type *int*

n_groups
Total number of labels.
Type *int*

LandmarkGroup

class menpo.landmark.**LandmarkGroup**(*pointcloud*, *labels_to_masks*, *copy=True*)
Bases: MutableMapping, *Copyable*, Viewable

An immutable object that holds a *PointCloud* (or a subclass) and stores labels for each point. These labels are defined via masks on the *PointCloud*. For this reason, the *PointCloud* is considered to be immutable.

The labels to masks must be within an *OrderedDict* so that semantic ordering can be maintained.

Parameters
- **pointcloud** (*PointCloud*) – The pointcloud representing the landmarks.
- **labels_to_masks** (*ordereddict* {*str* -> *bool ndarray*}) – For each label, the mask that specifies the indices in to the pointcloud that belong to the label.
- **copy** (*bool*, optional) – If True, a copy of the *PointCloud* is stored on the group.

Raises
- ValueError – If *dict* passed instead of *OrderedDict*
- ValueError – If no set of label masks is passed.
- ValueError – If any of the label masks differs in size to the pointcloud.
- ValueError – If there exists any point in the pointcloud that is not covered by a label.

clear() → None. Remove all items from D.

copy()
Generate an efficient copy of this *LandmarkGroup*.
Returns type(self) – A copy of this object

get(*k*[, *d*]) → D[k] if k in D, else d. d defaults to None.

has_nan_values()
Tests if the LandmarkGroup contains nan values or not. This is particularly useful for annotations with unknown values or non-visible landmarks that have been mapped to nan values.
Returns **has_nan_values** (*bool*) – If the LandmarkGroup contains nan values.

classmethod init_with_all_label(*pointcloud*, *copy=True*)
Static constructor to create a *LandmarkGroup* with a single default 'all' label that covers all points.
Parameters
- **pointcloud** (*PointCloud*) – The pointcloud representing the landmarks.

- **copy** (*boolean*, optional) – If `True`, a copy of the `PointCloud` is stored on the group.

Returnslmark_group (`LandmarkGroup`) – Landmark group wrapping the given pointcloud with a single label called 'all' that is `True` for all points.

items() → list of D's (key, value) pairs, as 2-tuples

iteritems() → an iterator over the (key, value) items of D

iterkeys() → an iterator over the keys of D

itervalues() → an iterator over the values of D

keys() → list of D's keys

pop(*k*[, *d*]) → v, remove specified key and return the corresponding value.
If key is not found, d is returned if given, otherwise KeyError is raised.

popitem() → (k, v), remove and return some (key, value) pair
as a 2-tuple; but raise KeyError if D is empty.

setdefault(*k*[, *d*]) → D.get(k,d), also set D[k]=d if k not in D

tojson()
Convert this *LandmarkGroup* to a dictionary JSON representation.

Returnsjson (`dict`) – Dictionary conforming to the LJSON v2 specification.

update([*E*], **F) → None. Update D from mapping/iterable E and F.
If E present and has a .keys() method, does: for k in E: D[k] = E[k] If E present and lacks .keys() method, does: for (k, v) in E: D[k] = v In either case, this is followed by: for k, v in F.items(): D[k] = v

values() → list of D's values

view_widget(*browser_style='buttons', figure_size=(10, 8), style='coloured'*)
Visualizes the landmark group object using the `visualize_landmarkgroups` widget.

Parameters

- **browser_style** (`{'buttons', 'slider'}`, optional) – It defines whether the selector of the landmark managers will have the form of plus/minus buttons or a slider.
- **figure_size** ((*int*, *int*), optional) – The initial size of the rendered figure.
- **style** (`{'coloured', 'minimal'}`, optional) – If `'coloured'`, then the style of the widget will be coloured. If `minimal`, then the style is simple using black and white colours.

with_labels(*labels=None*)
A new landmark group that contains only the certain labels

Parameterslabels (*str* or *list* of *str*, optional) – Labels that should be kept in the returned landmark group. If `None` is passed, and if there is only one label on this group, the label will be substituted automatically.

Returnslandmark_group (`LandmarkGroup`) – A new landmark group with the same group label but containing only the given label.

without_labels(*labels*)
A new landmark group that excludes certain labels label.

Parameterslabels (*str* or *list* of *str*) – Labels that should be excluded in the returned landmark group.

Returnslandmark_group (`LandmarkGroup`) – A new landmark group with the same group label but containing all labels except the given label.

labels
The list of labels that belong to this group.

Type*list* of *str*

lms
The pointcloud representing all the landmarks in the group.
Type*PointCloud*

n_dims
The dimensionality of these landmarks.
Type*int*

n_labels
Number of labels in the group.
Type*int*

n_landmarks
The total number of landmarks in the group.
Type*int*

labeller

`menpo.landmark.`**`labeller`**(*landmarkable*, *group*, *label_func*)

Re-label an existing landmark group on a `Landmarkable` object with a new label set.

Parameters
- **landmarkable** (`Landmarkable`) – `Landmarkable` that will have it's `LandmarkManager` augmented with a new `LandmarkGroup`
- **group** (*str*) – The group label of the existing landmark group that should be re-labelled. A copy of this group will be attached to it's landmark manager with new labels. The group label of this new group and the labels it will have is determined by `label_func`
- **label_func** (*func -> (str, LandmarkGroup)*) – A labelling function taken from this module, Takes as input a `LandmarkGroup` and returns a tuple of (new group label, new LandmarkGroup with semantic labels applied).

Returnslandmarkable (`Landmarkable`) – Augmented `landmarkable` (this is just for convenience, the object will actually be modified in place)

2.5.3 Face Labels

ibug_face_49

`menpo.landmark.`**`ibug_face_49`**(*landmark_group*)

Apply the ibug's "standard" 49 point semantic labels (based on the original semantic labels of multiPIE but removing the annotations corresponding to the jaw region and the 2 describing the inner mouth corners) to the landmark group.

The group label will be `ibug_face_49`.

The semantic labels applied are as follows:
- left_eyebrow
- right_eyebrow
- nose
- left_eye
- right_eye
- mouth

Parameterslandmark_group (`LandmarkGroup`) – The landmark group to apply semantic labels to.

Returns
- **group** (*str*) – The group label: `ibug_face_49`
- **landmark_group** (*LandmarkGroup*) – New landmark group.

Raises `error` (*LabellingError*) – If the given landmark group contains less than 68 points

References

ibug_face_51

`menpo.landmark.`**`ibug_face_51`**(*landmark_group*)

Apply the ibug's "standard" 51 point semantic labels (based on the original semantic labels of multiPIE but removing the annotations corresponding to the jaw region) to the landmark group.

The group label will be `ibug_face_51`.

The semantic labels applied are as follows:
- left_eyebrow
- right_eyebrow
- nose
- left_eye
- right_eye
- mouth

Parameters **`landmark_group`** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns
- **group** (*str*) – The group label: `ibug_face_51`
- **landmark_group** (*LandmarkGroup*) – New landmark group.

Raises `error` (*LabellingError*) – If the given landmark group contains less than 68 points

References

ibug_face_66

`menpo.landmark.`**`ibug_face_66`**(*landmark_group*)

Apply the ibug's "standard" 66 point semantic labels (based on the original semantic labels of multiPIE but ignoring the 2 points describing the inner mouth corners) to the landmark group.

The group label will be `ibug_face_66`.

The semantic labels applied are as follows:
- jaw
- left_eyebrow
- right_eyebrow
- nose
- left_eye
- right_eye
- mouth

Parameters **`landmark_group`** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns
- **group** (*str*) – The group label: `ibug_face_66`
- **landmark_group** (*LandmarkGroup*) – New landmark group.

Raises`error` (*LabellingError*) – If the given landmark group contains less than 68 points

References

ibug_face_68

`menpo.landmark.`**`ibug_face_68`**(*landmark_group*)

Apply the ibug's "standard" 68 point semantic labels (based on the original semantic labels of multiPIE) to the landmark group.

The group label will be `ibug_face_68`.

The semantic labels applied are as follows:

- jaw
- left_eyebrow
- right_eyebrow
- nose
- left_eye
- right_eye
- mouth

Parameters **`landmark_group`** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns

- **group** (*str*) – The group label: `ibug_face_68`
- **landmark_group** (*LandmarkGroup*) – New landmark group.

Raises`error` (*LabellingError*) – If the given landmark group contains less than 68 points

References

ibug_face_68_trimesh

`menpo.landmark.`**`ibug_face_68_trimesh`**(*landmark_group*)

Apply the ibug's "standard" 68 point triangulation to the landmarks in the given landmark group.

The group label will be `ibug_face_68_trimesh`.

The semantic labels applied are as follows:

- tri

Parameters **`landmark_group`** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns

- **group** (*str*) – The group label: `ibug_face_68_trimesh`
- **landmark_group** (*LandmarkGroup*) – New landmark group.

Raises`error` (*LabellingError*) – If the given landmark group contains less than 68 points

References

ibug_face_65_closed_mouth

`menpo.landmark.`**`ibug_face_65_closed_mouth`**(*landmark_group*)

Apply the ibug's "standard" 68 point semantic labels (based on the original semantic labels of multiPIE) to

the landmarks in the given landmark group - but ignore the 3 points that are coincident for a closed mouth. Therefore, there only 65 points are returned.

The group label will be `ibug_face_65_closed_mouth`.

The semantic labels applied are as follows:

- jaw
- left_eyebrow
- right_eyebrow
- nose
- left_eye
- right_eye
- mouth

Parameters **landmark_group** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns

- **group** (*str*) – The group label: `ibug_face_65_closed_mouth`
- **landmark_group** (*LandmarkGroup*) – New landmark group.

Raises `error` (*LabellingError*) – If the given landmark group contains less than 68 points

References

imm_face

`menpo.landmark.`**`imm_face`**(*landmark_group*)

Apply the 58 point semantic labels from the IMM dataset to the landmarks in the given landmark group.

The group label will be `imm_face`.

The semantic labels applied are as follows:

- jaw
- left_eye
- right_eye
- left_eyebrow
- right_eyebrow
- mouth
- nose

Parameters **landmark_group** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns

- **group** (*str*) – The group label: `imm_face`
- **landmark_group** (*LandmarkGroup*) – New landmark group

Raises `error` (*LabellingError*) – If the given landmark group contains less than 58 points

References

lfpw_face

`menpo.landmark.`**`lfpw_face`**(*landmark_group*)

Apply the 29 point semantic labels from the LFPW dataset to the landmarks in the given landmark group.

The group label will be `lfpw_face`.

The semantic labels applied are as follows:

- chin
- left_eye
- right_eye
- left_eyebrow
- right_eyebrow
- mouth
- nose

Parameters **landmark_group** (`LandmarkGroup`) – The landmark group to apply semantic labels to.

Returns

- **group** (*str*) – The group label: `lfpw_face`
- **landmark_group** (*LandmarkGroup*) – New landmark group

Raises `error` (*LabellingError*) – If the given landmark group contains less than 29 points

References

bu3dfe_83

`menpo.landmark.`**`bu3dfe_83`**(*landmark_group*)

Apply the BU-3DFE (Binghamton University 3D Facial Expression) Database 83 point facial annotation markup to this landmark group.

The group label will be `bu3dfe_83`.

The semantic labels applied are as follows:

- right_eye
- left_eye
- right_eyebrow
- left_eyebrow
- right_nose
- left_nose
- nostrils
- outer_mouth
- inner_mouth
- jaw

Parameters **landmark_group** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns

- **group** (*str*) – The group label: `bu3dfe_83`
- **landmark_group** (*LandmarkGroup*) – New landmark group.

Raises class:*menpo.landmark.exceptions.LabellingError* – If the given landmark group contains less than 83 points

References

2.5.4 Eyes Labels

ibug_open_eye

menpo.landmark.**ibug_open_eye**(*landmark_group*)

Apply the ibug's "standard" open eye semantic labels to the landmarks in the given landmark group.

The group label will be `ibug_open_eye`.

The semantic labels applied are as follows:

- upper_eyelid
- lower_eyelid
- iris
- pupil
- sclera

Parameters **landmark_group** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns

- **group** (*str*) – The group label: `ibug_open_eye`
- **landmark_group** (*LandmarkGroup*) – New landmark group.

Raises `error` (*LabellingError*) – If the given landmark group contains less than 38 points

ibug_open_eye_trimesh

menpo.landmark.**ibug_open_eye_trimesh**(*landmark_group*)

Apply the ibug's "standard" open eye semantic labels to the landmarks in the given landmark group.

The group label will be `ibug_open_eye_trimesh`.

The semantic labels applied are as follows:

- tri

Parameters **landmark_group** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns

- **group** (*str*) – The group label: `ibug_open_eye_trimesh`
- **landmark_group** (*LandmarkGroup*) – New landmark group.

Raises `error` (*LabellingError*) – If the given landmark group contains less than 38 points

ibug_close_eye_trimesh

menpo.landmark.**ibug_close_eye_trimesh**(*landmark_group*)

Apply the ibug's "standard" close eye semantic labels to the landmarks in the given landmark group.

The group label will be `ibug_close_eye_trimesh`.

The semantic labels applied are as follows:

- tri

Parameters **landmark_group** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns

- **group** (*str*) – The group label: `ibug_close_eye_trimesh`
- **landmark_group** (*LandmarkGroup*) – New landmark group.

Raises `error` (*LabellingError*) – If the given landmark group contains less than 38 points

ibug_close_eye_points

`menpo.landmark.`**`ibug_close_eye_points`**(*landmark_group*)

Apply the ibug's "standard" close eye semantic labels to the landmarks in the given landmark group.

The group label will be `ibug_close_eye`.

The semantic labels applied are as follows:

- upper_eyelid
- lower_eyelid

Parameters **`landmark_group`** (`LandmarkGroup`) – The landmark group to apply semantic labels to.

Returns

- **group** (*str*) – The group label: `ibug_close_eye`
- **landmark_group** (`LandmarkGroup`) – New landmark group.

Raises `error` (`LabellingError`) – If the given landmark group contains less than 17 points

2.5.5 Hands Labels

ibug_hand

`menpo.landmark.`**`ibug_hand`**(*landmark_group*)

Apply the ibug's "standard" 39 point semantic labels to the landmark group.

The group label will be `ibug_hand`.

The semantic labels applied are as follows:

- thumb
- index
- middle
- ring
- pinky
- palm

Parameters **`landmark_group`** (`LandmarkGroup`) – The landmark group to apply semantic labels to.

Returns

- **group** (*str*) – The group label: `ibug_hand`
- **landmark_group** (`LandmarkGroup`) – New landmark group.

Raises `error` (`LabellingError`) – If the given landmark group contains less than 39 points

2.5.6 Pose Labels

stickmen_pose

`menpo.landmark.`**`stickmen_pose`**(*landmark_group*)

Apply the stickmen "standard" 12 point semantic labels to the landmark group.

The group label will be `stickmen_pose`.

The semantic labels applied are as follows:

- torso
- right_upper_arm
- left_upper_arm
- right_lower_arm

- left_lower_arm
- head

Parameters **landmark_group** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns
- **group** (*str*) – The group label: `stickmen_pose`
- **landmark_group** (*LandmarkGroup*) – New landmark group.

Raises `error` (*LabellingError*) – If the given landmark group contains less than 12 points

References

flic_pose

`menpo.landmark.`**`flic_pose`**(*landmark_group*)

Apply the flic "standard" 11 point semantic labels to the landmark group.

The group label will be `flic_pose`.

The semantic labels applied are as follows:
- left_arm
- right_arm
- hips
- face

Parameters **landmark_group** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns
- **group** (*str*) – The group label: `flic_pose`
- **landmark_group** (*LandmarkGroup*) – New landmark group.

Raises `error` (*LabellingError*) – If the given landmark group contains less than 11 points

References

lsp_pose

`menpo.landmark.`**`lsp_pose`**(*landmark_group*)

Apply the lsp "standard" 14 point semantic labels to the landmark group.

The group label will be `lsp_pose`.

The semantic labels applied are as follows:
- left_leg
- right_leg
- left_arm
- right_arm
- head

Parameters **landmark_group** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns
- **group** (*str*) – The group label: `lsp_pose`
- **landmark_group** (*LandmarkGroup*) – New landmark group.

Raises `error` (*LabellingError*) – If the given landmark group contains less than 14 points

References

2.5.7 Car Labels

streetscene_car_view_0

menpo.landmark.**streetscene_car_view_0**(*landmark_group*)

Apply the 8 point semantic labels of the view 0 of the MIT Street Scene Car dataset to the landmark group.

The group label will be `streetscene_car_view_0`.

The semantic labels applied are as follows:

- front
- bonnet
- windshield

Parameters **landmark_group** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns

- **group** (*str*) – The group label: `streetscene_car_view_0`
- **landmark_group** (*LandmarkGroup*) – New landmark group.

Raises `error` (*LabellingError*) – If the given landmark group contains less than 20 points

References

streetscene_car_view_1

menpo.landmark.**streetscene_car_view_1**(*landmark_group*)

Apply the 14 point semantic labels of the view 1 of the MIT Street Scene Car dataset to the landmark group.

The group label will be `streetscene_car_view_1`.

The semantic labels applied are as follows:

- front
- bonnet
- windshield
- left_side

Parameters **landmark_group** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns

- **group** (*str*) – The group label: `streetscene_car_view_1`
- **landmark_group** (*LandmarkGroup*) – New landmark group.

Raises `error` (*LabellingError*) – If the given landmark group contains less than 20 points

References

streetscene_car_view_2

menpo.landmark.**streetscene_car_view_2**(*landmark_group*)

Apply the 10 point semantic labels of the view 2 of the MIT Street Scene Car dataset to the landmark group.

The group label will be `streetscene_car_view_2`.

The semantic labels applied are as follows:
- left_side

Parameters **landmark_group** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns
- **group** (*str*) – The group label: 'streetscene_car_view_2'
- **landmark_group** (*LandmarkGroup*) – New landmark group.

Raises `error` (*LabellingError*) – If the given landmark group contains less than 20 points

References

streetscene_car_view_3

`menpo.landmark.`**`streetscene_car_view_3`**(*landmark_group*)

Apply the 14 point semantic labels of the view 3 of the MIT Street Scene Car dataset to the landmark group.

The group label will be `streetscene_car_view_2`.

The semantic labels applied are as follows:
- left_side
- rear windshield
- trunk
- rear

Parameters **landmark_group** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns
- **group** (*str*) – The group label: `streetscene_car_view_3`
- **landmark_group** (*LandmarkGroup*) – New landmark group.

Raises `error` (*LabellingError*) – If the given landmark group contains less than 20 points

References

streetscene_car_view_4

`menpo.landmark.`**`streetscene_car_view_4`**(*landmark_group*)

Apply the 14 point semantic labels of the view 4 of the MIT Street Scene Car dataset to the landmark group.

The group label will be `streetscene_car_view_4`.

The semantic labels applied are as follows:
- front
- bonnet
- windshield
- right_side

Parameters **landmark_group** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns
- **group** (*str*) – The group label: 'streetscene_car_view_4'
- **landmark_group** (*LandmarkGroup*) – New landmark group.

Raises `error` (*LabellingError*) – If the given landmark group contains less than 20 points

References

streetscene_car_view_5

menpo.landmark.**streetscene_car_view_5**(*landmark_group*)

Apply the 10 point semantic labels of the view 5 of the MIT Street Scene Car dataset to the landmark group.

The group label will be `streetscene_car_view_5`.

The semantic labels applied are as follows:

- right_side

Parameters **landmark_group** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns

- **group** (*str*) – The group label: `streetscene_car_view_5`
- **landmark_group** (*LandmarkGroup*) – New landmark group.

Raises `error` (*LabellingError*) – If the given landmark group contains less than 20 points

References

streetscene_car_view_6

menpo.landmark.**streetscene_car_view_6**(*landmark_group*)

Apply the 14 point semantic labels of the view 6 of the MIT Street Scene Car dataset to the landmark group.

The group label will be `streetscene_car_view_6`.

The semantic labels applied are as follows:

- right_side
- rear_windshield
- trunk
- rear

Parameters **landmark_group** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns

- **group** (*str*) – The group label: `streetscene_car_view_3`
- **landmark_group** (*LandmarkGroup*) – New landmark group.

Raises `error` (*LabellingError*) – If the given landmark group contains less than 20 points

References

streetscene_car_view_7

menpo.landmark.**streetscene_car_view_7**(*landmark_group*)

Apply the 8 point semantic labels of the view 0 of the MIT Street Scene Car dataset to the landmark group.

The group label will be `streetscene_car_view_7`.

The semantic labels applied are as follows:

- rear_windshield
- trunk

•rear

Parameters **landmark_group** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns

•**group** (*str*) – The group label: `streetscene_car_view_7`

•**landmark_group** (*LandmarkGroup*) – New landmark group.

Raises `error` (*LabellingError*) – If the given landmark group contains less than 20 points

References

2.5.8 Tongue Labels

ibug_tongue

`menpo.landmark.`**`ibug_tongue`**(*landmark_group*)

Apply the ibug's "standard" tongue semantic labels to the landmarks in the given landmark group.

The group label will be `ibug_tongue`.

The semantic labels applied are as follows:

•outline

•bisector

Parameters **landmark_group** (*LandmarkGroup*) – The landmark group to apply semantic labels to.

Returns

•**group** (*str*) – The group label: `ibug_tongue`

•**landmark_group** (*LandmarkGroup*) – New landmark group.

Raises `error` (*LabellingError*) – If the given landmark group contains less than 19 points

2.6 menpo.math

2.6.1 Decomposition

eigenvalue_decomposition

`menpo.math.`**`eigenvalue_decomposition`**(*C*, *eps=1e-10*)

Eigenvalue decomposition of a given covariance (or scatter) matrix.

Parameters

•**C** (`(N, N)` *ndarray*) – Covariance/Scatter matrix

•**eps** (*float*, optional) – Tolerance value for positive eigenvalue. Those eigenvalues smaller than the specified eps value, together with their corresponding eigenvectors, will be automatically discarded. The final limit is computed as

```
limit = np.max(np.abs(eigenvalues)) * eps
```

Returns

•**pos_eigenvectors** (`(N, p)` *ndarray*) – The matrix with the eigenvectors corresponding to positive eigenvalues.

•**pos_eigenvalues** (`(p,)` *ndarray*) – The array of positive eigenvalues.

ipca

`menpo.math.ipca`(*B*, *U_a*, *l_a*, *n_a*, *m_a=None*, *f=1.0*, *eps=1e-10*)

Perform Incremental PCA on the eigenvectors `U_a`, eigenvalues `l_a` and mean vector `m_a` (if present) given a new data matrix `B`.

Parameters

- **B** (`(n_samples, n_dims)` *ndarray*) – New data matrix.
- **U_a** (`(n_components, n_dims)` *ndarray*) – Eigenvectors to be updated.
- **l_a** ((n_components) *ndarray*) – Eigenvalues to be updated.
- **n_a** (*int*) – Total number of samples used to produce U_a, s_a and m_a.
- **m_a** (`(n_dims,)` *ndarray*, optional) – Mean to be updated. If `None` or `(n_dims,)` *ndarray* filled with 0s the data matrix will not be centred.
- **f** (`[0, 1]` *float*, optional) – Forgetting factor that weights the relative contribution of new samples vs old samples. If 1.0, all samples are weighted equally and, hence, the results is the exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples. See [1] for details.
- **eps** (*float*, optional) – Tolerance value for positive eigenvalue. Those eigenvalues smaller than the specified eps value, together with their corresponding eigenvectors, will be automatically discarded.

Returns

- **U (eigenvectors)** (`(n_components, n_dims)` *ndarray*) – Updated eigenvectors.
- **s (eigenvalues)** (`(n_components,)` *ndarray*) – Updated positive eigenvalues.
- **m (mean vector)** (`(n_dims,)` *ndarray*) – Updated mean.

References

pca

`menpo.math.pca`(*X*, *centre=True*, *inplace=False*, *eps=1e-10*)

Apply Principal Component Analysis (PCA) on the data matrix *X*. In the case where the data matrix is very large, it is advisable to set `inplace = True`. However, note this destructively edits the data matrix by subtracting the mean inplace.

Parameters

- **X** (`(n_samples, n_dims)` *ndarray*) – Data matrix.
- **centre** (*bool*, optional) – Whether to centre the data matrix. If *False*, zero will be subtracted.
- **inplace** (*bool*, optional) – Whether to do the mean subtracting inplace or not. This is crucial if the data matrix is greater than half the available memory size.
- **eps** (*float*, optional) – Tolerance value for positive eigenvalue. Those eigenvalues smaller than the specified eps value, together with their corresponding eigenvectors, will be automatically discarded.

Returns

- **U (eigenvectors)** (`(``(n_components, n_dims))`` *ndarray*) – Eigenvectors of the data matrix.
- **l (eigenvalues)** (`(n_components,)` *ndarray*) – Positive eigenvalues of the data matrix.
- **m (mean vector)** (`(n_dimensions,)` *ndarray*) – Mean that was subtracted from the data matrix.

2.6.2 Linear Algebra

dot_inplace_right

`menpo.math.dot_inplace_right`(*a*, *b*, *block_size=1000*)

Inplace dot product for memory efficiency. It computes `a * b = c` where `b` will be replaced inplace with `c`.

Parameters

- **a** (`(n_small, k)` *ndarray*, n_small <= k) – The first array to dot - assumed to be small. `n_small` must be smaller than `k` so the result can be stored within the memory space of `b`.
- **b** (`(k, n_big)` *ndarray*) – Second array to dot - assumed to be large. Will be damaged by this function call as it is used to store the output inplace.
- **block_size** (*int*, optional) – The size of the block of `b` that `a` will be dotted against in each iteration. larger block sizes increase the time performance of the dot product at the cost of a higher memory overhead for the operation.

Returnsc (`(n_small, n_big)` *ndarray*) – The output of the operation. Exactly the same as a memory view onto `b` (`b[:n_small]`) as `b` is modified inplace to store the result.

dot_inplace_left

`menpo.math.dot_inplace_left`(*a*, *b*, *block_size=1000*)

Inplace dot product for memory efficiency. It computes `a * b = c`, where `a` will be replaced inplace with `c`.

Parameters

- **a** (`(n_big, k)` *ndarray*) – First array to dot - assumed to be large. Will be damaged by this function call as it is used to store the output inplace.
- **b** (`(k, n_small)` *ndarray*, `n_small <= k`) – The second array to dot - assumed to be small. `n_small` must be smaller than `k` so the result can be stored within the memory space of `a`.
- **block_size** (*int*, optional) – The size of the block of `a` that will be dotted against `b` in each iteration. larger block sizes increase the time performance of the dot product at the cost of a higher memory overhead for the operation.

Returnsc (`(n_big, n_small)` *ndarray*) – The output of the operation. Exactly the same as a memory view onto `a` (`a[:, :n_small]`) as `a` is modified inplace to store the result.

as_matrix

`menpo.math.as_matrix`(*vectorizables*, *length=None*, *return_template=False*, *verbose=False*)

Create a matrix from a list/generator of `Vectorizable` objects. All the objects in the list **must** be the same size when vectorized.

Consider using a generator if the matrix you are creating is large and passing the length of the generator explicitly.

Parameters

- **vectorizables** (*list* or generator if `Vectorizable` objects) – A list or generator of objects that supports the vectorizable interface
- **length** (*int*, optional) – Length of the vectorizable list. Useful if you are passing a generator with a known length.
- **verbose** (*bool*, optional) – If `True`, will print the progress of building the matrix.
- **return_template** (*bool*, optional) – If `True`, will return the first element of the list/generator, which was used as the template. Useful if you need to map back from the matrix to a list of vectorizable objects.

Returns

- **M** ((length, n_features) *ndarray*) – Every row is an element of the list.

- **template** (*Vectorizable*, optional) – If `return_template == True`, will return the template used to build the matrix *M*.

Raises `ValueError` – `vectorizables` terminates in fewer than `length` iterations

from_matrix

`menpo.math.`**`from_matrix`**(*matrix*, *template*)

Create a generator from a matrix given a template *Vectorizable* objects as a template. The `from_vector` method will be used to reconstruct each object.

If you want a list, warp the returned value in `list()`.

Parameters

- **matrix** ((n_items, n_features) *ndarray*) – A matrix whereby every *row* represents the data of a vectorizable object.
- **template** (*Vectorizable*) – The template object to use to reconstruct each row of the matrix with.

Returns **vectorizables** (generator of *Vectorizable*) – Every row of the matrix becomes an element of the list.

2.6.3 Convolution

log_gabor

`menpo.math.`**`log_gabor`**(*image*, ***kwargs*)

Creates a log-gabor filter bank, including smoothing the images via a low-pass filter at the edges.

To create a 2D filter bank, simply specify the number of phi orientations (orientations in the xy-plane).

To create a 3D filter bank, you must specify both the number of phi (azimuth) and theta (elevation) orientations.

This algorithm is directly derived from work by Peter Kovesi.

Parameters

- **image** (`(M, N, ...)` *ndarray*) – Image to be convolved
- **num_scales** (*int*, optional) – Number of wavelet scales.

Default 2D	4
Default 3D	4

- **num_phi_orientations** (*int*, optional) – Number of filter orientations in the xy-plane

Default 2D	6
Default 3D	6

- **num_theta_orientations** (*int*, optional) – **Only required for 3D**. Number of filter orientations in the z-plane

Default 2D	N/A
Default 3D	4

- **min_wavelength** (*int*, optional) – Wavelength of smallest scale filter.

Default 2D	3
Default 3D	3

- **scaling_constant** (*int*, optional) – Scaling factor between successive filters.

Default 2D	2
Default 3D	2

- **center_sigma** (*float*, optional) – Ratio of the standard deviation of the Gaussian describing the Log Gabor filter's transfer function in the frequency domain to the filter centre frequency.

Default 2D	0.65
Default 3D	0.65

- **d_phi_sigma** (*float*, optional) – Angular bandwidth in xy-plane

Default 2D	1.3
Default 3D	1.5

- **d_theta_sigma** (*float*, optional) – **Only required for 3D**. Angular bandwidth in z-plane

Default 2D	N/A
Default 3D	1.5

Returns

- **complex_conv** ((num_scales, num_orientations, image.shape) *ndarray*) – Complex valued convolution results. The real part is the result of convolving with the even symmetric filter, the imaginary part is the result from convolution with the odd symmetric filter.
- **bandpass** ((num_scales, image.shape) *ndarray*) – Bandpass images corresponding to each scale *s*
- **S** ((image.shape,) *ndarray*) – Convolved image

Examples

Return the magnitude of the convolution over the image at scale *s* and orientation *o*

```
np.abs(complex_conv[s, o, :, :])
```

Return the phase angles

```
np.angle(complex_conv[s, o, :, :])
```

References

2.7 menpo.model

2.7.1 LinearModel

class menpo.model.**LinearModel**(*components*)

Bases: *Copyable*

A Linear Model contains a matrix of vector components, each component vector being made up of *features*.

Parameters **components** ((n_components, n_features) *ndarray*) – The components array.

component_vector(*index*)

A particular component of the model, in vectorized form.

Parameters **index** (*int*) – The component that is to be returned.

Returns **component_vector** ((n_features,) *ndarray*) – The component vector.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other `Copyable` objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns `type(self)` – A copy of this object

instance_vector(*weights*)

Creates a new vector instance of the model by weighting together the components.

Parameters **weights** (`(n_weights,)` *ndarray* or *list*) – The weightings for the first *n_weights* components that should be used.

`weights[j]` is the linear contribution of the j'th principal component to the instance vector.

Returns **vector** (`(n_features,)` *ndarray*) – The instance vector for the weighting provided.

instance_vectors(*weights*)

Creates new vectorized instances of the model using all the components of the linear model.

Parameters **weights** (`(n_vectors, n_weights)` *ndarray* or *list* of *lists*) – The weightings for all components of the linear model. All components will be used to produce the instance.

`weights[i, j]` is the linear contribution of the j'th principal component to the i'th instance vector produced.

Raises `ValueError` – If n_weights > n_available_components

Returns **vectors** (`(n_vectors, n_features)` *ndarray*) – The instance vectors for the weighting provided.

orthonormalize_against_inplace(*linear_model*)

Enforces that the union of this model's components and another are both mutually orthonormal.

Both models keep its number of components unchanged or else a value error is raised.

Parameters **linear_model** (`LinearModel`) – A second linear model to orthonormalize this against.

Raises `ValueError` – The number of features must be greater or equal than the sum of the number of components in both linear models ({} < {})

orthonormalize_inplace()

Enforces that this model's components are orthonormalized, s.t. `component_vector(i).dot(component_vector(j) = dirac_delta`.

project_out_vector(*vector*)

Returns a version of *vector* where all the basis of the model have been projected out.

Parameters **vector** (`(n_features,)` *ndarray*) – A novel vector.

Returns **projected_out** (`(n_features,)` *ndarray*) – A copy of *vector* with all basis of the model projected out.

project_out_vectors(*vectors*)

Returns a version of *vectors* where all the basis of the model have been projected out.

Parameters **vectors** (`(n_vectors, n_features)` *ndarray*) – A matrix of novel vectors.

Returns **projected_out** (`(n_vectors, n_features)` *ndarray*) – A copy of *vectors* with all basis of the model projected out.

project_vector(*vector*)

Projects the *vector* onto the model, retrieving the optimal linear reconstruction weights.

Parameters **vector** (`(n_features,)` *ndarray*) – A vectorized novel instance.

Returns **weights** (`(n_components,)` *ndarray*) – A vector of optimal linear weights.

project_vectors(*vectors*)

Projects each of the *vectors* onto the model, retrieving the optimal linear reconstruction weights for each instance.

Parameters
vectors ((n_samples, n_features) *ndarray*) – Array of vectorized novel instances.

Returns
weights ((n_samples, n_components) *ndarray*) – The matrix of optimal linear weights.

reconstruct_vector(*vector*)

Project a *vector* onto the linear space and rebuild from the weights found.

Parameters
vector ((n_features,) *ndarray*) – A vectorized novel instance to project.

Returns
reconstructed ((n_features,) *ndarray*) – The reconstructed vector.

reconstruct_vectors(*vectors*)

Projects the *vectors* onto the linear space and rebuilds vectors from the weights found.

Parameters
vectors ((n_vectors, n_features) *ndarray*) – A set of vectors to project.

Returns
reconstructed ((n_vectors, n_features) *ndarray*) – The reconstructed vectors.

components

The components matrix of the linear model.

Type (n_available_components, n_features) *ndarray*

n_components

The number of bases of the model.

Type *int*

n_features

The number of elements in each linear component.

Type *int*

2.7.2 InstanceLinearModel

class menpo.model.**InstanceLinearModel**(*components*)

Bases: LinearModel, InstanceBackedModel

Mixin of LinearModel and InstanceBackedModel objects.

Parameters
- **components** ((n_components, n_features) *ndarray*) – The components array.
- **template_instance** (*Vectorizable*) – The template instance.

component(*index*)

A particular component of the model, in vectorized form.

Parameters
index (*int*) – The component that is to be returned.

Returns
component_vector (*type(self.template_instance)*) – The component vector.

component_vector(*index*)

A particular component of the model, in vectorized form.

Parameters
index (*int*) – The component that is to be returned.

Returns
component_vector ((n_features,) *ndarray*) – The component vector.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns `type(self)` – A copy of this object

instance(*weights*)

Creates a new instance of the model using the first `len(weights)` components.

Parameters **weights** (`(n_weights,)` *ndarray* or *list*) – `weights[i]` is the linear contribution of the i'th component to the instance vector.

Raises `ValueError` – If n_weights > n_components

Returns **instance** (*type(self.template_instance)*) – An instance of the model.

instance_vector(*weights*)

Creates a new vector instance of the model by weighting together the components.

Parameters **weights** (`(n_weights,)` *ndarray* or *list*) – The weightings for the first *n_weights* components that should be used.

`weights[j]` is the linear contribution of the j'th principal component to the instance vector.

Returns **vector** (`(n_features,)` *ndarray*) – The instance vector for the weighting provided.

instance_vectors(*weights*)

Creates new vectorized instances of the model using all the components of the linear model.

Parameters **weights** (`(n_vectors, n_weights)` *ndarray* or *list* of *lists*) – The weightings for all components of the linear model. All components will be used to produce the instance.

`weights[i, j]` is the linear contribution of the j'th principal component to the i'th instance vector produced.

Raises `ValueError` – If n_weights > n_available_components

Returns **vectors** (`(n_vectors, n_features)` *ndarray*) – The instance vectors for the weighting provided.

orthonormalize_against_inplace(*linear_model*)

Enforces that the union of this model's components and another are both mutually orthonormal.

Both models keep its number of components unchanged or else a value error is raised.

Parameters **linear_model** (*LinearModel*) – A second linear model to orthonormalize this against.

Raises `ValueError` – The number of features must be greater or equal than the sum of the number of components in both linear models ({} < {})

orthonormalize_inplace()

Enforces that this model's components are orthonormalized, s.t. `component_vector(i).dot(component_vector(j) = dirac_delta`.

project(*instance*)

Projects the *instance* onto the model, retrieving the optimal linear weightings.

Parameters **novel_instance** (*Vectorizable*) – A novel instance.

Returns **projected** (`(n_components,)` *ndarray*) – A vector of optimal linear weightings.

project_out(*instance*)

Returns a version of *instance* where all the basis of the model have been projected out.

Parameters **instance** (`Vectorizable`) – A novel instance of `Vectorizable`.

Returns **projected_out** (*self.instance_class*) – A copy of *instance*, with all basis of the model projected out.

project_out_vector(*vector*)

Returns a version of *vector* where all the basis of the model have been projected out.

Parameters`vector` (`(n_features,)` *ndarray*) – A novel vector.
Returns`projected_out` (`(n_features,)` *ndarray*) – A copy of *vector* with all basis of the model projected out.

`project_out_vectors`(*vectors*)
Returns a version of *vectors* where all the basis of the model have been projected out.
Parameters`vectors` (`(n_vectors, n_features)` *ndarray*) – A matrix of novel vectors.
Returns`projected_out` (`(n_vectors, n_features)` *ndarray*) – A copy of *vectors* with all basis of the model projected out.

`project_vector`(*vector*)
Projects the *vector* onto the model, retrieving the optimal linear reconstruction weights.
Parameters`vector` (`(n_features,)` *ndarray*) – A vectorized novel instance.
Returns`weights` (`(n_components,)` *ndarray*) – A vector of optimal linear weights.

`project_vectors`(*vectors*)
Projects each of the *vectors* onto the model, retrieving the optimal linear reconstruction weights for each instance.
Parameters`vectors` (`(n_samples, n_features)` *ndarray*) – Array of vectorized novel instances.
Returns`weights` (`(n_samples, n_components)` *ndarray*) – The matrix of optimal linear weights.

`reconstruct`(*instance*)
Projects a *instance* onto the linear space and rebuilds from the weights found.

Syntactic sugar for:

```
instance(project(instance))
```

but faster, as it avoids the conversion that takes place each time.
Parameters`instance` (`Vectorizable`) – A novel instance of `Vectorizable`.
Returns`reconstructed` (*self.instance_class*) – The reconstructed object.

`reconstruct_vector`(*vector*)
Project a *vector* onto the linear space and rebuild from the weights found.
Parameters`vector` (`(n_features, )` *ndarray*) – A vectorized novel instance to project.
Returns`reconstructed` (`(n_features,)` *ndarray*) – The reconstructed vector.

`reconstruct_vectors`(*vectors*)
Projects the *vectors* onto the linear space and rebuilds vectors from the weights found.
Parameters`vectors` (`(n_vectors, n_features)` *ndarray*) – A set of vectors to project.
Returns`reconstructed` (`(n_vectors, n_features)` *ndarray*) – The reconstructed vectors.

`components`
The components matrix of the linear model.
Type `(n_available_components, n_features)` *ndarray*

`n_components`
The number of bases of the model.
Type*int*

`n_features`
The number of elements in each linear component.
Type*int*

2.7.3 MeanLinearModel

class `menpo.model.`**`MeanLinearModel`**(*components*, *mean_vector*)

Bases: `LinearModel`

A Linear Model containing a matrix of vector components, each component vector being made up of *features*. The model additionally has a mean component which is handled accordingly when either:

1. A component of the model is selected
2. A projection operation is performed

Parameters

- **`components`** (`(n_components, n_features)` *ndarray*) – The components array.
- **`mean_vector`** (`(n_features,)` *ndarray*) – The mean vector.

`component_vector`(*index*, *with_mean=True*, *scale=1.0*)

A particular component of the model, in vectorized form.

Parameters

- **`index`** (*int*) – The component that is to be returned
- **`with_mean`** (*bool*, optional) – If `True`, the component will be blended with the mean vector before being returned. If not, the component is returned on it's own.
- **`scale`** (*float*, optional) – A scale factor that should be directly applied to the component. Only valid in the case where `with_mean == True`.

Returns`component_vector` (`(n_features,)` *ndarray*) – The component vector.

`copy`()

Generate an efficient copy of this object.

Note that Numpy arrays and other `Copyable` objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns`type(self)` – A copy of this object

`instance_vector`(*weights*)

Creates a new vector instance of the model by weighting together the components.

Parameters`weights` (`(n_weights,)` *ndarray* or *list*) – The weightings for the first *n_weights* components that should be used.

`weights[j]` is the linear contribution of the j'th principal component to the instance vector.

Returns`vector` (`(n_features,)` *ndarray*) – The instance vector for the weighting provided.

`instance_vectors`(*weights*)

Creates new vectorized instances of the model using all the components of the linear model.

Parameters`weights` (`(n_vectors, n_weights)` *ndarray* or *list* of *lists*) – The weightings for all components of the linear model. All components will be used to produce the instance.

`weights[i, j]` is the linear contribution of the j'th principal component to the i'th instance vector produced.

Raises`ValueError` – If n_weights > n_available_components

Returns`vectors` (`(n_vectors, n_features)` *ndarray*) – The instance vectors for the weighting provided.

orthonormalize_against_inplace(*linear_model*)

Enforces that the union of this model's components and another are both mutually orthonormal.

Both models keep its number of components unchanged or else a value error is raised.

Parameters **linear_model** (*LinearModel*) – A second linear model to orthonormalize this against.

Raises ValueError – The number of features must be greater or equal than the sum of the number of components in both linear models ({} < {})

orthonormalize_inplace()

Enforces that this model's components are orthonormalized, s.t. `component_vector(i).dot(component_vector(j) = dirac_delta`.

project_out_vector(*vector*)

Returns a version of *vector* where all the basis of the model have been projected out.

Parameters **vector** ((n_features,) *ndarray*) – A novel vector.

Returns **projected_out** ((n_features,) *ndarray*) – A copy of *vector* with all basis of the model projected out.

project_out_vectors(*vectors*)

Returns a version of *vectors* where all the basis of the model have been projected out.

Parameters **vectors** ((n_vectors, n_features) *ndarray*) – A matrix of novel vectors.

Returns **projected_out** ((n_vectors, n_features) *ndarray*) – A copy of *vectors* with all basis of the model projected out.

project_vector(*vector*)

Projects the *vector* onto the model, retrieving the optimal linear reconstruction weights.

Parameters **vector** ((n_features,) *ndarray*) – A vectorized novel instance.

Returns **weights** ((n_components,) *ndarray*) – A vector of optimal linear weights.

project_vectors(*vectors*)

Projects each of the *vectors* onto the model, retrieving the optimal linear reconstruction weights for each instance.

Parameters **vectors** ((n_samples, n_features) *ndarray*) – Array of vectorized novel instances.

Returns **projected** ((n_samples, n_components) *ndarray*) – The matrix of optimal linear weights.

reconstruct_vector(*vector*)

Project a *vector* onto the linear space and rebuild from the weights found.

Parameters **vector** ((n_features,) *ndarray*) – A vectorized novel instance to project.

Returns **reconstructed** ((n_features,) *ndarray*) – The reconstructed vector.

reconstruct_vectors(*vectors*)

Projects the *vectors* onto the linear space and rebuilds vectors from the weights found.

Parameters **vectors** ((n_vectors, n_features) *ndarray*) – A set of vectors to project.

Returns **reconstructed** ((n_vectors, n_features) *ndarray*) – The reconstructed vectors.

components

The components matrix of the linear model.

Type (n_available_components, n_features) *ndarray*

n_components

The number of bases of the model.

Type *int*

n_features
The number of elements in each linear component.
Type*int*

2.7.4 MeanInstanceLinearModel

class `menpo.model.`**`MeanInstanceLinearModel`**(*components*, *mean_vector*, *template_instance*)
Bases: `MeanLinearModel`, `InstanceBackedModel`

Mixin of `MeanLinearModel` and `InstanceBackedModel` objects.
Parameters
- **components** (`(n_components, n_features)` *ndarray*) – The components array.
- **mean_vector** (`(n_features,)` *ndarray*) – The mean vector.
- **template_instance** (`Vectorizable`) – The template instance.

component(*index*, *with_mean=True*, *scale=1.0*)
Return a particular component of the linear model.
Parameters
- **index** (*int*) – The component that is to be returned
- **with_mean** (*bool*, optional) – If `True`, the component will be blended with the mean vector before being returned. If not, the component is returned on it's own.
- **scale** (*float*, optional) – A scale factor that should be applied to the component. Only valid in the case where `with_mean == True`. See `component_vector()` for how this scale factor is interpreted.

Returnscomponent (*type(self.template_instance)*) – The requested component.

component_vector(*index*, *with_mean=True*, *scale=1.0*)
A particular component of the model, in vectorized form.
Parameters
- **index** (*int*) – The component that is to be returned
- **with_mean** (*bool*, optional) – If `True`, the component will be blended with the mean vector before being returned. If not, the component is returned on it's own.
- **scale** (*float*, optional) – A scale factor that should be directly applied to the component. Only valid in the case where `with_mean == True`.

Returnscomponent_vector (`(n_features,)` *ndarray*) – The component vector.

copy()
Generate an efficient copy of this object.

Note that Numpy arrays and other `Copyable` objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.
Returns`type(self)` – A copy of this object

instance(*weights*)
Creates a new instance of the model using the first `len(weights)` components.
Parametersweights (`(n_weights,)` *ndarray* or *list*) – `weights[i]` is the linear contribution of the i'th component to the instance vector.
Raises`ValueError` – If n_weights > n_components
Returnsinstance (*type(self.template_instance)*) – An instance of the model.

instance_vector(*weights*)
Creates a new vector instance of the model by weighting together the components.

Parameters **weights** ((n_weights,) *ndarray* or *list*) – The weightings for the first *n_weights* components that should be used.

`weights[j]` is the linear contribution of the j'th principal component to the instance vector.

Returns **vector** ((n_features,) *ndarray*) – The instance vector for the weighting provided.

instance_vectors(*weights*)

Creates new vectorized instances of the model using all the components of the linear model.

Parameters **weights** ((n_vectors, n_weights) *ndarray* or *list* of *lists*) – The weightings for all components of the linear model. All components will be used to produce the instance.

`weights[i, j]` is the linear contribution of the j'th principal component to the i'th instance vector produced.

Raises `ValueError` – If n_weights > n_available_components

Returns **vectors** ((n_vectors, n_features) *ndarray*) – The instance vectors for the weighting provided.

mean()

Return the mean of the model.

Type *Vectorizable*

orthonormalize_against_inplace(*linear_model*)

Enforces that the union of this model's components and another are both mutually orthonormal.

Both models keep its number of components unchanged or else a value error is raised.

Parameters **linear_model** (*LinearModel*) – A second linear model to orthonormalize this against.

Raises `ValueError` – The number of features must be greater or equal than the sum of the number of components in both linear models ({} < {})

orthonormalize_inplace()

Enforces that this model's components are orthonormalized, s.t. `component_vector(i).dot(component_vector(j) = dirac_delta`.

project(*instance*)

Projects the *instance* onto the model, retrieving the optimal linear weightings.

Parameters **novel_instance** (*Vectorizable*) – A novel instance.

Returns **projected** ((n_components,) *ndarray*) – A vector of optimal linear weightings.

project_out(*instance*)

Returns a version of *instance* where all the basis of the model have been projected out.

Parameters **instance** (`Vectorizable`) – A novel instance of `Vectorizable`.

Returns **projected_out** (*self.instance_class*) – A copy of *instance*, with all basis of the model projected out.

project_out_vector(*vector*)

Returns a version of *vector* where all the basis of the model have been projected out.

Parameters **vector** ((n_features,) *ndarray*) – A novel vector.

Returns **projected_out** ((n_features,) *ndarray*) – A copy of *vector* with all basis of the model projected out.

project_out_vectors(*vectors*)

Returns a version of *vectors* where all the basis of the model have been projected out.

Parameters **vectors** ((n_vectors, n_features) *ndarray*) – A matrix of novel vectors.

Returnsprojected_out ((n_vectors, n_features) *ndarray*) – A copy of *vectors* with all basis of the model projected out.

project_vector(*vector*)

Projects the *vector* onto the model, retrieving the optimal linear reconstruction weights.

Parametersvector ((n_features,) *ndarray*) – A vectorized novel instance.

Returnsweights ((n_components,) *ndarray*) – A vector of optimal linear weights.

project_vectors(*vectors*)

Projects each of the *vectors* onto the model, retrieving the optimal linear reconstruction weights for each instance.

Parametersvectors ((n_samples, n_features) *ndarray*) – Array of vectorized novel instances.

Returnsprojected ((n_samples, n_components) *ndarray*) – The matrix of optimal linear weights.

reconstruct(*instance*)

Projects a *instance* onto the linear space and rebuilds from the weights found.

Syntactic sugar for:

```
instance(project(instance))
```

but faster, as it avoids the conversion that takes place each time.

Parametersinstance (Vectorizable) – A novel instance of Vectorizable.

Returnsreconstructed (*self.instance_class*) – The reconstructed object.

reconstruct_vector(*vector*)

Project a *vector* onto the linear space and rebuild from the weights found.

Parametersvector ((n_features,) *ndarray*) – A vectorized novel instance to project.

Returnsreconstructed ((n_features,) *ndarray*) – The reconstructed vector.

reconstruct_vectors(*vectors*)

Projects the *vectors* onto the linear space and rebuilds vectors from the weights found.

Parametersvectors ((n_vectors, n_features) *ndarray*) – A set of vectors to project.

Returnsreconstructed ((n_vectors, n_features) *ndarray*) – The reconstructed vectors.

components

The components matrix of the linear model.

Type (n_available_components, n_features) *ndarray*

n_components

The number of bases of the model.

Type*int*

n_features

The number of elements in each linear component.

Type*int*

2.7.5 PCAModel

class menpo.model.**PCAModel**(*samples*, *centre=True*, *n_samples=None*, *verbose=False*)

Bases: MeanInstanceLinearModel

A *MeanInstanceLinearModel* where components are Principal Components.

Principal Component Analysis (PCA) by eigenvalue decomposition of the data's scatter matrix. For details of the implementation of PCA, see `pca`.

Parameters

- **samples** (*list* or *iterable* of `Vectorizable`) – List or iterable of samples to build the model from.
- **centre** (*bool*, optional) – When `True` (default) PCA is performed after mean centering the data. If `False` the data is assumed to be centred, and the mean will be `0`.
- **n_samples** (*int*, optional) – If provided then `samples` must be an iterator that yields `n_samples`. If not provided then samples has to be a *list* (so we know how large the data matrix needs to be).

component(*index*, *with_mean=True*, *scale=1.0*)

Return a particular component of the linear model.

Parameters

- **index** (*int*) – The component that is to be returned
- **with_mean** (*bool*, optional) – If `True`, the component will be blended with the mean vector before being returned. If not, the component is returned on it's own.
- **scale** (*float*, optional) – A scale factor that should be applied to the component. Only valid in the case where `with_mean == True`. See `component_vector()` for how this scale factor is interpreted.

Returnscomponent (*type(self.template_instance)*) – The requested component.

component_vector(*index*, *with_mean=True*, *scale=1.0*)

A particular component of the model, in vectorized form.

Parameters

- **index** (*int*) – The component that is to be returned
- **with_mean** (*bool*, optional) – If `True`, the component will be blended with the mean vector before being returned. If not, the component is returned on it's own.
- **scale** (*float*, optional) – A scale factor that should be applied to the component. Only valid in the case where with_mean is `True`. The scale is applied in units of standard deviations (so a scale of `1.0` *with_mean* visualizes the mean plus `1` std. dev of the component in question).

Returnscomponent_vector (`(n_features,)` *ndarray*) – The component vector of the given index.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other `Copyable` objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns`type(self)` – A copy of this object

eigenvalues_cumulative_ratio()

Returns the cumulative ratio between the variance captured by the active components and the total amount of variance present on the original samples.

Returnseigenvalues_cumulative_ratio (`(n_active_components,)` *ndarray*) – Array of cumulative eigenvalues.

eigenvalues_ratio()

Returns the ratio between the variance captured by each active component and the total amount of variance present on the original samples.

Returnseigenvalues_ratio ((n_active_components,) *ndarray*) – The active eigenvalues array scaled by the original variance.

increment(*samples*, *n_samples=None*, *forgetting_factor=1.0*, *verbose=False*)

Update the eigenvectors, eigenvalues and mean vector of this model by performing incremental PCA on the given samples.

Parameters

- **samples** (*list* of `Vectorizable`) – List of new samples to update the model from.
- **n_samples** (*int*, optional) – If provided then `samples` must be an iterator that yields `n_samples`. If not provided then samples has to be a list (so we know how large the data matrix needs to be).
- **forgetting_factor** ([0.0, 1.0] *float*, optional) – Forgetting factor that weights the relative contribution of new samples vs old samples. If 1.0, all samples are weighted equally and, hence, the results is the exact same as performing batch PCA on the concatenated list of old and new simples. If <1.0, more emphasis is put on the new samples. See [1] for details.

References

instance(*weights*)

Creates a new instance of the model using the first `len(weights)` components.

Parametersweights ((n_weights,) *ndarray* or *list*) – `weights[i]` is the linear contribution of the i'th component to the instance vector.

Raises`ValueError` – If n_weights > n_components

Returnsinstance (*type(self.template_instance)*) – An instance of the model.

instance_vector(*weights*)

Creates a new vector instance of the model by weighting together the components.

Parametersweights ((n_weights,) *ndarray* or *list*) – The weightings for the first *n_weights* components that should be used.

`weights[j]` is the linear contribution of the j'th principal component to the instance vector.

Returnsvector ((n_features,) *ndarray*) – The instance vector for the weighting provided.

instance_vectors(*weights*)

Creates new vectorized instances of the model using the first components in a particular weighting.

Parametersweights ((n_vectors, n_weights) *ndarray* or *list* of *lists*) – The weightings for the first *n_weights* components that should be used per instance that is to be produced

`weights[i, j]` is the linear contribution of the j'th principal component to the i'th instance vector produced. Note that if `n_weights < n_components`, only the first `n_weight` components are used in the reconstruction (i.e. unspecified weights are implicitly `0`).

Returnsvectors ((n_vectors, n_features) *ndarray*) – The instance vectors for the weighting provided.

Raises`ValueError` – If n_weights > n_components

inverse_noise_variance()

Returns the inverse of the noise variance.

Returnsinverse_noise_variance (*float*) – Inverse of the noise variance.

Raises`ValueError` – If `noise_variance() == 0`

mean()

Return the mean of the model.

Type *Vectorizable*

noise_variance()

Returns the average variance captured by the inactive components, i.e. the sample noise assumed in a Probabilistic PCA formulation.

If all components are active, then `noise_variance == 0.0`.

Returns **noise_variance** (*float*) – The mean variance of the inactive components.

noise_variance_ratio()

Returns the ratio between the noise variance and the total amount of variance present on the original samples.

Returns **noise_variance_ratio** (*float*) – The ratio between the noise variance and the variance present in the original samples.

original_variance()

Returns the total amount of variance captured by the original model, i.e. the amount of variance present on the original samples.

Returns **optional_variance** (*float*) – The variance captured by the model.

orthonormalize_against_inplace(*linear_model*)

Enforces that the union of this model's components and another are both mutually orthonormal.

Note that the model passed in is guaranteed to not have it's number of available components changed. This model, however, may loose some dimensionality due to reaching a degenerate state.

The removed components will always be trimmed from the end of components (i.e. the components which capture the least variance). If trimming is performed, *n_components* and *n_available_components* would be altered - see *trim_components()* for details.

Parameters **linear_model** (`LinearModel`) – A second linear model to orthonormalize this against.

orthonormalize_inplace()

Enforces that this model's components are orthonormalized, s.t. `component_vector(i).dot(component_vector(j) = dirac_delta`.

plot_eigenvalues(*figure_id=None, new_figure=False, render_lines=True, line_colour='b', line_style='-', line_width=2, render_markers=True, marker_style='o', marker_size=6, marker_face_colour='b', marker_edge_colour='k', marker_edge_width=1.0, render_axes=True, axes_font_name='sans-serif', axes_font_size=10, axes_font_style='normal', axes_font_weight='normal', figure_size=(10, 6), render_grid=True, grid_line_style='–', grid_line_width=0.5*)

Plot of the eigenvalues.

Parameters

- **figure_id** (*object*, optional) – The id of the figure to be used.
- **new_figure** (*bool*, optional) – If `True`, a new figure is created.
- **render_lines** (*bool*, optional) – If `True`, the line will be rendered.
- **line_colour** (*See Below, optional*) – The colour of the lines. Example options

```
{``r``, ``g``, ``b``, ``c``, ``m``, ``k``, ``w``}
or
``(3, )`` `ndarray`
or
`list` of length ``3``
```

- **line_style** ({`-`, `--`, `-.`, `:`}, optional) – The style of the lines.
- **line_width** (*float*, optional) – The width of the lines.

- **render_markers** (*bool*, optional) – If `True`, the markers will be rendered.
- **marker_style** (*See Below, optional*) – The style of the markers. Example options

```
{``.``, ``,``, ``o``, ``v``, ``^``, ``<``, ``>``, ``+``,
 ``x``, ``D``, ``d``, ``s``, ``p``, ``*``, ``h``, ``H``,
 ``1``, ``2``, ``3``, ``4``, ``8``}
```

- **marker_size** (*int*, optional) – The size of the markers in points^2.
- **marker_face_colour** (*See Below, optional*) – The face (filling) colour of the markers. Example options

```
{``r``, ``g``, ``b``, ``c``, ``m``, ``k``, ``w``}
or
``(3, )`` `ndarray`
or
`list` of length ``3``
```

- **marker_edge_colour** (*See Below, optional*) – The edge colour of the markers. Example options

```
{``r``, ``g``, ``b``, ``c``, ``m``, ``k``, ``w``}
or
``(3, )`` `ndarray`
or
`list` of length ``3``
```

- **marker_edge_width** (*float*, optional) – The width of the markers' edge.
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.
- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{``serif``, ``sans-serif``, ``cursive``, ``fantasy``,
 ``monospace``}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** ({`normal`, `italic`, `oblique`}, optional) – The font style of the axes.
- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{``ultralight``, ``light``, ``normal``, ``regular``,
 ``book``, ``medium``, ``roman``, ``semibold``,
 ``demibold``, ``demi``, ``bold``, ``heavy``,
 ``extra bold``, ``black``}
```

- **figure_size** ((*float*, *float*) or `None`, optional) – The size of the figure in inches.
- **render_grid** (*bool*, optional) – If `True`, the grid will be rendered.
- **grid_line_style** ({`-`, `--`, `-.`, `:`}, optional) – The style of the grid lines.
- **grid_line_width** (*float*, optional) – The width of the grid lines.

Returns **viewer** (`MatplotlibRenderer`) – The viewer object.

plot_eigenvalues_cumulative_ratio(*figure_id=None*, *new_figure=False*, *render_lines=True*, *line_colour='b'*, *line_style='-'*, *line_width=2*, *render_markers=True*, *marker_style='o'*, *marker_size=6*, *marker_face_colour='b'*, *marker_edge_colour='k'*, *marker_edge_width=1.0*, *render_axes=True*, *axes_font_name='sans-serif'*, *axes_font_size=10*, *axes_font_style='normal'*, *axes_font_weight='normal'*, *figure_size=(10, 6)*, *render_grid=True*, *grid_line_style='–'*, *grid_line_width=0.5*)

Plot of the cumulative variance ratio captured by the eigenvalues.

Parameters

- **figure_id** (*object*, optional) – The id of the figure to be used.
- **new_figure** (*bool*, optional) – If `True`, a new figure is created.
- **render_lines** (*bool*, optional) – If `True`, the line will be rendered.
- **line_colour** (*See Below, optional*) – The colour of the lines. Example options

```
{``r``, ``g``, ``b``, ``c``, ``m``, ``k``, ``w``}
or
``(3, )`` `ndarray`
or
`list` of length ``3``
```

- **line_style** ({`-`, `--`, `-.`, `:`}, optional) – The style of the lines.
- **line_width** (*float*, optional) – The width of the lines.
- **render_markers** (*bool*, optional) – If `True`, the markers will be rendered.
- **marker_style** (*See Below, optional*) – The style of the markers. Example options

```
{``.``, ``,``, ``o``, ``v``, ``^``, ``<``, ``>``, ``+``,
 ``x``, ``D``, ``d``, ``s``, ``p``, ``*``, ``h``, ``H``,
 ``1``, ``2``, ``3``, ``4``, ``8``}
```

- **marker_size** (*int*, optional) – The size of the markers in points^2.
- **marker_face_colour** (*See Below, optional*) – The face (filling) colour of the markers. Example options

```
{``r``, ``g``, ``b``, ``c``, ``m``, ``k``, ``w``}
or
``(3, )`` `ndarray`
or
`list` of length ``3``
```

- **marker_edge_colour** (*See Below, optional*) – The edge colour of the markers. Example options

```
{``r``, ``g``, ``b``, ``c``, ``m``, ``k``, ``w``}
or
``(3, )`` `ndarray`
or
`list` of length ``3``
```

- **marker_edge_width** (*float*, optional) – The width of the markers' edge.
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.
- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{``serif``, ``sans-serif``, ``cursive``, ``fantasy``,
 ``monospace``}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** ({`normal`, `italic`, `oblique`}, optional) – The font style of the axes.
- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{``ultralight``, ``light``, ``normal``, ``regular``,
 ``book``, ``medium``, ``roman``, ``semibold``,
 ``demibold``, ``demi``, ``bold``, ``heavy``,
 ``extra bold``, ``black``}
```

- **figure_size** ((*float*, *float*) or *None*, optional) – The size of the figure in inches.
- **render_grid** (*bool*, optional) – If `True`, the grid will be rendered.
- **grid_line_style** ({`-`, `--`, `-.`, `:`}, optional) – The style of the grid lines.
- **grid_line_width** (*float*, optional) – The width of the grid lines.

Returns **viewer** (`MatplotlibRenderer`) – The viewer object.

plot_eigenvalues_cumulative_ratio_widget (*figure_size=(10, 6), style='coloured'*)

Plot of the cumulative variance ratio captured by the eigenvalues using `plot_graph` widget.

Parameters

- **figure_size** ((*float*, *float*) or `None`, optional) – The size of the figure in inches.
- **style** ({`'coloured'`, `'minimal'`}, optional) – If `'coloured'`, then the style of the widget will be coloured. If `minimal`, then the style is simple using black and white colours.

plot_eigenvalues_ratio (*figure_id=None, new_figure=False, render_lines=True, line_colour='b', line_style='-', line_width=2, render_markers=True, marker_style='o', marker_size=6, marker_face_colour='b', marker_edge_colour='k', marker_edge_width=1.0, render_axes=True, axes_font_name='sans-serif', axes_font_size=10, axes_font_style='normal', axes_font_weight='normal', figure_size=(10, 6), render_grid=True, grid_line_style='–', grid_line_width=0.5*)

Plot of the variance ratio captured by the eigenvalues.

Parameters

- **figure_id** (*object*, optional) – The id of the figure to be used.
- **new_figure** (*bool*, optional) – If `True`, a new figure is created.
- **render_lines** (*bool*, optional) – If `True`, the line will be rendered.
- **line_colour** (*See Below, optional*) – The colour of the lines. Example options

```
{``r``, ``g``, ``b``, ``c``, ``m``, ``k``, ``w``}
or
``(3, )`` `ndarray`
or
`list` of length ``3``
```

- **line_style** ({`-`, `--`, `-.`, `:`}, optional) – The style of the lines.
- **line_width** (*float*, optional) – The width of the lines.
- **render_markers** (*bool*, optional) – If `True`, the markers will be rendered.
- **marker_style** (*See Below, optional*) – The style of the markers. Example options

```
{``.``, ``,``, ``o``, ``v``, ``^``, ``<``, ``>``, ``+``,
 ``x``, ``D``, ``d``, ``s``, ``p``, ``*``, ``h``, ``H``,
 ``1``, ``2``, ``3``, ``4``, ``8``}
```

- **marker_size** (*int*, optional) – The size of the markers in points^2.
- **marker_face_colour** (*See Below, optional*) – The face (filling) colour of the markers. Example options

```
{``r``, ``g``, ``b``, ``c``, ``m``, ``k``, ``w``}
or
``(3, )`` `ndarray`
or
`list` of length ``3``
```

- **marker_edge_colour** (*See Below, optional*) – The edge colour of the markers. Example options

```
{``r``, ``g``, ``b``, ``c``, ``m``, ``k``, ``w``}
or
``(3, )`` `ndarray`
or
`list` of length ``3``
```

- **marker_edge_width** (*float*, optional) – The width of the markers' edge.
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.
- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{``serif``, ``sans-serif``, ``cursive``, ``fantasy``,
 ``monospace``}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** ({`normal`, `italic`, `oblique`}, optional) – The font style of the axes.
- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{``ultralight``, ``light``, ``normal``, ``regular``,
 ``book``, ``medium``, ``roman``, ``semibold``,
 ``demibold``, ``demi``, ``bold``, ``heavy``,
 ``extra bold``, ``black``}
```

- **figure_size** ((*float*, *float*) or *None*, optional) – The size of the figure in inches.
- **render_grid** (*bool*, optional) – If `True`, the grid will be rendered.
- **grid_line_style** ({`-`, `--`, `-.`, `:`}, optional) – The style of the grid lines.
- **grid_line_width** (*float*, optional) – The width of the grid lines.

Returns **viewer** (`MatplotlibRenderer`) – The viewer object.

plot_eigenvalues_ratio_widget(*figure_size=(10, 6)*, *style='coloured'*)

Plot of the variance ratio captured by the eigenvalues using `plot_graph` widget.

Parameters

- **figure_size** ((*float*, *float*) or `None`, optional) – The size of the figure in inches.
- **style** ({`'coloured'`, `'minimal'`}, optional) – If `'coloured'`, then the style of the widget will be coloured. If `minimal`, then the style is simple using black and white colours.

plot_eigenvalues_widget(*figure_size=(10, 6)*, *style='coloured'*)

Plot of the eigenvalues using `plot_graph` widget.

Parameters

- **figure_size** ((*float*, *float*) or `None`, optional) – The size of the figure in inches.
- **style** ({`'coloured'`, `'minimal'`}, optional) – If `'coloured'`, then the style of the widget will be coloured. If `minimal`, then the style is simple using black and white colours.

project(*instance*)

Projects the *instance* onto the model, retrieving the optimal linear weightings.

Parameters **novel_instance** (`Vectorizable`) – A novel instance.

Returns **projected** (`(n_components,)` *ndarray*) – A vector of optimal linear weightings.

project_out(*instance*)

Returns a version of *instance* where all the basis of the model have been projected out.

Parameters **instance** (`Vectorizable`) – A novel instance of `Vectorizable`.

Returns **projected_out** (*self.instance_class*) – A copy of *instance*, with all basis of the model projected out.

project_out_vector(*vector*)

Returns a version of *vector* where all the basis of the model have been projected out.

Parameters **vector** (`(n_features,)` *ndarray*) – A novel vector.

Returns **projected_out** (`(n_features,)` *ndarray*) – A copy of *vector* with all basis of the model projected out.

project_out_vectors(*vectors*)

Returns a version of *vectors* where all the basis of the model have been projected out.

Parameters **vectors** (`(n_vectors, n_features)` *ndarray*) – A matrix of novel vectors.

Returns **projected_out** (`(n_vectors, n_features)` *ndarray*) – A copy of *vectors* with all basis of the model projected out.

project_vector(*vector*)

Projects the *vector* onto the model, retrieving the optimal linear reconstruction weights.

Parameters **vector** (`(n_features,)` *ndarray*) – A vectorized novel instance.

Returns **weights** (`(n_components,)` *ndarray*) – A vector of optimal linear weights.

project_vectors(*vectors*)

Projects each of the *vectors* onto the model, retrieving the optimal linear reconstruction weights for each instance.

Parameters **vectors** (`(n_samples, n_features)` *ndarray*) – Array of vectorized novel instances.

Returns **projected** (`(n_samples, n_components)` *ndarray*) – The matrix of optimal linear weights.

project_whitened(*instance*)

Projects the *instance* onto the whitened components, retrieving the whitened linear weightings.

Parameters **instance** (`Vectorizable`) – A novel instance.

Returns **projected** (*(n_components,)*) – A vector of whitened linear weightings

project_whitened_vector(*vector_instance*)

Projects the *vector_instance* onto the whitened components, retrieving the whitened linear weightings.

Parameters **vector_instance** (`(n_features,)` *ndarray*) – A novel vector.

Returns **projected** (`(n_features,)` *ndarray*) – A vector of whitened linear weightings

reconstruct(*instance*)

Projects a *instance* onto the linear space and rebuilds from the weights found.

Syntactic sugar for:

```
instance(project(instance))
```

but faster, as it avoids the conversion that takes place each time.

Parameters`instance` (`Vectorizable`) – A novel instance of `Vectorizable`.

Returns`reconstructed` (*self.instance_class*) – The reconstructed object.

`reconstruct_vector`(*vector*)

Project a *vector* onto the linear space and rebuild from the weights found.

Parameters`vector` (`(n_features, )` *ndarray*) – A vectorized novel instance to project.

Returns`reconstructed` (`(n_features,)` *ndarray*) – The reconstructed vector.

`reconstruct_vectors`(*vectors*)

Projects the *vectors* onto the linear space and rebuilds vectors from the weights found.

Parameters`vectors` (`(n_vectors, n_features)` *ndarray*) – A set of vectors to project.

Returns`reconstructed` (`(n_vectors, n_features)` *ndarray*) – The reconstructed vectors.

`trim_components`(*n_components=None*)

Permanently trims the components down to a certain amount. The number of active components will be automatically reset to this particular value.

This will reduce *self.n_components* down to *n_components* (if `None`, *self.n_active_components* will be used), freeing up memory in the process.

Once the model is trimmed, the trimmed components cannot be recovered.

Parameters`n_components` (*int* >= `1` or *float* > `0.0` or `None`, optional) – The number of components that are kept or else the amount (ratio) of variance that is kept. If `None`, *self.n_active_components* is used.

Notes

In case *n_components* is greater than the total number of components or greater than the amount of variance currently kept, this method does not perform any action.

`variance`()

Returns the total amount of variance retained by the active components.

Returns`variance` (*float*) – Total variance captured by the active components.

`variance_ratio`()

Returns the ratio between the amount of variance retained by the active components and the total amount of variance present on the original samples.

Returns`variance_ratio` (*float*) – Ratio of active components variance and total variance present in original samples.

`whitened_components`()

Returns the active components of the model whitened.

Returns`whitened_components` (`(n_active_components, n_features)` *ndarray*) – The whitened components.

`components`

Returns the active components of the model.

Type `(n_active_components, n_features)` *ndarray*

`eigenvalues`

Returns the eigenvalues associated to the active components of the model, i.e. the amount of variance

captured by each active component.

Type `(n_active_components,)` *ndarray*

n_active_components

The number of components currently in use on this model.

Type *int*

n_components

The number of bases of the model.

Type *int*

n_features

The number of elements in each linear component.

Type *int*

2.8 menpo.shape

2.8.1 Base Classes

Shape

class `menpo.shape.base.`**Shape**

Bases: *Vectorizable*, *Transformable*, `Landmarkable`, `LandmarkableViewable`, `Viewable`

Abstract representation of shape. Shapes are `Transformable`, *Vectorizable*, *Landmarkable*, *LandmarkableViewable* and *Viewable*. This base class handles transforming landmarks when the shape is transformed. Therefore, implementations of `Shape` have to implement the abstract `_transform_self_inplace()` method that handles transforming the `Shape` itself.

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returns **vector** (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns `type(self)` – A copy of this object

from_vector(*vector*)

Build a new instance of the object from it's vectorized state.

`self` is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is which is a `deepcopy` of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parameters **vector** (`(n_parameters,)` *ndarray*) – Flattened representation of the object.

Returns **object** (`type(self)`) – An new instance of this class.

from_vector_inplace(*vector*)

Update the state of this object from a vector form.

Parameters
vector ((n_parameters,) *ndarray*) – Flattened representation of this object

has_nan_values()
Tests if the vectorized form of the object contains `nan` values or not. This is particularly useful for objects with unknown values that have been mapped to `nan` values.
Returns
has_nan_values (*bool*) – If the vectorized object contains `nan` values.

n_dims()
The total number of dimensions.
Type *int*

has_landmarks
Whether the object has landmarks.
Type *bool*

landmarks
The landmarks object.
Type *LandmarkManager*

n_landmark_groups
The number of landmark groups on this object.
Type *int*

n_parameters
The length of the vector that this object produces.
Type *int*

2.8.2 PointCloud

PointCloud

class menpo.shape.**PointCloud**(*points*, *copy=True*)
Bases: *Shape*

An N-dimensional point cloud. This is internally represented as an *ndarray* of shape `(n_points, n_dims)`. This class is important for dealing with complex functionality such as viewing and representing metadata such as landmarks.

Currently only 2D and 3D pointclouds are viewable.
Parameters
- **points** ((n_points, n_dims) *ndarray*) – The array representing the points.
- **copy** (*bool*, optional) – If `False`, the points will not be copied on assignment. Note that this will miss out on additional checks. Further note that we still demand that the array is C-contiguous - if it isn't, a copy will be generated anyway. In general this should only be used if you know what you are doing.

_view_2d(*figure_id=None*, *new_figure=False*, *image_view=True*, *render_markers=True*, *marker_style='o'*, *marker_size=20*, *marker_face_colour='r'*, *marker_edge_colour='k'*, *marker_edge_width=1.0*, *render_axes=True*, *axes_font_name='sans-serif'*, *axes_font_size=10*, *axes_font_style='normal'*, *axes_font_weight='normal'*, *axes_x_limits=None*, *axes_y_limits=None*, *figure_size=(10, 8)*, *label=None*, ***kwargs*)
Visualization of the PointCloud in 2D.
Returns
- **figure_id** (*object*, optional) – The id of the figure to be used.
- **new_figure** (*bool*, optional) – If `True`, a new figure is created.
- **image_view** (*bool*, optional) – If `True` the PointCloud will be viewed as if it is in the image coordinate system.

- **render_lines** (*bool*, optional) – If `True`, the edges will be rendered.
- **line_colour** (*See Below, optional*) – The colour of the lines. Example options:

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **line_style** (`{-, --, -., :}`, optional) – The style of the lines.
- **line_width** (*float*, optional) – The width of the lines.
- **render_markers** (*bool*, optional) – If `True`, the markers will be rendered.
- **marker_style** (*See Below, optional*) – The style of the markers. Example options

```
{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}
```

- **marker_size** (*int*, optional) – The size of the markers in points^2.
- **marker_face_colour** (*See Below, optional*) – The face (filling) colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_colour** (*See Below, optional*) – The edge colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_width** (*float*, optional) – The width of the markers' edge.
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.
- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** (`{normal, italic, oblique}`, optional) – The font style of the axes.
- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **axes_x_limits** ((*float*, *float*) *tuple* or `None`, optional) – The limits of the x axis.
- **axes_y_limits** ((*float*, *float*) *tuple* or `None`, optional) – The limits of the y axis.
- **figure_size** ((*float*, *float*) *tuple* or `None`, optional) – The size of the figure in inches.
- **label** (*str*, optional) – The name entry in case of a legend.

Returnsviewer (`PointGraphViewer2d`) – The viewer object.

_view_landmarks_2d(*group=None*, *with_labels=None*, *without_labels=None*, *figure_id=None*, *new_figure=False*, *image_view=True*, *render_lines=True*, *line_colour=None*, *line_style='-'*, *line_width=1*, *render_markers=True*, *marker_style='o'*, *marker_size=20*, *marker_face_colour=None*, *marker_edge_colour=None*, *marker_edge_width=1.0*, *render_numbering=False*, *numbers_horizontal_align='center'*, *numbers_vertical_align='bottom'*, *numbers_font_name='sans-serif'*, *numbers_font_size=10*, *numbers_font_style='normal'*, *numbers_font_weight='normal'*, *numbers_font_colour='k'*, *render_legend=False*, *legend_title=''*, *legend_font_name='sans-serif'*, *legend_font_style='normal'*, *legend_font_size=10*, *legend_font_weight='normal'*, *legend_marker_scale=None*, *legend_location=2*, *legend_bbox_to_anchor=(1.05, 1.0)*, *legend_border_axes_pad=None*, *legend_n_columns=1*, *legend_horizontal_spacing=None*, *legend_vertical_spacing=None*, *legend_border=True*, *legend_border_padding=None*, *legend_shadow=False*, *legend_rounded_corners=False*, *render_axes=False*, *axes_font_name='sans-serif'*, *axes_font_size=10*, *axes_font_style='normal'*, *axes_font_weight='normal'*, *axes_x_limits=None*, *axes_y_limits=None*, *figure_size=(10, 8)*)

Visualize the landmarks. This method will appear on the Image as `view_landmarks` if the Image is 2D.

Parameters

- **group** (*str* or''None'' optional) – The landmark group to be visualized. If `None` and there are more than one landmark groups, an error is raised.
- **with_labels** (`None` or *str* or *list* of *str*, optional) – If not `None`, only show the given label(s). Should **not** be used with the `without_labels` kwarg.
- **without_labels** (`None` or *str* or *list* of *str*, optional) – If not `None`, show all except the given label(s). Should **not** be used with the `with_labels` kwarg.
- **figure_id** (*object*, optional) – The id of the figure to be used.
- **new_figure** (*bool*, optional) – If `True`, a new figure is created.
- **image_view** (*bool*, optional) – If `True` the PointCloud will be viewed as if it is in the image coordinate system.
- **render_lines** (*bool*, optional) – If `True`, the edges will be rendered.
- **line_colour** (*See Below, optional*) – The colour of the lines. Example options:

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **line_style** (`{-, --, -., :}`, optional) – The style of the lines.
- **line_width** (*float*, optional) – The width of the lines.
- **render_markers** (*bool*, optional) – If `True`, the markers will be rendered.
- **marker_style** (*See Below, optional*) – The style of the markers. Example options

```
{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}
```

- **marker_size** (*int*, optional) – The size of the markers in points^2.
- **marker_face_colour** (*See Below, optional*) – The face (filling) colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
```

```
(3, ) ndarray
```

- **marker_edge_colour** (*See Below, optional*) – The edge colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_width** (*float*, optional) – The width of the markers' edge.
- **render_numbering** (*bool*, optional) – If `True`, the landmarks will be numbered.
- **numbers_horizontal_align** (`{center, right, left}`, optional) – The horizontal alignment of the numbers' texts.
- **numbers_vertical_align** (`{center, top, bottom, baseline}`, optional) – The vertical alignment of the numbers' texts.
- **numbers_font_name** (*See Below, optional*) – The font of the numbers. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **numbers_font_size** (*int*, optional) – The font size of the numbers.
- **numbers_font_style** (`{normal, italic, oblique}`, optional) – The font style of the numbers.
- **numbers_font_weight** (*See Below, optional*) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **numbers_font_colour** (*See Below, optional*) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **render_legend** (*bool*, optional) – If `True`, the legend will be rendered.
- **legend_title** (*str*, optional) – The title of the legend.
- **legend_font_name** (*See below, optional*) – The font of the legend. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **legend_font_style** (`{normal, italic, oblique}`, optional) – The font style of the legend.
- **legend_font_size** (*int*, optional) – The font size of the legend.
- **legend_font_weight** (*See Below, optional*) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **legend_marker_scale** (*float*, optional) – The relative size of the legend markers with respect to the original
- **legend_location** (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

- **legend_bbox_to_anchor** ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.
- **legend_border_axes_pad** (*float*, optional) – The pad between the axes and legend border.
- **legend_n_columns** (*int*, optional) – The number of the legend's columns.
- **legend_horizontal_spacing** (*float*, optional) – The spacing between the columns.
- **legend_vertical_spacing** (*float*, optional) – The vertical space between the legend entries.
- **legend_border** (*bool*, optional) – If `True`, a frame will be drawn around the legend.
- **legend_border_padding** (*float*, optional) – The fractional whitespace inside the legend border.
- **legend_shadow** (*bool*, optional) – If `True`, a shadow will be drawn behind legend.
- **legend_rounded_corners** (*bool*, optional) – If `True`, the frame's corners will be rounded (fancybox).
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.
- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** (`{normal, italic, oblique}`, optional) – The font style of the axes.
- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold,demibold, demi, bold, heavy, extra bold, black}
```

- **axes_x_limits** ((*float*, *float*) *tuple* or `None` optional) – The limits of the x axis.
- **axes_y_limits** ((*float*, *float*) *tuple* or `None` optional) – The limits of the y axis.
- **figure_size** ((*float*, *float*) *tuple* or `None` optional) – The size of the figure in inches.

Raises

- `ValueError` – If both `with_labels` and `without_labels` are passed.
- `ValueError` – If the landmark manager doesn't contain the provided group label.

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returnsvector (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

bounding_box()

Return a bounding box from two corner points as a directed graph. The the first point (0) should be nearest the origin. In the case of an image, this ordering would appear as:

```
0<--3
|   ^
|   |
v   |
1-->2
```

In the case of a pointcloud, the ordering will appear as:

```
3<--2
|   ^
|   |
v   |
0-->1
```

Returnsbounding_box (*PointDirectedGraph*) – The axis aligned bounding box of the PointCloud.

bounds(*boundary=0*)

The minimum to maximum extent of the PointCloud. An optional boundary argument can be provided to expand the bounds by a constant margin.

Parametersboundary (*float*) – A optional padding distance that is added to the bounds. Default is `0`, meaning the max/min of tightest possible containing square/cube/hypercube is returned.

Returns

- **min_b** (`(n_dims,)` *ndarray*) – The minimum extent of the *PointCloud* and boundary along each dimension
- **max_b** (`(n_dims,)` *ndarray*) – The maximum extent of the *PointCloud* and boundary along each dimension

centre()

The mean of all the points in this PointCloud (centre of mass).

Returnscentre (`(n_dims)` *ndarray*) – The mean of this PointCloud's points.

centre_of_bounds()

The centre of the absolute bounds of this PointCloud. Contrast with *centre()*, which is the mean point position.

Returnscentre (`n_dims` *ndarray*) – The centre of the bounds of this PointCloud.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns`type(self)` – A copy of this object

distance_to(*pointcloud*, ***kwargs*)

Returns a distance matrix between this PointCloud and another. By default the Euclidean distance is calculated - see *scipy.spatial.distance.cdist* for valid kwargs to change the metric and other properties.

Parameters **pointcloud** (*PointCloud*) – The second pointcloud to compute distances between. This must be of the same dimension as this PointCloud.

Returns **distance_matrix** ((n_points, n_points) *ndarray*) – The symmetric pairwise distance matrix between the two PointClouds s.t. `distance_matrix[i, j]` is the distance between the i'th point of this PointCloud and the j'th point of the input PointCloud.

from_mask(*mask*)

A 1D boolean array with the same number of elements as the number of points in the PointCloud. This is then broadcast across the dimensions of the PointCloud and returns a new PointCloud containing only those points that were `True` in the mask.

Parameters **mask** ((n_points,) *ndarray*) – 1D array of booleans

Returns **pointcloud** (*PointCloud*) – A new pointcloud that has been masked.

Raises `ValueError` – Mask must have same number of points as pointcloud.

from_vector(*vector*)

Build a new instance of the object from it's vectorized state.

`self` is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is which is a `deepcopy` of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parameters **vector** ((n_parameters,) *ndarray*) – Flattened representation of the object.

Returns **object** (`type(self)`) – An new instance of this class.

from_vector_inplace(*vector*)

Updates the points of this PointCloud in-place with the reshaped points from the provided vector. Note that the vector should have the form `[x0, y0, x1, y1, ....., xn, yn]` for 2D.

Parameters **vector** ((n_points,) *ndarray*) – The vector from which to create the points' array.

h_points()

Convert poincloud to a homogeneous array: `(n_dims + 1, n_points)`

Type `type(self)`

has_nan_values()

Tests if the vectorized form of the object contains `nan` values or not. This is particularly useful for objects with unknown values that have been mapped to `nan` values.

Returns **has_nan_values** (*bool*) – If the vectorized object contains `nan` values.

norm(***kwargs*)

Returns the norm of this PointCloud. This is a translation and rotation invariant measure of the point cloud's intrinsic size - in other words, it is always taken around the point cloud's centre.

By default, the Frobenius norm is taken, but this can be changed by setting kwargs - see `numpy.linalg.norm` for valid options.

Returns **norm** (*float*) – The norm of this *PointCloud*

range(*boundary=0*)

The range of the extent of the PointCloud.

Parameters **boundary** (*float*) – A optional padding distance that is used to extend the bounds from which the range is computed. Default is `0`, no extension is performed.

Returns **range** ((n_dims,) *ndarray*) – The range of the *PointCloud* extent in each dimension.

tojson()

Convert this *PointCloud* to a dictionary representation suitable for inclusion in the LJSON landmark format.

Returns **json** (*dict*) – Dictionary with `points` keys.

view_widget (*browser_style='buttons'*, *figure_size=(10, 8)*, *style='coloured'*)

Visualization of the PointCloud using the `visualize_pointclouds` widget.

Parameters

- **browser_style** ({'buttons', 'slider'}, optional) – It defines whether the selector of the objects will have the form of plus/minus buttons or a slider.
- **figure_size** ((*int*, *int*), optional) – The initial size of the rendered figure.
- **style** ({'coloured', 'minimal'}, optional) – If 'coloured', then the style of the widget will be coloured. If `minimal`, then the style is simple using black and white colours.

has_landmarks

Whether the object has landmarks.

Type *bool*

landmarks

The landmarks object.

Type `LandmarkManager`

n_dims

The number of dimensions in the pointcloud.

Type *int*

n_landmark_groups

The number of landmark groups on this object.

Type *int*

n_parameters

The length of the vector that this object produces.

Type *int*

n_points

The number of points in the pointcloud.

Type *int*

2.8.3 Graphs

UndirectedGraph

class `menpo.shape.`**UndirectedGraph** (*adjacency_matrix*, *copy=True*, *skip_checks=False*)

Bases: `Graph`

Class for Undirected Graph definition and manipulation.

Parameters

- **adjacency_matrix** (`(n_vertices, n_vertices, )` *ndarray* or *csr_matrix*) – The adjacency matrix of the graph. The non-edges must be represented with zeros and the edges can have a weight value.

  Note `adjacency_matrix` must be symmetric.
- **copy** (*bool*, optional) – If `False`, the `adjacency_matrix` will not be copied on assignment.
- **skip_checks** (*bool*, optional) – If `True`, no checks will be performed.

Raises

- `ValueError` – adjacency_matrix must be either a numpy.ndarray or a scipy.sparse.csr_matrix.
- `ValueError` – Graph must have at least two vertices.
- `ValueError` – adjacency_matrix must be square (n_vertices, n_vertices,), ({adjacency_matrix.shape[0]}, {adjacency_matrix.shape[1]}) given instead.

•`ValueError` – The adjacency matrix of an undirected graph must be symmetric.

Examples

The following undirected graph

```
|---0---|
|       |
|       |
1-------2
|       |
|       |
3-------4
|
|
5
```

can be defined as

```
import numpy as np
adjacency_matrix = np.array([[0, 1, 1, 0, 0, 0],
                             [1, 0, 1, 1, 0, 0],
                             [1, 1, 0, 0, 1, 0],
                             [0, 1, 0, 0, 1, 1],
                             [0, 0, 1, 1, 0, 0],
                             [0, 0, 0, 1, 0, 0]])
graph = UndirectedGraph(adjacency_matrix)
```

or

```
from scipy.sparse import csr_matrix
adjacency_matrix = csr_matrix(
                    ([1] * 14,
                     ([0, 1, 0, 2, 1, 2, 1, 3, 2, 4, 3, 4, 3, 5],
                      [1, 0, 2, 0, 2, 1, 3, 1, 4, 2, 4, 3, 5, 3])),
                    shape=(6, 6))
graph = UndirectedGraph(adjacency_matrix)
```

The adjacency matrix of the following graph with isolated vertices

```
       0---|
           |
           |
   1       2
           |
           |
   3-------4

5
```

can be defined as

```
import numpy as np
adjacency_matrix = np.array([[0, 0, 1, 0, 0, 0],
                             [0, 0, 0, 0, 0, 0],
                             [1, 0, 0, 0, 1, 0],
                             [0, 0, 0, 0, 1, 0],
```

```
                                [0, 0, 1, 1, 0, 0],
                                [0, 0, 0, 0, 0, 0]])
graph = UndirectedGraph(adjacency_matrix)
```

or

```
from scipy.sparse import csr_matrix
adjacency_matrix = csr_matrix(([1] * 6, ([0, 2, 2, 4, 3, 4],
                                          [2, 0, 4, 2, 4, 3])),
                              shape=(6, 6))
graph = UndirectedGraph(adjacency_matrix)
```

find_all_paths (*start*, *end*, *path=[]*)

Returns a list of lists with all the paths (without cycles) found from start vertex to end vertex.

Parameters

- **start** (*int*) – The vertex from which the paths start.
- **end** (*int*) – The vertex from which the paths end.
- **path** (*list*, optional) – An existing path to append to.

Returnspaths (*list* of *list*) – The list containing all the paths from start to end.

find_all_shortest_paths (*algorithm='auto'*, *unweighted=False*)

Returns the distances and predecessors arrays of the graph's shortest paths.

Parameters

- **algorithm** (*'str', see below, optional*) – The algorithm to be used. Possible options are:

'dijkstra'	Dijkstra's algorithm with Fibonacci heaps
'bellman-ford'	Bellman-Ford algorithm
'johnson'	Johnson's algorithm
'floyd-warshall'	Floyd-Warshall algorithm
'auto'	Select the best among the above

- **unweighted** (*bool*, optional) – If `True`, then find unweighted distances. That is, rather than finding the path between each vertex such that the sum of weights is minimized, find the path such that the number of edges is minimized.

Returns

- **distances** (`(n_vertices, n_vertices,)` *ndarray*) – The matrix of distances between all graph vertices. `distances[i,j]` gives the shortest distance from vertex `i` to vertex `j` along the graph.
- **predecessors** (`(n_vertices, n_vertices,)` *ndarray*) – The matrix of predecessors, which can be used to reconstruct the shortest paths. Each entry `predecessors[i, j]` gives the index of the previous vertex in the path from vertex `i` to vertex `j`. If no path exists between vertices `i` and `j`, then `predecessors[i, j] = -9999`.

find_path (*start*, *end*, *method='bfs'*, *skip_checks=False*)

Returns a *list* with the first path (without cycles) found from the `start` vertex to the `end` vertex. It can employ either depth-first search or breadth-first search.

Parameters

- **start** (*int*) – The vertex from which the path starts.
- **end** (*int*) – The vertex to which the path ends.
- **method** (`{bfs, dfs}`, optional) – The method to be used.
- **skip_checks** (*bool*, optional) – If `True`, then input arguments won't pass through checks. Useful for efficiency.

Returnspath (*list*) – The path's vertices.

Raises`ValueError` – Method must be either bfs or dfs.

find_shortest_path(*start*, *end*, *algorithm='auto'*, *unweighted=False*, *skip_checks=False*)

Returns a *list* with the shortest path (without cycles) found from `start` vertex to `end` vertex.

Parameters

- **start** (*int*) – The vertex from which the path starts.
- **end** (*int*) – The vertex to which the path ends.
- **algorithm** (*'str', see below, optional*) – The algorithm to be used. Possible options are:

'dijkstra'	Dijkstra's algorithm with Fibonacci heaps
'bellman-ford'	Bellman-Ford algorithm
'johnson'	Johnson's algorithm
'floyd-warshall'	Floyd-Warshall algorithm
'auto'	Select the best among the above

- **unweighted** (*bool*, optional) – If `True`, then find unweighted distances. That is, rather than finding the path such that the sum of weights is minimized, find the path such that the number of edges is minimized.
- **skip_checks** (*bool*, optional) – If `True`, then input arguments won't pass through checks. Useful for efficiency.

Returns

- **path** (*list*) – The shortest path's vertices, including `start` and `end`. If there was not path connecting the vertices, then an empty *list* is returned.
- **distance** (*int* or *float*) – The distance (cost) of the path from `start` to `end`.

get_adjacency_list()

Returns the adjacency list of the graph, i.e. a *list* of length `n_vertices` that for each vertex has a *list* of the vertex neighbours. If the graph is directed, the neighbours are children.

Returnsadjacency_list (*list* of *list* of length `n_vertices`) – The adjacency list of the graph.

has_cycles()

Checks if the graph has at least one cycle.

Returnshas_cycles (*bool*) – `True` if the graph has cycles.

has_isolated_vertices()

Whether the graph has any isolated vertices, i.e. vertices with no edge connections.

Returnshas_isolated_vertices (*bool*) – `True` if the graph has at least one isolated vertex.

classmethod init_from_edges(*edges*, *n_vertices*, *skip_checks=False*)

Initialize graph from edges array.

Parameters

- **edges** (`(n_edges, 2, )` *ndarray*) – The *ndarray* of edges, i.e. all the pairs of vertices that are connected with an edge.
- **n_vertices** (*int*) – The total number of vertices, assuming that the numbering of vertices starts from `0`. `edges` and `n_vertices` can be defined in a way to set isolated vertices.
- **skip_checks** (*bool*, optional) – If `True`, no checks will be performed.

Examples

The following undirected graph

```
|---0---|
|       |
|       |
1-------2
|       |
|       |
3-------4
```

```
        |
        |
        5
```

can be defined as

```
from menpo.shape import UndirectedGraph
import numpy as np
edges = np.array([[0, 1], [1, 0], [0, 2], [2, 0], [1, 2], [2, 1],
                  [1, 3], [3, 1], [2, 4], [4, 2], [3, 4], [4, 3],
                  [3, 5], [5, 3]])
graph = UndirectedGraph.init_from_edges(edges, n_vertices=6)
```

Finally, the following graph with isolated vertices

```
        0---|
            |
            |
   1        2
            |
            |
   3-------4

5
```

---

can be defined as

```
from menpo.shape import UndirectedGraph
import numpy as np
edges = np.array([[0, 2], [2, 0], [2, 4], [4, 2], [3, 4], [4, 3]])
graph = UndirectedGraph.init_from_edges(edges, n_vertices=6)
```

is_edge(*vertex_1*, *vertex_2*, *skip_checks=False*)

Whether there is an edge between the provided vertices.

Parameters

- **vertex_1** (*int*) – The first selected vertex. Parent if the graph is directed.
- **vertex_2** (*int*) – The second selected vertex. Child if the graph is directed.
- **skip_checks** (*bool*, optional) – If `False`, the given vertices will be checked.

Returnsis_edge (*bool*) – `True` if there is an edge connecting `vertex_1` and `vertex_2`.

Raises`ValueError` – The vertex must be between 0 and {n_vertices-1}.

is_tree()

Checks if the graph is tree.

Returnsis_true (*bool*) – If the graph is a tree.

isolated_vertices()

Returns the isolated vertices of the graph (if any), i.e. the vertices that have no edge connections.

Returnsisolated_vertices (*list*) – A *list* of the isolated vertices. If there aren't any, it returns an empty *list*.

minimum_spanning_tree(*root_vertex*)

Returns the minimum spanning tree of the graph using Kruskal's algorithm.

Parametersroot_vertex (*int*) – The vertex that will be set as root in the output MST.

Returnsmst (`Tree`) – The computed minimum spanning tree.

Raises`ValueError` – Cannot compute minimum spanning tree of a graph with isolated vertices

n_neighbours (*vertex*, *skip_checks=False*)

Returns the number of neighbours of the selected vertex.

Parameters

- **vertex** (*int*) – The selected vertex.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returnsn_neighbours (*int*) – The number of neighbours.

Raises`ValueError` – The vertex must be between 0 and {n_vertices-1}.

n_paths (*start*, *end*)

Returns the number of all the paths (without cycles) existing from start vertex to end vertex.

Parameters

- **start** (*int*) – The vertex from which the paths start.
- **end** (*int*) – The vertex from which the paths end.

Returnspaths (*int*) – The paths' numbers.

neighbours (*vertex*, *skip_checks=False*)

Returns the neighbours of the selected vertex.

Parameters

- **vertex** (*int*) – The selected vertex.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returnsneighbours (*list*) – The list of neighbours.

Raises`ValueError` – The vertex must be between 0 and {n_vertices-1}.

n_edges

Returns the number of edges.

Type*int*

n_vertices

Returns the number of vertices.

Type*int*

vertices

Returns the *list* of vertices.

Type*list*

DirectedGraph

class `menpo.shape.`**DirectedGraph** (*adjacency_matrix*, *copy=True*, *skip_checks=False*)

Bases: `Graph`

Class for Directed Graph definition and manipulation.

Parameters

- **adjacency_matrix** (`(n_vertices, n_vertices, )` *ndarray* or *csr_matrix*) – The adjacency matrix of the graph in which the rows represent source vertices and columns represent destination vertices. The non-edges must be represented with zeros and the edges can have a weight value.
- **copy** (*bool*, optional) – If `False`, the `adjacency_matrix` will not be copied on assignment.
- **skip_checks** (*bool*, optional) – If `True`, no checks will be performed.

Raises

- `ValueError` – adjacency_matrix must be either a numpy.ndarray or a scipy.sparse.csr_matrix.
- `ValueError` – Graph must have at least two vertices.
- `ValueError` – adjacency_matrix must be square (n_vertices, n_vertices,), ({adjacency_matrix.shape[0]}, {adjacency_matrix.shape[1]}) given instead.

Examples

The following directed graph

```
|-->0<--|
|       |
|       |
1<----->2
|       |
v       v
3------>4
|
v
5
```

can be defined as

```
import numpy as np
adjacency_matrix = np.array([[0, 0, 0, 0, 0, 0],
                             [1, 0, 1, 1, 0, 0],
                             [1, 1, 0, 0, 1, 0],
                             [0, 0, 0, 0, 1, 1],
                             [0, 0, 0, 0, 0, 0],
                             [0, 0, 0, 0, 0, 0]])
graph = DirectedGraph(adjacency_matrix)
```

or

```
from scipy.sparse import csr_matrix
adjacency_matrix = csr_matrix(([1] * 8, ([1, 2, 1, 2, 1, 2, 3, 3],
                                          [0, 0, 2, 1, 3, 4, 4, 5])),
                              shape=(6, 6))
graph = DirectedGraph(adjacency_matrix)
```

The following graph with isolated vertices

```
       0<--|
           |
           |
   1       2
           |
           v
   3------>4

5
```

---

can be defined as

```
import numpy as np
adjacency_matrix = np.array([[0, 0, 0, 0, 0, 0],
                             [0, 0, 0, 0, 0, 0],
                             [1, 0, 0, 0, 1, 0],
                             [0, 0, 0, 0, 1, 0],
                             [0, 0, 0, 0, 0, 0],
                             [0, 0, 0, 0, 0, 0]])
graph = DirectedGraph(adjacency_matrix)
```

or

```
from scipy.sparse import csr_matrix
adjacency_matrix = csr_matrix(([1] * 3, ([2, 2, 3], [0, 4, 4])),
                              shape=(6, 6))
graph = DirectedGraph(adjacency_matrix)
```

children (*vertex*, *skip_checks=False*)

Returns the children of the selected vertex.

Parameters

- **vertex** (*int*) – The selected vertex.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returnschildren (*list*) – The list of children.

Raises`ValueError` – The vertex must be between 0 and {n_vertices-1}.

find_all_paths (*start*, *end*, *path=[]*)

Returns a list of lists with all the paths (without cycles) found from start vertex to end vertex.

Parameters

- **start** (*int*) – The vertex from which the paths start.
- **end** (*int*) – The vertex from which the paths end.
- **path** (*list*, optional) – An existing path to append to.

Returnspaths (*list* of *list*) – The list containing all the paths from start to end.

find_all_shortest_paths (*algorithm='auto'*, *unweighted=False*)

Returns the distances and predecessors arrays of the graph's shortest paths.

Parameters

- **algorithm** (*'str', see below, optional*) – The algorithm to be used. Possible options are:

'dijkstra'	Dijkstra's algorithm with Fibonacci heaps
'bellman-ford'	Bellman-Ford algorithm
'johnson'	Johnson's algorithm
'floyd-warshall'	Floyd-Warshall algorithm
'auto'	Select the best among the above

- **unweighted** (*bool*, optional) – If `True`, then find unweighted distances. That is, rather than finding the path between each vertex such that the sum of weights is minimized, find the path such that the number of edges is minimized.

Returns

- **distances** (`(n_vertices, n_vertices,)` *ndarray*) – The matrix of distances between all graph vertices. `distances[i,j]` gives the shortest distance from vertex `i` to vertex `j` along the graph.
- **predecessors** (`(n_vertices, n_vertices,)` *ndarray*) – The matrix of predecessors, which can be used to reconstruct the shortest paths. Each entry `predecessors[i, j]` gives the index of the previous vertex in the path from vertex `i` to vertex `j`. If no path exists between vertices `i` and `j`, then `predecessors[i, j] = -9999`.

find_path (*start*, *end*, *method='bfs'*, *skip_checks=False*)

Returns a *list* with the first path (without cycles) found from the `start` vertex to the `end` vertex. It can employ either depth-first search or breadth-first search.

Parameters

- **start** (*int*) – The vertex from which the path starts.
- **end** (*int*) – The vertex to which the path ends.
- **method** ({`bfs`, `dfs`}, optional) – The method to be used.
- **skip_checks** (*bool*, optional) – If `True`, then input arguments won't pass through checks. Useful for efficiency.

Returnspath (*list*) – The path's vertices.

Raises `ValueError` – Method must be either bfs or dfs.

find_shortest_path(*start*, *end*, *algorithm='auto'*, *unweighted=False*, *skip_checks=False*)

Returns a *list* with the shortest path (without cycles) found from `start` vertex to `end` vertex.

Parameters

- **start** (*int*) – The vertex from which the path starts.
- **end** (*int*) – The vertex to which the path ends.
- **algorithm** (*'str', see below, optional*) – The algorithm to be used. Possible options are:

'dijkstra'	Dijkstra's algorithm with Fibonacci heaps
'bellman-ford'	Bellman-Ford algorithm
'johnson'	Johnson's algorithm
'floyd-warshall'	Floyd-Warshall algorithm
'auto'	Select the best among the above

- **unweighted** (*bool*, optional) – If `True`, then find unweighted distances. That is, rather than finding the path such that the sum of weights is minimized, find the path such that the number of edges is minimized.
- **skip_checks** (*bool*, optional) – If `True`, then input arguments won't pass through checks. Useful for efficiency.

Returns

- **path** (*list*) – The shortest path's vertices, including `start` and `end`. If there was not path connecting the vertices, then an empty *list* is returned.
- **distance** (*int* or *float*) – The distance (cost) of the path from `start` to `end`.

get_adjacency_list()

Returns the adjacency list of the graph, i.e. a *list* of length `n_vertices` that for each vertex has a *list* of the vertex neighbours. If the graph is directed, the neighbours are children.

Returns **adjacency_list** (*list* of *list* of length `n_vertices`) – The adjacency list of the graph.

has_cycles()

Checks if the graph has at least one cycle.

Returns **has_cycles** (*bool*) – `True` if the graph has cycles.

has_isolated_vertices()

Whether the graph has any isolated vertices, i.e. vertices with no edge connections.

Returns **has_isolated_vertices** (*bool*) – `True` if the graph has at least one isolated vertex.

init_from_edges(*edges*, *n_vertices*, *skip_checks=False*)

Initialize graph from edges array.

Parameters

- **edges** (`(n_edges, 2, )` *ndarray*) – The *ndarray* of edges, i.e. all the pairs of vertices that are connected with an edge.
- **n_vertices** (*int*) – The total number of vertices, assuming that the numbering of vertices starts from `0`. `edges` and `n_vertices` can be defined in a way to set isolated vertices.
- **skip_checks** (*bool*, optional) – If `True`, no checks will be performed.

Examples

The following undirected graph

```
|---0---|
|       |
|       |
1-------2
|       |
```

```
|       |
3-------4
|
|
5
```

can be defined as

```
from menpo.shape import UndirectedGraph
import numpy as np
edges = np.array([[0, 1], [1, 0], [0, 2], [2, 0], [1, 2], [2, 1],
                  [1, 3], [3, 1], [2, 4], [4, 2], [3, 4], [4, 3],
                  [3, 5], [5, 3]])
graph = UndirectedGraph.init_from_edges(edges, n_vertices=6)
```

The following directed graph

```
|-->0<--|
|       |
|       |
1<----->2
|       |
v       v
3------>4
|
v
5
```

can be represented as

```
from menpo.shape import DirectedGraph
import numpy as np
edges = np.array([[1, 0], [2, 0], [1, 2], [2, 1], [1, 3], [2, 4],
                  [3, 4], [3, 5]])
graph = DirectedGraph.init_from_edges(edges, n_vertices=6)
```

Finally, the following graph with isolated vertices

```
    0---|
        |
        |
1       2
        |
        |
3-------4


5
```

can be defined as

```
from menpo.shape import UndirectedGraph
import numpy as np
edges = np.array([[0, 2], [2, 0], [2, 4], [4, 2], [3, 4], [4, 3]])
graph = UndirectedGraph.init_from_edges(edges, n_vertices=6)
```

is_edge(*vertex_1*, *vertex_2*, *skip_checks=False*)

Whether there is an edge between the provided vertices.

Parameters

- **vertex_1** (*int*) – The first selected vertex. Parent if the graph is directed.
- **vertex_2** (*int*) – The second selected vertex. Child if the graph is directed.
- **skip_checks** (*bool*, optional) – If `False`, the given vertices will be checked.

Returnsis_edge (*bool*) – `True` if there is an edge connecting `vertex_1` and `vertex_2`.

Raises`ValueError` – The vertex must be between 0 and {n_vertices-1}.

is_tree()

Checks if the graph is tree.

Returnsis_true (*bool*) – If the graph is a tree.

isolated_vertices()

Returns the isolated vertices of the graph (if any), i.e. the vertices that have no edge connections.

Returnsisolated_vertices (*list*) – A *list* of the isolated vertices. If there aren't any, it returns an empty *list*.

n_children(*vertex*, *skip_checks=False*)

Returns the number of children of the selected vertex.

Parametersvertex (*int*) – The selected vertex.

Returns

- **n_children** (*int*) – The number of children.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Raises`ValueError` – The vertex must be in the range `[0, n_vertices - 1]`.

n_parents(*vertex*, *skip_checks=False*)

Returns the number of parents of the selected vertex.

Parameters

- **vertex** (*int*) – The selected vertex.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returnsn_parents (*int*) – The number of parents.

Raises`ValueError` – The vertex must be in the range `[0, n_vertices - 1]`.

n_paths(*start*, *end*)

Returns the number of all the paths (without cycles) existing from start vertex to end vertex.

Parameters

- **start** (*int*) – The vertex from which the paths start.
- **end** (*int*) – The vertex from which the paths end.

Returnspaths (*int*) – The paths' numbers.

parents(*vertex*, *skip_checks=False*)

Returns the parents of the selected vertex.

Parameters

- **vertex** (*int*) – The selected vertex.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returnsparents (*list*) – The list of parents.

Raises`ValueError` – The vertex must be in the range `[0, n_vertices - 1]`.

n_edges

Returns the number of edges.

Type*int*

n_vertices

Returns the number of vertices.

Type*int*

vertices

Returns the *list* of vertices.

Type *list*

Tree

class `menpo.shape.Tree`(*adjacency_matrix*, *root_vertex*, *copy=True*, *skip_checks=False*)

Bases: `DirectedGraph`

Class for Tree definitions and manipulation.

Parameters

- **`adjacency_matrix`** (`(n_vertices, n_vertices, )` *ndarray* or *csr_matrix*) – The adjacency matrix of the tree in which the rows represent parents and columns represent children. The non-edges must be represented with zeros and the edges can have a weight value.

  Note A tree must not have isolated vertices.
- **`root_vertex`** (*int*) – The vertex to be set as root.
- **`copy`** (*bool*, optional) – If `False`, the `adjacency_matrix` will not be copied on assignment.
- **`skip_checks`** (*bool*, optional) – If `True`, no checks will be performed.

Raises

- `ValueError` – adjacency_matrix must be either a numpy.ndarray or a scipy.sparse.csr_matrix.
- `ValueError` – Graph must have at least two vertices.
- `ValueError` – adjacency_matrix must be square (n_vertices, n_vertices,), ({adjacency_matrix.shape[0]}, {adjacency_matrix.shape[1]}) given instead.
- `ValueError` – The provided edges do not represent a tree.
- `ValueError` – The root_vertex must be in the range `[0, n_vertices - 1]`.
- `ValueError` – The combination of adjacency matrix and root vertex is not valid. BFS returns a different tree.

Examples

The following tree

```
        0
        |
     ___|___
    1       2
    |       |
  _|_       |
 3   4      5
 |   |      |
 |   |      |
 6   7      8
```

can be defined as

```
import numpy as np
adjacency_matrix = np.array([[0, 1, 1, 0, 0, 0, 0, 0, 0],
                             [0, 0, 0, 1, 1, 0, 0, 0, 0],
                             [0, 0, 0, 0, 0, 1, 0, 0, 0],
                             [0, 0, 0, 0, 0, 0, 1, 0, 0],
                             [0, 0, 0, 0, 0, 0, 0, 1, 0],
                             [0, 0, 0, 0, 0, 0, 0, 0, 1],
                             [0, 0, 0, 0, 0, 0, 0, 0, 0],
                             [0, 0, 0, 0, 0, 0, 0, 0, 0],
```

```
                                [0, 0, 0, 0, 0, 0, 0, 0, 0]])
tree = Tree(adjacency_matrix, root_vertex=0)
```

or

```
from scipy.sparse import csr_matrix
adjacency_matrix = csr_matrix(([1] * 8, ([0, 0, 1, 1, 2, 3, 4, 5],
                                          [1, 2, 3, 4, 5, 6, 7, 8])),
                              shape=(9, 9))
tree = Tree(adjacency_matrix, root_vertex=0)
```

---

children (*vertex*, *skip_checks=False*)

Returns the children of the selected vertex.

Parameters

- **vertex** (*int*) – The selected vertex.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returnschildren (*list*) – The list of children.

Raises`ValueError` – The vertex must be between 0 and {n_vertices-1}.

depth_of_vertex (*vertex*, *skip_checks=False*)

Returns the depth of the specified vertex.

Parameters

- **vertex** (*int*) – The selected vertex.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returnsdepth (*int*) – The depth of the selected vertex.

Raises`ValueError` – The vertex must be in the range `[0, n_vertices - 1]`.

find_all_paths (*start*, *end*, *path=[]*)

Returns a list of lists with all the paths (without cycles) found from start vertex to end vertex.

Parameters

- **start** (*int*) – The vertex from which the paths start.
- **end** (*int*) – The vertex from which the paths end.
- **path** (*list*, optional) – An existing path to append to.

Returnspaths (*list* of *list*) – The list containing all the paths from start to end.

find_all_shortest_paths (*algorithm='auto'*, *unweighted=False*)

Returns the distances and predecessors arrays of the graph's shortest paths.

Parameters

- **algorithm** (*'str', see below, optional*) – The algorithm to be used. Possible options are:

'dijkstra'	Dijkstra's algorithm with Fibonacci heaps
'bellman-ford'	Bellman-Ford algorithm
'johnson'	Johnson's algorithm
'floyd-warshall'	Floyd-Warshall algorithm
'auto'	Select the best among the above

- **unweighted** (*bool*, optional) – If `True`, then find unweighted distances. That is, rather than finding the path between each vertex such that the sum of weights is minimized, find the path such that the number of edges is minimized.

Returns

- **distances** (`(n_vertices, n_vertices,)` *ndarray*) – The matrix of distances between all graph vertices. `distances[i,j]` gives the shortest distance from vertex `i` to vertex `j` along the graph.
- **predecessors** (`(n_vertices, n_vertices,)` *ndarray*) – The matrix of predecessors, which can be used to reconstruct the shortest paths. Each entry

`predecessors[i, j]` gives the index of the previous vertex in the path from vertex `i` to vertex `j`. If no path exists between vertices `i` and `j`, then `predecessors[i, j] = -9999`.

find_path(*start*, *end*, *method='bfs'*, *skip_checks=False*)

Returns a *list* with the first path (without cycles) found from the `start` vertex to the `end` vertex. It can employ either depth-first search or breadth-first search.

Parameters

- **start** (*int*) – The vertex from which the path starts.
- **end** (*int*) – The vertex to which the path ends.
- **method** ({`bfs`, `dfs`}, optional) – The method to be used.
- **skip_checks** (*bool*, optional) – If `True`, then input arguments won't pass through checks. Useful for efficiency.

Returnspath (*list*) – The path's vertices.

Raises`ValueError` – Method must be either bfs or dfs.

find_shortest_path(*start*, *end*, *algorithm='auto'*, *unweighted=False*, *skip_checks=False*)

Returns a *list* with the shortest path (without cycles) found from `start` vertex to `end` vertex.

Parameters

- **start** (*int*) – The vertex from which the path starts.
- **end** (*int*) – The vertex to which the path ends.
- **algorithm** (*'str', see below, optional*) – The algorithm to be used. Possible options are:

'dijkstra'	Dijkstra's algorithm with Fibonacci heaps
'bellman-ford'	Bellman-Ford algorithm
'johnson'	Johnson's algorithm
'floyd-warshall'	Floyd-Warshall algorithm
'auto'	Select the best among the above

- **unweighted** (*bool*, optional) – If `True`, then find unweighted distances. That is, rather than finding the path such that the sum of weights is minimized, find the path such that the number of edges is minimized.
- **skip_checks** (*bool*, optional) – If `True`, then input arguments won't pass through checks. Useful for efficiency.

Returns

- **path** (*list*) – The shortest path's vertices, including `start` and `end`. If there was not path connecting the vertices, then an empty *list* is returned.
- **distance** (*int* or *float*) – The distance (cost) of the path from `start` to `end`.

get_adjacency_list()

Returns the adjacency list of the graph, i.e. a *list* of length `n_vertices` that for each vertex has a *list* of the vertex neighbours. If the graph is directed, the neighbours are children.

Returnsadjacency_list (*list* of *list* of length `n_vertices`) – The adjacency list of the graph.

has_cycles()

Checks if the graph has at least one cycle.

Returnshas_cycles (*bool*) – `True` if the graph has cycles.

has_isolated_vertices()

Whether the graph has any isolated vertices, i.e. vertices with no edge connections.

Returnshas_isolated_vertices (*bool*) – `True` if the graph has at least one isolated vertex.

init_from_edges(*edges*, *n_vertices*, *skip_checks=False*)

Initialize graph from edges array.

Parameters

- **edges** (`(n_edges, 2, )` *ndarray*) – The *ndarray* of edges, i.e. all the pairs of vertices that are connected with an edge.
- **n_vertices** (*int*) – The total number of vertices, assuming that the numbering of vertices starts from `0`. `edges` and `n_vertices` can be defined in a way to set isolated vertices.
- **skip_checks** (*bool*, optional) – If `True`, no checks will be performed.

Examples

The following undirected graph

```
|---0---|
|       |
|       |
1-------2
|       |
|       |
3-------4
|
|
5
```

can be defined as

```
from menpo.shape import UndirectedGraph
import numpy as np
edges = np.array([[0, 1], [1, 0], [0, 2], [2, 0], [1, 2], [2, 1],
                  [1, 3], [3, 1], [2, 4], [4, 2], [3, 4], [4, 3],
                  [3, 5], [5, 3]])
graph = UndirectedGraph.init_from_edges(edges, n_vertices=6)
```

The following directed graph

```
|-->0<--|
|       |
|       |
1<----->2
|       |
v       v
3------>4
|
v
5
```

can be represented as

```
from menpo.shape import DirectedGraph
import numpy as np
edges = np.array([[1, 0], [2, 0], [1, 2], [2, 1], [1, 3], [2, 4],
                  [3, 4], [3, 5]])
graph = DirectedGraph.init_from_edges(edges, n_vertices=6)
```

Finally, the following graph with isolated vertices

```
    0---|
        |
        |
```

```
1       2
        |
        |
3-------4


5
```

can be defined as

```
from menpo.shape import UndirectedGraph
import numpy as np
edges = np.array([[0, 2], [2, 0], [2, 4], [4, 2], [3, 4], [4, 3]])
graph = UndirectedGraph.init_from_edges(edges, n_vertices=6)
```

is_edge (*vertex_1*, *vertex_2*, *skip_checks=False*)

Whether there is an edge between the provided vertices.

Parameters

- **vertex_1** (*int*) – The first selected vertex. Parent if the graph is directed.
- **vertex_2** (*int*) – The second selected vertex. Child if the graph is directed.
- **skip_checks** (*bool*, optional) – If `False`, the given vertices will be checked.

Returnsis_edge (*bool*) – `True` if there is an edge connecting `vertex_1` and `vertex_2`.

Raises`ValueError` – The vertex must be between 0 and {n_vertices-1}.

is_leaf (*vertex*, *skip_checks=False*)

Whether the vertex is a leaf.

Parameters

- **vertex** (*int*) – The selected vertex.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returnsis_leaf (*bool*) – If `True`, then selected vertex is a leaf.

Raises`ValueError` – The vertex must be in the range `[0, n_vertices - 1]`.

is_tree ()

Checks if the graph is tree.

Returnsis_true (*bool*) – If the graph is a tree.

isolated_vertices ()

Returns the isolated vertices of the graph (if any), i.e. the vertices that have no edge connections.

Returnsisolated_vertices (*list*) – A *list* of the isolated vertices. If there aren't any, it returns an empty *list*.

n_children (*vertex*, *skip_checks=False*)

Returns the number of children of the selected vertex.

Parametersvertex (*int*) – The selected vertex.

Returns

- **n_children** (*int*) – The number of children.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Raises`ValueError` – The vertex must be in the range `[0, n_vertices - 1]`.

n_parents (*vertex*, *skip_checks=False*)

Returns the number of parents of the selected vertex.

Parameters

- **vertex** (*int*) – The selected vertex.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returnsn_parents (*int*) – The number of parents.

Raises`ValueError` – The vertex must be in the range `[0, n_vertices - 1]`.

n_paths (*start*, *end*)

Returns the number of all the paths (without cycles) existing from start vertex to end vertex.

Parameters

- **start** (*int*) – The vertex from which the paths start.
- **end** (*int*) – The vertex from which the paths end.

Returnspaths (*int*) – The paths' numbers.

n_vertices_at_depth (*depth*)

Returns the number of vertices at the specified depth.

Parametersdepth (*int*) – The selected depth.

Returnsn_vertices (*int*) – The number of vertices that lie in the specified depth.

parent (*vertex*, *skip_checks=False*)

Returns the parent of the selected vertex.

Parameters

- **vertex** (*int*) – The selected vertex.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returnsparent (*int*) – The parent vertex.

Raises`ValueError` – The vertex must be in the range `[0, n_vertices - 1]`.

parents (*vertex*, *skip_checks=False*)

Returns the parents of the selected vertex.

Parameters

- **vertex** (*int*) – The selected vertex.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returnsparents (*list*) – The list of parents.

Raises`ValueError` – The vertex must be in the range `[0, n_vertices - 1]`.

vertices_at_depth (*depth*)

Returns a list of vertices at the specified depth.

Parametersdepth (*int*) – The selected depth.

Returnsvertices (*list*) – The vertices that lie in the specified depth.

leaves

Returns a *list* with the all leaves of the tree.

Type*list*

maximum_depth

Returns the maximum depth of the tree.

Type*int*

n_edges

Returns the number of edges.

Type*int*

n_leaves

Returns the number of leaves of the tree.

Type*int*

n_vertices

Returns the number of vertices.

Type*int*

vertices

Returns the *list* of vertices.

Type*list*

2.8.4 PointGraphs

Mix-ins of Graphs and `PointCloud` for graphs with geometry.

PointUndirectedGraph

class `menpo.shape.`**`PointUndirectedGraph`**(*points*, *adjacency_matrix*, *copy=True*, *skip_checks=False*)

Bases: `PointGraph`, `UndirectedGraph`

Class for defining an Undirected Graph with geometry.

Parameters

- **`points`** (`(n_vertices, n_dims, )` *ndarray*) – The array of point locations.
- **`adjacency_matrix`** (`(n_vertices, n_vertices, )` *ndarray* or *csr_matrix*) – The adjacency matrix of the graph. The non-edges must be represented with zeros and the edges can have a weight value.

  Note `adjacency_matrix` must be symmetric.
- **`copy`** (*bool*, optional) – If `False`, the `adjacency_matrix` will not be copied on assignment.
- **`skip_checks`** (*bool*, optional) – If `True`, no checks will be performed.

Raises

- `ValueError` – A point for each graph vertex needs to be passed. Got `n_points` points instead of `n_vertices`.
- `ValueError` – adjacency_matrix must be either a numpy.ndarray or a scipy.sparse.csr_matrix.
- `ValueError` – Graph must have at least two vertices.
- `ValueError` – adjacency_matrix must be square (n_vertices, n_vertices,), ({adjacency_matrix.shape[0]}, {adjacency_matrix.shape[1]}) given instead.
- `ValueError` – The adjacency matrix of an undirected graph must be symmetric.

Examples

The following undirected graph

```
|---0---|
|       |
|       |
1-------2
|       |
|       |
3-------4
|
|
5
```

can be defined as

```
import numpy as np
adjacency_matrix = np.array([[0, 1, 1, 0, 0, 0],
                             [1, 0, 1, 1, 0, 0],
                             [1, 1, 0, 0, 1, 0],
                             [0, 1, 0, 0, 1, 1],
                             [0, 0, 1, 1, 0, 0],
                             [0, 0, 0, 1, 0, 0]])
points = np.array([[10, 30], [0, 20], [20, 20], [0, 10], [20, 10],
```

```
                    [0, 0]])
graph = PointUndirectedGraph(points, adjacency_matrix)
```

or

```
from scipy.sparse import csr_matrix
adjacency_matrix = csr_matrix(
                    ([1] * 14,
                     ([0, 1, 0, 2, 1, 2, 1, 3, 2, 4, 3, 4, 3, 5],
                      [1, 0, 2, 0, 2, 1, 3, 1, 4, 2, 4, 3, 5, 3])),
                    shape=(6, 6))
points = np.array([[10, 30], [0, 20], [20, 20], [0, 10], [20, 10],
                   [0, 0]])
graph = PointUndirectedGraph(points, adjacency_matrix)
```

The adjacency matrix of the following graph with isolated vertices

```
       0---|
           |
           |
   1       2
           |
           |
   3-------4

5
```

---

can be defined as

```
import numpy as np
adjacency_matrix = np.array([[0, 0, 1, 0, 0, 0],
                             [0, 0, 0, 0, 0, 0],
                             [1, 0, 0, 0, 1, 0],
                             [0, 0, 0, 0, 1, 0],
                             [0, 0, 1, 1, 0, 0],
                             [0, 0, 0, 0, 0, 0]])
points = np.array([[10, 30], [0, 20], [20, 20], [0, 10], [20, 10],
                   [0, 0]])
graph = PointUndirectedGraph(points, adjacency_matrix)
```

or

```
from scipy.sparse import csr_matrix
adjacency_matrix = csr_matrix(([1] * 6, ([0, 2, 2, 4, 3, 4],
                                          [2, 0, 4, 2, 4, 3])),
                              shape=(6, 6))
points = np.array([[10, 30], [0, 20], [20, 20], [0, 10], [20, 10],
                   [0, 0]])
graph = PointUndirectedGraph(points, adjacency_matrix)
```

_view_2d(*figure_id=None*, *new_figure=False*, *image_view=True*, *render_lines=True*, *line_colour='r'*, *line_style='-'*, *line_width=1.0*, *render_markers=True*, *marker_style='o'*, *marker_size=20*, *marker_face_colour='k'*, *marker_edge_colour='k'*, *marker_edge_width=1.0*, *render_axes=True*, *axes_font_name='sans-serif'*, *axes_font_size=10*, *axes_font_style='normal'*, *axes_font_weight='normal'*, *axes_x_limits=None*, *axes_y_limits=None*, *figure_size=(10, 8)*, *label=None*)

Visualization of the PointGraph in 2D.

Returns

- **figure_id** (*object*, optional) – The id of the figure to be used.
- **new_figure** (*bool*, optional) – If `True`, a new figure is created.
- **image_view** (*bool*, optional) – If `True` the PointGraph will be viewed as if it is in the image coordinate system.
- **render_lines** (*bool*, optional) – If `True`, the edges will be rendered.
- **line_colour** (*See Below, optional*) – The colour of the lines. Example options:

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **line_style** (`{-, --, -., :}`, optional) – The style of the lines.
- **line_width** (*float*, optional) – The width of the lines.
- **render_markers** (*bool*, optional) – If `True`, the markers will be rendered.
- **marker_style** (*See Below, optional*) – The style of the markers. Example options

```
{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}
```

- **marker_size** (*int*, optional) – The size of the markers in points^2.
- **marker_face_colour** (*See Below, optional*) – The face (filling) colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_colour** (*See Below, optional*) – The edge colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_width** (*float*, optional) – The width of the markers' edge.
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.
- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** (`{normal, italic, oblique}`, optional) – The font style of the axes.
- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **axes_x_limits** ((*float*, *float*) *tuple* or `None`, optional) – The limits of the x axis.
- **axes_y_limits** ((*float*, *float*) *tuple* or `None`, optional) – The limits of the y axis.
- **figure_size** ((*float*, *float*) *tuple* or `None`, optional) – The size of the figure in inches.
- **label** (*str*, optional) – The name entry in case of a legend.

Returns

viewer (`PointGraphViewer2d`) – The viewer object.

_view_landmarks_2d(*group=None*, *with_labels=None*, *without_labels=None*, *figure_id=None*, *new_figure=False*, *image_view=True*, *render_lines=True*, *line_colour=None*, *line_style='-'*, *line_width=1*, *render_markers=True*, *marker_style='o'*, *marker_size=20*, *marker_face_colour=None*, *marker_edge_colour=None*, *marker_edge_width=1.0*, *render_numbering=False*, *numbers_horizontal_align='center'*, *numbers_vertical_align='bottom'*, *numbers_font_name='sans-serif'*, *numbers_font_size=10*, *numbers_font_style='normal'*, *numbers_font_weight='normal'*, *numbers_font_colour='k'*, *render_legend=False*, *legend_title=''*, *legend_font_name='sans-serif'*, *legend_font_style='normal'*, *legend_font_size=10*, *legend_font_weight='normal'*, *legend_marker_scale=None*, *legend_location=2*, *legend_bbox_to_anchor=(1.05, 1.0)*, *legend_border_axes_pad=None*, *legend_n_columns=1*, *legend_horizontal_spacing=None*, *legend_vertical_spacing=None*, *legend_border=True*, *legend_border_padding=None*, *legend_shadow=False*, *legend_rounded_corners=False*, *render_axes=False*, *axes_font_name='sans-serif'*, *axes_font_size=10*, *axes_font_style='normal'*, *axes_font_weight='normal'*, *axes_x_limits=None*, *axes_y_limits=None*, *figure_size=(10, 8)*)

Visualize the landmarks. This method will appear on the Image as `view_landmarks` if the Image is 2D.

Parameters

- **group** (*str* or''None'' optional) – The landmark group to be visualized. If `None` and there are more than one landmark groups, an error is raised.
- **with_labels** (`None` or *str* or *list* of *str*, optional) – If not `None`, only show the given label(s). Should **not** be used with the `without_labels` kwarg.
- **without_labels** (`None` or *str* or *list* of *str*, optional) – If not `None`, show all except the given label(s). Should **not** be used with the `with_labels` kwarg.
- **figure_id** (*object*, optional) – The id of the figure to be used.
- **new_figure** (*bool*, optional) – If `True`, a new figure is created.
- **image_view** (*bool*, optional) – If `True` the PointCloud will be viewed as if it is in the image coordinate system.
- **render_lines** (*bool*, optional) – If `True`, the edges will be rendered.
- **line_colour** (*See Below, optional*) – The colour of the lines. Example options:

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **line_style** (`{-, --, -., :}`, optional) – The style of the lines.
- **line_width** (*float*, optional) – The width of the lines.
- **render_markers** (*bool*, optional) – If `True`, the markers will be rendered.
- **marker_style** (*See Below, optional*) – The style of the markers. Example options

```
{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}
```

- **marker_size** (*int*, optional) – The size of the markers in points^2.
- **marker_face_colour** (*See Below, optional*) – The face (filling) colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
```

```
(3, ) ndarray
```

- **marker_edge_colour** (*See Below, optional*) – The edge colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_width** (*float*, optional) – The width of the markers' edge.
- **render_numbering** (*bool*, optional) – If `True`, the landmarks will be numbered.
- **numbers_horizontal_align** (`{center, right, left}`, optional) – The horizontal alignment of the numbers' texts.
- **numbers_vertical_align** (`{center, top, bottom, baseline}`, optional) – The vertical alignment of the numbers' texts.
- **numbers_font_name** (*See Below, optional*) – The font of the numbers. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **numbers_font_size** (*int*, optional) – The font size of the numbers.
- **numbers_font_style** (`{normal, italic, oblique}`, optional) – The font style of the numbers.
- **numbers_font_weight** (*See Below, optional*) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **numbers_font_colour** (*See Below, optional*) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **render_legend** (*bool*, optional) – If `True`, the legend will be rendered.
- **legend_title** (*str*, optional) – The title of the legend.
- **legend_font_name** (*See below, optional*) – The font of the legend. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **legend_font_style** (`{normal, italic, oblique}`, optional) – The font style of the legend.
- **legend_font_size** (*int*, optional) – The font size of the legend.
- **legend_font_weight** (*See Below, optional*) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **legend_marker_scale** (*float*, optional) – The relative size of the legend markers with respect to the original
- **legend_location** (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

- **legend_bbox_to_anchor** ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.
- **legend_border_axes_pad** (*float*, optional) – The pad between the axes and legend border.
- **legend_n_columns** (*int*, optional) – The number of the legend's columns.
- **legend_horizontal_spacing** (*float*, optional) – The spacing between the columns.
- **legend_vertical_spacing** (*float*, optional) – The vertical space between the legend entries.
- **legend_border** (*bool*, optional) – If `True`, a frame will be drawn around the legend.
- **legend_border_padding** (*float*, optional) – The fractional whitespace inside the legend border.
- **legend_shadow** (*bool*, optional) – If `True`, a shadow will be drawn behind legend.
- **legend_rounded_corners** (*bool*, optional) – If `True`, the frame's corners will be rounded (fancybox).
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.
- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** (`{normal, italic, oblique}`, optional) – The font style of the axes.
- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold,demibold, demi, bold, heavy, extra bold, black}
```

- **axes_x_limits** ((*float*, *float*) *tuple* or `None` optional) – The limits of the x axis.
- **axes_y_limits** ((*float*, *float*) *tuple* or `None` optional) – The limits of the y axis.
- **figure_size** ((*float*, *float*) *tuple* or `None` optional) – The size of the figure in inches.

Raises

- `ValueError` – If both `with_labels` and `without_labels` are passed.
- `ValueError` – If the landmark manager doesn't contain the provided group label.

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returnsvector (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

bounding_box()

Return a bounding box from two corner points as a directed graph. The the first point (0) should be nearest the origin. In the case of an image, this ordering would appear as:

```
0<--3
|   ^
|   |
v   |
1-->2
```

In the case of a pointcloud, the ordering will appear as:

```
3<--2
|   ^
|   |
v   |
0-->1
```

Returnsbounding_box (*PointDirectedGraph*) – The axis aligned bounding box of the PointCloud.

bounds(*boundary=0*)

The minimum to maximum extent of the PointCloud. An optional boundary argument can be provided to expand the bounds by a constant margin.

Parametersboundary (*float*) – A optional padding distance that is added to the bounds. Default is `0`, meaning the max/min of tightest possible containing square/cube/hypercube is returned.

Returns

- **min_b** (`(n_dims,)` *ndarray*) – The minimum extent of the *PointCloud* and boundary along each dimension
- **max_b** (`(n_dims,)` *ndarray*) – The maximum extent of the *PointCloud* and boundary along each dimension

centre()

The mean of all the points in this PointCloud (centre of mass).

Returnscentre (`(n_dims)` *ndarray*) – The mean of this PointCloud's points.

centre_of_bounds()

The centre of the absolute bounds of this PointCloud. Contrast with *centre()*, which is the mean point position.

Returnscentre (`n_dims` *ndarray*) – The centre of the bounds of this PointCloud.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns`type(self)` – A copy of this object

distance_to(*pointcloud*, ***kwargs*)

Returns a distance matrix between this PointCloud and another. By default the Euclidean distance is calculated - see *scipy.spatial.distance.cdist* for valid kwargs to change the metric and other properties.

Parameters **pointcloud** (*PointCloud*) – The second pointcloud to compute distances between. This must be of the same dimension as this PointCloud.

Returns **distance_matrix** (`(n_points, n_points)` *ndarray*) – The symmetric pairwise distance matrix between the two PointClouds s.t. `distance_matrix[i, j]` is the distance between the i'th point of this PointCloud and the j'th point of the input PointCloud.

find_all_paths (*start*, *end*, *path=[]*)

Returns a list of lists with all the paths (without cycles) found from start vertex to end vertex.

Parameters

- **start** (*int*) – The vertex from which the paths start.
- **end** (*int*) – The vertex from which the paths end.
- **path** (*list*, optional) – An existing path to append to.

Returns **paths** (*list* of *list*) – The list containing all the paths from start to end.

find_all_shortest_paths (*algorithm='auto'*, *unweighted=False*)

Returns the distances and predecessors arrays of the graph's shortest paths.

Parameters

- **algorithm** (*'str', see below, optional*) – The algorithm to be used. Possible options are:

'dijkstra'	Dijkstra's algorithm with Fibonacci heaps
'bellman-ford'	Bellman-Ford algorithm
'johnson'	Johnson's algorithm
'floyd-warshall'	Floyd-Warshall algorithm
'auto'	Select the best among the above

- **unweighted** (*bool*, optional) – If `True`, then find unweighted distances. That is, rather than finding the path between each vertex such that the sum of weights is minimized, find the path such that the number of edges is minimized.

Returns

- **distances** (`(n_vertices, n_vertices,)` *ndarray*) – The matrix of distances between all graph vertices. `distances[i,j]` gives the shortest distance from vertex `i` to vertex `j` along the graph.
- **predecessors** (`(n_vertices, n_vertices,)` *ndarray*) – The matrix of predecessors, which can be used to reconstruct the shortest paths. Each entry `predecessors[i, j]` gives the index of the previous vertex in the path from vertex `i` to vertex `j`. If no path exists between vertices `i` and `j`, then `predecessors[i, j] = -9999`.

find_path (*start*, *end*, *method='bfs'*, *skip_checks=False*)

Returns a *list* with the first path (without cycles) found from the `start` vertex to the `end` vertex. It can employ either depth-first search or breadth-first search.

Parameters

- **start** (*int*) – The vertex from which the path starts.
- **end** (*int*) – The vertex to which the path ends.
- **method** ({`bfs`, `dfs`}, optional) – The method to be used.
- **skip_checks** (*bool*, optional) – If `True`, then input arguments won't pass through checks. Useful for efficiency.

Returns **path** (*list*) – The path's vertices.

Raises `ValueError` – Method must be either bfs or dfs.

find_shortest_path (*start*, *end*, *algorithm='auto'*, *unweighted=False*, *skip_checks=False*)

Returns a *list* with the shortest path (without cycles) found from `start` vertex to `end` vertex.

Parameters

- **start** (*int*) – The vertex from which the path starts.
- **end** (*int*) – The vertex to which the path ends.

- **algorithm** (*'str', see below, optional*) – The algorithm to be used. Possible options are:

'dijkstra'	Dijkstra's algorithm with Fibonacci heaps
'bellman-ford'	Bellman-Ford algorithm
'johnson'	Johnson's algorithm
'floyd-warshall'	Floyd-Warshall algorithm
'auto'	Select the best among the above

- **unweighted** (*bool*, optional) – If `True`, then find unweighted distances. That is, rather than finding the path such that the sum of weights is minimized, find the path such that the number of edges is minimized.
- **skip_checks** (*bool*, optional) – If `True`, then input arguments won't pass through checks. Useful for efficiency.

Returns

- **path** (*list*) – The shortest path's vertices, including `start` and `end`. If there was not path connecting the vertices, then an empty *list* is returned.
- **distance** (*int* or *float*) – The distance (cost) of the path from `start` to `end`.

from_mask(*mask*)

A 1D boolean array with the same number of elements as the number of points in the *PointUndirectedGraph*. This is then broadcast across the dimensions of the *PointUndirectedGraph* and returns a new *PointUndirectedGraph* containing only those points that were `True` in the mask.

Parameters **mask** (`(n_vertices,)` *ndarray*) – 1D array of booleans

Returns **pointgraph** (`PointUndirectedGraph`) – A new pointgraph that has been masked.

Raises `ValueError` – Mask must be a 1D boolean array of the same number of entries as points in this PointUndirectedGraph.

from_vector(*vector*)

Build a new instance of the object from it's vectorized state.

`self` is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is which is a `deepcopy` of the object followed by a call to `from_vector_inplace()`. This method can be overridden for a performance benefit if desired.

Parameters **vector** (`(n_parameters,)` *ndarray*) – Flattened representation of the object.

Returns **object** (`type(self)`) – An new instance of this class.

from_vector_inplace(*vector*)

Updates the points of this PointCloud in-place with the reshaped points from the provided vector. Note that the vector should have the form `[x0, y0, x1, y1, ....., xn, yn]` for 2D.

Parameters **vector** (`(n_points,)` *ndarray*) – The vector from which to create the points' array.

get_adjacency_list()

Returns the adjacency list of the graph, i.e. a *list* of length `n_vertices` that for each vertex has a *list* of the vertex neighbours. If the graph is directed, the neighbours are children.

Returns **adjacency_list** (*list* of *list* of length `n_vertices`) – The adjacency list of the graph.

h_points()

Convert poincloud to a homogeneous array: `(n_dims + 1, n_points)`

Type `type(self)`

has_cycles()

Checks if the graph has at least one cycle.

Returns **has_cycles** (*bool*) – `True` if the graph has cycles.

has_isolated_vertices()

Whether the graph has any isolated vertices, i.e. vertices with no edge connections.

Returnshas_isolated_vertices (*bool*) – `True` if the graph has at least one isolated vertex.

has_nan_values()

Tests if the vectorized form of the object contains `nan` values or not. This is particularly useful for objects with unknown values that have been mapped to `nan` values.

Returnshas_nan_values (*bool*) – If the vectorized object contains `nan` values.

classmethod init_from_edges(*points*, *edges*, *copy=True*, *skip_checks=False*)

Construct a `PointUndirectedGraph` from edges array.

Parameters

- **points** (`(n_vertices, n_dims, )` *ndarray*) – The array of point locations.
- **edges** (`(n_edges, 2, )` *ndarray*) – The *ndarray* of edges, i.e. all the pairs of vertices that are connected with an edge.
- **copy** (*bool*, optional) – If `False`, the `adjacency_matrix` will not be copied on assignment.
- **skip_checks** (*bool*, optional) – If `True`, no checks will be performed.

Examples

The following undirected graph

```
|---0---|
|       |
|       |
1-------2
|       |
|       |
3-------4
|
|
5
```

can be defined as

```
from menpo.shape import PointUndirectedGraph
import numpy as np
points = np.array([[10, 30], [0, 20], [20, 20], [0, 10], [20, 10],
                   [0, 0]])
edges = np.array([[0, 1], [1, 0], [0, 2], [2, 0], [1, 2], [2, 1],
                  [1, 3], [3, 1], [2, 4], [4, 2], [3, 4], [4, 3],
                  [3, 5], [5, 3]])
graph = PointUndirectedGraph.init_from_edges(points, edges)
```

Finally, the following graph with isolated vertices

```
    0---|
        |
        |
1       2
        |
        |
3-------4
```

```
5
```

can be defined as

```
from menpo.shape import PointUndirectedGraph
import numpy as np
points = np.array([[10, 30], [0, 20], [20, 20], [0, 10], [20, 10],
                   [0, 0]])
edges = np.array([[0, 2], [2, 0], [2, 4], [4, 2], [3, 4], [4, 3]])
graph = PointUndirectedGraph.init_from_edges(points, edges)
```

is_edge(*vertex_1*, *vertex_2*, *skip_checks=False*)

Whether there is an edge between the provided vertices.

Parameters

- **vertex_1** (*int*) – The first selected vertex. Parent if the graph is directed.
- **vertex_2** (*int*) – The second selected vertex. Child if the graph is directed.
- **skip_checks** (*bool*, optional) – If `False`, the given vertices will be checked.

Returnsis_edge (*bool*) – `True` if there is an edge connecting `vertex_1` and `vertex_2`.

Raises`ValueError` – The vertex must be between 0 and {n_vertices-1}.

is_tree()

Checks if the graph is tree.

Returnsis_true (*bool*) – If the graph is a tree.

isolated_vertices()

Returns the isolated vertices of the graph (if any), i.e. the vertices that have no edge connections.

Returnsisolated_vertices (*list*) – A *list* of the isolated vertices. If there aren't any, it returns an empty *list*.

minimum_spanning_tree(*root_vertex*)

Returns the minimum spanning tree of the graph using Kruskal's algorithm.

Parametersroot_vertex (*int*) – The vertex that will be set as root in the output MST.

Returnsmst (`PointTree`) – The computed minimum spanning tree with the *points* of *self*.

Raises`ValueError` – Cannot compute minimum spanning tree of a graph with isolated vertices

n_neighbours(*vertex*, *skip_checks=False*)

Returns the number of neighbours of the selected vertex.

Parameters

- **vertex** (*int*) – The selected vertex.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returnsn_neighbours (*int*) – The number of neighbours.

Raises`ValueError` – The vertex must be between 0 and {n_vertices-1}.

n_paths(*start*, *end*)

Returns the number of all the paths (without cycles) existing from start vertex to end vertex.

Parameters

- **start** (*int*) – The vertex from which the paths start.
- **end** (*int*) – The vertex from which the paths end.

Returnspaths (*int*) – The paths' numbers.

neighbours(*vertex*, *skip_checks=False*)

Returns the neighbours of the selected vertex.

Parameters

- **vertex** (*int*) – The selected vertex.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returnsneighbours (*list*) – The list of neighbours.

Raises `ValueError` – The vertex must be between 0 and {n_vertices-1}.

norm(***kwargs*)

Returns the norm of this PointCloud. This is a translation and rotation invariant measure of the point cloud's intrinsic size - in other words, it is always taken around the point cloud's centre.

By default, the Frobenius norm is taken, but this can be changed by setting kwargs - see `numpy.linalg.norm` for valid options.

Returns **norm** (*float*) – The norm of this `PointCloud`

range(*boundary=0*)

The range of the extent of the PointCloud.

Parameters **boundary** (*float*) – A optional padding distance that is used to extend the bounds from which the range is computed. Default is `0`, no extension is performed.

Returns **range** (`(n_dims,)` *ndarray*) – The range of the `PointCloud` extent in each dimension.

tojson()

Convert this PointGraph to a dictionary representation suitable for inclusion in the LJSON landmark format.

Returns **json** (*dict*) – Dictionary with `points` and `connectivity` keys.

view_widget(*browser_style='buttons', figure_size=(10, 8), style='coloured'*)

Visualization of the PointGraph using the `visualize_pointclouds` widget.

Parameters

- **browser_style** (`{'buttons','slider'}`, optional) – It defines whether the selector of the objects will have the form of plus/minus buttons or a slider.
- **figure_size** ((*int*, *int*) *tuple*, optional) – The initial size of the rendered figure.
- **style** (`{'coloured','minimal'}`, optional) – If `'coloured'`, then the style of the widget will be coloured. If `minimal`, then the style is simple using black and white colours.

has_landmarks

Whether the object has landmarks.

Type *bool*

landmarks

The landmarks object.

Type `LandmarkManager`

n_dims

The number of dimensions in the pointcloud.

Type *int*

n_edges

Returns the number of edges.

Type *int*

n_landmark_groups

The number of landmark groups on this object.

Type *int*

n_parameters

The length of the vector that this object produces.

Type *int*

n_points

The number of points in the pointcloud.

Type *int*

n_vertices
Returns the number of vertices.
Type *int*

vertices
Returns the *list* of vertices.
Type *list*

PointDirectedGraph

class menpo.shape.**PointDirectedGraph**(*points*, *adjacency_matrix*, *copy=True*, *skip_checks=False*)
Bases: PointGraph, DirectedGraph

Class for defining a directed graph with geometry.

Parameters

- **points** ((n_vertices, n_dims) *ndarray*) – The array representing the points.
- **adjacency_matrix** ((n_vertices, n_vertices,) *ndarray* or *csr_matrix*) – The adjacency matrix of the graph in which the rows represent source vertices and columns represent destination vertices. The non-edges must be represented with zeros and the edges can have a weight value.
- **copy** (*bool*, optional) – If False, the adjacency_matrix will not be copied on assignment.
- **skip_checks** (*bool*, optional) – If True, no checks will be performed.

Raises

- ValueError – A point for each graph vertex needs to be passed. Got {n_points} points instead of {n_vertices}.
- ValueError – adjacency_matrix must be either a numpy.ndarray or a scipy.sparse.csr_matrix.
- ValueError – Graph must have at least two vertices.
- ValueError – adjacency_matrix must be square (n_vertices, n_vertices,), ({adjacency_matrix.shape[0]}, {adjacency_matrix.shape[1]}) given instead.

Examples

The following directed graph

```
|-->0<--|
|       |
|       |
1<----->2
|       |
v       v
3------>4
|
v
5
```

can be defined as

```
import numpy as np
adjacency_matrix = np.array([[0, 0, 0, 0, 0, 0],
                             [1, 0, 1, 1, 0, 0],
                             [1, 1, 0, 0, 1, 0],
                             [0, 0, 0, 0, 1, 1],
                             [0, 0, 0, 0, 0, 0],
                             [0, 0, 0, 0, 0, 0]])
points = np.array([[10, 30], [0, 20], [20, 20], [0, 10], [20, 10],
```

```
                    [0, 0]])
graph = PointDirectedGraph(points, adjacency_matrix)
```

or

```
from scipy.sparse import csr_matrix
adjacency_matrix = csr_matrix(([1] * 8, ([1, 2, 1, 2, 1, 2, 3, 3],
                                          [0, 0, 2, 1, 3, 4, 4, 5])),
                              shape=(6, 6))
points = np.array([[10, 30], [0, 20], [20, 20], [0, 10], [20, 10],
                   [0, 0]])
graph = PointDirectedGraph(points, adjacency_matrix)
```

The following graph with isolated vertices

```
       0<--|
           |
           |
   1       2
           |
           v
   3------>4

5
```

---

can be defined as

```
import numpy as np
adjacency_matrix = np.array([[0, 0, 0, 0, 0, 0],
                             [0, 0, 0, 0, 0, 0],
                             [1, 0, 0, 0, 1, 0],
                             [0, 0, 0, 0, 1, 0],
                             [0, 0, 0, 0, 0, 0],
                             [0, 0, 0, 0, 0, 0]])
points = np.array([[10, 30], [0, 20], [20, 20], [0, 10], [20, 10],
                   [0, 0]])
graph = PointDirectedGraph(points, adjacency_matrix)
```

or

```
from scipy.sparse import csr_matrix
adjacency_matrix = csr_matrix(([1] * 3, ([2, 2, 3], [0, 4, 4])),
                              shape=(6, 6))
points = np.array([[10, 30], [0, 20], [20, 20], [0, 10], [20, 10],
                   [0, 0]])
graph = PointDirectedGraph(points, adjacency_matrix)
```

_view_2d(*figure_id=None*, *new_figure=False*, *image_view=True*, *render_lines=True*, *line_colour='r'*, *line_style='-'*, *line_width=1.0*, *render_markers=True*, *marker_style='o'*, *marker_size=20*, *marker_face_colour='k'*, *marker_edge_colour='k'*, *marker_edge_width=1.0*, *render_axes=True*, *axes_font_name='sans-serif'*, *axes_font_size=10*, *axes_font_style='normal'*, *axes_font_weight='normal'*, *axes_x_limits=None*, *axes_y_limits=None*, *figure_size=(10, 8)*, *label=None*)

Visualization of the PointGraph in 2D.

Returns

- **figure_id** (*object*, optional) – The id of the figure to be used.

- **new_figure** (*bool*, optional) – If `True`, a new figure is created.
- **image_view** (*bool*, optional) – If `True` the PointGraph will be viewed as if it is in the image coordinate system.
- **render_lines** (*bool*, optional) – If `True`, the edges will be rendered.
- **line_colour** (*See Below, optional*) – The colour of the lines. Example options:

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **line_style** (`{-, --, -., :}`, optional) – The style of the lines.
- **line_width** (*float*, optional) – The width of the lines.
- **render_markers** (*bool*, optional) – If `True`, the markers will be rendered.
- **marker_style** (*See Below, optional*) – The style of the markers. Example options

```
{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}
```

- **marker_size** (*int*, optional) – The size of the markers in points^2.
- **marker_face_colour** (*See Below, optional*) – The face (filling) colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_colour** (*See Below, optional*) – The edge colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_width** (*float*, optional) – The width of the markers' edge.
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.
- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** (`{normal, italic, oblique}`, optional) – The font style of the axes.
- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **axes_x_limits** ((*float*, *float*) *tuple* or `None`, optional) – The limits of the x axis.
- **axes_y_limits** ((*float*, *float*) *tuple* or `None`, optional) – The limits of the y axis.
- **figure_size** ((*float*, *float*) *tuple* or `None`, optional) – The size of the figure in inches.
- **label** (*str*, optional) – The name entry in case of a legend.

Returns **viewer** (`PointGraphViewer2d`) – The viewer object.

_view_landmarks_2d(*group=None*, *with_labels=None*, *without_labels=None*, *figure_id=None*, *new_figure=False*, *image_view=True*, *render_lines=True*, *line_colour=None*, *line_style='-'*, *line_width=1*, *render_markers=True*, *marker_style='o'*, *marker_size=20*, *marker_face_colour=None*, *marker_edge_colour=None*, *marker_edge_width=1.0*, *render_numbering=False*, *numbers_horizontal_align='center'*, *numbers_vertical_align='bottom'*, *numbers_font_name='sans-serif'*, *numbers_font_size=10*, *numbers_font_style='normal'*, *numbers_font_weight='normal'*, *numbers_font_colour='k'*, *render_legend=False*, *legend_title=''*, *legend_font_name='sans-serif'*, *legend_font_style='normal'*, *legend_font_size=10*, *legend_font_weight='normal'*, *legend_marker_scale=None*, *legend_location=2*, *legend_bbox_to_anchor=(1.05, 1.0)*, *legend_border_axes_pad=None*, *legend_n_columns=1*, *legend_horizontal_spacing=None*, *legend_vertical_spacing=None*, *legend_border=True*, *legend_border_padding=None*, *legend_shadow=False*, *legend_rounded_corners=False*, *render_axes=False*, *axes_font_name='sans-serif'*, *axes_font_size=10*, *axes_font_style='normal'*, *axes_font_weight='normal'*, *axes_x_limits=None*, *axes_y_limits=None*, *figure_size=(10, 8)*)

Visualize the landmarks. This method will appear on the Image as `view_landmarks` if the Image is 2D.

Parameters

- **group** (*str* or''None'' optional) – The landmark group to be visualized. If `None` and there are more than one landmark groups, an error is raised.
- **with_labels** (`None` or *str* or *list* of *str*, optional) – If not `None`, only show the given label(s). Should **not** be used with the `without_labels` kwarg.
- **without_labels** (`None` or *str* or *list* of *str*, optional) – If not `None`, show all except the given label(s). Should **not** be used with the `with_labels` kwarg.
- **figure_id** (*object*, optional) – The id of the figure to be used.
- **new_figure** (*bool*, optional) – If `True`, a new figure is created.
- **image_view** (*bool*, optional) – If `True` the PointCloud will be viewed as if it is in the image coordinate system.
- **render_lines** (*bool*, optional) – If `True`, the edges will be rendered.
- **line_colour** (*See Below, optional*) – The colour of the lines. Example options:

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **line_style** (`{-, --, -., :}`, optional) – The style of the lines.
- **line_width** (*float*, optional) – The width of the lines.
- **render_markers** (*bool*, optional) – If `True`, the markers will be rendered.
- **marker_style** (*See Below, optional*) – The style of the markers. Example options

```
{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}
```

- **marker_size** (*int*, optional) – The size of the markers in points^2.
- **marker_face_colour** (*See Below, optional*) – The face (filling) colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
```

```
(3, ) ndarray
```

- **marker_edge_colour** (*See Below, optional*) – The edge colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_width** (*float*, optional) – The width of the markers' edge.
- **render_numbering** (*bool*, optional) – If `True`, the landmarks will be numbered.
- **numbers_horizontal_align** (`{center, right, left}`, optional) – The horizontal alignment of the numbers' texts.
- **numbers_vertical_align** (`{center, top, bottom, baseline}`, optional) – The vertical alignment of the numbers' texts.
- **numbers_font_name** (*See Below, optional*) – The font of the numbers. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **numbers_font_size** (*int*, optional) – The font size of the numbers.
- **numbers_font_style** (`{normal, italic, oblique}`, optional) – The font style of the numbers.
- **numbers_font_weight** (*See Below, optional*) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **numbers_font_colour** (*See Below, optional*) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **render_legend** (*bool*, optional) – If `True`, the legend will be rendered.
- **legend_title** (*str*, optional) – The title of the legend.
- **legend_font_name** (*See below, optional*) – The font of the legend. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **legend_font_style** (`{normal, italic, oblique}`, optional) – The font style of the legend.
- **legend_font_size** (*int*, optional) – The font size of the legend.
- **legend_font_weight** (*See Below, optional*) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **legend_marker_scale** (*float*, optional) – The relative size of the legend markers with respect to the original
- **legend_location** (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

- **legend_bbox_to_anchor** ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.
- **legend_border_axes_pad** (*float*, optional) – The pad between the axes and legend border.
- **legend_n_columns** (*int*, optional) – The number of the legend's columns.
- **legend_horizontal_spacing** (*float*, optional) – The spacing between the columns.
- **legend_vertical_spacing** (*float*, optional) – The vertical space between the legend entries.
- **legend_border** (*bool*, optional) – If `True`, a frame will be drawn around the legend.
- **legend_border_padding** (*float*, optional) – The fractional whitespace inside the legend border.
- **legend_shadow** (*bool*, optional) – If `True`, a shadow will be drawn behind legend.
- **legend_rounded_corners** (*bool*, optional) – If `True`, the frame's corners will be rounded (fancybox).
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.
- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** (`{normal, italic, oblique}`, optional) – The font style of the axes.
- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold,demibold, demi, bold, heavy, extra bold, black}
```

- **axes_x_limits** ((*float*, *float*) *tuple* or `None` optional) – The limits of the x axis.
- **axes_y_limits** ((*float*, *float*) *tuple* or `None` optional) – The limits of the y axis.
- **figure_size** ((*float*, *float*) *tuple* or `None` optional) – The size of the figure in inches.

Raises

- `ValueError` – If both `with_labels` and `without_labels` are passed.
- `ValueError` – If the landmark manager doesn't contain the provided group label.

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returnsvector (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

bounding_box()

Return a bounding box from two corner points as a directed graph. The the first point (0) should be nearest the origin. In the case of an image, this ordering would appear as:

```
0<--3
|   ^
|   |
v   |
1-->2
```

In the case of a pointcloud, the ordering will appear as:

```
3<--2
|   ^
|   |
v   |
0-->1
```

Returnsbounding_box (*PointDirectedGraph*) – The axis aligned bounding box of the PointCloud.

bounds(*boundary=0*)

The minimum to maximum extent of the PointCloud. An optional boundary argument can be provided to expand the bounds by a constant margin.

Parametersboundary (*float*) – A optional padding distance that is added to the bounds. Default is `0`, meaning the max/min of tightest possible containing square/cube/hypercube is returned.

Returns

- **min_b** (`(n_dims,)` *ndarray*) – The minimum extent of the *PointCloud* and boundary along each dimension
- **max_b** (`(n_dims,)` *ndarray*) – The maximum extent of the *PointCloud* and boundary along each dimension

centre()

The mean of all the points in this PointCloud (centre of mass).

Returnscentre (`(n_dims)` *ndarray*) – The mean of this PointCloud's points.

centre_of_bounds()

The centre of the absolute bounds of this PointCloud. Contrast with *centre()*, which is the mean point position.

Returnscentre (`n_dims` *ndarray*) – The centre of the bounds of this PointCloud.

children(*vertex*, *skip_checks=False*)

Returns the children of the selected vertex.

Parameters

- **vertex** (*int*) – The selected vertex.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returnschildren (*list*) – The list of children.

Raises`ValueError` – The vertex must be between 0 and {n_vertices-1}.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns `type(self)` – A copy of this object

distance_to (*pointcloud*, ***kwargs*)

Returns a distance matrix between this PointCloud and another. By default the Euclidean distance is calculated - see *scipy.spatial.distance.cdist* for valid kwargs to change the metric and other properties.

Parameters **pointcloud** (`PointCloud`) – The second pointcloud to compute distances between. This must be of the same dimension as this PointCloud.

Returns **distance_matrix** (`(n_points, n_points)` *ndarray*) – The symmetric pairwise distance matrix between the two PointClouds s.t. `distance_matrix[i, j]` is the distance between the i'th point of this PointCloud and the j'th point of the input PointCloud.

find_all_paths (*start*, *end*, *path=[]*)

Returns a list of lists with all the paths (without cycles) found from start vertex to end vertex.

Parameters

- **start** (*int*) – The vertex from which the paths start.
- **end** (*int*) – The vertex from which the paths end.
- **path** (*list*, optional) – An existing path to append to.

Returns **paths** (*list* of *list*) – The list containing all the paths from start to end.

find_all_shortest_paths (*algorithm='auto'*, *unweighted=False*)

Returns the distances and predecessors arrays of the graph's shortest paths.

Parameters

- **algorithm** (*'str', see below, optional*) – The algorithm to be used. Possible options are:

'dijkstra'	Dijkstra's algorithm with Fibonacci heaps
'bellman-ford'	Bellman-Ford algorithm
'johnson'	Johnson's algorithm
'floyd-warshall'	Floyd-Warshall algorithm
'auto'	Select the best among the above

- **unweighted** (*bool*, optional) – If `True`, then find unweighted distances. That is, rather than finding the path between each vertex such that the sum of weights is minimized, find the path such that the number of edges is minimized.

Returns

- **distances** (`(n_vertices, n_vertices,)` *ndarray*) – The matrix of distances between all graph vertices. `distances[i,j]` gives the shortest distance from vertex `i` to vertex `j` along the graph.
- **predecessors** (`(n_vertices, n_vertices,)` *ndarray*) – The matrix of predecessors, which can be used to reconstruct the shortest paths. Each entry `predecessors[i, j]` gives the index of the previous vertex in the path from vertex `i` to vertex `j`. If no path exists between vertices `i` and `j`, then `predecessors[i, j] = -9999`.

find_path (*start*, *end*, *method='bfs'*, *skip_checks=False*)

Returns a *list* with the first path (without cycles) found from the `start` vertex to the `end` vertex. It can employ either depth-first search or breadth-first search.

Parameters

- **start** (*int*) – The vertex from which the path starts.
- **end** (*int*) – The vertex to which the path ends.
- **method** ({`bfs`, `dfs`}, optional) – The method to be used.
- **skip_checks** (*bool*, optional) – If `True`, then input arguments won't pass through checks. Useful for efficiency.

Returns **path** (*list*) – The path's vertices.

Raises `ValueError` – Method must be either bfs or dfs.

find_shortest_path(*start*, *end*, *algorithm='auto'*, *unweighted=False*, *skip_checks=False*)

Returns a *list* with the shortest path (without cycles) found from `start` vertex to `end` vertex.

Parameters

- **start** (*int*) – The vertex from which the path starts.
- **end** (*int*) – The vertex to which the path ends.
- **algorithm** (*'str', see below, optional*) – The algorithm to be used. Possible options are:

'dijkstra'	Dijkstra's algorithm with Fibonacci heaps
'bellman-ford'	Bellman-Ford algorithm
'johnson'	Johnson's algorithm
'floyd-warshall'	Floyd-Warshall algorithm
'auto'	Select the best among the above

- **unweighted** (*bool*, optional) – If `True`, then find unweighted distances. That is, rather than finding the path such that the sum of weights is minimized, find the path such that the number of edges is minimized.
- **skip_checks** (*bool*, optional) – If `True`, then input arguments won't pass through checks. Useful for efficiency.

Returns

- **path** (*list*) – The shortest path's vertices, including `start` and `end`. If there was not path connecting the vertices, then an empty *list* is returned.
- **distance** (*int* or *float*) – The distance (cost) of the path from `start` to `end`.

from_mask(*mask*)

A 1D boolean array with the same number of elements as the number of points in the *PointDirectedGraph*. This is then broadcast across the dimensions of the *PointDirectedGraph* and returns a new *PointDirectedGraph* containing only those points that were `True` in the mask.

Parameters **mask** (`(n_points,)` *ndarray*) – 1D array of booleans

Returns **pointgraph** (*`PointDirectedGraph`*) – A new pointgraph that has been masked.

Raises `ValueError` – Mask must be a 1D boolean array of the same number of entries as points in this PointDirectedGraph.

from_vector(*vector*)

Build a new instance of the object from it's vectorized state.

`self` is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is which is a `deepcopy` of the object followed by a call to *`from_vector_inplace()`*. This method can be overridden for a performance benefit if desired.

Parameters **vector** (`(n_parameters,)` *ndarray*) – Flattened representation of the object.

Returns **object** (`type(self)`) – An new instance of this class.

from_vector_inplace(*vector*)

Updates the points of this PointCloud in-place with the reshaped points from the provided vector. Note that the vector should have the form `[x0, y0, x1, y1, ....., xn, yn]` for 2D.

Parameters **vector** (`(n_points,)` *ndarray*) – The vector from which to create the points' array.

get_adjacency_list()

Returns the adjacency list of the graph, i.e. a *list* of length `n_vertices` that for each vertex has a *list* of the vertex neighbours. If the graph is directed, the neighbours are children.

Returns **adjacency_list** (*list* of *list* of length `n_vertices`) – The adjacency list of the graph.

h_points()

Convert poincloud to a homogeneous array: `(n_dims + 1, n_points)`

Type `type(self)`

has_cycles()

Checks if the graph has at least one cycle.

Returns **has_cycles** (*bool*) – `True` if the graph has cycles.

has_isolated_vertices()

Whether the graph has any isolated vertices, i.e. vertices with no edge connections.

Returns **has_isolated_vertices** (*bool*) – `True` if the graph has at least one isolated vertex.

has_nan_values()

Tests if the vectorized form of the object contains `nan` values or not. This is particularly useful for objects with unknown values that have been mapped to `nan` values.

Returns **has_nan_values** (*bool*) – If the vectorized object contains `nan` values.

init_from_edges(*points*, *edges*, *copy=True*, *skip_checks=False*)

Construct a PointGraph from edges array.

Parameters

- **points** (`(n_vertices, n_dims, )` *ndarray*) – The array of point locations.
- **edges** (`(n_edges, 2, )` *ndarray*) – The *ndarray* of edges, i.e. all the pairs of vertices that are connected with an edge.
- **copy** (*bool*, optional) – If `False`, the `adjacency_matrix` will not be copied on assignment.
- **skip_checks** (*bool*, optional) – If `True`, no checks will be performed.

Examples

The following undirected graph

```
|---0---|
|       |
|       |
1-------2
|       |
|       |
3-------4
|
|
5
```

can be defined as

```
from menpo.shape import PointUndirectedGraph
import numpy as np
points = np.array([[10, 30], [0, 20], [20, 20], [0, 10], [20, 10],
                   [0, 0]])
edges = np.array([[0, 1], [1, 0], [0, 2], [2, 0], [1, 2], [2, 1],
                  [1, 3], [3, 1], [2, 4], [4, 2], [3, 4], [4, 3],
                  [3, 5], [5, 3]])
graph = PointUndirectedGraph.init_from_edges(points, edges)
```

The following directed graph

```
|-->0<--|
|       |
|       |
1<----->2
```

```
|       |
v       v
3------>4
|
v
5
```

can be represented as

```
from menpo.shape import PointDirectedGraph
import numpy as np
points = np.array([[10, 30], [0, 20], [20, 20], [0, 10], [20, 10],
                   [0, 0]])
edges = np.array([[1, 0], [2, 0], [1, 2], [2, 1], [1, 3], [2, 4],
                  [3, 4], [3, 5]])
graph = PointDirectedGraph.init_from_edges(points, edges)
```

Finally, the following graph with isolated vertices

```
    0---|
        |
        |
1       2
        |
        |
3-------4


5
```

can be defined as

```
from menpo.shape import PointUndirectedGraph
import numpy as np
points = np.array([[10, 30], [0, 20], [20, 20], [0, 10], [20, 10],
                   [0, 0]])
edges = np.array([[0, 2], [2, 0], [2, 4], [4, 2], [3, 4], [4, 3]])
graph = PointUndirectedGraph.init_from_edges(points, edges)
```

is_edge(*vertex_1*, *vertex_2*, *skip_checks=False*)

Whether there is an edge between the provided vertices.

Parameters

- **vertex_1** (*int*) – The first selected vertex. Parent if the graph is directed.
- **vertex_2** (*int*) – The second selected vertex. Child if the graph is directed.
- **skip_checks** (*bool*, optional) – If `False`, the given vertices will be checked.

Returnsis_edge (*bool*) – `True` if there is an edge connecting `vertex_1` and `vertex_2`.

Raises`ValueError` – The vertex must be between 0 and {n_vertices-1}.

is_tree()

Checks if the graph is tree.

Returnsis_true (*bool*) – If the graph is a tree.

isolated_vertices()

Returns the isolated vertices of the graph (if any), i.e. the vertices that have no edge connections.

Returnsisolated_vertices (*list*) – A *list* of the isolated vertices. If there aren't any, it returns an empty *list*.

n_children (*vertex*, *skip_checks=False*)

Returns the number of children of the selected vertex.

Parameters **vertex** (*int*) – The selected vertex.

Returns

- **n_children** (*int*) – The number of children.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Raises `ValueError` – The vertex must be in the range `[0, n_vertices - 1]`.

n_parents (*vertex*, *skip_checks=False*)

Returns the number of parents of the selected vertex.

Parameters

- **vertex** (*int*) – The selected vertex.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returns **n_parents** (*int*) – The number of parents.

Raises `ValueError` – The vertex must be in the range `[0, n_vertices - 1]`.

n_paths (*start*, *end*)

Returns the number of all the paths (without cycles) existing from start vertex to end vertex.

Parameters

- **start** (*int*) – The vertex from which the paths start.
- **end** (*int*) – The vertex from which the paths end.

Returns **paths** (*int*) – The paths' numbers.

norm (***kwargs*)

Returns the norm of this PointCloud. This is a translation and rotation invariant measure of the point cloud's intrinsic size - in other words, it is always taken around the point cloud's centre.

By default, the Frobenius norm is taken, but this can be changed by setting kwargs - see `numpy.linalg.norm` for valid options.

Returns **norm** (*float*) – The norm of this *PointCloud*

parents (*vertex*, *skip_checks=False*)

Returns the parents of the selected vertex.

Parameters

- **vertex** (*int*) – The selected vertex.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returns **parents** (*list*) – The list of parents.

Raises `ValueError` – The vertex must be in the range `[0, n_vertices - 1]`.

range (*boundary=0*)

The range of the extent of the PointCloud.

Parameters **boundary** (*float*) – A optional padding distance that is used to extend the bounds from which the range is computed. Default is `0`, no extension is performed.

Returns **range** (`(n_dims,)` *ndarray*) – The range of the *PointCloud* extent in each dimension.

relative_location_edge (*parent*, *child*)

Returns the relative location between the provided vertices. That is if vertex j is the parent and vertex i is its child and vector l denotes the coordinates of a vertex, then

```
l_i - l_j = [[x_i], [y_i]] - [[x_j], [y_j]] =
          = [[x_i - x_j], [y_i - y_j]]
```

Parameters

- **parent** (*int*) – The first selected vertex which is considered as the parent.
- **child** (*int*) – The second selected vertex which is considered as the child.

Returns **relative_location** (`(2,)` *ndarray*) – The relative location vector.

Raises `ValueError` – Vertices `parent` and `child` are not connected with an edge.

relative_locations()

Returns the relative location between the vertices of each edge. If vertex j is the parent and vertex i is its child and vector l denotes the coordinates of a vertex, then:

```
l_i - l_j = [[x_i], [y_i]] - [[x_j], [y_j]] =
          = [[x_i - x_j], [y_i - y_j]]
```

Returnsrelative_locations ((n_vertexes, 2) *ndarray*) – The relative locations vector.

tojson()

Convert this PointGraph to a dictionary representation suitable for inclusion in the LJSON landmark format.

Returnsjson (*dict*) – Dictionary with `points` and `connectivity` keys.

view_widget(*browser_style='buttons'*, *figure_size=(10, 8)*, *style='coloured'*)

Visualization of the PointGraph using the `visualize_pointclouds` widget.

Parameters

- **browser_style** ({'buttons', 'slider'}, optional) – It defines whether the selector of the objects will have the form of plus/minus buttons or a slider.
- **figure_size** ((*int*, *int*) *tuple*, optional) – The initial size of the rendered figure.
- **style** ({'coloured', 'minimal'}, optional) – If 'coloured', then the style of the widget will be coloured. If `minimal`, then the style is simple using black and white colours.

has_landmarks

Whether the object has landmarks.

Type*bool*

landmarks

The landmarks object.

Type*LandmarkManager*

n_dims

The number of dimensions in the pointcloud.

Type*int*

n_edges

Returns the number of edges.

Type*int*

n_landmark_groups

The number of landmark groups on this object.

Type*int*

n_parameters

The length of the vector that this object produces.

Type*int*

n_points

The number of points in the pointcloud.

Type*int*

n_vertices

Returns the number of vertices.

Type*int*

vertices

Returns the *list* of vertices.

Type*list*

PointTree

class `menpo.shape.`**`PointTree`**(*points*, *adjacency_matrix*, *root_vertex*, *copy=True*, *skip_checks=False*)

Bases: `PointDirectedGraph`, `Tree`

Class for defining a Tree with geometry.

Parameters

- **`points`** (`(n_vertices, n_dims)` *ndarray*) – The array representing the points.
- **`adjacency_matrix`** (`(n_vertices, n_vertices, )` *ndarray* or *csr_matrix*) – The adjacency matrix of the tree in which the rows represent parents and columns represent children. The non-edges must be represented with zeros and the edges can have a weight value.

  NoteA tree must not have isolated vertices.
- **`root_vertex`** (*int*) – The vertex to be set as root.
- **`copy`** (*bool*, optional) – If `False`, the `adjacency_matrix` will not be copied on assignment.
- **`skip_checks`** (*bool*, optional) – If `True`, no checks will be performed.

Raises

- `ValueError` – A point for each graph vertex needs to be passed. Got {n_points} points instead of {n_vertices}.
- `ValueError` – adjacency_matrix must be either a numpy.ndarray or a scipy.sparse.csr_matrix.
- `ValueError` – Graph must have at least two vertices.
- `ValueError` – adjacency_matrix must be square (n_vertices, n_vertices,), ({adjacency_matrix.shape[0]}, {adjacency_matrix.shape[1]}) given instead.
- `ValueError` – The provided edges do not represent a tree.
- `ValueError` – The root_vertex must be in the range `[0, n_vertices - 1]`.
- `ValueError` – The combination of adjacency matrix and root vertex is not valid. BFS returns a different tree.

Examples

The following tree

```
        0
        |
    ____|____
   1        2
   |        |
 _|_        |
3   4       5
|   |       |
|   |       |
6   7       8
```

can be defined as

```
import numpy as np
adjacency_matrix = np.array([[0, 1, 1, 0, 0, 0, 0, 0, 0],
                             [0, 0, 0, 1, 1, 0, 0, 0, 0],
                             [0, 0, 0, 0, 0, 1, 0, 0, 0],
                             [0, 0, 0, 0, 0, 0, 1, 0, 0],
                             [0, 0, 0, 0, 0, 0, 0, 1, 0],
                             [0, 0, 0, 0, 0, 0, 0, 0, 1],
                             [0, 0, 0, 0, 0, 0, 0, 0, 0],
                             [0, 0, 0, 0, 0, 0, 0, 0, 0],
                             [0, 0, 0, 0, 0, 0, 0, 0, 0]])
```

```
points = np.array([[30, 30], [10, 20], [50, 20], [0, 10], [20, 10],
                   [50, 10], [0, 0], [20, 0], [50, 0]])
tree = PointTree(points, adjacency_matrix, root_vertex=0)
```

or

```
from scipy.sparse import csr_matrix
adjacency_matrix = csr_matrix(([1] * 8, ([0, 0, 1, 1, 2, 3, 4, 5],
                                          [1, 2, 3, 4, 5, 6, 7, 8])),
                              shape=(9, 9))
points = np.array([[30, 30], [10, 20], [50, 20], [0, 10], [20, 10],
                   [50, 10], [0, 0], [20, 0], [50, 0]])
tree = PointTree(points, adjacency_matrix, root_vertex=0)
```

_view_2d(*figure_id=None*, *new_figure=False*, *image_view=True*, *render_lines=True*, *line_colour='r'*, *line_style='-'*, *line_width=1.0*, *render_markers=True*, *marker_style='o'*, *marker_size=20*, *marker_face_colour='k'*, *marker_edge_colour='k'*, *marker_edge_width=1.0*, *render_axes=True*, *axes_font_name='sans-serif'*, *axes_font_size=10*, *axes_font_style='normal'*, *axes_font_weight='normal'*, *axes_x_limits=None*, *axes_y_limits=None*, *figure_size=(10, 8)*, *label=None*)

Visualization of the PointGraph in 2D.

Returns

- **figure_id** (*object*, optional) – The id of the figure to be used.
- **new_figure** (*bool*, optional) – If `True`, a new figure is created.
- **image_view** (*bool*, optional) – If `True` the PointGraph will be viewed as if it is in the image coordinate system.
- **render_lines** (*bool*, optional) – If `True`, the edges will be rendered.
- **line_colour** (*See Below, optional*) – The colour of the lines. Example options:

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **line_style** (`{-, --, -., :}`, optional) – The style of the lines.
- **line_width** (*float*, optional) – The width of the lines.
- **render_markers** (*bool*, optional) – If `True`, the markers will be rendered.
- **marker_style** (*See Below, optional*) – The style of the markers. Example options

```
{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}
```

- **marker_size** (*int*, optional) – The size of the markers in points^2.
- **marker_face_colour** (*See Below, optional*) – The face (filling) colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_colour** (*See Below, optional*) – The edge colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_width** (*float*, optional) – The width of the markers' edge.
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.

- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** ({`normal`, `italic`, `oblique`}, optional) – The font style of the axes.
- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **axes_x_limits** ((*float*, *float*) *tuple* or `None`, optional) – The limits of the x axis.
- **axes_y_limits** ((*float*, *float*) *tuple* or `None`, optional) – The limits of the y axis.
- **figure_size** ((*float*, *float*) *tuple* or `None`, optional) – The size of the figure in inches.
- **label** (*str*, optional) – The name entry in case of a legend.

Returns **viewer** (`PointGraphViewer2d`) – The viewer object.

_view_landmarks_2d(*group=None*, *with_labels=None*, *without_labels=None*, *figure_id=None*, *new_figure=False*, *image_view=True*, *render_lines=True*, *line_colour=None*, *line_style='-'*, *line_width=1*, *render_markers=True*, *marker_style='o'*, *marker_size=20*, *marker_face_colour=None*, *marker_edge_colour=None*, *marker_edge_width=1.0*, *render_numbering=False*, *numbers_horizontal_align='center'*, *numbers_vertical_align='bottom'*, *numbers_font_name='sans-serif'*, *numbers_font_size=10*, *numbers_font_style='normal'*, *numbers_font_weight='normal'*, *numbers_font_colour='k'*, *render_legend=False*, *legend_title=''*, *legend_font_name='sans-serif'*, *legend_font_style='normal'*, *legend_font_size=10*, *legend_font_weight='normal'*, *legend_marker_scale=None*, *legend_location=2*, *legend_bbox_to_anchor=(1.05, 1.0)*, *legend_border_axes_pad=None*, *legend_n_columns=1*, *legend_horizontal_spacing=None*, *legend_vertical_spacing=None*, *legend_border=True*, *legend_border_padding=None*, *legend_shadow=False*, *legend_rounded_corners=False*, *render_axes=False*, *axes_font_name='sans-serif'*, *axes_font_size=10*, *axes_font_style='normal'*, *axes_font_weight='normal'*, *axes_x_limits=None*, *axes_y_limits=None*, *figure_size=(10, 8)*)

Visualize the landmarks. This method will appear on the Image as `view_landmarks` if the Image is 2D.

Parameters

- **group** (*str* or''None'' optional) – The landmark group to be visualized. If `None` and there are more than one landmark groups, an error is raised.
- **with_labels** (`None` or *str* or *list* of *str*, optional) – If not `None`, only show the given label(s). Should **not** be used with the `without_labels` kwarg.
- **without_labels** (`None` or *str* or *list* of *str*, optional) – If not `None`, show all except the given label(s). Should **not** be used with the `with_labels` kwarg.
- **figure_id** (*object*, optional) – The id of the figure to be used.
- **new_figure** (*bool*, optional) – If `True`, a new figure is created.
- **image_view** (*bool*, optional) – If `True` the PointCloud will be viewed as if it is in the image coordinate system.
- **render_lines** (*bool*, optional) – If `True`, the edges will be rendered.
- **line_colour** (*See Below, optional*) – The colour of the lines. Example options:

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **line_style** ({-, --, -., :}, optional) – The style of the lines.
- **line_width** (*float*, optional) – The width of the lines.
- **render_markers** (*bool*, optional) – If True, the markers will be rendered.
- **marker_style** (*See Below, optional*) – The style of the markers. Example options

```
{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}
```

- **marker_size** (*int*, optional) – The size of the markers in points^2.
- **marker_face_colour** (*See Below, optional*) – The face (filling) colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_colour** (*See Below, optional*) – The edge colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_width** (*float*, optional) – The width of the markers' edge.
- **render_numbering** (*bool*, optional) – If True, the landmarks will be numbered.
- **numbers_horizontal_align** ({center, right, left}, optional) – The horizontal alignment of the numbers' texts.
- **numbers_vertical_align** ({center, top, bottom, baseline}, optional) – The vertical alignment of the numbers' texts.
- **numbers_font_name** (*See Below, optional*) – The font of the numbers. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **numbers_font_size** (*int*, optional) – The font size of the numbers.
- **numbers_font_style** ({normal, italic, oblique}, optional) – The font style of the numbers.
- **numbers_font_weight** (*See Below, optional*) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **numbers_font_colour** (*See Below, optional*) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **render_legend** (*bool*, optional) – If True, the legend will be rendered.
- **legend_title** (*str*, optional) – The title of the legend.

- **legend_font_name** (*See below, optional*) – The font of the legend. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **legend_font_style** (`{normal, italic, oblique}`, optional) – The font style of the legend.
- **legend_font_size** (*int*, optional) – The font size of the legend.
- **legend_font_weight** (*See Below, optional*) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **legend_marker_scale** (*float*, optional) – The relative size of the legend markers with respect to the original
- **legend_location** (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

- **legend_bbox_to_anchor** ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.
- **legend_border_axes_pad** (*float*, optional) – The pad between the axes and legend border.
- **legend_n_columns** (*int*, optional) – The number of the legend's columns.
- **legend_horizontal_spacing** (*float*, optional) – The spacing between the columns.
- **legend_vertical_spacing** (*float*, optional) – The vertical space between the legend entries.
- **legend_border** (*bool*, optional) – If `True`, a frame will be drawn around the legend.
- **legend_border_padding** (*float*, optional) – The fractional whitespace inside the legend border.
- **legend_shadow** (*bool*, optional) – If `True`, a shadow will be drawn behind legend.
- **legend_rounded_corners** (*bool*, optional) – If `True`, the frame's corners will be rounded (fancybox).
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.
- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** (`{normal, italic, oblique}`, optional) – The font style of the axes.

- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold,demibold, demi, bold, heavy, extra bold, black}
```

- **axes_x_limits** ((*float*, *float*) *tuple* or `None` optional) – The limits of the x axis.
- **axes_y_limits** ((*float*, *float*) *tuple* or `None` optional) – The limits of the y axis.
- **figure_size** ((*float*, *float*) *tuple* or `None` optional) – The size of the figure in inches.

Raises

- `ValueError` – If both `with_labels` and `without_labels` are passed.
- `ValueError` – If the landmark manager doesn't contain the provided group label.

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returnsvector (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

bounding_box()

Return a bounding box from two corner points as a directed graph. The the first point (0) should be nearest the origin. In the case of an image, this ordering would appear as:

```
0<--3
|   ^
|   |
v   |
1-->2
```

In the case of a pointcloud, the ordering will appear as:

```
3<--2
|   ^
|   |
v   |
0-->1
```

Returnsbounding_box (`PointDirectedGraph`) – The axis aligned bounding box of the PointCloud.

bounds(*boundary=0*)

The minimum to maximum extent of the PointCloud. An optional boundary argument can be provided to expand the bounds by a constant margin.

Parametersboundary (*float*) – A optional padding distance that is added to the bounds. Default is `0`, meaning the max/min of tightest possible containing square/cube/hypercube is returned.

Returns

- **min_b** (`(n_dims,)` *ndarray*) – The minimum extent of the `PointCloud` and boundary along each dimension
- **max_b** (`(n_dims,)` *ndarray*) – The maximum extent of the `PointCloud` and boundary along each dimension

centre()

The mean of all the points in this PointCloud (centre of mass).

Returnscentre (`(n_dims)` *ndarray*) – The mean of this PointCloud's points.

centre_of_bounds()

The centre of the absolute bounds of this PointCloud. Contrast with `centre()`, which is the mean point position.

Returns **centre** (`n_dims` *ndarray*) – The centre of the bounds of this PointCloud.

children(*vertex*, *skip_checks=False*)

Returns the children of the selected vertex.

Parameters

- **vertex** (*int*) – The selected vertex.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returns **children** (*list*) – The list of children.

Raises `ValueError` – The vertex must be between 0 and {n_vertices-1}.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other `Copyable` objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns `type(self)` – A copy of this object

depth_of_vertex(*vertex*, *skip_checks=False*)

Returns the depth of the specified vertex.

Parameters

- **vertex** (*int*) – The selected vertex.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returns **depth** (*int*) – The depth of the selected vertex.

Raises `ValueError` – The vertex must be in the range `[0, n_vertices - 1]`.

distance_to(*pointcloud*, ***kwargs*)

Returns a distance matrix between this PointCloud and another. By default the Euclidean distance is calculated - see *scipy.spatial.distance.cdist* for valid kwargs to change the metric and other properties.

Parameters **pointcloud** (`PointCloud`) – The second pointcloud to compute distances between. This must be of the same dimension as this PointCloud.

Returns **distance_matrix** (`(n_points, n_points)` *ndarray*) – The symmetric pairwise distance matrix between the two PointClouds s.t. `distance_matrix[i, j]` is the distance between the i'th point of this PointCloud and the j'th point of the input PointCloud.

find_all_paths(*start*, *end*, *path=[]*)

Returns a list of lists with all the paths (without cycles) found from start vertex to end vertex.

Parameters

- **start** (*int*) – The vertex from which the paths start.
- **end** (*int*) – The vertex from which the paths end.
- **path** (*list*, optional) – An existing path to append to.

Returns **paths** (*list* of *list*) – The list containing all the paths from start to end.

find_all_shortest_paths(*algorithm='auto'*, *unweighted=False*)

Returns the distances and predecessors arrays of the graph's shortest paths.

Parameters

- **algorithm** (*'str', see below, optional*) – The algorithm to be used. Possible options are:

'dijkstra'	Dijkstra's algorithm with Fibonacci heaps
'bellman-ford'	Bellman-Ford algorithm
'johnson'	Johnson's algorithm
'floyd-warshall'	Floyd-Warshall algorithm
'auto'	Select the best among the above

- **unweighted** (*bool*, optional) – If `True`, then find unweighted distances. That is, rather than finding the path between each vertex such that the sum of weights is minimized, find the path such that the number of edges is minimized.

Returns

- **distances** (`(n_vertices, n_vertices,)` *ndarray*) – The matrix of distances between all graph vertices. `distances[i,j]` gives the shortest distance from vertex `i` to vertex `j` along the graph.
- **predecessors** (`(n_vertices, n_vertices,)` *ndarray*) – The matrix of predecessors, which can be used to reconstruct the shortest paths. Each entry `predecessors[i, j]` gives the index of the previous vertex in the path from vertex `i` to vertex `j`. If no path exists between vertices `i` and `j`, then `predecessors[i, j] = -9999`.

find_path (*start*, *end*, *method='bfs'*, *skip_checks=False*)

Returns a *list* with the first path (without cycles) found from the `start` vertex to the `end` vertex. It can employ either depth-first search or breadth-first search.

Parameters

- **start** (*int*) – The vertex from which the path starts.
- **end** (*int*) – The vertex to which the path ends.
- **method** (`{bfs, dfs}`, optional) – The method to be used.
- **skip_checks** (*bool*, optional) – If `True`, then input arguments won't pass through checks. Useful for efficiency.

Returnspath (*list*) – The path's vertices.

Raises`ValueError` – Method must be either bfs or dfs.

find_shortest_path (*start*, *end*, *algorithm='auto'*, *unweighted=False*, *skip_checks=False*)

Returns a *list* with the shortest path (without cycles) found from `start` vertex to `end` vertex.

Parameters

- **start** (*int*) – The vertex from which the path starts.
- **end** (*int*) – The vertex to which the path ends.
- **algorithm** (*'str', see below, optional*) – The algorithm to be used. Possible options are:

'dijkstra'	Dijkstra's algorithm with Fibonacci heaps
'bellman-ford'	Bellman-Ford algorithm
'johnson'	Johnson's algorithm
'floyd-warshall'	Floyd-Warshall algorithm
'auto'	Select the best among the above

- **unweighted** (*bool*, optional) – If `True`, then find unweighted distances. That is, rather than finding the path such that the sum of weights is minimized, find the path such that the number of edges is minimized.
- **skip_checks** (*bool*, optional) – If `True`, then input arguments won't pass through checks. Useful for efficiency.

Returns

- **path** (*list*) – The shortest path's vertices, including `start` and `end`. If there was not path connecting the vertices, then an empty *list* is returned.
- **distance** (*int* or *float*) – The distance (cost) of the path from `start` to `end`.

from_mask (*mask*)

A 1D boolean array with the same number of elements as the number of points in the *PointTree*. This is then broadcast across the dimensions of the *PointTree* and returns a new *PointTree* containing only those

points that were `True` in the mask.

Parameters`mask` (`(n_points,)` *ndarray*) – 1D array of booleans

Returns`pointtree` (`PointTree`) – A new pointtree that has been masked.

Raises

- `ValueError` – Mask must be a 1D boolean array of the same number of entries as points in this PointTree.
- `ValueError` – Cannot remove root vertex.

from_vector(*vector*)

Build a new instance of the object from it's vectorized state.

`self` is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is which is a `deepcopy` of the object followed by a call to `from_vector_inplace()`. This method can be overridden for a performance benefit if desired.

Parameters`vector` (`(n_parameters,)` *ndarray*) – Flattened representation of the object.

Returns`object` (`type(self)`) – An new instance of this class.

from_vector_inplace(*vector*)

Updates the points of this PointCloud in-place with the reshaped points from the provided vector. Note that the vector should have the form `[x0, y0, x1, y1, ....., xn, yn]` for 2D.

Parameters`vector` (`(n_points,)` *ndarray*) – The vector from which to create the points' array.

get_adjacency_list()

Returns the adjacency list of the graph, i.e. a *list* of length `n_vertices` that for each vertex has a *list* of the vertex neighbours. If the graph is directed, the neighbours are children.

Returns`adjacency_list` (*list* of *list* of length `n_vertices`) – The adjacency list of the graph.

h_points()

Convert poincloud to a homogeneous array: `(n_dims + 1, n_points)`

Type`type(self)`

has_cycles()

Checks if the graph has at least one cycle.

Returns`has_cycles` (*bool*) – `True` if the graph has cycles.

has_isolated_vertices()

Whether the graph has any isolated vertices, i.e. vertices with no edge connections.

Returns`has_isolated_vertices` (*bool*) – `True` if the graph has at least one isolated vertex.

has_nan_values()

Tests if the vectorized form of the object contains `nan` values or not. This is particularly useful for objects with unknown values that have been mapped to `nan` values.

Returns`has_nan_values` (*bool*) – If the vectorized object contains `nan` values.

classmethod init_from_edges(*points*, *edges*, *root_vertex*, *copy=True*, *skip_checks=False*)

Construct a `PointTree` from edges array.

Parameters

- **points** (`(n_vertices, n_dims, )` *ndarray*) – The array of point locations.
- **edges** (`(n_edges, 2, )` *ndarray*) – The *ndarray* of edges, i.e. all the pairs of vertices that are connected with an edge.
- **root_vertex** (*int*) – That vertex that will be set as root.
- **copy** (*bool*, optional) – If `False`, the `adjacency_matrix` will not be copied on assignment.
- **skip_checks** (*bool*, optional) – If `True`, no checks will be performed.

Examples

The following tree

```
        0
        |
     ___|___
    1       2
    |       |
  _|_       |
 3   4      5
 |   |      |
 |   |      |
 6   7      8
```

can be defined as

```
from menpo.shape import PointTree
import numpy as np
points = np.array([[30, 30], [10, 20], [50, 20], [0, 10], [20, 10],
                   [50, 10], [0, 0], [20, 0], [50, 0]])
edges = np.array([[0, 1], [0, 2], [1, 3], [1, 4], [2, 5], [3, 6],
                  [4, 7], [5, 8]])
tree = PointTree.init_from_edges(points, edges, root_vertex=0)
```

is_edge (*vertex_1*, *vertex_2*, *skip_checks=False*)

Whether there is an edge between the provided vertices.

Parameters

- **vertex_1** (*int*) – The first selected vertex. Parent if the graph is directed.
- **vertex_2** (*int*) – The second selected vertex. Child if the graph is directed.
- **skip_checks** (*bool*, optional) – If `False`, the given vertices will be checked.

Returnsis_edge (*bool*) – `True` if there is an edge connecting `vertex_1` and `vertex_2`.

Raises`ValueError` – The vertex must be between 0 and {n_vertices-1}.

is_leaf (*vertex*, *skip_checks=False*)

Whether the vertex is a leaf.

Parameters

- **vertex** (*int*) – The selected vertex.
- **skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returnsis_leaf (*bool*) – If `True`, then selected vertex is a leaf.

Raises`ValueError` – The vertex must be in the range `[0, n_vertices - 1]`.

is_tree ()

Checks if the graph is tree.

Returnsis_true (*bool*) – If the graph is a tree.

isolated_vertices ()

Returns the isolated vertices of the graph (if any), i.e. the vertices that have no edge connections.

Returnsisolated_vertices (*list*) – A *list* of the isolated vertices. If there aren't any, it returns an empty *list*.

n_children (*vertex*, *skip_checks=False*)

Returns the number of children of the selected vertex.

Parametersvertex (*int*) – The selected vertex.

Returns

- **n_children** (*int*) – The number of children.

•**skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Raises `ValueError` – The vertex must be in the range `[0, n_vertices - 1]`.

n_parents (*vertex*, *skip_checks=False*)

Returns the number of parents of the selected vertex.

Parameters

•**vertex** (*int*) – The selected vertex.

•**skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returns **n_parents** (*int*) – The number of parents.

Raises `ValueError` – The vertex must be in the range `[0, n_vertices - 1]`.

n_paths (*start*, *end*)

Returns the number of all the paths (without cycles) existing from start vertex to end vertex.

Parameters

•**start** (*int*) – The vertex from which the paths start.

•**end** (*int*) – The vertex from which the paths end.

Returns **paths** (*int*) – The paths' numbers.

n_vertices_at_depth (*depth*)

Returns the number of vertices at the specified depth.

Parameters **depth** (*int*) – The selected depth.

Returns **n_vertices** (*int*) – The number of vertices that lie in the specified depth.

norm (***kwargs*)

Returns the norm of this PointCloud. This is a translation and rotation invariant measure of the point cloud's intrinsic size - in other words, it is always taken around the point cloud's centre.

By default, the Frobenius norm is taken, but this can be changed by setting kwargs - see `numpy.linalg.norm` for valid options.

Returns **norm** (*float*) – The norm of this `PointCloud`

parent (*vertex*, *skip_checks=False*)

Returns the parent of the selected vertex.

Parameters

•**vertex** (*int*) – The selected vertex.

•**skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returns **parent** (*int*) – The parent vertex.

Raises `ValueError` – The vertex must be in the range `[0, n_vertices - 1]`.

parents (*vertex*, *skip_checks=False*)

Returns the parents of the selected vertex.

Parameters

•**vertex** (*int*) – The selected vertex.

•**skip_checks** (*bool*, optional) – If `False`, the given vertex will be checked.

Returns **parents** (*list*) – The list of parents.

Raises `ValueError` – The vertex must be in the range `[0, n_vertices - 1]`.

range (*boundary=0*)

The range of the extent of the PointCloud.

Parameters **boundary** (*float*) – A optional padding distance that is used to extend the bounds from which the range is computed. Default is `0`, no extension is performed.

Returns **range** (`(n_dims,)` *ndarray*) – The range of the `PointCloud` extent in each dimension.

relative_location_edge (*parent*, *child*)

Returns the relative location between the provided vertices. That is if vertex j is the parent and vertex i is its child and vector l denotes the coordinates of a vertex, then

```
l_i - l_j = [[x_i], [y_i]] - [[x_j], [y_j]] =
          = [[x_i - x_j], [y_i - y_j]]
```

Parameters

- **parent** (*int*) – The first selected vertex which is considered as the parent.
- **child** (*int*) – The second selected vertex which is considered as the child.

Returnsrelative_location (`(2,)` *ndarray*) – The relative location vector.

Raises`ValueError` – Vertices `parent` and `child` are not connected with an edge.

relative_locations()

Returns the relative location between the vertices of each edge. If vertex j is the parent and vertex i is its child and vector l denotes the coordinates of a vertex, then:

```
l_i - l_j = [[x_i], [y_i]] - [[x_j], [y_j]] =
          = [[x_i - x_j], [y_i - y_j]]
```

Returnsrelative_locations (`(n_vertexes, 2)` *ndarray*) – The relative locations vector.

tojson()

Convert this PointGraph to a dictionary representation suitable for inclusion in the LJSON landmark format.

Returnsjson (*dict*) – Dictionary with `points` and `connectivity` keys.

vertices_at_depth(*depth*)

Returns a list of vertices at the specified depth.

Parametersdepth (*int*) – The selected depth.

Returnsvertices (*list*) – The vertices that lie in the specified depth.

view_widget(*browser_style='buttons', figure_size=(10, 8), style='coloured'*)

Visualization of the PointGraph using the `visualize_pointclouds` widget.

Parameters

- **browser_style** (`{'buttons', 'slider'}`, optional) – It defines whether the selector of the objects will have the form of plus/minus buttons or a slider.
- **figure_size** ((*int*, *int*) *tuple*, optional) – The initial size of the rendered figure.
- **style** (`{'coloured', 'minimal'}`, optional) – If `'coloured'`, then the style of the widget will be coloured. If `minimal`, then the style is simple using black and white colours.

has_landmarks

Whether the object has landmarks.

Type*bool*

landmarks

The landmarks object.

Type`LandmarkManager`

leaves

Returns a *list* with the all leaves of the tree.

Type*list*

maximum_depth

Returns the maximum depth of the tree.

Type*int*

n_dims

The number of dimensions in the pointcloud.

Type*int*

n_edges
Returns the number of edges.
Type *int*

n_landmark_groups
The number of landmark groups on this object.
Type *int*

n_leaves
Returns the number of leaves of the tree.
Type *int*

n_parameters
The length of the vector that this object produces.
Type *int*

n_points
The number of points in the pointcloud.
Type *int*

n_vertices
Returns the number of vertices.
Type *int*

vertices
Returns the *list* of vertices.
Type *list*

2.8.5 Triangular Meshes

TriMesh

class `menpo.shape.`**`TriMesh`**(*points*, *trilist=None*, *copy=True*)
Bases: `PointCloud`

A `PointCloud` with a connectivity defined by a triangle list. These are designed to be explicitly 2D or 3D.
Parameters
- **points** (`(n_points, n_dims)` *ndarray*) – The array representing the points.
- **trilist** (`(M, 3)` *ndarray* or `None`, optional) – The triangle list. If *None*, a Delaunay triangulation of the points will be used instead.
- **copy** (*bool*, optional) – If `False`, the points will not be copied on assignment. Any trilist will also not be copied. In general this should only be used if you know what you are doing.

_view_2d(*figure_id=None*, *new_figure=False*, *image_view=True*, *render_lines=True*, *line_colour='r'*, *line_style='-'*, *line_width=1.0*, *render_markers=True*, *marker_style='o'*, *marker_size=20*, *marker_face_colour='k'*, *marker_edge_colour='k'*, *marker_edge_width=1.0*, *render_axes=True*, *axes_font_name='sans-serif'*, *axes_font_size=10*, *axes_font_style='normal'*, *axes_font_weight='normal'*, *axes_x_limits=None*, *axes_y_limits=None*, *figure_size=(10, 8)*, *label=None*)
Visualization of the TriMesh in 2D.
Returns
- **figure_id** (*object*, optional) – The id of the figure to be used.
- **new_figure** (*bool*, optional) – If `True`, a new figure is created.
- **image_view** (*bool*, optional) – If `True` the TriMesh will be viewed as if it is in the image coordinate system.
- **render_lines** (*bool*, optional) – If `True`, the edges will be rendered.

- **line_colour** (*See Below, optional*) – The colour of the lines. Example options:

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **line_style** (`{-, --, -., :}`, optional) – The style of the lines.
- **line_width** (*float*, optional) – The width of the lines.
- **render_markers** (*bool*, optional) – If `True`, the markers will be rendered.
- **marker_style** (*See Below, optional*) – The style of the markers. Example options

```
{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}
```

- **marker_size** (*int*, optional) – The size of the markers in points^2.
- **marker_face_colour** (*See Below, optional*) – The face (filling) colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_colour** (*See Below, optional*) – The edge colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_width** (*float*, optional) – The width of the markers' edge.
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.
- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** (`{normal, italic, oblique}`, optional) – The font style of the axes.
- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **axes_x_limits** ((*float*, *float*) *tuple* or `None`, optional) – The limits of the x axis.
- **axes_y_limits** ((*float*, *float*) *tuple* or `None`, optional) – The limits of the y axis.
- **figure_size** ((*float*, *float*) *tuple* or `None`, optional) – The size of the figure in inches.
- **label** (*str*, optional) – The name entry in case of a legend.

Returns **viewer** (`PointGraphViewer2d`) – The viewer object.

_view_landmarks_2d(*group=None*, *with_labels=None*, *without_labels=None*, *figure_id=None*, *new_figure=False*, *image_view=True*, *render_lines=True*, *line_colour=None*, *line_style='-'*, *line_width=1*, *render_markers=True*, *marker_style='o'*, *marker_size=20*, *marker_face_colour=None*, *marker_edge_colour=None*, *marker_edge_width=1.0*, *render_numbering=False*, *numbers_horizontal_align='center'*, *numbers_vertical_align='bottom'*, *numbers_font_name='sans-serif'*, *numbers_font_size=10*, *numbers_font_style='normal'*, *numbers_font_weight='normal'*, *numbers_font_colour='k'*, *render_legend=False*, *legend_title=''*, *legend_font_name='sans-serif'*, *legend_font_style='normal'*, *legend_font_size=10*, *legend_font_weight='normal'*, *legend_marker_scale=None*, *legend_location=2*, *legend_bbox_to_anchor=(1.05, 1.0)*, *legend_border_axes_pad=None*, *legend_n_columns=1*, *legend_horizontal_spacing=None*, *legend_vertical_spacing=None*, *legend_border=True*, *legend_border_padding=None*, *legend_shadow=False*, *legend_rounded_corners=False*, *render_axes=False*, *axes_font_name='sans-serif'*, *axes_font_size=10*, *axes_font_style='normal'*, *axes_font_weight='normal'*, *axes_x_limits=None*, *axes_y_limits=None*, *figure_size=(10, 8)*)

Visualize the landmarks. This method will appear on the Image as `view_landmarks` if the Image is 2D.

Parameters

- **group** (*str* or''None'' optional) – The landmark group to be visualized. If `None` and there are more than one landmark groups, an error is raised.
- **with_labels** (`None` or *str* or *list* of *str*, optional) – If not `None`, only show the given label(s). Should **not** be used with the `without_labels` kwarg.
- **without_labels** (`None` or *str* or *list* of *str*, optional) – If not `None`, show all except the given label(s). Should **not** be used with the `with_labels` kwarg.
- **figure_id** (*object*, optional) – The id of the figure to be used.
- **new_figure** (*bool*, optional) – If `True`, a new figure is created.
- **image_view** (*bool*, optional) – If `True` the PointCloud will be viewed as if it is in the image coordinate system.
- **render_lines** (*bool*, optional) – If `True`, the edges will be rendered.
- **line_colour** (*See Below, optional*) – The colour of the lines. Example options:

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **line_style** (`{-, --, -., :}`, optional) – The style of the lines.
- **line_width** (*float*, optional) – The width of the lines.
- **render_markers** (*bool*, optional) – If `True`, the markers will be rendered.
- **marker_style** (*See Below, optional*) – The style of the markers. Example options

```
{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}
```

- **marker_size** (*int*, optional) – The size of the markers in points^2.
- **marker_face_colour** (*See Below, optional*) – The face (filling) colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
```

```
(3, ) ndarray
```

- **marker_edge_colour** (*See Below, optional*) – The edge colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_width** (*float*, optional) – The width of the markers' edge.
- **render_numbering** (*bool*, optional) – If `True`, the landmarks will be numbered.
- **numbers_horizontal_align** (`{center, right, left}`, optional) – The horizontal alignment of the numbers' texts.
- **numbers_vertical_align** (`{center, top, bottom, baseline}`, optional) – The vertical alignment of the numbers' texts.
- **numbers_font_name** (*See Below, optional*) – The font of the numbers. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **numbers_font_size** (*int*, optional) – The font size of the numbers.
- **numbers_font_style** (`{normal, italic, oblique}`, optional) – The font style of the numbers.
- **numbers_font_weight** (*See Below, optional*) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **numbers_font_colour** (*See Below, optional*) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **render_legend** (*bool*, optional) – If `True`, the legend will be rendered.
- **legend_title** (*str*, optional) – The title of the legend.
- **legend_font_name** (*See below, optional*) – The font of the legend. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **legend_font_style** (`{normal, italic, oblique}`, optional) – The font style of the legend.
- **legend_font_size** (*int*, optional) – The font size of the legend.
- **legend_font_weight** (*See Below, optional*) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **legend_marker_scale** (*float*, optional) – The relative size of the legend markers with respect to the original
- **legend_location** (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

- **legend_bbox_to_anchor** ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.
- **legend_border_axes_pad** (*float*, optional) – The pad between the axes and legend border.
- **legend_n_columns** (*int*, optional) – The number of the legend's columns.
- **legend_horizontal_spacing** (*float*, optional) – The spacing between the columns.
- **legend_vertical_spacing** (*float*, optional) – The vertical space between the legend entries.
- **legend_border** (*bool*, optional) – If `True`, a frame will be drawn around the legend.
- **legend_border_padding** (*float*, optional) – The fractional whitespace inside the legend border.
- **legend_shadow** (*bool*, optional) – If `True`, a shadow will be drawn behind legend.
- **legend_rounded_corners** (*bool*, optional) – If `True`, the frame's corners will be rounded (fancybox).
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.
- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** (`{normal, italic, oblique}`, optional) – The font style of the axes.
- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold,demibold, demi, bold, heavy, extra bold, black}
```

- **axes_x_limits** ((*float*, *float*) *tuple* or `None` optional) – The limits of the x axis.
- **axes_y_limits** ((*float*, *float*) *tuple* or `None` optional) – The limits of the y axis.
- **figure_size** ((*float*, *float*) *tuple* or `None` optional) – The size of the figure in inches.

Raises

- `ValueError` – If both `with_labels` and `without_labels` are passed.
- `ValueError` – If the landmark manager doesn't contain the provided group label.

as_pointgraph(*copy=True*, *skip_checks=False*)

Converts the TriMesh to a `PointUndirectedGraph`.

Parameters

- **copy** (*bool*, optional) – If `True`, the graph will be a copy.
- **skip_checks** (*bool*, optional) – If `True`, no checks will be performed.

Returns

pointgraph (*PointUndirectedGraph*) – The point graph.

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returns

vector (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

boundary_tri_index()

Boolean index into triangles that are at the edge of the TriMesh

Returns

boundary_tri_index (`(n_tris,)` *ndarray*) – For each triangle (ABC), returns whether any of it's edges is not also an edge of another triangle (and so this triangle exists on the boundary of the TriMesh)

bounding_box()

Return a bounding box from two corner points as a directed graph. The the first point (0) should be nearest the origin. In the case of an image, this ordering would appear as:

```
0<--3
|   ^
|   |
v   |
1-->2
```

In the case of a pointcloud, the ordering will appear as:

```
3<--2
|   ^
|   |
v   |
0-->1
```

Returns

bounding_box (*PointDirectedGraph*) – The axis aligned bounding box of the PointCloud.

bounds(*boundary=0*)

The minimum to maximum extent of the PointCloud. An optional boundary argument can be provided to expand the bounds by a constant margin.

Parameters

boundary (*float*) – A optional padding distance that is added to the bounds. Default is `0`, meaning the max/min of tightest possible containing square/cube/hypercube is returned.

Returns

- **min_b** (`(n_dims,)` *ndarray*) – The minimum extent of the *PointCloud* and boundary along each dimension
- **max_b** (`(n_dims,)` *ndarray*) – The maximum extent of the *PointCloud* and boundary along each dimension

centre()

The mean of all the points in this PointCloud (centre of mass).

Returns

centre (`(n_dims)` *ndarray*) – The mean of this PointCloud's points.

centre_of_bounds()

The centre of the absolute bounds of this PointCloud. Contrast with *centre()*, which is the mean point position.

Returns

centre (`n_dims` *ndarray*) – The centre of the bounds of this PointCloud.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns `type(self)` – A copy of this object

distance_to(*pointcloud*, ***kwargs*)

Returns a distance matrix between this PointCloud and another. By default the Euclidean distance is calculated - see *scipy.spatial.distance.cdist* for valid kwargs to change the metric and other properties.

Parameters **pointcloud** (*PointCloud*) – The second pointcloud to compute distances between. This must be of the same dimension as this PointCloud.

Returns **distance_matrix** (`(n_points, n_points)` *ndarray*) – The symmetric pairwise distance matrix between the two PointClouds s.t. `distance_matrix[i, j]` is the distance between the i'th point of this PointCloud and the j'th point of the input PointCloud.

edge_indices()

An unordered index into points that rebuilds the edges of this *TriMesh*.

Note that there will be two edges present in cases where two triangles 'share' an edge. Consider `unique_edge_indices()` for a single index for each physical edge on the *TriMesh*.

Returns **edge_indices** (`(n_tris * 3, 2)` *ndarray*) – For each triangle (ABC), returns the pair of point indices that rebuild AB, AC, BC. All edge indices are concatenated for a total of `n_tris * 3` edge_indices. The ordering is done so that all AB vectors are first in the returned list, followed by BC, then CA.

edge_lengths()

The length of each edge in this *TriMesh*.

Note that there will be two edges present in cases where two triangles 'share' an edge. Consider `unique_edge_indices()` for a single index for each physical edge on the *TriMesh*. The ordering matches the case for edges and edge_indices.

Returns **edge_lengths** (`(n_tris * 3, )` *ndarray*) – Scalar euclidean lengths for each edge in this *TriMesh*.

edge_vectors()

A vector of edges of each triangle face.

Note that there will be two edges present in cases where two triangles 'share' an edge. Consider *unique_edge_vectors()* for a single vector for each physical edge on the *TriMesh*.

Returns **edges** (`(n_tris * 3, n_dims)` *ndarray*) – For each triangle (ABC), returns the edge vectors AB, BC, CA. All edges are concatenated for a total of `n_tris * 3` edges. The ordering is done so that all AB vectors are first in the returned list, followed by BC, then CA.

from_mask(*mask*)

A 1D boolean array with the same number of elements as the number of points in the TriMesh. This is then broadcast across the dimensions of the mesh and returns a new mesh containing only those points that were `True` in the mask.

Parameters **mask** (`(n_points,)` *ndarray*) – 1D array of booleans

Returns **mesh** (*TriMesh*) – A new mesh that has been masked.

from_vector(*vector*)

Build a new instance of the object from it's vectorized state.

`self` is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is which is a `deepcopy` of the object followed by a call to `from_vector_inplace()`. This method can be overridden for a performance benefit if desired.

Parameters **vector** (`(n_parameters,)` *ndarray*) – Flattened representation of the object.

Returns **object** (`type(self)`) – An new instance of this class.

from_vector_inplace(*vector*)

Updates the points of this PointCloud in-place with the reshaped points from the provided vector. Note that the vector should have the form `[x0, y0, x1, y1, ....., xn, yn]` for 2D.

Parameters **vector** (`(n_points,)` *ndarray*) – The vector from which to create the points' array.

h_points()

Convert poincloud to a homogeneous array: `(n_dims + 1, n_points)`

Type `type(self)`

has_nan_values()

Tests if the vectorized form of the object contains `nan` values or not. This is particularly useful for objects with unknown values that have been mapped to `nan` values.

Returns **has_nan_values** (*bool*) – If the vectorized object contains `nan` values.

mean_edge_length(*unique=True*)

The mean length of each edge in this `TriMesh`.

Parameters **unique** (*bool*, optional) – If `True`, each shared edge will only be counted once towards the average. If false, shared edges will be counted twice.

Returns **mean_edge_length** (`float`) – The mean length of each edge in this `TriMesh`

mean_tri_area()

The mean area of each triangle face in this `TriMesh`.

Returns **mean_tri_area** (`float`) – The mean area of each triangle face in this `TriMesh`

Raises `ValueError` – If mesh is not 3D

norm(***kwargs*)

Returns the norm of this PointCloud. This is a translation and rotation invariant measure of the point cloud's intrinsic size - in other words, it is always taken around the point cloud's centre.

By default, the Frobenius norm is taken, but this can be changed by setting kwargs - see `numpy.linalg.norm` for valid options.

Returns **norm** (*float*) – The norm of this `PointCloud`

range(*boundary=0*)

The range of the extent of the PointCloud.

Parameters **boundary** (*float*) – A optional padding distance that is used to extend the bounds from which the range is computed. Default is `0`, no extension is performed.

Returns **range** (`(n_dims,)` *ndarray*) – The range of the `PointCloud` extent in each dimension.

tojson()

Convert this `TriMesh` to a dictionary representation suitable for inclusion in the LJSON landmark format. Note that this enforces a simpler representation, and as such is not suitable for a permanent serialization of a `TriMesh` (to be clear, `TriMesh`'s serialized as part of a landmark set will be rebuilt as a `PointUndirectedGraph`).

Returns **json** (*dict*) – Dictionary with `points` and `connectivity` keys.

tri_areas()

The area of each triangle face.

Returns **areas** (`(n_tris,)` *ndarray*) – Area of each triangle, ordered as the trilist is

Raises `ValueError` – If mesh is not 2D or 3D

tri_normals()

Compute the triangle face normals from the current set of points and triangle list. Only valid for 3D dimensional meshes.

Returnsnormals ((n_tris, 3) *ndarray*) – Normal at each triangle face.

RaisesValueError – If mesh is not 3D

unique_edge_indicies()

An unordered index into points that rebuilds the unique edges of this *TriMesh*.

Note that each physical edge will only be counted once in this method (i.e. edges shared between neighbouring triangles are only counted once not twice). The ordering should be considered random.

Returnsunique_edge_indicies ((n_unique_edges, 2) *ndarray*) – Return a point index that rebuilds all edges present in this *TriMesh* only once.

unique_edge_lengths()

The length of each edge in this *TriMesh*.

Note that each physical edge will only be counted once in this method (i.e. edges shared between neighbouring triangles are only counted once not twice). The ordering should be considered random.

Returnsedge_lengths ((n_tris * 3,) *ndarray*) – Scalar euclidean lengths for each edge in this *TriMesh*.

unique_edge_vectors()

An unordered vector of unique edges for the whole *TriMesh*.

Note that each physical edge will only be counted once in this method (i.e. edges shared between neighbouring triangles are only counted once not twice). The ordering should be considered random.

Returnsunique_edge_vectors ((n_unique_edges, n_dims) *ndarray*) – Vectors for each unique edge in this *TriMesh*.

vertex_normals()

Compute the per-vertex normals from the current set of points and triangle list. Only valid for 3D dimensional meshes.

Returnsnormals ((n_points, 3) *ndarray*) – Normal at each point.

RaisesValueError – If mesh is not 3D

view_widget(*browser_style='buttons'*, *figure_size=(10, 8)*, *style='coloured'*)

Visualization of the TriMesh using the *visualize_pointclouds* widget.

Parameters

- **browser_style** ({'buttons', 'slider'}, optional) – It defines whether the selector of the objects will have the form of plus/minus buttons or a slider.
- **figure_size** ((*int*, *int*) *tuple*, optional) – The initial size of the rendered figure.
- **style** ({'coloured', 'minimal'}, optional) – If 'coloured', then the style of the widget will be coloured. If minimal, then the style is simple using black and white colours.

has_landmarks

Whether the object has landmarks.

Type*bool*

landmarks

The landmarks object.

Type*LandmarkManager*

n_dims

The number of dimensions in the pointcloud.

Type*int*

n_landmark_groups
The number of landmark groups on this object.
Type *int*

n_parameters
The length of the vector that this object produces.
Type *int*

n_points
The number of points in the pointcloud.
Type *int*

n_tris
The number of triangles in the triangle list.
Type *int*

ColouredTriMesh

class menpo.shape.**ColouredTriMesh**(*points*, *trilist=None*, *colours=None*, *copy=True*)
Bases: TriMesh

Combines a *TriMesh* with a colour per vertex.

Parameters
- **points** ((n_points, n_dims) *ndarray*) – The array representing the points.
- **trilist** ((M, 3) *ndarray* or None, optional) – The triangle list. If *None*, a Delaunay triangulation of the points will be used instead.
- **colours** ((N, 3) *ndarray*, optional) – The floating point RGB colour per vertex. If not given, grey will be assigned to each vertex.
- **copy** (*bool*, optional) – If False, the points, trilist and colours will not be copied on assignment. In general this should only be used if you know what you are doing.

Raises ValueError – If the number of colour values does not match the number of vertices.

_view_2d(*figure_id=None*, *new_figure=False*, *image_view=True*, *render_lines=True*, *line_colour='r'*, *line_style='-'*, *line_width=1.0*, *render_markers=True*, *marker_style='o'*, *marker_size=20*, *marker_face_colour='k'*, *marker_edge_colour='k'*, *marker_edge_width=1.0*, *render_axes=True*, *axes_font_name='sans-serif'*, *axes_font_size=10*, *axes_font_style='normal'*, *axes_font_weight='normal'*, *axes_x_limits=None*, *axes_y_limits=None*, *figure_size=(10, 8)*, *label=None*)
Visualization of the TriMesh in 2D. Currently, explicit coloured TriMesh viewing is not supported, and therefore viewing falls back to uncoloured 2D TriMesh viewing.

Returns
- **figure_id** (*object*, optional) – The id of the figure to be used.
- **new_figure** (*bool*, optional) – If True, a new figure is created.
- **image_view** (*bool*, optional) – If True the ColouredTriMesh will be viewed as if it is in the image coordinate system.
- **render_lines** (*bool*, optional) – If True, the edges will be rendered.
- **line_colour** (*See Below, optional*) – The colour of the lines. Example options:

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **line_style** ({-, --, -., :}, optional) – The style of the lines.
- **line_width** (*float*, optional) – The width of the lines.
- **render_markers** (*bool*, optional) – If True, the markers will be rendered.
- **marker_style** (*See Below, optional*) – The style of the markers. Example options

```
{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}
```

- **marker_size** (*int*, optional) – The size of the markers in points^2.
- **marker_face_colour** (*See Below, optional*) – The face (filling) colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_colour** (*See Below, optional*) – The edge colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_width** (*float*, optional) – The width of the markers' edge.
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.
- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** ({`normal`, `italic`, `oblique`}, optional) – The font style of the axes.
- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **axes_x_limits** ((*float*, *float*) *tuple* or `None`, optional) – The limits of the x axis.
- **axes_y_limits** ((*float*, *float*) *tuple* or `None`, optional) – The limits of the y axis.
- **figure_size** ((*float*, *float*) *tuple* or `None`, optional) – The size of the figure in inches.
- **label** (*str*, optional) – The name entry in case of a legend.

Returns **viewer** (`PointGraphViewer2d`) – The viewer object.

Raises `warning` – 2D Viewing of Coloured TriMeshes is not supported, automatically falls back to 2D *`TriMesh`* viewing.

_view_landmarks_2d(*group=None*, *with_labels=None*, *without_labels=None*, *figure_id=None*, *new_figure=False*, *image_view=True*, *render_lines=True*, *line_colour=None*, *line_style='-'*, *line_width=1*, *render_markers=True*, *marker_style='o'*, *marker_size=20*, *marker_face_colour=None*, *marker_edge_colour=None*, *marker_edge_width=1.0*, *render_numbering=False*, *numbers_horizontal_align='center'*, *numbers_vertical_align='bottom'*, *numbers_font_name='sans-serif'*, *numbers_font_size=10*, *numbers_font_style='normal'*, *numbers_font_weight='normal'*, *numbers_font_colour='k'*, *render_legend=False*, *legend_title=''*, *legend_font_name='sans-serif'*, *legend_font_style='normal'*, *legend_font_size=10*, *legend_font_weight='normal'*, *legend_marker_scale=None*, *legend_location=2*, *legend_bbox_to_anchor=(1.05, 1.0)*, *legend_border_axes_pad=None*, *legend_n_columns=1*, *legend_horizontal_spacing=None*, *legend_vertical_spacing=None*, *legend_border=True*, *legend_border_padding=None*, *legend_shadow=False*, *legend_rounded_corners=False*, *render_axes=False*, *axes_font_name='sans-serif'*, *axes_font_size=10*, *axes_font_style='normal'*, *axes_font_weight='normal'*, *axes_x_limits=None*, *axes_y_limits=None*, *figure_size=(10, 8)*)

Visualize the landmarks. This method will appear on the Image as `view_landmarks` if the Image is 2D.

Parameters

- **group** (*str* or''None'' optional) – The landmark group to be visualized. If `None` and there are more than one landmark groups, an error is raised.
- **with_labels** (`None` or *str* or *list* of *str*, optional) – If not `None`, only show the given label(s). Should **not** be used with the `without_labels` kwarg.
- **without_labels** (`None` or *str* or *list* of *str*, optional) – If not `None`, show all except the given label(s). Should **not** be used with the `with_labels` kwarg.
- **figure_id** (*object*, optional) – The id of the figure to be used.
- **new_figure** (*bool*, optional) – If `True`, a new figure is created.
- **image_view** (*bool*, optional) – If `True` the PointCloud will be viewed as if it is in the image coordinate system.
- **render_lines** (*bool*, optional) – If `True`, the edges will be rendered.
- **line_colour** (*See Below, optional*) – The colour of the lines. Example options:

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **line_style** (`{-, --, -., :}`, optional) – The style of the lines.
- **line_width** (*float*, optional) – The width of the lines.
- **render_markers** (*bool*, optional) – If `True`, the markers will be rendered.
- **marker_style** (*See Below, optional*) – The style of the markers. Example options

```
{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}
```

- **marker_size** (*int*, optional) – The size of the markers in points^2.
- **marker_face_colour** (*See Below, optional*) – The face (filling) colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
```

```
(3, ) ndarray
```

- **marker_edge_colour** (*See Below, optional*) – The edge colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_width** (*float*, optional) – The width of the markers' edge.
- **render_numbering** (*bool*, optional) – If `True`, the landmarks will be numbered.
- **numbers_horizontal_align** (`{center, right, left}`, optional) – The horizontal alignment of the numbers' texts.
- **numbers_vertical_align** (`{center, top, bottom, baseline}`, optional) – The vertical alignment of the numbers' texts.
- **numbers_font_name** (*See Below, optional*) – The font of the numbers. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **numbers_font_size** (*int*, optional) – The font size of the numbers.
- **numbers_font_style** (`{normal, italic, oblique}`, optional) – The font style of the numbers.
- **numbers_font_weight** (*See Below, optional*) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **numbers_font_colour** (*See Below, optional*) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **render_legend** (*bool*, optional) – If `True`, the legend will be rendered.
- **legend_title** (*str*, optional) – The title of the legend.
- **legend_font_name** (*See below, optional*) – The font of the legend. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **legend_font_style** (`{normal, italic, oblique}`, optional) – The font style of the legend.
- **legend_font_size** (*int*, optional) – The font size of the legend.
- **legend_font_weight** (*See Below, optional*) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **legend_marker_scale** (*float*, optional) – The relative size of the legend markers with respect to the original
- **legend_location** (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

- **legend_bbox_to_anchor** ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.
- **legend_border_axes_pad** (*float*, optional) – The pad between the axes and legend border.
- **legend_n_columns** (*int*, optional) – The number of the legend's columns.
- **legend_horizontal_spacing** (*float*, optional) – The spacing between the columns.
- **legend_vertical_spacing** (*float*, optional) – The vertical space between the legend entries.
- **legend_border** (*bool*, optional) – If `True`, a frame will be drawn around the legend.
- **legend_border_padding** (*float*, optional) – The fractional whitespace inside the legend border.
- **legend_shadow** (*bool*, optional) – If `True`, a shadow will be drawn behind legend.
- **legend_rounded_corners** (*bool*, optional) – If `True`, the frame's corners will be rounded (fancybox).
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.
- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** (`{normal, italic, oblique}`, optional) – The font style of the axes.
- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold,demibold, demi, bold, heavy, extra bold, black}
```

- **axes_x_limits** ((*float*, *float*) *tuple* or `None` optional) – The limits of the x axis.
- **axes_y_limits** ((*float*, *float*) *tuple* or `None` optional) – The limits of the y axis.
- **figure_size** ((*float*, *float*) *tuple* or `None` optional) – The size of the figure in inches.

Raises

- `ValueError` – If both `with_labels` and `without_labels` are passed.
- `ValueError` – If the landmark manager doesn't contain the provided group label.

as_pointgraph(*copy=True*, *skip_checks=False*)

Converts the TriMesh to a `PointUndirectedGraph`.

Parameters

- **copy** (*bool*, optional) – If `True`, the graph will be a copy.
- **skip_checks** (*bool*, optional) – If `True`, no checks will be performed.

Returns

pointgraph (*PointUndirectedGraph*) – The point graph.

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returns

vector (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

boundary_tri_index()

Boolean index into triangles that are at the edge of the TriMesh

Returns

boundary_tri_index (`(n_tris,)` *ndarray*) – For each triangle (ABC), returns whether any of it's edges is not also an edge of another triangle (and so this triangle exists on the boundary of the TriMesh)

bounding_box()

Return a bounding box from two corner points as a directed graph. The the first point (0) should be nearest the origin. In the case of an image, this ordering would appear as:

```
0<--3
|   ^
|   |
v   |
1-->2
```

In the case of a pointcloud, the ordering will appear as:

```
3<--2
|   ^
|   |
v   |
0-->1
```

Returns

bounding_box (*PointDirectedGraph*) – The axis aligned bounding box of the PointCloud.

bounds(*boundary=0*)

The minimum to maximum extent of the PointCloud. An optional boundary argument can be provided to expand the bounds by a constant margin.

Parameters

boundary (*float*) – A optional padding distance that is added to the bounds. Default is `0`, meaning the max/min of tightest possible containing square/cube/hypercube is returned.

Returns

- **min_b** (`(n_dims,)` *ndarray*) – The minimum extent of the *PointCloud* and boundary along each dimension
- **max_b** (`(n_dims,)` *ndarray*) – The maximum extent of the *PointCloud* and boundary along each dimension

centre()

The mean of all the points in this PointCloud (centre of mass).

Returns

centre (`(n_dims)` *ndarray*) – The mean of this PointCloud's points.

centre_of_bounds()

The centre of the absolute bounds of this PointCloud. Contrast with *centre()*, which is the mean point position.

Returns

centre (`n_dims` *ndarray*) – The centre of the bounds of this PointCloud.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other `Copyable` objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns `type(self)` – A copy of this object

distance_to(*pointcloud*, ***kwargs*)

Returns a distance matrix between this PointCloud and another. By default the Euclidean distance is calculated - see *scipy.spatial.distance.cdist* for valid kwargs to change the metric and other properties.

Parameters **pointcloud** (`PointCloud`) – The second pointcloud to compute distances between. This must be of the same dimension as this PointCloud.

Returns **distance_matrix** (`(n_points, n_points)` *ndarray*) – The symmetric pairwise distance matrix between the two PointClouds s.t. `distance_matrix[i, j]` is the distance between the i'th point of this PointCloud and the j'th point of the input PointCloud.

edge_indices()

An unordered index into points that rebuilds the edges of this `TriMesh`.

Note that there will be two edges present in cases where two triangles 'share' an edge. Consider `unique_edge_indices()` for a single index for each physical edge on the `TriMesh`.

Returns **edge_indices** (`(n_tris * 3, 2)` *ndarray*) – For each triangle (ABC), returns the pair of point indices that rebuild AB, AC, BC. All edge indices are concatenated for a total of `n_tris * 3` edge_indices. The ordering is done so that all AB vectors are first in the returned list, followed by BC, then CA.

edge_lengths()

The length of each edge in this `TriMesh`.

Note that there will be two edges present in cases where two triangles 'share' an edge. Consider `unique_edge_indices()` for a single index for each physical edge on the `TriMesh`. The ordering matches the case for edges and edge_indices.

Returns **edge_lengths** (`(n_tris * 3, )` *ndarray*) – Scalar euclidean lengths for each edge in this `TriMesh`.

edge_vectors()

A vector of edges of each triangle face.

Note that there will be two edges present in cases where two triangles 'share' an edge. Consider `unique_edge_vectors()` for a single vector for each physical edge on the `TriMesh`.

Returns **edges** (`(n_tris * 3, n_dims)` *ndarray*) – For each triangle (ABC), returns the edge vectors AB, BC, CA. All edges are concatenated for a total of `n_tris * 3` edges. The ordering is done so that all AB vectors are first in the returned list, followed by BC, then CA.

from_mask(*mask*)

A 1D boolean array with the same number of elements as the number of points in the ColouredTriMesh. This is then broadcast across the dimensions of the mesh and returns a new mesh containing only those points that were `True` in the mask.

Parameters **mask** (`(n_points,)` *ndarray*) – 1D array of booleans

Returns **mesh** (`ColouredTriMesh`) – A new mesh that has been masked.

from_vector(*vector*)

Build a new instance of the object from it's vectorized state.

`self` is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is which is a `deepcopy` of the object followed by a call to *`from_vector_inplace()`*. This method can be overridden for a performance benefit if desired.

Parameters **vector** (`(n_parameters,)` *ndarray*) – Flattened representation of the object.

Returns **object** (`type(self)`) – An new instance of this class.

`from_vector_inplace`(*vector*)

Updates the points of this PointCloud in-place with the reshaped points from the provided vector. Note that the vector should have the form `[x0, y0, x1, y1, ....., xn, yn]` for 2D.

Parameters **vector** (`(n_points,)` *ndarray*) – The vector from which to create the points' array.

`h_points`()

Convert poincloud to a homogeneous array: `(n_dims + 1, n_points)`

Type `type(self)`

`has_nan_values`()

Tests if the vectorized form of the object contains `nan` values or not. This is particularly useful for objects with unknown values that have been mapped to `nan` values.

Returns **has_nan_values** (*bool*) – If the vectorized object contains `nan` values.

`mean_edge_length`(*unique=True*)

The mean length of each edge in this *`TriMesh`*.

Parameters **unique** (*bool*, optional) – If `True`, each shared edge will only be counted once towards the average. If false, shared edges will be counted twice.

Returns **mean_edge_length** (`float`) – The mean length of each edge in this *`TriMesh`*

`mean_tri_area`()

The mean area of each triangle face in this *`TriMesh`*.

Returns **mean_tri_area** (`float`) – The mean area of each triangle face in this *`TriMesh`*

Raises `ValueError` – If mesh is not 3D

`norm`(***kwargs*)

Returns the norm of this PointCloud. This is a translation and rotation invariant measure of the point cloud's intrinsic size - in other words, it is always taken around the point cloud's centre.

By default, the Frobenius norm is taken, but this can be changed by setting kwargs - see `numpy.linalg.norm` for valid options.

Returns **norm** (*float*) – The norm of this *`PointCloud`*

`range`(*boundary=0*)

The range of the extent of the PointCloud.

Parameters **boundary** (*float*) – A optional padding distance that is used to extend the bounds from which the range is computed. Default is `0`, no extension is performed.

Returns **range** (`(n_dims,)` *ndarray*) – The range of the *`PointCloud`* extent in each dimension.

`tojson`()

Convert this *`TriMesh`* to a dictionary representation suitable for inclusion in the LJSON landmark format. Note that this enforces a simpler representation, and as such is not suitable for a permanent serialization of a *`TriMesh`* (to be clear, *`TriMesh`*'s serialized as part of a landmark set will be rebuilt as a *`PointUndirectedGraph`*).

Returns **json** (*dict*) – Dictionary with `points` and `connectivity` keys.

`tri_areas`()

The area of each triangle face.

Returns **areas** (`(n_tris,)` *ndarray*) – Area of each triangle, ordered as the trilist is

Raises `ValueError` – If mesh is not 2D or 3D

tri_normals()

Compute the triangle face normals from the current set of points and triangle list. Only valid for 3D dimensional meshes.

Returnsnormals ((n_tris, 3) *ndarray*) – Normal at each triangle face.

RaisesValueError – If mesh is not 3D

unique_edge_indicies()

An unordered index into points that rebuilds the unique edges of this *TriMesh*.

Note that each physical edge will only be counted once in this method (i.e. edges shared between neighbouring triangles are only counted once not twice). The ordering should be considered random.

Returnsunique_edge_indicies ((n_unique_edges, 2) *ndarray*) – Return a point index that rebuilds all edges present in this *TriMesh* only once.

unique_edge_lengths()

The length of each edge in this *TriMesh*.

Note that each physical edge will only be counted once in this method (i.e. edges shared between neighbouring triangles are only counted once not twice). The ordering should be considered random.

Returnsedge_lengths ((n_tris * 3,) *ndarray*) – Scalar euclidean lengths for each edge in this *TriMesh*.

unique_edge_vectors()

An unordered vector of unique edges for the whole *TriMesh*.

Note that each physical edge will only be counted once in this method (i.e. edges shared between neighbouring triangles are only counted once not twice). The ordering should be considered random.

Returnsunique_edge_vectors ((n_unique_edges, n_dims) *ndarray*) – Vectors for each unique edge in this *TriMesh*.

vertex_normals()

Compute the per-vertex normals from the current set of points and triangle list. Only valid for 3D dimensional meshes.

Returnsnormals ((n_points, 3) *ndarray*) – Normal at each point.

RaisesValueError – If mesh is not 3D

view_widget(*browser_style='buttons'*, *figure_size=(10, 8)*, *style='coloured'*)

Visualization of the TriMesh using the *visualize_pointclouds* widget.

Parameters

- **browser_style** ({'buttons', 'slider'}, optional) – It defines whether the selector of the objects will have the form of plus/minus buttons or a slider.
- **figure_size** ((*int*, *int*) *tuple*, optional) – The initial size of the rendered figure.
- **style** ({'coloured', 'minimal'}, optional) – If 'coloured', then the style of the widget will be coloured. If minimal, then the style is simple using black and white colours.

has_landmarks

Whether the object has landmarks.

Type*bool*

landmarks

The landmarks object.

Type*LandmarkManager*

n_dims

The number of dimensions in the pointcloud.

Type*int*

n_landmark_groups
The number of landmark groups on this object.
Type *int*

n_parameters
The length of the vector that this object produces.
Type *int*

n_points
The number of points in the pointcloud.
Type *int*

n_tris
The number of triangles in the triangle list.
Type *int*

TexturedTriMesh

class menpo.shape.**TexturedTriMesh**(*points*, *tcoords*, *texture*, *trilist=None*, *copy=True*)
Bases: TriMesh

Combines a *TriMesh* with a texture. Also encapsulates the texture coordinates required to render the texture on the mesh.

Parameters
- **points** ((n_points, n_dims) *ndarray*) – The array representing the points.
- **tcoords** ((N, 2) *ndarray*) – The texture coordinates for the mesh.
- **texture** (*Image*) – The texture for the mesh.
- **trilist** ((M, 3) *ndarray* or None, optional) – The triangle list. If None, a Delaunay triangulation of the points will be used instead.
- **copy** (*bool*, optional) – If False, the points, trilist and texture will not be copied on assignment. In general this should only be used if you know what you are doing.

_view_2d(*figure_id=None*, *new_figure=False*, *image_view=True*, *render_lines=True*, *line_colour='r'*, *line_style='-'*, *line_width=1.0*, *render_markers=True*, *marker_style='o'*, *marker_size=20*, *marker_face_colour='k'*, *marker_edge_colour='k'*, *marker_edge_width=1.0*, *render_axes=True*, *axes_font_name='sans-serif'*, *axes_font_size=10*, *axes_font_style='normal'*, *axes_font_weight='normal'*, *axes_x_limits=None*, *axes_y_limits=None*, *figure_size=(10, 8)*, *label=None*)
Visualization of the TriMesh in 2D. Currently, explicit textured TriMesh viewing is not supported, and therefore viewing falls back to untextured 2D TriMesh viewing.

Returns
- **figure_id** (*object*, optional) – The id of the figure to be used.
- **new_figure** (*bool*, optional) – If True, a new figure is created.
- **image_view** (*bool*, optional) – If True the TexturedTriMesh will be viewed as if it is in the image coordinate system.
- **render_lines** (*bool*, optional) – If True, the edges will be rendered.
- **line_colour** (*See Below, optional*) – The colour of the lines. Example options:

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **line_style** ({-, --, -., :}, optional) – The style of the lines.
- **line_width** (*float*, optional) – The width of the lines.
- **render_markers** (*bool*, optional) – If True, the markers will be rendered.
- **marker_style** (*See Below, optional*) – The style of the markers. Example options

```
{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}
```

- **marker_size** (*int*, optional) – The size of the markers in points^2.
- **marker_face_colour** (*See Below, optional*) – The face (filling) colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_colour** (*See Below, optional*) – The edge colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_width** (*float*, optional) – The width of the markers' edge.
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.
- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** ({`normal`, `italic`, `oblique`}, optional) – The font style of the axes.
- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **axes_x_limits** ((*float*, *float*) *tuple* or `None`, optional) – The limits of the x axis.
- **axes_y_limits** ((*float*, *float*) *tuple* or `None`, optional) – The limits of the y axis.
- **figure_size** ((*float*, *float*) *tuple* or `None`, optional) – The size of the figure in inches.
- **label** (*str*, optional) – The name entry in case of a legend.

Returns **viewer** (`PointGraphViewer2d`) – The viewer object.

Raises `warning` – 2D Viewing of Coloured TriMeshes is not supported, automatically falls back to 2D *`TriMesh`* viewing.

_view_landmarks_2d(*group=None*, *with_labels=None*, *without_labels=None*, *figure_id=None*, *new_figure=False*, *image_view=True*, *render_lines=True*, *line_colour=None*, *line_style='-'*, *line_width=1*, *render_markers=True*, *marker_style='o'*, *marker_size=20*, *marker_face_colour=None*, *marker_edge_colour=None*, *marker_edge_width=1.0*, *render_numbering=False*, *numbers_horizontal_align='center'*, *numbers_vertical_align='bottom'*, *numbers_font_name='sans-serif'*, *numbers_font_size=10*, *numbers_font_style='normal'*, *numbers_font_weight='normal'*, *numbers_font_colour='k'*, *render_legend=False*, *legend_title=''*, *legend_font_name='sans-serif'*, *legend_font_style='normal'*, *legend_font_size=10*, *legend_font_weight='normal'*, *legend_marker_scale=None*, *legend_location=2*, *legend_bbox_to_anchor=(1.05, 1.0)*, *legend_border_axes_pad=None*, *legend_n_columns=1*, *legend_horizontal_spacing=None*, *legend_vertical_spacing=None*, *legend_border=True*, *legend_border_padding=None*, *legend_shadow=False*, *legend_rounded_corners=False*, *render_axes=False*, *axes_font_name='sans-serif'*, *axes_font_size=10*, *axes_font_style='normal'*, *axes_font_weight='normal'*, *axes_x_limits=None*, *axes_y_limits=None*, *figure_size=(10, 8)*)

Visualize the landmarks. This method will appear on the Image as `view_landmarks` if the Image is 2D.

Parameters

- **group** (*str* or''None'' optional) – The landmark group to be visualized. If `None` and there are more than one landmark groups, an error is raised.
- **with_labels** (`None` or *str* or *list* of *str*, optional) – If not `None`, only show the given label(s). Should **not** be used with the `without_labels` kwarg.
- **without_labels** (`None` or *str* or *list* of *str*, optional) – If not `None`, show all except the given label(s). Should **not** be used with the `with_labels` kwarg.
- **figure_id** (*object*, optional) – The id of the figure to be used.
- **new_figure** (*bool*, optional) – If `True`, a new figure is created.
- **image_view** (*bool*, optional) – If `True` the PointCloud will be viewed as if it is in the image coordinate system.
- **render_lines** (*bool*, optional) – If `True`, the edges will be rendered.
- **line_colour** (*See Below, optional*) – The colour of the lines. Example options:

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **line_style** (`{-, --, -., :}`, optional) – The style of the lines.
- **line_width** (*float*, optional) – The width of the lines.
- **render_markers** (*bool*, optional) – If `True`, the markers will be rendered.
- **marker_style** (*See Below, optional*) – The style of the markers. Example options

```
{., ,, o, v, ^, <, >, +, x, D, d, s, p, *, h, H, 1, 2, 3, 4, 8}
```

- **marker_size** (*int*, optional) – The size of the markers in points^2.
- **marker_face_colour** (*See Below, optional*) – The face (filling) colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
```

```
(3, ) ndarray
```

- **marker_edge_colour** (*See Below, optional*) – The edge colour of the markers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **marker_edge_width** (*float*, optional) – The width of the markers' edge.
- **render_numbering** (*bool*, optional) – If `True`, the landmarks will be numbered.
- **numbers_horizontal_align** (`{center, right, left}`, optional) – The horizontal alignment of the numbers' texts.
- **numbers_vertical_align** (`{center, top, bottom, baseline}`, optional) – The vertical alignment of the numbers' texts.
- **numbers_font_name** (*See Below, optional*) – The font of the numbers. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **numbers_font_size** (*int*, optional) – The font size of the numbers.
- **numbers_font_style** (`{normal, italic, oblique}`, optional) – The font style of the numbers.
- **numbers_font_weight** (*See Below, optional*) – The font weight of the numbers. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **numbers_font_colour** (*See Below, optional*) – The font colour of the numbers. Example options

```
{r, g, b, c, m, k, w}
or
(3, ) ndarray
```

- **render_legend** (*bool*, optional) – If `True`, the legend will be rendered.
- **legend_title** (*str*, optional) – The title of the legend.
- **legend_font_name** (*See below, optional*) – The font of the legend. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **legend_font_style** (`{normal, italic, oblique}`, optional) – The font style of the legend.
- **legend_font_size** (*int*, optional) – The font size of the legend.
- **legend_font_weight** (*See Below, optional*) – The font weight of the legend. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold, demibold, demi, bold, heavy, extra bold, black}
```

- **legend_marker_scale** (*float*, optional) – The relative size of the legend markers with respect to the original
- **legend_location** (*int*, optional) – The location of the legend. The predefined values are:

'best'	0
'upper right'	1
'upper left'	2
'lower left'	3
'lower right'	4
'right'	5
'center left'	6
'center right'	7
'lower center'	8
'upper center'	9
'center'	10

- **legend_bbox_to_anchor** ((*float*, *float*) *tuple*, optional) – The bbox that the legend will be anchored.
- **legend_border_axes_pad** (*float*, optional) – The pad between the axes and legend border.
- **legend_n_columns** (*int*, optional) – The number of the legend's columns.
- **legend_horizontal_spacing** (*float*, optional) – The spacing between the columns.
- **legend_vertical_spacing** (*float*, optional) – The vertical space between the legend entries.
- **legend_border** (*bool*, optional) – If `True`, a frame will be drawn around the legend.
- **legend_border_padding** (*float*, optional) – The fractional whitespace inside the legend border.
- **legend_shadow** (*bool*, optional) – If `True`, a shadow will be drawn behind legend.
- **legend_rounded_corners** (*bool*, optional) – If `True`, the frame's corners will be rounded (fancybox).
- **render_axes** (*bool*, optional) – If `True`, the axes will be rendered.
- **axes_font_name** (*See Below, optional*) – The font of the axes. Example options

```
{serif, sans-serif, cursive, fantasy, monospace}
```

- **axes_font_size** (*int*, optional) – The font size of the axes.
- **axes_font_style** (`{normal, italic, oblique}`, optional) – The font style of the axes.
- **axes_font_weight** (*See Below, optional*) – The font weight of the axes. Example options

```
{ultralight, light, normal, regular, book, medium, roman,
semibold,demibold, demi, bold, heavy, extra bold, black}
```

- **axes_x_limits** ((*float*, *float*) *tuple* or `None` optional) – The limits of the x axis.
- **axes_y_limits** ((*float*, *float*) *tuple* or `None` optional) – The limits of the y axis.
- **figure_size** ((*float*, *float*) *tuple* or `None` optional) – The size of the figure in inches.

Raises

- `ValueError` – If both `with_labels` and `without_labels` are passed.
- `ValueError` – If the landmark manager doesn't contain the provided group label.

as_pointgraph(*copy=True*, *skip_checks=False*)

Converts the TriMesh to a `PointUndirectedGraph`.

Parameters

- **copy** (*bool*, optional) – If `True`, the graph will be a copy.
- **skip_checks** (*bool*, optional) – If `True`, no checks will be performed.

Returns

pointgraph (*PointUndirectedGraph*) – The point graph.

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returns

vector (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

boundary_tri_index()

Boolean index into triangles that are at the edge of the TriMesh

Returns

boundary_tri_index (`(n_tris,)` *ndarray*) – For each triangle (ABC), returns whether any of it's edges is not also an edge of another triangle (and so this triangle exists on the boundary of the TriMesh)

bounding_box()

Return a bounding box from two corner points as a directed graph. The the first point (0) should be nearest the origin. In the case of an image, this ordering would appear as:

```
0<--3
|   ^
|   |
v   |
1-->2
```

In the case of a pointcloud, the ordering will appear as:

```
3<--2
|   ^
|   |
v   |
0-->1
```

Returns

bounding_box (*PointDirectedGraph*) – The axis aligned bounding box of the PointCloud.

bounds(*boundary=0*)

The minimum to maximum extent of the PointCloud. An optional boundary argument can be provided to expand the bounds by a constant margin.

Parameters

boundary (*float*) – A optional padding distance that is added to the bounds. Default is `0`, meaning the max/min of tightest possible containing square/cube/hypercube is returned.

Returns

- **min_b** (`(n_dims,)` *ndarray*) – The minimum extent of the *PointCloud* and boundary along each dimension
- **max_b** (`(n_dims,)` *ndarray*) – The maximum extent of the *PointCloud* and boundary along each dimension

centre()

The mean of all the points in this PointCloud (centre of mass).

Returns

centre (`(n_dims)` *ndarray*) – The mean of this PointCloud's points.

centre_of_bounds()

The centre of the absolute bounds of this PointCloud. Contrast with *centre()*, which is the mean point position.

Returns

centre (`n_dims` *ndarray*) – The centre of the bounds of this PointCloud.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns `type(self)` – A copy of this object

distance_to(*pointcloud*, ***kwargs*)

Returns a distance matrix between this PointCloud and another. By default the Euclidean distance is calculated - see *scipy.spatial.distance.cdist* for valid kwargs to change the metric and other properties.

Parameters **pointcloud** (*PointCloud*) – The second pointcloud to compute distances between. This must be of the same dimension as this PointCloud.

Returns **distance_matrix** (`(n_points, n_points)` *ndarray*) – The symmetric pairwise distance matrix between the two PointClouds s.t. `distance_matrix[i, j]` is the distance between the i'th point of this PointCloud and the j'th point of the input PointCloud.

edge_indices()

An unordered index into points that rebuilds the edges of this *TriMesh*.

Note that there will be two edges present in cases where two triangles 'share' an edge. Consider `unique_edge_indices()` for a single index for each physical edge on the *TriMesh*.

Returns **edge_indices** (`(n_tris * 3, 2)` *ndarray*) – For each triangle (ABC), returns the pair of point indices that rebuild AB, AC, BC. All edge indices are concatenated for a total of `n_tris * 3` edge_indices. The ordering is done so that all AB vectors are first in the returned list, followed by BC, then CA.

edge_lengths()

The length of each edge in this *TriMesh*.

Note that there will be two edges present in cases where two triangles 'share' an edge. Consider `unique_edge_indices()` for a single index for each physical edge on the *TriMesh*. The ordering matches the case for edges and edge_indices.

Returns **edge_lengths** (`(n_tris * 3, )` *ndarray*) – Scalar euclidean lengths for each edge in this *TriMesh*.

edge_vectors()

A vector of edges of each triangle face.

Note that there will be two edges present in cases where two triangles 'share' an edge. Consider *unique_edge_vectors()* for a single vector for each physical edge on the *TriMesh*.

Returns **edges** (`(n_tris * 3, n_dims)` *ndarray*) – For each triangle (ABC), returns the edge vectors AB, BC, CA. All edges are concatenated for a total of `n_tris * 3` edges. The ordering is done so that all AB vectors are first in the returned list, followed by BC, then CA.

from_mask(*mask*)

A 1D boolean array with the same number of elements as the number of points in the TexturedTriMesh. This is then broadcast across the dimensions of the mesh and returns a new mesh containing only those points that were `True` in the mask.

Parameters **mask** (`(n_points,)` *ndarray*) – 1D array of booleans

Returns **mesh** (*TexturedTriMesh*) – A new mesh that has been masked.

from_vector(*flattened*)

Builds a new *TexturedTriMesh* given the *flattened* 1D vector. Note that the trilist, texture, and tcoords will be drawn from self.

Parameters

- **flattened** ((N,) *ndarray*) – Vector representing a set of points.
- **Returns** –
- **--------** –
- **trimesh** (*TriMesh*) – A new trimesh created from the vector with `self` trilist.

from_vector_inplace(*vector*)

Updates the points of this PointCloud in-place with the reshaped points from the provided vector. Note that the vector should have the form `[x0, y0, x1, y1, ....., xn, yn]` for 2D.

Parameters
vector ((n_points,) *ndarray*) – The vector from which to create the points' array.

h_points()

Convert poincloud to a homogeneous array: `(n_dims + 1, n_points)`

Type `type(self)`

has_nan_values()

Tests if the vectorized form of the object contains `nan` values or not. This is particularly useful for objects with unknown values that have been mapped to `nan` values.

Returns **has_nan_values** (*bool*) – If the vectorized object contains `nan` values.

mean_edge_length(*unique=True*)

The mean length of each edge in this *TriMesh*.

Parameters **unique** (*bool*, optional) – If `True`, each shared edge will only be counted once towards the average. If false, shared edges will be counted twice.

Returns **mean_edge_length** (`float`) – The mean length of each edge in this *TriMesh*

mean_tri_area()

The mean area of each triangle face in this *TriMesh*.

Returns **mean_tri_area** (`float`) – The mean area of each triangle face in this *TriMesh*

Raises `ValueError` – If mesh is not 3D

norm(***kwargs*)

Returns the norm of this PointCloud. This is a translation and rotation invariant measure of the point cloud's intrinsic size - in other words, it is always taken around the point cloud's centre.

By default, the Frobenius norm is taken, but this can be changed by setting kwargs - see `numpy.linalg.norm` for valid options.

Returns **norm** (*float*) – The norm of this *PointCloud*

range(*boundary=0*)

The range of the extent of the PointCloud.

Parameters **boundary** (*float*) – A optional padding distance that is used to extend the bounds from which the range is computed. Default is `0`, no extension is performed.

Returns **range** ((n_dims,) *ndarray*) – The range of the *PointCloud* extent in each dimension.

tcoords_pixel_scaled()

Returns a *PointCloud* that is modified to be suitable for directly indexing into the pixels of the texture (e.g. for manual mapping operations). The resulting tcoords behave just like image landmarks do.

The operations that are performed are:

- Flipping the origin from bottom-left to top-left
- Scaling the tcoords by the image shape (denormalising them)
- Permuting the axis so that

Returns **tcoords_scaled** (*PointCloud*) – A copy of the tcoords that behave like *Image* landmarks

Examples

Recovering pixel values for every texture coordinate:

```
>>> texture = texturedtrimesh.texture
>>> tc_ps = texturedtrimesh.tcoords_pixel_scaled()
>>> pixel_values_at_tcs = texture[tc_ps[: ,0], tc_ps[:, 1]]
```

tojson()

Convert this *TriMesh* to a dictionary representation suitable for inclusion in the LJSON landmark format. Note that this enforces a simpler representation, and as such is not suitable for a permanent serialization of a *TriMesh* (to be clear, *TriMesh*'s serialized as part of a landmark set will be rebuilt as a *PointUndirectedGraph*).

Returnsjson (*dict*) – Dictionary with `points` and `connectivity` keys.

tri_areas()

The area of each triangle face.

Returnsareas (`(n_tris,)` *ndarray*) – Area of each triangle, ordered as the trilist is

Raises`ValueError` – If mesh is not 2D or 3D

tri_normals()

Compute the triangle face normals from the current set of points and triangle list. Only valid for 3D dimensional meshes.

Returnsnormals (`(n_tris, 3)` *ndarray*) – Normal at each triangle face.

Raises`ValueError` – If mesh is not 3D

unique_edge_indicies()

An unordered index into points that rebuilds the unique edges of this *TriMesh*.

Note that each physical edge will only be counted once in this method (i.e. edges shared between neighbouring triangles are only counted once not twice). The ordering should be considered random.

Returnsunique_edge_indicies (`(n_unique_edges, 2)` *ndarray*) – Return a point index that rebuilds all edges present in this *TriMesh* only once.

unique_edge_lengths()

The length of each edge in this *TriMesh*.

Note that each physical edge will only be counted once in this method (i.e. edges shared between neighbouring triangles are only counted once not twice). The ordering should be considered random.

Returnsedge_lengths (`(n_tris * 3, )` *ndarray*) – Scalar euclidean lengths for each edge in this *TriMesh*.

unique_edge_vectors()

An unordered vector of unique edges for the whole *TriMesh*.

Note that each physical edge will only be counted once in this method (i.e. edges shared between neighbouring triangles are only counted once not twice). The ordering should be considered random.

Returnsunique_edge_vectors (`(n_unique_edges, n_dims)` *ndarray*) – Vectors for each unique edge in this *TriMesh*.

vertex_normals()

Compute the per-vertex normals from the current set of points and triangle list. Only valid for 3D dimensional meshes.

Returnsnormals (`(n_points, 3)` *ndarray*) – Normal at each point.

Raises`ValueError` – If mesh is not 3D

view_widget(*browser_style='buttons'*, *figure_size=(10, 8)*, *style='coloured'*)

Visualization of the TriMesh using the *visualize_pointclouds* widget.

Parameters

- **browser_style** ({'buttons', 'slider'}, optional) – It defines whether the selector of the objects will have the form of plus/minus buttons or a slider.
- **figure_size** ((*int*, *int*) *tuple*, optional) – The initial size of the rendered figure.
- **style** ({'coloured', 'minimal'}, optional) – If 'coloured', then the style of the widget will be coloured. If minimal, then the style is simple using black and white colours.

has_landmarks

Whether the object has landmarks.

Type *bool*

landmarks

The landmarks object.

Type *LandmarkManager*

n_dims

The number of dimensions in the pointcloud.

Type *int*

n_landmark_groups

The number of landmark groups on this object.

Type *int*

n_parameters

The length of the vector that this object produces.

Type *int*

n_points

The number of points in the pointcloud.

Type *int*

n_tris

The number of triangles in the triangle list.

Type *int*

2.8.6 Group Operations

mean_pointcloud

menpo.shape.**mean_pointcloud**(*pointclouds*)

Compute the mean of a *list* of *PointCloud* or subclass objects. The list is assumed to be homogeneous i.e all elements of the list are assumed to belong to the same point cloud subclass just as all elements are also assumed to have the same number of points and represent semantically equivalent point clouds.

Parameters **pointclouds** (*list* of *PointCloud* or subclass) – List of point cloud or subclass objects from which we want to compute the mean.

Returns **mean_pointcloud** (*PointCloud* or subclass) – The mean point cloud or subclass.

2.9 menpo.transform

2.9.1 Homogeneous Transforms

Homogeneous

class menpo.transform.**Homogeneous**(*h_matrix*, *copy=True*, *skip_checks=False*)

Bases: ComposableTransform, Vectorizable, VComposable, VInvertible

A simple n-dimensional homogeneous transformation.

Adds a unit homogeneous coordinate to points, performs the dot product, re-normalizes by division by the homogeneous coordinate, and returns the result.

Can be composed with another Homogeneous, so long as the dimensionality matches.

Parameters

- **h_matrix** ((n_dims + 1, n_dims + 1) *ndarray*) – The homogeneous matrix defining this transform.
- **copy** (*bool*, optional) – If False, avoid copying h_matrix. Useful for performance.
- **skip_checks** (*bool*, optional) – If True, avoid sanity checks on the h_matrix. Useful for performance.

apply(*x*, *batch_size=None*, ***kwargs*)

Applies this transform to x.

If x is Transformable, x will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, x is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any kwargs will be passed to the specific transform _apply() method.

Parameters

- **x** (Transformable or (n_points, n_dims) *ndarray*) – The array or object to be transformed.
- **batch_size** (*int*, optional) – If not None, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.
- **kwargs** (*dict*) – Passed through to _apply().

Returnstransformed (type(x)) – The transformed object or array

apply_inplace(*x*, ***kwargs*)

Applies this transform to a Transformable x destructively.

Any kwargs will be passed to the specific transform _apply() method.

Parameters

- **x** (Transformable) – The Transformable object to be transformed.
- **kwargs** (*dict*) – Passed through to _apply().

Returnstransformed (type(x)) – The transformed object

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returnsvector (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

compose_after(*transform*)

A Transform that represents **this** transform composed **after** the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

a and b are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, o.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameters **transform** (*Transform*) – Transform to be applied **before** self

Returns transform (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_after_inplace(*transform*)

Update self so that it represents **this** transform composed **after** the given transform:

```
a_orig = a.copy()
a.compose_after_inplace(b)
a.apply(p) == a_orig.apply(b.apply(p))
```

a is permanently altered to be the result of the composition. b is left unchanged.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **before** self

Raises ValueError – If transform isn't an instance of *composes_inplace_with*

compose_before(*transform*)

A *Transform* that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

a and b are left unchanged.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameters **transform** (*Transform*) – Transform to be applied **after** self

Returns transform (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_before_inplace(*transform*)

Update self so that it represents **this** transform composed **before** the given transform:

```
a_orig = a.copy()
a.compose_before_inplace(b)
a.apply(p) == b.apply(a_orig.apply(p))
```

a is permanently altered to be the result of the composition. b is left unchanged.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **after** self

Raises ValueError – If transform isn't an instance of *composes_inplace_with*

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns `type(self)` – A copy of this object

from_vector(*vector*)

Build a new instance of the object from its vectorized state.

`self` is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is a `deepcopy` of the object followed by a call to `from_vector_inplace()`. This method can be overridden for a performance benefit if desired.

Parameters **vector** (`(n_parameters,)` *ndarray*) – Flattened representation of the object.

Returns **transform** (`Homogeneous`) – An new instance of this class.

from_vector_inplace(*vector*)

Update the state of this object from a vector form.

Parameters **vector** (`(n_parameters,)` *ndarray*) – Flattened representation of this object

has_nan_values()

Tests if the vectorized form of the object contains `nan` values or not. This is particularly useful for objects with unknown values that have been mapped to `nan` values.

Returns **has_nan_values** (*bool*) – If the vectorized object contains `nan` values.

classmethod init_identity(*n_dims*)

Creates an identity matrix Homogeneous transform.

Parameters **n_dims** (*int*) – The number of dimensions.

Returns **identity** (`Homogeneous`) – The identity matrix transform.

pseudoinverse()

The pseudoinverse of the transform - that is, the transform that results from swapping *source* and *target*, or more formally, negating the transforms parameters. If the transform has a true inverse this is returned instead.

Type `Homogeneous`

pseudoinverse_vector(*vector*)

The vectorized pseudoinverse of a provided vector instance. Syntactic sugar for:

```
self.from_vector(vector).pseudoinverse().as_vector()
```

Can be much faster than the explict call as object creation can be entirely avoided in some cases.

Parameters **vector** (`(n_parameters,)` *ndarray*) – A vectorized version of `self`

Returns **pseudoinverse_vector** (`(n_parameters,)` *ndarray*) – The pseudoinverse of the vector provided

set_h_matrix(*value*, *copy=True*, *skip_checks=False*)

Updates `h_matrix`, optionally performing sanity checks.

Note that it won't always be possible to manually specify the `h_matrix` through this method, specifically if changing the `h_matrix` could change the nature of the transform. See `h_matrix_is_mutable` for how you can discover if the `h_matrix` is allowed to be set for a given class.

Parameters

- **value** (*ndarray*) – The new homogeneous matrix to set.
- **copy** (*bool*, optional) – If `False`, do not copy the h_matrix. Useful for performance.
- **skip_checks** (*bool*, optional) – If `True`, skip checking. Useful for performance.

Raises `NotImplementedError` – If `h_matrix_is_mutable` returns `False`.

composes_inplace_with
`Homogeneous` can swallow composition with any other `Homogeneous`, subclasses will have to override and be more specific.

composes_with
Any Homogeneous can compose with any other Homogeneous.

h_matrix
The homogeneous matrix defining this transform.
Type `(n_dims + 1, n_dims + 1)` *ndarray*

h_matrix_is_mutable
`True` iff `set_h_matrix()` is permitted on this type of transform.

If this returns `False` calls to `set_h_matrix()` will raise a `NotImplementedError`.
Type *bool*

has_true_inverse
The pseudoinverse is an exact inverse.
Type `True`

n_dims
The dimensionality of the data the transform operates on.
Type *int*

n_dims_output
The output of the data from the transform.
Type *int*

n_parameters
The length of the vector that this object produces.
Type *int*

Affine

class `menpo.transform.`**`Affine`**(*h_matrix*, *copy=True*, *skip_checks=False*)
Bases: `Homogeneous`

Base class for all `n`-dimensional affine transformations. Provides methods to break the transform down into its constituent scale/rotation/translation, to view the homogeneous matrix equivalent, and to chain this transform with other affine transformations.

Parameters
- **h_matrix** (`(n_dims + 1, n_dims + 1)` *ndarray*) – The homogeneous matrix of the affine transformation.
- **copy** (*bool*, optional) – If `False` avoid copying `h_matrix` for performance.
- **skip_checks** (*bool*, optional) – If `True` avoid sanity checks on `h_matrix` for performance.

apply(*x*, *batch_size=None*, ***kwargs*)
Applies this transform to `x`.

If `x` is `Transformable`, `x` will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, `x` is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any `kwargs` will be passed to the specific transform `_apply()` method.
Parameters

- **x** (`Transformable` or `(n_points, n_dims)` *ndarray*) – The array or object to be transformed.
- **batch_size** (*int*, optional) – If not `None`, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returns **transformed** (`type(x)`) – The transformed object or array

apply_inplace(*x*, ***kwargs*)

Applies this transform to a `Transformable` `x` destructively.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters

- **x** (`Transformable`) – The `Transformable` object to be transformed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returns **transformed** (`type(x)`) – The transformed object

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returns **vector** (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

compose_after(*transform*)

A *Transform* that represents **this** transform composed **after** the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

`a` and `b` are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, `o`.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameters **transform** (*Transform*) – Transform to be applied **before** `self`

Returns **transform** (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_after_inplace(*transform*)

Update `self` so that it represents **this** transform composed **after** the given transform:

```
a_orig = a.copy()
a.compose_after_inplace(b)
a.apply(p) == a_orig.apply(b.apply(p))
```

`a` is permanently altered to be the result of the composition. `b` is left unchanged.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **before** `self`

Raises `ValueError` – If `transform` isn't an instance of *composes_inplace_with*

compose_before(*transform*)

A *Transform* that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

a and b are left unchanged.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameters **transform** (*Transform*) – Transform to be applied **after** self

Returns **transform** (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_before_inplace(*transform*)

Update self so that it represents **this** transform composed **before** the given transform:

```
a_orig = a.copy()
a.compose_before_inplace(b)
a.apply(p) == b.apply(a_orig.apply(p))
```

a is permanently altered to be the result of the composition. b is left unchanged.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **after** self

Raises ValueError – If transform isn't an instance of *composes_inplace_with*

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns type(self) – A copy of this object

decompose()

Decompose this transform into discrete Affine Transforms.

Useful for understanding the effect of a complex composite transform.

Returns

transforms (*list* of DiscreteAffine) – Equivalent to this affine transform, such that:

```
reduce(lambda x,y: x.chain(y), self.decompose()) == self
```

from_vector(*vector*)

Build a new instance of the object from its vectorized state.

self is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is a deepcopy of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parameters **vector** ((n_parameters,) *ndarray*) – Flattened representation of the object.

Returns **transform** (*Homogeneous*) – An new instance of this class.

from_vector_inplace(*p*)

Updates this Affine in-place from the new parameters. See from_vector for details of the parameter format

has_nan_values()

Tests if the vectorized form of the object contains nan values or not. This is particularly useful for objects with unknown values that have been mapped to nan values.

Returns **has_nan_values** (*bool*) – If the vectorized object contains nan values.

classmethod init_identity(*n_dims*)

Creates an identity matrix Affine transform.

Parameters **n_dims** (*int*) – The number of dimensions.

Returns **identity** (*Affine*) – The identity matrix transform.

pseudoinverse()

The pseudoinverse of the transform - that is, the transform that results from swapping *source* and *target*, or more formally, negating the transforms parameters. If the transform has a true inverse this is returned instead.

Type *Homogeneous*

pseudoinverse_vector(*vector*)

The vectorized pseudoinverse of a provided vector instance. Syntactic sugar for:

```
self.from_vector(vector).pseudoinverse().as_vector()
```

Can be much faster than the explict call as object creation can be entirely avoided in some cases.

Parameters **vector** ((n_parameters,) *ndarray*) – A vectorized version of `self`

Returns **pseudoinverse_vector** ((n_parameters,) *ndarray*) – The pseudoinverse of the vector provided

set_h_matrix(*value*, *copy=True*, *skip_checks=False*)

Updates `h_matrix`, optionally performing sanity checks.

Note that it won't always be possible to manually specify the `h_matrix` through this method, specifically if changing the `h_matrix` could change the nature of the transform. See *h_matrix_is_mutable* for how you can discover if the `h_matrix` is allowed to be set for a given class.

Parameters

- **value** (*ndarray*) – The new homogeneous matrix to set.
- **copy** (*bool*, optional) – If `False`, do not copy the h_matrix. Useful for performance.
- **skip_checks** (*bool*, optional) – If `True`, skip checking. Useful for performance.

Raises `NotImplementedError` – If *h_matrix_is_mutable* returns `False`.

composes_inplace_with

Affine can swallow composition with any other *Affine*.

composes_with

Any Homogeneous can compose with any other Homogeneous.

h_matrix

The homogeneous matrix defining this transform.

Type (n_dims + 1, n_dims + 1) *ndarray*

h_matrix_is_mutable

`True` iff *set_h_matrix()* is permitted on this type of transform.

If this returns `False` calls to *set_h_matrix()* will raise a `NotImplementedError`.

Type *bool*

has_true_inverse

The pseudoinverse is an exact inverse.

Type `True`

linear_component

The linear component of this affine transform.

Type (n_dims, n_dims) *ndarray*

n_dims
The dimensionality of the data the transform operates on.
Type *int*

n_dims_output
The output of the data from the transform.
Type *int*

n_parameters
`n_dims * (n_dims + 1)` parameters - every element of the matrix but the homogeneous part.
Type int

Examples

2D Affine: 6 parameters:

```
[p1, p3, p5]
[p2, p4, p6]
```

3D Affine: 12 parameters:

```
[p1, p4, p7, p10]
[p2, p5, p8, p11]
[p3, p6, p9, p12]
```

translation_component
The translation component of this affine transform.
Type `(n_dims,)` *ndarray*

Similarity

class `menpo.transform.`**`Similarity`**(*h_matrix*, *copy=True*, *skip_checks=False*)
Bases: `Affine`

Specialist version of an `Affine` that is guaranteed to be a Similarity transform.
Parameters
- **h_matrix** (`(n_dims + 1, n_dims + 1)` *ndarray*) – The homogeneous matrix of the affine transformation.
- **copy** (*bool*, optional) – If `False` avoid copying `h_matrix` for performance.
- **skip_checks** (*bool*, optional) – If `True` avoid sanity checks on `h_matrix` for performance.

apply(*x*, *batch_size=None*, ***kwargs*)
Applies this transform to `x`.

If `x` is `Transformable`, `x` will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, `x` is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any `kwargs` will be passed to the specific transform `_apply()` method.
Parameters
- **x** (`Transformable` or `(n_points, n_dims)` *ndarray*) – The array or object to be transformed.
- **batch_size** (*int*, optional) – If not `None`, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.

•**kwargs** (*dict*) – Passed through to `_apply()`.

Returnstransformed (`type(x)`) – The transformed object or array

apply_inplace(*x*, ***kwargs*)

Applies this transform to a `Transformable` `x` destructively.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters

•**x** (`Transformable`) – The `Transformable` object to be transformed.

•**kwargs** (*dict*) – Passed through to `_apply()`.

Returnstransformed (`type(x)`) – The transformed object

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returnsvector (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

compose_after(*transform*)

A *Transform* that represents **this** transform composed **after** the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

`a` and `b` are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, `o`.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameterstransform (*Transform*) – Transform to be applied **before** `self`

Returnstransform (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_after_inplace(*transform*)

Update `self` so that it represents **this** transform composed **after** the given transform:

```
a_orig = a.copy()
a.compose_after_inplace(b)
a.apply(p) == a_orig.apply(b.apply(p))
```

`a` is permanently altered to be the result of the composition. `b` is left unchanged.

Parameterstransform (*composes_inplace_with*) – Transform to be applied **before** `self`

Raises`ValueError` – If `transform` isn't an instance of *composes_inplace_with*

compose_before(*transform*)

A *Transform* that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

`a` and `b` are left unchanged.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameterstransform (*Transform*) – Transform to be applied **after** `self`

Returnstransform (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_before_inplace(*transform*)

Update `self` so that it represents **this** transform composed **before** the given transform:

```
a_orig = a.copy()
a.compose_before_inplace(b)
a.apply(p) == b.apply(a_orig.apply(p))
```

`a` is permanently altered to be the result of the composition. `b` is left unchanged.

Parameterstransform (*composes_inplace_with*) – Transform to be applied **after** `self`

Raises`ValueError` – If `transform` isn't an instance of *composes_inplace_with*

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns`type(self)` – A copy of this object

decompose()

Decompose this transform into discrete Affine Transforms.

Useful for understanding the effect of a complex composite transform.

Returns

transforms (*list* of `DiscreteAffine`) – Equivalent to this affine transform, such that:

```
reduce(lambda x,y: x.chain(y), self.decompose()) == self
```

from_vector(*vector*)

Build a new instance of the object from its vectorized state.

`self` is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is a `deepcopy` of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parametersvector (`(n_parameters,)` *ndarray*) – Flattened representation of the object.

Returnstransform (*Homogeneous*) – An new instance of this class.

from_vector_inplace(*p*)

Returns an instance of the transform from the given parameters, expected to be in Fortran ordering.

Supports rebuilding from 2D parameter sets.

2D Similarity: 4 parameters:

```
[a, b, tx, ty]
```

Parametersp (`(P,)` *ndarray*) – The array of parameters.

RaisesDimensionalityError, NotImplementedError – Only 2D transforms are supported.

has_nan_values()

Tests if the vectorized form of the object contains `nan` values or not. This is particularly useful for objects with unknown values that have been mapped to `nan` values.

Returnshas_nan_values (*bool*) – If the vectorized object contains `nan` values.

classmethod init_identity(*n_dims*)

Creates an identity transform.

Parametersn_dims (*int*) – The number of dimensions.

Returnsidentity (*Similarity*) – The identity matrix transform.

pseudoinverse()

The pseudoinverse of the transform - that is, the transform that results from swapping *source* and *target*, or more formally, negating the transforms parameters. If the transform has a true inverse this is returned instead.

Type*Homogeneous*

pseudoinverse_vector(*vector*)

The vectorized pseudoinverse of a provided vector instance. Syntactic sugar for:

```
self.from_vector(vector).pseudoinverse().as_vector()
```

Can be much faster than the explict call as object creation can be entirely avoided in some cases.

Parametersvector ((n_parameters,) *ndarray*) – A vectorized version of `self`

Returnspseudoinverse_vector ((n_parameters,) *ndarray*) – The pseudoinverse of the vector provided

set_h_matrix(*value*, *copy=True*, *skip_checks=False*)

Updates `h_matrix`, optionally performing sanity checks.

Note that it won't always be possible to manually specify the `h_matrix` through this method, specifically if changing the `h_matrix` could change the nature of the transform. See *h_matrix_is_mutable* for how you can discover if the `h_matrix` is allowed to be set for a given class.

Parameters

- **value** (*ndarray*) – The new homogeneous matrix to set.
- **copy** (*bool*, optional) – If `False`, do not copy the h_matrix. Useful for performance.
- **skip_checks** (*bool*, optional) – If `True`, skip checking. Useful for performance.

Raises`NotImplementedError` – If *h_matrix_is_mutable* returns `False`.

composes_inplace_with

Affine can swallow composition with any other *Affine*.

composes_with

Any Homogeneous can compose with any other Homogeneous.

h_matrix

The homogeneous matrix defining this transform.

Type`(n_dims + 1, n_dims + 1)` *ndarray*

h_matrix_is_mutable

`h_matrix` is not mutable.

Type`False`

has_true_inverse

The pseudoinverse is an exact inverse.

Type`True`

linear_component

The linear component of this affine transform.

Type `(n_dims, n_dims)` *ndarray*

n_dims
The dimensionality of the data the transform operates on.
Type *int*

n_dims_output
The output of the data from the transform.
Type *int*

n_parameters
2D Similarity: 4 parameters:

```
[(1 + a), -b,       tx]
[b,        (1 + a), ty]
```

3D Similarity: Currently not supported
Returns n_parameters (*int*) – The transform parameters
Raises DimensionalityError, NotImplementedError – Only 2D transforms are supported.

translation_component
The translation component of this affine transform.
Type `(n_dims,)` *ndarray*

Rotation

class `menpo.transform.`**Rotation**(*rotation_matrix*, *skip_checks=False*)
Bases: `DiscreteAffine`, `Similarity`

Abstract *n_dims* rotation transform.
Parameters
- **rotation_matrix** (`(n_dims, n_dims)` *ndarray*) – A valid, square rotation matrix
- **skip_checks** (*bool*, optional) – If `True` avoid sanity checks on `rotation_matrix` for performance.

apply(*x*, *batch_size=None*, ***kwargs*)
Applies this transform to `x`.

If `x` is `Transformable`, `x` will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, `x` is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any `kwargs` will be passed to the specific transform `_apply()` method.
Parameters
- **x** (`Transformable` or `(n_points, n_dims)` *ndarray*) – The array or object to be transformed.
- **batch_size** (*int*, optional) – If not `None`, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returns transformed (`type(x)`) – The transformed object or array

apply_inplace(*x*, ***kwargs*)
Applies this transform to a `Transformable` `x` destructively.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters
- **x** (`Transformable`) – The `Transformable` object to be transformed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returnstransformed (`type(x)`) – The transformed object

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returnsvector (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

axis_and_angle_of_rotation()

Abstract method for computing the axis and angle of rotation.

Returns
- **axis** (`(n_dims,)` *ndarray*) – The unit vector representing the axis of rotation
- **angle_of_rotation** (*float*) – The angle in radians of the rotation about the axis. The angle is signed in a right handed sense.

compose_after(*transform*)

A `Transform` that represents **this** transform composed **after** the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

`a` and `b` are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, `o`.

An attempt is made to perform native composition, but will fall back to a `TransformChain` as a last resort. See `composes_with` for a description of how the mode of composition is decided.

Parameterstransform (`Transform`) – Transform to be applied **before** `self`

Returnstransform (`Transform` or `TransformChain`) – If the composition was native, a single new `Transform` will be returned. If not, a `TransformChain` is returned instead.

compose_after_inplace(*transform*)

Update `self` so that it represents **this** transform composed **after** the given transform:

```
a_orig = a.copy()
a.compose_after_inplace(b)
a.apply(p) == a_orig.apply(b.apply(p))
```

`a` is permanently altered to be the result of the composition. `b` is left unchanged.

Parameterstransform (`composes_inplace_with`) – Transform to be applied **before** `self`

Raises`ValueError` – If `transform` isn't an instance of `composes_inplace_with`

compose_before(*transform*)

A `Transform` that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

`a` and `b` are left unchanged.

An attempt is made to perform native composition, but will fall back to a `TransformChain` as a last resort. See `composes_with` for a description of how the mode of composition is decided.

Parameterstransform (`Transform`) – Transform to be applied **after** `self`

Returnstransform (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_before_inplace(*transform*)

Update `self` so that it represents **this** transform composed **before** the given transform:

```
a_orig = a.copy()
a.compose_before_inplace(b)
a.apply(p) == b.apply(a_orig.apply(p))
```

`a` is permanently altered to be the result of the composition. `b` is left unchanged.

Parameterstransform (*composes_inplace_with*) – Transform to be applied **after** `self`

Raises`ValueError` – If `transform` isn't an instance of *composes_inplace_with*

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns`type(self)` – A copy of this object

decompose()

A `DiscreteAffine` is already maximally decomposed - return a copy of self in a *list*.

Returnstransform (`DiscreteAffine`) – Deep copy of *self*.

from_vector(*vector*)

Build a new instance of the object from its vectorized state.

`self` is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is a `deepcopy` of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parametersvector (`(n_parameters,)` *ndarray*) – Flattened representation of the object.

Returnstransform (*Homogeneous*) – An new instance of this class.

from_vector_inplace(*p*)

Returns an instance of the transform from the given parameters, expected to be in Fortran ordering.

Supports rebuilding from 2D parameter sets.

2D Rotation: 1 parameter:

```
[theta]
```

Parametersp (`(1,)` *ndarray*) – The array of parameters.

Returnstransform (*Rotation*) – The transform initialised to the given parameters.

has_nan_values()

Tests if the vectorized form of the object contains `nan` values or not. This is particularly useful for objects with unknown values that have been mapped to `nan` values.

Returnshas_nan_values (*bool*) – If the vectorized object contains `nan` values.

classmethod init_from_2d_ccw_angle(*theta*, *degrees=True*)

Convenience constructor for 2D CCW rotations about the origin.

Parameters

- **theta** (*float*) – The angle of rotation about the origin
- **degrees** (*bool*, optional) – If `True` theta is interpreted as a degree. If `False`, theta is interpreted as radians.

Returns **rotation** (`Rotation`) – A 2D rotation transform.

classmethod **init_identity**(*n_dims*)

Creates an identity transform.

Parameters **n_dims** (*int*) – The number of dimensions.

Returns **identity** (*Rotation*) – The identity matrix transform.

pseudoinverse()

The inverse rotation matrix.

Type *Rotation*

pseudoinverse_vector(*vector*)

The vectorized pseudoinverse of a provided vector instance. Syntactic sugar for:

```
self.from_vector(vector).pseudoinverse().as_vector()
```

Can be much faster than the explict call as object creation can be entirely avoided in some cases.

Parameters **vector** ((`n_parameters,`) *ndarray*) – A vectorized version of `self`

Returns **pseudoinverse_vector** ((`n_parameters,`) *ndarray*) – The pseudoinverse of the vector provided

set_h_matrix(*value*, *copy=True*, *skip_checks=False*)

Updates `h_matrix`, optionally performing sanity checks.

Note that it won't always be possible to manually specify the `h_matrix` through this method, specifically if changing the `h_matrix` could change the nature of the transform. See *h_matrix_is_mutable* for how you can discover if the `h_matrix` is allowed to be set for a given class.

Parameters

- **value** (*ndarray*) – The new homogeneous matrix to set.
- **copy** (*bool*, optional) – If `False`, do not copy the h_matrix. Useful for performance.
- **skip_checks** (*bool*, optional) – If `True`, skip checking. Useful for performance.

Raises `NotImplementedError` – If *h_matrix_is_mutable* returns `False`.

set_rotation_matrix(*value*, *skip_checks=False*)

Sets the rotation matrix.

Parameters

- **value** ((`n_dims, n_dims`) *ndarray*) – The new rotation matrix.
- **skip_checks** (*bool*, optional) – If `True` avoid sanity checks on `value` for performance.

composes_inplace_with

Rotation can swallow composition with any other *Rotation*.

composes_with

Any Homogeneous can compose with any other Homogeneous.

h_matrix

The homogeneous matrix defining this transform.

Type (`n_dims + 1, n_dims + 1`) *ndarray*

h_matrix_is_mutable

`h_matrix` is not mutable.

Type `False`

has_true_inverse
The pseudoinverse is an exact inverse.
Type `True`

linear_component
The linear component of this affine transform.
Type `(n_dims, n_dims)` *ndarray*

n_dims
The dimensionality of the data the transform operates on.
Type *int*

n_dims_output
The output of the data from the transform.
Type *int*

rotation_matrix
The rotation matrix.
Type `(n_dims, n_dims)` *ndarray*

translation_component
The translation component of this affine transform.
Type `(n_dims,)` *ndarray*

Translation

class `menpo.transform.`**`Translation`**(*translation*, *skip_checks=False*)
Bases: *`DiscreteAffine`*, `Similarity`

An `n_dims`-dimensional translation transform.
Parameters
- **translation** (`(n_dims,)` *ndarray*) – The translation in each axis.
- **skip_checks** (*bool*, optional) – If `True` avoid sanity checks on `h_matrix` for performance.

apply(*x*, *batch_size=None*, ***kwargs*)
Applies this transform to `x`.

If `x` is `Transformable`, `x` will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, `x` is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any `kwargs` will be passed to the specific transform `_apply()` method.
Parameters
- **x** (`Transformable` or `(n_points, n_dims)` *ndarray*) – The array or object to be transformed.
- **batch_size** (*int*, optional) – If not `None`, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returns **transformed** (`type(x)`) – The transformed object or array

apply_inplace(*x*, ***kwargs*)
Applies this transform to a `Transformable` `x` destructively.

Any `kwargs` will be passed to the specific transform `_apply()` method.
Parameters
- **x** (`Transformable`) – The `Transformable` object to be transformed.

•**kwargs** (*dict*) – Passed through to `_apply()`.

Returnstransformed (`type(x)`) – The transformed object

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returnsvector (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

compose_after(*transform*)

A `Transform` that represents **this** transform composed **after** the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

`a` and `b` are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, `o`.

An attempt is made to perform native composition, but will fall back to a `TransformChain` as a last resort. See `composes_with` for a description of how the mode of composition is decided.

Parameterstransform (`Transform`) – Transform to be applied **before** `self`

Returnstransform (`Transform` or `TransformChain`) – If the composition was native, a single new `Transform` will be returned. If not, a `TransformChain` is returned instead.

compose_after_inplace(*transform*)

Update `self` so that it represents **this** transform composed **after** the given transform:

```
a_orig = a.copy()
a.compose_after_inplace(b)
a.apply(p) == a_orig.apply(b.apply(p))
```

`a` is permanently altered to be the result of the composition. `b` is left unchanged.

Parameterstransform (`composes_inplace_with`) – Transform to be applied **before** `self`

Raises`ValueError` – If `transform` isn't an instance of `composes_inplace_with`

compose_before(*transform*)

A `Transform` that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

`a` and `b` are left unchanged.

An attempt is made to perform native composition, but will fall back to a `TransformChain` as a last resort. See `composes_with` for a description of how the mode of composition is decided.

Parameterstransform (`Transform`) – Transform to be applied **after** `self`

Returnstransform (`Transform` or `TransformChain`) – If the composition was native, a single new `Transform` will be returned. If not, a `TransformChain` is returned instead.

compose_before_inplace(*transform*)

Update `self` so that it represents **this** transform composed **before** the given transform:

```
a_orig = a.copy()
a.compose_before_inplace(b)
a.apply(p) == b.apply(a_orig.apply(p))
```

a is permanently altered to be the result of the composition. b is left unchanged.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **after** self

Raises ValueError – If transform isn't an instance of *composes_inplace_with*

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns type(self) – A copy of this object

decompose()

A DiscreteAffine is already maximally decomposed - return a copy of self in a *list*.

Returns **transform** (DiscreteAffine) – Deep copy of *self*.

from_vector(*vector*)

Build a new instance of the object from its vectorized state.

self is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is a deepcopy of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parameters **vector** ((n_parameters,) *ndarray*) – Flattened representation of the object.

Returns **transform** (*Homogeneous*) – An new instance of this class.

from_vector_inplace(*p*)

Updates the *Translation* inplace.

Parameters **vector** ((n_dims,) *ndarray*) – The array of parameters.

has_nan_values()

Tests if the vectorized form of the object contains nan values or not. This is particularly useful for objects with unknown values that have been mapped to nan values.

Returns **has_nan_values** (*bool*) – If the vectorized object contains nan values.

classmethod **init_identity**(*n_dims*)

Creates an identity transform.

Parameters **n_dims** (*int*) – The number of dimensions.

Returns **identity** (*Translation*) – The identity matrix transform.

pseudoinverse()

The inverse translation (negated).

Type *Translation*

pseudoinverse_vector(*vector*)

The vectorized pseudoinverse of a provided vector instance. Syntactic sugar for:

```
self.from_vector(vector).pseudoinverse().as_vector()
```

Can be much faster than the explict call as object creation can be entirely avoided in some cases.

Parameters **vector** ((n_parameters,) *ndarray*) – A vectorized version of self

Returns **pseudoinverse_vector** ((n_parameters,) *ndarray*) – The pseudoinverse of the vector provided

set_h_matrix(*value*, *copy=True*, *skip_checks=False*)

Updates h_matrix, optionally performing sanity checks.

Note that it won't always be possible to manually specify the `h_matrix` through this method, specifically if changing the `h_matrix` could change the nature of the transform. See *h_matrix_is_mutable* for how you can discover if the `h_matrix` is allowed to be set for a given class.

Parameters

- **value** (*ndarray*) – The new homogeneous matrix to set.
- **copy** (*bool*, optional) – If `False`, do not copy the h_matrix. Useful for performance.
- **skip_checks** (*bool*, optional) – If `True`, skip checking. Useful for performance.

Raises `NotImplementedError` – If *h_matrix_is_mutable* returns `False`.

composes_inplace_with

Affine can swallow composition with any other *Affine*.

composes_with

Any Homogeneous can compose with any other Homogeneous.

h_matrix

The homogeneous matrix defining this transform.

Type `(n_dims + 1, n_dims + 1)` *ndarray*

h_matrix_is_mutable

`h_matrix` is not mutable.

Type `False`

has_true_inverse

The pseudoinverse is an exact inverse.

Type `True`

linear_component

The linear component of this affine transform.

Type `(n_dims, n_dims)` *ndarray*

n_dims

The dimensionality of the data the transform operates on.

Type *int*

n_dims_output

The output of the data from the transform.

Type *int*

n_parameters

The number of parameters: `n_dims`

Type *int*

translation_component

The translation component of this affine transform.

Type `(n_dims,)` *ndarray*

Scale

`menpo.transform.`**`Scale`**(*scale_factor*, *n_dims=None*)

Factory function for producing Scale transforms. Zero scale factors are not permitted.

A *UniformScale* will be produced if:

- A *float* `scale_factor` and a `n_dims` *kwarg* are provided
- A *ndarray* `scale_factor` with shape `(n_dims,)` is provided with all elements being the same

A *NonUniformScale* will be provided if:

- A *ndarray* `scale_factor` with shape `(n_dims,)` is provided with at least two differing scale factors.

Parameters
- **scale_factor** (*float* or `(n_dims,)` *ndarray*) – Scale for each axis.
- **n_dims** (*int*, optional) – The dimensionality of the output transform.

Returnsscale (`UniformScale` or `NonUniformScale`) – The correct type of scale
Raises`ValueError` – If any of the scale factors is zero

UniformScale

class `menpo.transform.`**`UniformScale`**(*scale*, *n_dims*, *skip_checks=False*)
Bases: `DiscreteAffine`, `Similarity`

An abstract similarity scale transform, with a single scale component applied to all dimensions. This is abstracted out to remove unnecessary code duplication.

Parameters
- **scale** (`(n_dims,)` *ndarray*) – A scale for each axis.
- **n_dims** (*int*) – The number of dimensions
- **skip_checks** (*bool*, optional) – If `True` avoid sanity checks on `h_matrix` for performance.

apply(*x*, *batch_size=None*, ***kwargs*)
Applies this transform to `x`.

If `x` is `Transformable`, `x` will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, `x` is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters
- **x** (`Transformable` or `(n_points, n_dims)` *ndarray*) – The array or object to be transformed.
- **batch_size** (*int*, optional) – If not `None`, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returnstransformed (`type(x)`) – The transformed object or array

apply_inplace(*x*, ***kwargs*)
Applies this transform to a `Transformable` `x` destructively.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters
- **x** (`Transformable`) – The `Transformable` object to be transformed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returnstransformed (`type(x)`) – The transformed object

as_vector(***kwargs*)
Returns a flattened representation of the object as a single vector.

Returnsvector (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

compose_after(*transform*)
A `Transform` that represents **this** transform composed **after** the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

a and b are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, o.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameters **transform** (*Transform*) – Transform to be applied **before** self

Returns transform (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_after_inplace(*transform*)

Update self so that it represents **this** transform composed **after** the given transform:

```
a_orig = a.copy()
a.compose_after_inplace(b)
a.apply(p) == a_orig.apply(b.apply(p))
```

a is permanently altered to be the result of the composition. b is left unchanged.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **before** self

Raises ValueError – If transform isn't an instance of *composes_inplace_with*

compose_before(*transform*)

A *Transform* that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

a and b are left unchanged.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameters **transform** (*Transform*) – Transform to be applied **after** self

Returns transform (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_before_inplace(*transform*)

Update self so that it represents **this** transform composed **before** the given transform:

```
a_orig = a.copy()
a.compose_before_inplace(b)
a.apply(p) == b.apply(a_orig.apply(p))
```

a is permanently altered to be the result of the composition. b is left unchanged.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **after** self

Raises ValueError – If transform isn't an instance of *composes_inplace_with*

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns type(self) – A copy of this object

decompose()

A `DiscreteAffine` is already maximally decomposed - return a copy of self in a *list*.

Returns **transform** (`DiscreteAffine`) – Deep copy of *self*.

from_vector(*vector*)

Build a new instance of the object from its vectorized state.

`self` is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is a `deepcopy` of the object followed by a call to `from_vector_inplace()`. This method can be overridden for a performance benefit if desired.

Parameters **vector** (`(n_parameters,)` *ndarray*) – Flattened representation of the object.

Returns **transform** (`Homogeneous`) – An new instance of this class.

from_vector_inplace(*p*)

Returns an instance of the transform from the given parameters, expected to be in Fortran ordering.

Parameters **p** (*float*) – The parameter

has_nan_values()

Tests if the vectorized form of the object contains `nan` values or not. This is particularly useful for objects with unknown values that have been mapped to `nan` values.

Returns **has_nan_values** (*bool*) – If the vectorized object contains `nan` values.

classmethod init_identity(*n_dims*)

Creates an identity transform.

Parameters **n_dims** (*int*) – The number of dimensions.

Returns **identity** (`UniformScale`) – The identity matrix transform.

pseudoinverse()

The inverse scale.

Type `UniformScale`

pseudoinverse_vector(*vector*)

The vectorized pseudoinverse of a provided vector instance. Syntactic sugar for:

```
self.from_vector(vector).pseudoinverse().as_vector()
```

Can be much faster than the explict call as object creation can be entirely avoided in some cases.

Parameters **vector** (`(n_parameters,)` *ndarray*) – A vectorized version of `self`

Returns **pseudoinverse_vector** (`(n_parameters,)` *ndarray*) – The pseudoinverse of the vector provided

set_h_matrix(*value*, *copy=True*, *skip_checks=False*)

Updates `h_matrix`, optionally performing sanity checks.

Note that it won't always be possible to manually specify the `h_matrix` through this method, specifically if changing the `h_matrix` could change the nature of the transform. See `h_matrix_is_mutable` for how you can discover if the `h_matrix` is allowed to be set for a given class.

Parameters

- **value** (*ndarray*) – The new homogeneous matrix to set.
- **copy** (*bool*, optional) – If `False`, do not copy the h_matrix. Useful for performance.
- **skip_checks** (*bool*, optional) – If `True`, skip checking. Useful for performance.

Raises `NotImplementedError` – If `h_matrix_is_mutable` returns `False`.

composes_inplace_with

`UniformScale` can swallow composition with any other `UniformScale`.

composes_with
Any Homogeneous can compose with any other Homogeneous.

h_matrix
The homogeneous matrix defining this transform.
Type `(n_dims + 1, n_dims + 1)` *ndarray*

h_matrix_is_mutable
`h_matrix` is not mutable.
Type `False`

has_true_inverse
The pseudoinverse is an exact inverse.
Type `True`

linear_component
The linear component of this affine transform.
Type `(n_dims, n_dims)` *ndarray*

n_dims
The dimensionality of the data the transform operates on.
Type *int*

n_dims_output
The output of the data from the transform.
Type *int*

n_parameters
The number of parameters: 1
Type *int*

scale
The single scale value.
Type *float*

translation_component
The translation component of this affine transform.
Type `(n_dims,)` *ndarray*

NonUniformScale

class `menpo.transform.`**`NonUniformScale`**(*scale*, *skip_checks=False*)
Bases: *`DiscreteAffine`*, `Affine`

An `n_dims` scale transform, with a scale component for each dimension.
Parameters
- **scale** (`(n_dims,)` *ndarray*) – A scale for each axis.
- **skip_checks** (*bool*, optional) – If `True` avoid sanity checks on `h_matrix` for performance.

apply(*x*, *batch_size=None*, ***kwargs*)
Applies this transform to `x`.

If `x` is `Transformable`, `x` will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, `x` is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any `kwargs` will be passed to the specific transform `_apply()` method.
Parameters

- **x** (`Transformable` or `(n_points, n_dims)` *ndarray*) – The array or object to be transformed.
- **batch_size** (*int*, optional) – If not `None`, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returns **transformed** (`type(x)`) – The transformed object or array

apply_inplace(*x*, ***kwargs*)

Applies this transform to a `Transformable` `x` destructively.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters

- **x** (`Transformable`) – The `Transformable` object to be transformed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returns **transformed** (`type(x)`) – The transformed object

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returns **vector** (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

compose_after(*transform*)

A *Transform* that represents **this** transform composed **after** the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

`a` and `b` are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, `o`.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameters **transform** (*Transform*) – Transform to be applied **before** `self`

Returns **transform** (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_after_inplace(*transform*)

Update `self` so that it represents **this** transform composed **after** the given transform:

```
a_orig = a.copy()
a.compose_after_inplace(b)
a.apply(p) == a_orig.apply(b.apply(p))
```

`a` is permanently altered to be the result of the composition. `b` is left unchanged.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **before** `self`

Raises `ValueError` – If `transform` isn't an instance of *composes_inplace_with*

compose_before(*transform*)

A *Transform* that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

a and b are left unchanged.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameters **transform** (*Transform*) – Transform to be applied **after** self

Returns **transform** (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_before_inplace(*transform*)

Update self so that it represents **this** transform composed **before** the given transform:

```
a_orig = a.copy()
a.compose_before_inplace(b)
a.apply(p) == b.apply(a_orig.apply(p))
```

a is permanently altered to be the result of the composition. b is left unchanged.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **after** self

Raises ValueError – If transform isn't an instance of *composes_inplace_with*

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns type(self) – A copy of this object

decompose()

A DiscreteAffine is already maximally decomposed - return a copy of self in a *list*.

Returns **transform** (DiscreteAffine) – Deep copy of *self*.

from_vector(*vector*)

Build a new instance of the object from its vectorized state.

self is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is a deepcopy of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parameters **vector** ((n_parameters,) *ndarray*) – Flattened representation of the object.

Returns **transform** (*Homogeneous*) – An new instance of this class.

from_vector_inplace(*vector*)

Updates the *NonUniformScale* inplace.

Parameters **vector** ((n_dims,) *ndarray*) – The array of parameters.

has_nan_values()

Tests if the vectorized form of the object contains nan values or not. This is particularly useful for objects with unknown values that have been mapped to nan values.

Returns **has_nan_values** (*bool*) – If the vectorized object contains nan values.

classmethod init_identity(*n_dims*)

Creates an identity transform.

Parameters **n_dims** (*int*) – The number of dimensions.

Returns **identity** (*NonUniformScale*) – The identity matrix transform.

pseudoinverse()

The inverse scale matrix.

Type *NonUniformScale*

pseudoinverse_vector(*vector*)

The vectorized pseudoinverse of a provided vector instance. Syntactic sugar for:

```
self.from_vector(vector).pseudoinverse().as_vector()
```

Can be much faster than the explict call as object creation can be entirely avoided in some cases.

Parameters **vector** ((n_parameters,) *ndarray*) – A vectorized version of `self`

Returns **pseudoinverse_vector** ((n_parameters,) *ndarray*) – The pseudoinverse of the vector provided

set_h_matrix(*value*, *copy=True*, *skip_checks=False*)

Updates `h_matrix`, optionally performing sanity checks.

Note that it won't always be possible to manually specify the `h_matrix` through this method, specifically if changing the `h_matrix` could change the nature of the transform. See *h_matrix_is_mutable* for how you can discover if the `h_matrix` is allowed to be set for a given class.

Parameters

- **value** (*ndarray*) – The new homogeneous matrix to set.
- **copy** (*bool*, optional) – If `False`, do not copy the h_matrix. Useful for performance.
- **skip_checks** (*bool*, optional) – If `True`, skip checking. Useful for performance.

Raises `NotImplementedError` – If *h_matrix_is_mutable* returns `False`.

composes_inplace_with

NonUniformScale can swallow composition with any other *NonUniformScale* and *UniformScale*.

composes_with

Any Homogeneous can compose with any other Homogeneous.

h_matrix

The homogeneous matrix defining this transform.

Type `(n_dims + 1, n_dims + 1)` *ndarray*

h_matrix_is_mutable

`h_matrix` is not mutable.

Type `False`

has_true_inverse

The pseudoinverse is an exact inverse.

Type `True`

linear_component

The linear component of this affine transform.

Type `(n_dims, n_dims)` *ndarray*

n_dims

The dimensionality of the data the transform operates on.

Type *int*

n_dims_output

The output of the data from the transform.

Type *int*

n_parameters
The number of parameters: `n_dims`. They have the form `[scale_x, scale_y, ....]` representing the scale across each axis.
Type *list* of *int*

scale
The scale vector.
Type `(n_dims,)` *ndarray*

translation_component
The translation component of this affine transform.
Type `(n_dims,)` *ndarray*

2.9.2 Alignments

ThinPlateSplines

class `menpo.transform.`**`ThinPlateSplines`**(*source*, *target*, *kernel=None*, *min_singular_val=0.0001*)
Bases: `Alignment`, `Transform`, `Invertible`

The thin plate splines (TPS) alignment between 2D *source* and *target* landmarks.

`kernel` can be used to specify an alternative kernel function. If `None` is supplied, the `R2LogR2RBF` kernel will be used.
Parameters
- **source** (`(N, 2)` *ndarray*) – The source points to apply the tps from
- **target** (`(N, 2)` *ndarray*) – The target points to apply the tps to
- **kernel** (`RadialBasisFunction`, optional) – The kernel to apply.
- **min_singular_val** (*float*, optional) – If the target has points that are nearly coincident, the coefficients matrix is rank deficient, and therefore not invertible. Therefore, we only take the inverse on the full-rank matrix and drop any singular values that are less than this value (close to zero).

Raises `ValueError` – TPS is only with on 2-dimensional data

aligned_source()
The result of applying `self` to `source`
Type `PointCloud`

alignment_error()
The Frobenius Norm of the difference between the target and the aligned source.
Type *float*

apply(*x*, *batch_size=None*, ***kwargs*)
Applies this transform to `x`.

If `x` is `Transformable`, `x` will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, `x` is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any `kwargs` will be passed to the specific transform `_apply()` method.
Parameters
- **x** (`Transformable` or `(n_points, n_dims)` *ndarray*) – The array or object to be transformed.
- **batch_size** (*int*, optional) – If not `None`, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.

- **kwargs** (*dict*) – Passed through to `_apply()`.

Returnstransformed (`type(x)`) – The transformed object or array

apply_inplace(*x*, ***kwargs*)

Applies this transform to a `Transformable` `x` destructively.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters

- **x** (`Transformable`) – The `Transformable` object to be transformed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returnstransformed (`type(x)`) – The transformed object

compose_after(*transform*)

Returns a *`TransformChain`* that represents **this** transform composed **after** the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

`a` and `b` are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, *o*.

Parameterstransform (*`Transform`*) – Transform to be applied **before** self

Returnstransform (*`TransformChain`*) – The resulting transform chain.

compose_before(*transform*)

Returns a *`TransformChain`* that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

`a` and `b` are left unchanged.

Parameterstransform (*`Transform`*) – Transform to be applied **after** self

Returnstransform (*`TransformChain`*) – The resulting transform chain.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *`Copyable`* objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns`type(self)` – A copy of this object

pseudoinverse()

The pseudoinverse of the transform - that is, the transform that results from swapping *source* and *target*, or more formally, negating the transforms parameters. If the transform has a true inverse this is returned instead.

Type`type(self)`

set_target(*new_target*)

Update this object so that it attempts to recreate the `new_target`.

Parametersnew_target (*`PointCloud`*) – The new target that this object should try and regenerate.

has_true_inverse

Type`False`

n_dims

The number of dimensions of the *`target`*.

Type*int*

n_dims_output
The output of the data from the transform.

`None` if the output of the transform is not dimension specific.
Type*int* or `None`

n_points
The number of points on the *target*.
Type*int*

source
The source *PointCloud* that is used in the alignment.

The source is not mutable.
Type*PointCloud*

target
The current *PointCloud* that this object produces.

To change the target, use *set_target()*.
Type*PointCloud*

PiecewiseAffine

menpo.transform.**PiecewiseAffine**
alias of `CachedPWA`

AlignmentAffine

class menpo.transform.**AlignmentAffine**(*source*, *target*)
Bases: `HomogFamilyAlignment`, `Affine`

Constructs an *Affine* by finding the optimal affine transform to align *source* to *target*.
Parameters
- **source** (*PointCloud*) – The source pointcloud instance used in the alignment
- **target** (*PointCloud*) – The target pointcloud instance used in the alignment

Notes

We want to find the optimal transform M which satisfies $Ma = b$ where a and b are the *source* and *target* homogeneous vectors respectively.

```
(M a)' = b'
a' M' = b'
a a' M' = a b'
```

a a' is of shape *(n_dim + 1, n_dim + 1)* and so can be inverted to solve for *M*.

This approach is the analytical linear least squares solution to the problem at hand. It will have a solution as long as *(a a')* is non-singular, which generally means at least 2 corresponding points are required.

aligned_source()
The result of applying `self` to *source*
Type*PointCloud*

alignment_error()
The Frobenius Norm of the difference between the target and the aligned source.

Type*float*

apply (*x*, *batch_size=None*, ***kwargs*)

Applies this transform to `x`.

If `x` is `Transformable`, `x` will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, `x` is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters

- **x** (`Transformable` or `(n_points, n_dims)` *ndarray*) – The array or object to be transformed.
- **batch_size** (*int*, optional) – If not `None`, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returnstransformed (`type(x)`) – The transformed object or array

apply_inplace (*x*, ***kwargs*)

Applies this transform to a `Transformable` `x` destructively.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters

- **x** (`Transformable`) – The `Transformable` object to be transformed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returnstransformed (`type(x)`) – The transformed object

as_non_alignment ()

Returns a copy of this *Affine* without its alignment nature.

Returnstransform (*Affine*) – A version of this affine with the same transform behavior but without the alignment logic.

as_vector (***kwargs*)

Returns a flattened representation of the object as a single vector.

Returnsvector (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

compose_after (*transform*)

A *Transform* that represents **this** transform composed **after** the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

`a` and `b` are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, `o`.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameterstransform (*Transform*) – Transform to be applied **before** `self`

Returnstransform (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_after_inplace (*transform*)

Update `self` so that it represents **this** transform composed **after** the given transform:

```
a_orig = a.copy()
a.compose_after_inplace(b)
a.apply(p) == a_orig.apply(b.apply(p))
```

a is permanently altered to be the result of the composition. b is left unchanged.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **before** self

Raises ValueError – If transform isn't an instance of *composes_inplace_with*

compose_before(*transform*)

A *Transform* that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

a and b are left unchanged.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameters **transform** (*Transform*) – Transform to be applied **after** self

Returns **transform** (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_before_inplace(*transform*)

Update self so that it represents **this** transform composed **before** the given transform:

```
a_orig = a.copy()
a.compose_before_inplace(b)
a.apply(p) == b.apply(a_orig.apply(p))
```

a is permanently altered to be the result of the composition. b is left unchanged.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **after** self

Raises ValueError – If transform isn't an instance of *composes_inplace_with*

copy()

Generate an efficient copy of this HomogFamilyAlignment.

Returns **new_transform** (type(self)) – A copy of this object

decompose()

Decompose this transform into discrete Affine Transforms.

Useful for understanding the effect of a complex composite transform.

Returns

transforms (*list* of DiscreteAffine) – Equivalent to this affine transform, such that:

```
reduce(lambda x,y: x.chain(y), self.decompose()) == self
```

from_vector(*vector*)

Build a new instance of the object from its vectorized state.

self is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is a deepcopy of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parameters`vector` ((`n_parameters,`) *ndarray*) – Flattened representation of the object.

Returns`transform` (`Homogeneous`) – An new instance of this class.

from_vector_inplace(*p*)

Updates this Affine in-place from the new parameters. See from_vector for details of the parameter format

has_nan_values()

Tests if the vectorized form of the object contains `nan` values or not. This is particularly useful for objects with unknown values that have been mapped to `nan` values.

Returns`has_nan_values` (*bool*) – If the vectorized object contains `nan` values.

init_identity(*n_dims*)

Creates an identity matrix Affine transform.

Parameters`n_dims` (*int*) – The number of dimensions.

Returns`identity` (`Affine`) – The identity matrix transform.

pseudoinverse()

The pseudoinverse of the transform - that is, the transform that results from swapping source and target, or more formally, negating the transforms parameters. If the transform has a true inverse this is returned instead.

Returns`transform` (`type(self)`) – The inverse of this transform.

pseudoinverse_vector(*vector*)

The vectorized pseudoinverse of a provided vector instance. Syntactic sugar for:

```
self.from_vector(vector).pseudoinverse().as_vector()
```

Can be much faster than the explict call as object creation can be entirely avoided in some cases.

Parameters`vector` ((`n_parameters,`) *ndarray*) – A vectorized version of `self`

Returns`pseudoinverse_vector` ((`n_parameters,`) *ndarray*) – The pseudoinverse of the vector provided

set_h_matrix(*value*, *copy=True*, *skip_checks=False*)

Updates `h_matrix`, optionally performing sanity checks.

Note: Updating the `h_matrix` on an `AlignmentAffine` triggers a sync of the target.

Note that it won't always be possible to manually specify the `h_matrix` through this method, specifically if changing the `h_matrix` could change the nature of the transform. See `h_matrix_is_mutable` for how you can discover if the `h_matrix` is allowed to be set for a given class.

Parameters

- **value** (*ndarray*) – The new homogeneous matrix to set
- **copy** (*bool*, optional) – If `False` do not copy the h_matrix. Useful for performance.
- **skip_checks** (*bool*, optional) – If `True` skip checking. Useful for performance.

Raises`NotImplementedError` – If `h_matrix_is_mutable` returns `False`.

set_target(*new_target*)

Update this object so that it attempts to recreate the `new_target`.

Parameters`new_target` (`PointCloud`) – The new target that this object should try and regenerate.

composes_inplace_with

`Affine` can swallow composition with any other `Affine`.

composes_with
Any Homogeneous can compose with any other Homogeneous.

h_matrix
The homogeneous matrix defining this transform.
Type `(n_dims + 1, n_dims + 1)` *ndarray*

h_matrix_is_mutable
`True` iff *`set_h_matrix()`* is permitted on this type of transform.

If this returns `False` calls to *`set_h_matrix()`* will raise a `NotImplementedError`.
Type*bool*

has_true_inverse
The pseudoinverse is an exact inverse.
Type`True`

linear_component
The linear component of this affine transform.
Type `(n_dims, n_dims)` *ndarray*

n_dims
The number of dimensions of the *`target`*.
Type*int*

n_dims_output
The output of the data from the transform.
Type*int*

n_parameters
`n_dims * (n_dims + 1)` parameters - every element of the matrix but the homogeneous part.
Typeint

Examples

2D Affine: 6 parameters:

```
[p1, p3, p5]
[p2, p4, p6]
```

3D Affine: 12 parameters:

```
[p1, p4, p7, p10]
[p2, p5, p8, p11]
[p3, p6, p9, p12]
```

---

n_points
The number of points on the *`target`*.
Type*int*

source
The source *`PointCloud`* that is used in the alignment.

The source is not mutable.
Type*`PointCloud`*

target
The current *`PointCloud`* that this object produces.

To change the target, use *`set_target()`*.
Type*`PointCloud`*

translation_component
The translation component of this affine transform.
Type (n_dims,) *ndarray*

AlignmentSimilarity

class menpo.transform.**AlignmentSimilarity**(*source*, *target*, *rotation=True*)
Bases: HomogFamilyAlignment, Similarity

Infers the similarity transform relating two vectors with the same dimensionality. This is simply the procrustes alignment of the *source* to the *target*.

Parameters
- **source** (*PointCloud*) – The source pointcloud instance used in the alignment
- **target** (*PointCloud*) – The target pointcloud instance used in the alignment
- **rotation** (*bool*, optional) – If False, the rotation component of the similarity transform is not inferred.

aligned_source()
The result of applying self to *source*
Type*PointCloud*

alignment_error()
The Frobenius Norm of the difference between the target and the aligned source.
Type*float*

apply(*x*, *batch_size=None*, ***kwargs*)
Applies this transform to x.

If x is Transformable, x will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, x is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any kwargs will be passed to the specific transform _apply() method.

Parameters
- **x** (Transformable or (n_points, n_dims) *ndarray*) – The array or object to be transformed.
- **batch_size** (*int*, optional) – If not None, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.
- **kwargs** (*dict*) – Passed through to _apply().

Returnstransformed (type(x)) – The transformed object or array

apply_inplace(*x*, ***kwargs*)
Applies this transform to a Transformable x destructively.

Any kwargs will be passed to the specific transform _apply() method.

Parameters
- **x** (Transformable) – The Transformable object to be transformed.
- **kwargs** (*dict*) – Passed through to _apply().

Returnstransformed (type(x)) – The transformed object

as_non_alignment()
Returns a copy of this similarity without it's alignment nature.
Returnstransform (*Similarity*) – A version of this similarity with the same transform behavior but without the alignment logic.

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returns **vector** (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

compose_after(*transform*)

A `Transform` that represents **this** transform composed **after** the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

`a` and `b` are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, `o`.

An attempt is made to perform native composition, but will fall back to a `TransformChain` as a last resort. See `composes_with` for a description of how the mode of composition is decided.

Parameters **transform** (`Transform`) – Transform to be applied **before** `self`

Returns **transform** (`Transform` or `TransformChain`) – If the composition was native, a single new `Transform` will be returned. If not, a `TransformChain` is returned instead.

compose_after_inplace(*transform*)

Update `self` so that it represents **this** transform composed **after** the given transform:

```
a_orig = a.copy()
a.compose_after_inplace(b)
a.apply(p) == a_orig.apply(b.apply(p))
```

`a` is permanently altered to be the result of the composition. `b` is left unchanged.

Parameters **transform** (`composes_inplace_with`) – Transform to be applied **before** `self`

Raises `ValueError` – If `transform` isn't an instance of `composes_inplace_with`

compose_before(*transform*)

A `Transform` that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

`a` and `b` are left unchanged.

An attempt is made to perform native composition, but will fall back to a `TransformChain` as a last resort. See `composes_with` for a description of how the mode of composition is decided.

Parameters **transform** (`Transform`) – Transform to be applied **after** `self`

Returns **transform** (`Transform` or `TransformChain`) – If the composition was native, a single new `Transform` will be returned. If not, a `TransformChain` is returned instead.

compose_before_inplace(*transform*)

Update `self` so that it represents **this** transform composed **before** the given transform:

```
a_orig = a.copy()
a.compose_before_inplace(b)
a.apply(p) == b.apply(a_orig.apply(p))
```

`a` is permanently altered to be the result of the composition. `b` is left unchanged.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **after** `self`

Raises `ValueError` – If `transform` isn't an instance of *composes_inplace_with*

copy()

Generate an efficient copy of this `HomogFamilyAlignment`.

Returns **new_transform** (`type(self)`) – A copy of this object

decompose()

Decompose this transform into discrete Affine Transforms.

Useful for understanding the effect of a complex composite transform.

Returns

transforms (*list* of `DiscreteAffine`) – Equivalent to this affine transform, such that:

```
reduce(lambda x,y: x.chain(y), self.decompose()) == self
```

from_vector(*vector*)

Build a new instance of the object from its vectorized state.

`self` is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is a `deepcopy` of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parameters **vector** (`(n_parameters,)` *ndarray*) – Flattened representation of the object.

Returns **transform** (*Homogeneous*) – An new instance of this class.

from_vector_inplace(*p*)

Returns an instance of the transform from the given parameters, expected to be in Fortran ordering.

Supports rebuilding from 2D parameter sets.

2D Similarity: 4 parameters:

```
[a, b, tx, ty]
```

Parameters **p** (`(P,)` *ndarray*) – The array of parameters.

Raises **DimensionalityError, NotImplementedError** – Only 2D transforms are supported.

has_nan_values()

Tests if the vectorized form of the object contains `nan` values or not. This is particularly useful for objects with unknown values that have been mapped to `nan` values.

Returns **has_nan_values** (*bool*) – If the vectorized object contains `nan` values.

init_identity(*n_dims*)

Creates an identity transform.

Parameters **n_dims** (*int*) – The number of dimensions.

Returns **identity** (*Similarity*) – The identity matrix transform.

pseudoinverse()

The pseudoinverse of the transform - that is, the transform that results from swapping source and target, or more formally, negating the transforms parameters. If the transform has a true inverse this is returned instead.

Returns **transform** (`type(self)`) – The inverse of this transform.

pseudoinverse_vector(*vector*)

The vectorized pseudoinverse of a provided vector instance. Syntactic sugar for:

```
        self.from_vector(vector).pseudoinverse().as_vector()
```

Can be much faster than the explict call as object creation can be entirely avoided in some cases.

Parameters
vector ((n_parameters,) *ndarray*) – A vectorized version of `self`

Returns
pseudoinverse_vector ((n_parameters,) *ndarray*) – The pseudoinverse of the vector provided

set_h_matrix(*value*, *copy=True*, *skip_checks=False*)

Updates `h_matrix`, optionally performing sanity checks.

Note that it won't always be possible to manually specify the `h_matrix` through this method, specifically if changing the `h_matrix` could change the nature of the transform. See *h_matrix_is_mutable* for how you can discover if the `h_matrix` is allowed to be set for a given class.

Parameters
- **value** (*ndarray*) – The new homogeneous matrix to set.
- **copy** (*bool*, optional) – If `False`, do not copy the h_matrix. Useful for performance.
- **skip_checks** (*bool*, optional) – If `True`, skip checking. Useful for performance.

Raises `NotImplementedError` – If *h_matrix_is_mutable* returns `False`.

set_target(*new_target*)

Update this object so that it attempts to recreate the `new_target`.

Parameters
new_target (*PointCloud*) – The new target that this object should try and regenerate.

composes_inplace_with

Affine can swallow composition with any other *Affine*.

composes_with

Any Homogeneous can compose with any other Homogeneous.

h_matrix

The homogeneous matrix defining this transform.

Type `(n_dims + 1, n_dims + 1)` *ndarray*

h_matrix_is_mutable

`h_matrix` is not mutable.

Type `False`

has_true_inverse

The pseudoinverse is an exact inverse.

Type `True`

linear_component

The linear component of this affine transform.

Type `(n_dims, n_dims)` *ndarray*

n_dims

The number of dimensions of the *target*.

Type *int*

n_dims_output

The output of the data from the transform.

Type *int*

n_parameters

2D Similarity: 4 parameters:

```
[(1 + a), -b,      tx]
[b,       (1 + a), ty]
```

3D Similarity: Currently not supported

Returnsn_parameters (*int*) – The transform parameters

RaisesDimensionalityError, NotImplementedError – Only 2D transforms are supported.

n_points

The number of points on the `target`.

Type*int*

source

The source `PointCloud` that is used in the alignment.

The source is not mutable.

Type*PointCloud*

target

The current `PointCloud` that this object produces.

To change the target, use `set_target()`.

Type*PointCloud*

translation_component

The translation component of this affine transform.

Type `(n_dims,)` *ndarray*

AlignmentRotation

class `menpo.transform.`**`AlignmentRotation`**(*source*, *target*)

Bases: `HomogFamilyAlignment`, `Rotation`

Constructs an `Rotation` by finding the optimal rotation transform to align *source* to *target*.

Parameters

- **source** (`PointCloud`) – The source pointcloud instance used in the alignment
- **target** (`PointCloud`) – The target pointcloud instance used in the alignment

aligned_source()

The result of applying `self` to `source`

Type*PointCloud*

alignment_error()

The Frobenius Norm of the difference between the target and the aligned source.

Type*float*

apply(*x*, *batch_size=None*, ***kwargs*)

Applies this transform to `x`.

If `x` is `Transformable`, `x` will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, `x` is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters

- **x** (`Transformable` or `(n_points, n_dims)` *ndarray*) – The array or object to be transformed.

- **batch_size** (*int*, optional) – If not `None`, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returnstransformed (`type(x)`) – The transformed object or array

apply_inplace(*x*, ***kwargs*)

Applies this transform to a `Transformable` `x` destructively.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters

- **x** (`Transformable`) – The `Transformable` object to be transformed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returnstransformed (`type(x)`) – The transformed object

as_non_alignment()

Returns a copy of this rotation without its alignment nature.

Returnstransform (`Rotation`) – A version of this rotation with the same transform behavior but without the alignment logic.

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returnsvector (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

axis_and_angle_of_rotation()

Abstract method for computing the axis and angle of rotation.

Returns

- **axis** (`(n_dims,)` *ndarray*) – The unit vector representing the axis of rotation
- **angle_of_rotation** (*float*) – The angle in radians of the rotation about the axis. The angle is signed in a right handed sense.

compose_after(*transform*)

A *`Transform`* that represents **this** transform composed **after** the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

`a` and `b` are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, `o`.

An attempt is made to perform native composition, but will fall back to a *`TransformChain`* as a last resort. See *`composes_with`* for a description of how the mode of composition is decided.

Parameterstransform (*`Transform`*) – Transform to be applied **before** `self`

Returnstransform (*`Transform`* or *`TransformChain`*) – If the composition was native, a single new *`Transform`* will be returned. If not, a *`TransformChain`* is returned instead.

compose_after_inplace(*transform*)

Update `self` so that it represents **this** transform composed **after** the given transform:

```
a_orig = a.copy()
a.compose_after_inplace(b)
a.apply(p) == a_orig.apply(b.apply(p))
```

`a` is permanently altered to be the result of the composition. `b` is left unchanged.

Parameterstransform (*`composes_inplace_with`*) – Transform to be applied **before** `self`

Raises `ValueError` – If `transform` isn't an instance of *composes_inplace_with*

compose_before(*transform*)

A *Transform* that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

`a` and `b` are left unchanged.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameters **transform** (*Transform*) – Transform to be applied **after** `self`

Returns **transform** (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_before_inplace(*transform*)

Update `self` so that it represents **this** transform composed **before** the given transform:

```
a_orig = a.copy()
a.compose_before_inplace(b)
a.apply(p) == b.apply(a_orig.apply(p))
```

`a` is permanently altered to be the result of the composition. `b` is left unchanged.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **after** `self`

Raises `ValueError` – If `transform` isn't an instance of *composes_inplace_with*

copy()

Generate an efficient copy of this `HomogFamilyAlignment`.

Returns **new_transform** (`type(self)`) – A copy of this object

decompose()

A `DiscreteAffine` is already maximally decomposed - return a copy of self in a *list*.

Returns **transform** (`DiscreteAffine`) – Deep copy of *self*.

from_vector(*vector*)

Build a new instance of the object from its vectorized state.

`self` is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is a `deepcopy` of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parameters **vector** (`(n_parameters,)` *ndarray*) – Flattened representation of the object.

Returns **transform** (*Homogeneous*) – An new instance of this class.

from_vector_inplace(*p*)

Returns an instance of the transform from the given parameters, expected to be in Fortran ordering.

Supports rebuilding from 2D parameter sets.

2D Rotation: 1 parameter:

```
[theta]
```

Parameters **p** (`(1,)` *ndarray*) – The array of parameters.

Returns **transform** (*Rotation*) – The transform initialised to the given parameters.

has_nan_values()

Tests if the vectorized form of the object contains `nan` values or not. This is particularly useful for objects with unknown values that have been mapped to `nan` values.

Returnshas_nan_values (*bool*) – If the vectorized object contains `nan` values.

init_from_2d_ccw_angle(*theta*, *degrees=True*)

Convenience constructor for 2D CCW rotations about the origin.

Parameters

- **theta** (*float*) – The angle of rotation about the origin
- **degrees** (*bool*, optional) – If `True` theta is interpreted as a degree. If `False`, theta is interpreted as radians.

Returnsrotation (`Rotation`) – A 2D rotation transform.

init_identity(*n_dims*)

Creates an identity transform.

Parametersn_dims (*int*) – The number of dimensions.

Returnsidentity (*Rotation*) – The identity matrix transform.

pseudoinverse()

The pseudoinverse of the transform - that is, the transform that results from swapping source and target, or more formally, negating the transforms parameters. If the transform has a true inverse this is returned instead.

Returnstransform (`type(self)`) – The inverse of this transform.

pseudoinverse_vector(*vector*)

The vectorized pseudoinverse of a provided vector instance. Syntactic sugar for:

```
self.from_vector(vector).pseudoinverse().as_vector()
```

Can be much faster than the explict call as object creation can be entirely avoided in some cases.

Parametersvector (`(n_parameters,)` *ndarray*) – A vectorized version of `self`

Returnspseudoinverse_vector (`(n_parameters,)` *ndarray*) – The pseudoinverse of the vector provided

set_h_matrix(*value*, *copy=True*, *skip_checks=False*)

Updates `h_matrix`, optionally performing sanity checks.

Note that it won't always be possible to manually specify the `h_matrix` through this method, specifically if changing the `h_matrix` could change the nature of the transform. See *h_matrix_is_mutable* for how you can discover if the `h_matrix` is allowed to be set for a given class.

Parameters

- **value** (*ndarray*) – The new homogeneous matrix to set.
- **copy** (*bool*, optional) – If `False`, do not copy the h_matrix. Useful for performance.
- **skip_checks** (*bool*, optional) – If `True`, skip checking. Useful for performance.

Raises`NotImplementedError` – If *h_matrix_is_mutable* returns `False`.

set_rotation_matrix(*value*, *skip_checks=False*)

Sets the rotation matrix.

Parameters

- **value** (`(n_dims, n_dims)` *ndarray*) – The new rotation matrix.
- **skip_checks** (*bool*, optional) – If `True` avoid sanity checks on `value` for performance.

set_target(*new_target*)

Update this object so that it attempts to recreate the `new_target`.

Parameters **new_target** (*PointCloud*) – The new target that this object should try and regenerate.

composes_inplace_with
Rotation can swallow composition with any other *Rotation*.

composes_with
Any Homogeneous can compose with any other Homogeneous.

h_matrix
The homogeneous matrix defining this transform.
Type `(n_dims + 1, n_dims + 1)` *ndarray*

h_matrix_is_mutable
`h_matrix` is not mutable.
Type `False`

has_true_inverse
The pseudoinverse is an exact inverse.
Type `True`

linear_component
The linear component of this affine transform.
Type `(n_dims, n_dims)` *ndarray*

n_dims
The number of dimensions of the *target*.
Type *int*

n_dims_output
The output of the data from the transform.
Type *int*

n_points
The number of points on the *target*.
Type *int*

rotation_matrix
The rotation matrix.
Type `(n_dims, n_dims)` *ndarray*

source
The source *PointCloud* that is used in the alignment.

The source is not mutable.
Type *PointCloud*

target
The current *PointCloud* that this object produces.

To change the target, use *set_target()*.
Type *PointCloud*

translation_component
The translation component of this affine transform.
Type `(n_dims,)` *ndarray*

AlignmentTranslation

class `menpo.transform.`**`AlignmentTranslation`**(*source*, *target*)
Bases: `HomogFamilyAlignment`, `Translation`

Constructs a `Translation` by finding the optimal translation transform to align *source* to *target*.

Parameters

- **source** (`PointCloud`) – The source pointcloud instance used in the alignment
- **target** (`PointCloud`) – The target pointcloud instance used in the alignment

aligned_source()

The result of applying `self` to `source`

Type `PointCloud`

alignment_error()

The Frobenius Norm of the difference between the target and the aligned source.

Type *float*

apply(*x*, *batch_size=None*, ***kwargs*)

Applies this transform to `x`.

If `x` is `Transformable`, `x` will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, `x` is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters

- **x** (`Transformable` or `(n_points, n_dims)` *ndarray*) – The array or object to be transformed.
- **batch_size** (*int*, optional) – If not `None`, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returns **transformed** (`type(x)`) – The transformed object or array

apply_inplace(*x*, ***kwargs*)

Applies this transform to a `Transformable` `x` destructively.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters

- **x** (`Transformable`) – The `Transformable` object to be transformed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returns **transformed** (`type(x)`) – The transformed object

as_non_alignment()

Returns a copy of this translation without its alignment nature.

Returns **transform** (`Translation`) – A version of this transform with the same transform behavior but without the alignment logic.

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returns **vector** (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

compose_after(*transform*)

A `Transform` that represents **this** transform composed **after** the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

`a` and `b` are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, `o`.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameters **transform** (*Transform*) – Transform to be applied **before** `self`

Returns **transform** (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_after_inplace(*transform*)

Update `self` so that it represents **this** transform composed **after** the given transform:

```
a_orig = a.copy()
a.compose_after_inplace(b)
a.apply(p) == a_orig.apply(b.apply(p))
```

`a` is permanently altered to be the result of the composition. `b` is left unchanged.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **before** `self`

Raises `ValueError` – If `transform` isn't an instance of *composes_inplace_with*

compose_before(*transform*)

A *Transform* that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

`a` and `b` are left unchanged.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameters **transform** (*Transform*) – Transform to be applied **after** `self`

Returns **transform** (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_before_inplace(*transform*)

Update `self` so that it represents **this** transform composed **before** the given transform:

```
a_orig = a.copy()
a.compose_before_inplace(b)
a.apply(p) == b.apply(a_orig.apply(p))
```

`a` is permanently altered to be the result of the composition. `b` is left unchanged.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **after** `self`

Raises `ValueError` – If `transform` isn't an instance of *composes_inplace_with*

copy()

Generate an efficient copy of this `HomogFamilyAlignment`.

Returns **new_transform** (`type(self)`) – A copy of this object

decompose()

A `DiscreteAffine` is already maximally decomposed - return a copy of self in a *list*.

Returns **transform** (`DiscreteAffine`) – Deep copy of *self*.

from_vector(*vector*)

Build a new instance of the object from its vectorized state.

`self` is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is a `deepcopy` of the object followed by a call to *`from_vector_inplace()`*. This method can be overridden for a performance benefit if desired.

Parameters
vector (`(n_parameters,)` *ndarray*) – Flattened representation of the object.

Returns
transform (*`Homogeneous`*) – An new instance of this class.

`from_vector_inplace`(*p*)

Updates the *`Translation`* inplace.

Parameters
vector (`(n_dims,)` *ndarray*) – The array of parameters.

`has_nan_values`()

Tests if the vectorized form of the object contains `nan` values or not. This is particularly useful for objects with unknown values that have been mapped to `nan` values.

Returns
has_nan_values (*bool*) – If the vectorized object contains `nan` values.

`init_identity`(*n_dims*)

Creates an identity transform.

Parameters
n_dims (*int*) – The number of dimensions.

Returns
identity (*`Translation`*) – The identity matrix transform.

`pseudoinverse`()

The pseudoinverse of the transform - that is, the transform that results from swapping source and target, or more formally, negating the transforms parameters. If the transform has a true inverse this is returned instead.

Returns
transform (`type(self)`) – The inverse of this transform.

`pseudoinverse_vector`(*vector*)

The vectorized pseudoinverse of a provided vector instance. Syntactic sugar for:

```
self.from_vector(vector).pseudoinverse().as_vector()
```

Can be much faster than the explict call as object creation can be entirely avoided in some cases.

Parameters
vector (`(n_parameters,)` *ndarray*) – A vectorized version of `self`

Returns
pseudoinverse_vector (`(n_parameters,)` *ndarray*) – The pseudoinverse of the vector provided

`set_h_matrix`(*value*, *copy=True*, *skip_checks=False*)

Updates `h_matrix`, optionally performing sanity checks.

Note that it won't always be possible to manually specify the `h_matrix` through this method, specifically if changing the `h_matrix` could change the nature of the transform. See *`h_matrix_is_mutable`* for how you can discover if the `h_matrix` is allowed to be set for a given class.

Parameters
- **value** (*ndarray*) – The new homogeneous matrix to set.
- **copy** (*bool*, optional) – If `False`, do not copy the h_matrix. Useful for performance.
- **skip_checks** (*bool*, optional) – If `True`, skip checking. Useful for performance.

Raises
`NotImplementedError` – If *`h_matrix_is_mutable`* returns `False`.

`set_target`(*new_target*)

Update this object so that it attempts to recreate the `new_target`.

Parameters
new_target (*`PointCloud`*) – The new target that this object should try and regenerate.

`composes_inplace_with`

`Affine` can swallow composition with any other *`Affine`*.

composes_with
Any Homogeneous can compose with any other Homogeneous.

h_matrix
The homogeneous matrix defining this transform.
Type `(n_dims + 1, n_dims + 1)` *ndarray*

h_matrix_is_mutable
`h_matrix` is not mutable.
Type `False`

has_true_inverse
The pseudoinverse is an exact inverse.
Type `True`

linear_component
The linear component of this affine transform.
Type `(n_dims, n_dims)` *ndarray*

n_dims
The number of dimensions of the `target`.
Type *int*

n_dims_output
The output of the data from the transform.
Type *int*

n_parameters
The number of parameters: `n_dims`
Type *int*

n_points
The number of points on the `target`.
Type *int*

source
The source `PointCloud` that is used in the alignment.

The source is not mutable.
Type `PointCloud`

target
The current `PointCloud` that this object produces.

To change the target, use `set_target()`.
Type `PointCloud`

translation_component
The translation component of this affine transform.
Type `(n_dims,)` *ndarray*

AlignmentUniformScale

class `menpo.transform.`**`AlignmentUniformScale`**(*source*, *target*)
Bases: `HomogFamilyAlignment`, `UniformScale`

Constructs a `UniformScale` by finding the optimal scale transform to align *source* to *target*.
Parameters
- **source** (`PointCloud`) – The source pointcloud instance used in the alignment
- **target** (`PointCloud`) – The target pointcloud instance used in the alignment

aligned_source()

The result of applying `self` to *source*

Type*PointCloud*

alignment_error()

The Frobenius Norm of the difference between the target and the aligned source.

Type*float*

apply(*x*, *batch_size=None*, ***kwargs*)

Applies this transform to `x`.

If `x` is `Transformable`, `x` will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, `x` is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters

- **x** (`Transformable` or `(n_points, n_dims)` *ndarray*) – The array or object to be transformed.
- **batch_size** (*int*, optional) – If not `None`, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returnstransformed (`type(x)`) – The transformed object or array

apply_inplace(*x*, ***kwargs*)

Applies this transform to a `Transformable` `x` destructively.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters

- **x** (`Transformable`) – The `Transformable` object to be transformed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returnstransformed (`type(x)`) – The transformed object

as_non_alignment()

Returns a copy of this uniform scale without it's alignment nature.

Returnstransform (`UniformScale`) – A version of this scale with the same transform behavior but without the alignment logic.

as_vector(***kwargs*)

Returns a flattened representation of the object as a single vector.

Returnsvector (*(N,) ndarray*) – The core representation of the object, flattened into a single vector. Note that this is always a view back on to the original object, but is not writable.

compose_after(*transform*)

A *Transform* that represents **this** transform composed **after** the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

`a` and `b` are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, `o`.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameterstransform (*Transform*) – Transform to be applied **before** `self`

Returnstransform (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_after_inplace(*transform*)

Update `self` so that it represents **this** transform composed **after** the given transform:

```
a_orig = a.copy()
a.compose_after_inplace(b)
a.apply(p) == a_orig.apply(b.apply(p))
```

`a` is permanently altered to be the result of the composition. `b` is left unchanged.

Parameterstransform (*composes_inplace_with*) – Transform to be applied **before** `self`

Raises`ValueError` – If `transform` isn't an instance of *composes_inplace_with*

compose_before(*transform*)

A *Transform* that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

`a` and `b` are left unchanged.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameterstransform (*Transform*) – Transform to be applied **after** `self`

Returnstransform (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_before_inplace(*transform*)

Update `self` so that it represents **this** transform composed **before** the given transform:

```
a_orig = a.copy()
a.compose_before_inplace(b)
a.apply(p) == b.apply(a_orig.apply(p))
```

`a` is permanently altered to be the result of the composition. `b` is left unchanged.

Parameterstransform (*composes_inplace_with*) – Transform to be applied **after** `self`

Raises`ValueError` – If `transform` isn't an instance of *composes_inplace_with*

copy()

Generate an efficient copy of this `HomogFamilyAlignment`.

Returnsnew_transform (`type(self)`) – A copy of this object

decompose()

A `DiscreteAffine` is already maximally decomposed - return a copy of self in a *list*.

Returnstransform (`DiscreteAffine`) – Deep copy of *self*.

from_vector(*vector*)

Build a new instance of the object from its vectorized state.

`self` is used to fill out the missing state required to rebuild a full object from it's standardized flattened state. This is the default implementation, which is a `deepcopy` of the object followed by a call to *from_vector_inplace()*. This method can be overridden for a performance benefit if desired.

Parametersvector (`(n_parameters,)` *ndarray*) – Flattened representation of the object.

Returnstransform (*Homogeneous*) – An new instance of this class.

from_vector_inplace(*p*)

Returns an instance of the transform from the given parameters, expected to be in Fortran ordering.

Parametersp (*float*) – The parameter

has_nan_values()

Tests if the vectorized form of the object contains `nan` values or not. This is particularly useful for objects with unknown values that have been mapped to `nan` values.

Returnshas_nan_values (*bool*) – If the vectorized object contains `nan` values.

init_identity(*n_dims*)

Creates an identity transform.

Parametersn_dims (*int*) – The number of dimensions.

Returnsidentity (*UniformScale*) – The identity matrix transform.

pseudoinverse()

The pseudoinverse of the transform - that is, the transform that results from swapping source and target, or more formally, negating the transforms parameters. If the transform has a true inverse this is returned instead.

Returnstransform (`type(self)`) – The inverse of this transform.

pseudoinverse_vector(*vector*)

The vectorized pseudoinverse of a provided vector instance. Syntactic sugar for:

```
self.from_vector(vector).pseudoinverse().as_vector()
```

Can be much faster than the explict call as object creation can be entirely avoided in some cases.

Parametersvector (`(n_parameters,)` *ndarray*) – A vectorized version of `self`

Returnspseudoinverse_vector (`(n_parameters,)` *ndarray*) – The pseudoinverse of the vector provided

set_h_matrix(*value*, *copy=True*, *skip_checks=False*)

Updates `h_matrix`, optionally performing sanity checks.

Note that it won't always be possible to manually specify the `h_matrix` through this method, specifically if changing the `h_matrix` could change the nature of the transform. See *h_matrix_is_mutable* for how you can discover if the `h_matrix` is allowed to be set for a given class.

Parameters

- **value** (*ndarray*) – The new homogeneous matrix to set.
- **copy** (*bool*, optional) – If `False`, do not copy the h_matrix. Useful for performance.
- **skip_checks** (*bool*, optional) – If `True`, skip checking. Useful for performance.

Raises`NotImplementedError` – If *h_matrix_is_mutable* returns `False`.

set_target(*new_target*)

Update this object so that it attempts to recreate the `new_target`.

Parametersnew_target (*PointCloud*) – The new target that this object should try and regenerate.

composes_inplace_with

UniformScale can swallow composition with any other *UniformScale*.

composes_with

Any Homogeneous can compose with any other Homogeneous.

h_matrix

The homogeneous matrix defining this transform.

Type `(n_dims + 1, n_dims + 1)` *ndarray*

h_matrix_is_mutable
`h_matrix` is not mutable.
Type `False`

has_true_inverse
The pseudoinverse is an exact inverse.
Type `True`

linear_component
The linear component of this affine transform.
Type `(n_dims, n_dims)` *ndarray*

n_dims
The number of dimensions of the `target`.
Type *int*

n_dims_output
The output of the data from the transform.
Type *int*

n_parameters
The number of parameters: 1
Type *int*

n_points
The number of points on the `target`.
Type *int*

scale
The single scale value.
Type *float*

source
The source `PointCloud` that is used in the alignment.

The source is not mutable.
Type `PointCloud`

target
The current `PointCloud` that this object produces.

To change the target, use `set_target()`.
Type `PointCloud`

translation_component
The translation component of this affine transform.
Type `(n_dims,)` *ndarray*

2.9.3 Group Alignments

GeneralizedProcrustesAnalysis

class `menpo.transform.`**`GeneralizedProcrustesAnalysis`**(*sources*, *target=None*)
Bases: `MultipleAlignment`

Class for aligning multiple source shapes between them.

After construction, the `AlignmentSimilarity` transforms used to map each *source* optimally to the *target* can be found at *transforms*.

Parameters

- **sources** (*list* of `PointCloud`) – List of pointclouds to be aligned.
- **target** (`PointCloud`, optional) – The target `PointCloud` to align each source to. If `None`, then the mean of the sources is used.

Raises `ValueError` – Need at least two sources to align

mean_aligned_shape()

Returns the mean of the aligned shapes.

Type `PointCloud`

mean_alignment_error()

Returns the average error of the recursive procrustes alignment.

Type *float*

2.9.4 Composite Transforms

TransformChain

class menpo.transform.**TransformChain**(*transforms*)

Bases: `ComposableTransform`

A chain of transforms that can be efficiently applied one after the other.

This class is the natural product of composition. Note that objects may know how to compose themselves more efficiently - such objects implement the `ComposableTransform` or `VComposable` interfaces.

Parameters **transforms** (*list* of `Transform`) – The *list* of transforms to be applied. Note that the first transform will be applied first - the result of which is fed into the second transform and so on until the chain is exhausted.

apply(*x*, *batch_size=None*, ***kwargs*)

Applies this transform to `x`.

If `x` is `Transformable`, `x` will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, `x` is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters

- **x** (`Transformable` or `(n_points, n_dims)` *ndarray*) – The array or object to be transformed.
- **batch_size** (*int*, optional) – If not `None`, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returns **transformed** (`type(x)`) – The transformed object or array

apply_inplace(*x*, ***kwargs*)

Applies this transform to a `Transformable` `x` destructively.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters

- **x** (`Transformable`) – The `Transformable` object to be transformed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returns **transformed** (`type(x)`) – The transformed object

compose_after(*transform*)

A *Transform* that represents **this** transform composed **after** the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

a and b are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, o.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameters **transform** (*Transform*) – Transform to be applied **before** self

Returns **transform** (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_after_inplace(*transform*)

Update self so that it represents **this** transform composed **after** the given transform:

```
a_orig = a.copy()
a.compose_after_inplace(b)
a.apply(p) == a_orig.apply(b.apply(p))
```

a is permanently altered to be the result of the composition. b is left unchanged.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **before** self

Raises ValueError – If transform isn't an instance of *composes_inplace_with*

compose_before(*transform*)

A *Transform* that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

a and b are left unchanged.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameters **transform** (*Transform*) – Transform to be applied **after** self

Returns **transform** (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_before_inplace(*transform*)

Update self so that it represents **this** transform composed **before** the given transform:

```
a_orig = a.copy()
a.compose_before_inplace(b)
a.apply(p) == b.apply(a_orig.apply(p))
```

a is permanently altered to be the result of the composition. b is left unchanged.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **after** self

Raises ValueError – If transform isn't an instance of *composes_inplace_with*

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns `type(self)` – A copy of this object

composes_inplace_with

The *Transform* s that this transform composes inplace with **natively** (i.e. no *TransformChain* will be produced).

An attempt to compose inplace against any type that is not an instance of this property on this class will result in an *Exception*.

Type *Transform* or *tuple* of *Transform* s

composes_with

The *Transform* s that this transform composes with **natively** (i.e. no *TransformChain* will be produced).

If native composition is not possible, falls back to producing a *TransformChain*.

By default, this is the same list as *composes_inplace_with*.

Type *Transform* or *tuple* of *Transform* s

n_dims

The dimensionality of the data the transform operates on.

`None` if the transform is not dimension specific.

Type *int* or `None`

n_dims_output

The output of the data from the transform.

`None` if the output of the transform is not dimension specific.

Type *int* or `None`

2.9.5 Radial Basis Functions

R2LogR2RBF

class menpo.transform.**R2LogR2RBF**(*c*)

Bases: `RadialBasisFunction`

The $r^2 \log r^2$ basis function.

The derivative of this function is $2r(\log r^2 + 1)$.

Note: $r = \|x - c\|$

Parameters **c** (`(n_centres, n_dims)` *ndarray*) – The set of centers that make the basis. Usually represents a set of source landmarks.

apply(*x*, *batch_size=None*, ***kwargs*)

Applies this transform to `x`.

If `x` is `Transformable`, `x` will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, `x` is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters

- **x** (`Transformable` or `(n_points, n_dims)` *ndarray*) – The array or object to be transformed.
- **batch_size** (*int*, optional) – If not `None`, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returnstransformed (`type(x)`) – The transformed object or array

apply_inplace(*x*, ***kwargs*)

Applies this transform to a `Transformable` `x` destructively.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters

- **x** (`Transformable`) – The `Transformable` object to be transformed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returnstransformed (`type(x)`) – The transformed object

compose_after(*transform*)

Returns a *TransformChain* that represents **this** transform composed **after** the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

`a` and `b` are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, *o*.

Parameterstransform (*Transform*) – Transform to be applied **before** self

Returnstransform (*TransformChain*) – The resulting transform chain.

compose_before(*transform*)

Returns a *TransformChain* that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

`a` and `b` are left unchanged.

Parameterstransform (*Transform*) – Transform to be applied **after** self

Returnstransform (*TransformChain*) – The resulting transform chain.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns`type(self)` – A copy of this object

n_centres

The number of centres.

Type*int*

n_dims

The RBF can only be applied on points with the same dimensionality as the centres.

Type*int*

n_dims_output
The result of the transform has a dimension (weight) for every centre.
Type*int*

R2LogRRBF

class menpo.transform.**R2LogRRBF**(*c*)
Bases: RadialBasisFunction

Calculates the $r^2 \log r$ basis function.

The derivative of this function is $r(1 + 2 \log r)$.

Note: $r = \|x - c\|$

Parametersc ((n_centres, n_dims) *ndarray*) – The set of centers that make the basis. Usually represents a set of source landmarks.

apply(*x*, *batch_size=None*, ***kwargs*)
Applies this transform to x.

If x is Transformable, x will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, x is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any kwargs will be passed to the specific transform _apply() method.
Parameters
- **x** (Transformable or (n_points, n_dims) *ndarray*) – The array or object to be transformed.
- **batch_size** (*int*, optional) – If not None, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.
- **kwargs** (*dict*) – Passed through to _apply().

Returnstransformed (type(x)) – The transformed object or array

apply_inplace(*x*, ***kwargs*)
Applies this transform to a Transformable x destructively.

Any kwargs will be passed to the specific transform _apply() method.
Parameters
- **x** (Transformable) – The Transformable object to be transformed.
- **kwargs** (*dict*) – Passed through to _apply().

Returnstransformed (type(x)) – The transformed object

compose_after(*transform*)
Returns a *TransformChain* that represents **this** transform composed **after** the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

a and b are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, *o*.
Parameterstransform (*Transform*) – Transform to be applied **before** self
Returnstransform (*TransformChain*) – The resulting transform chain.

compose_before(*transform*)

Returns a `TransformChain` that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

`a` and `b` are left unchanged.

Parameters`transform` (`Transform`) – Transform to be applied **after** self

Returns`transform` (`TransformChain`) – The resulting transform chain.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other `Copyable` objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns`type(self)` – A copy of this object

n_centres

The number of centres.

Type*int*

n_dims

The RBF can only be applied on points with the same dimensionality as the centres.

Type*int*

n_dims_output

The result of the transform has a dimension (weight) for every centre.

Type*int*

2.9.6 Abstract Bases

Transform

class menpo.transform.**Transform**

Bases: `Copyable`

Abstract representation of any spatial transform.

Provides a unified interface to apply the transform with `apply_inplace()` and `apply()`.

All Transforms support basic composition to form a `TransformChain`.

There are two useful forms of composition. Firstly, the mathematical composition symbol *o* has the following definition:

```
Let a(x) and b(x) be two transforms on x.
(a o b)(x) == a(b(x))
```

This functionality is provided by the `compose_after()` family of methods:

```
(a.compose_after(b)).apply(x) == a.apply(b.apply(x))
```

Equally useful is an inversion the order of composition - so that over time a large chain of transforms can be built to do a useful job, and composing on this chain adds another transform to the end (after all other preceding transforms have been performed).

For instance, let's say we want to rescale a *PointCloud* p around its mean, and then translate it some place else. It would be nice to be able to do something like:

```
t = Translation(-p.centre)  # translate to centre
s = Scale(2.0)  # rescale
move = Translate([10, 0 ,0])  # budge along the x axis
t.compose(s).compose(-t).compose(move)
```

In Menpo, this functionality is provided by the *compose_before()* family of methods:

```
(a.compose_before(b)).apply(x) == b.apply(a.apply(x))
```

For native composition, see the `ComposableTransform` subclass and the `VComposable` mix-in.

For inversion, see the `Invertible` and `VInvertible` mix-ins.

For alignment, see the `Alignment` mix-in.

apply(*x*, *batch_size=None*, ***kwargs*)

Applies this transform to `x`.

If `x` is `Transformable`, `x` will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, `x` is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters

- **x** (`Transformable` or `(n_points, n_dims)` *ndarray*) – The array or object to be transformed.
- **batch_size** (*int*, optional) – If not `None`, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returnstransformed (`type(x)`) – The transformed object or array

apply_inplace(*x*, ***kwargs*)

Applies this transform to a `Transformable` `x` destructively.

Any `kwargs` will be passed to the specific transform `_apply()` method.

Parameters

- **x** (`Transformable`) – The `Transformable` object to be transformed.
- **kwargs** (*dict*) – Passed through to `_apply()`.

Returnstransformed (`type(x)`) – The transformed object

compose_after(*transform*)

Returns a *TransformChain* that represents **this** transform composed **after** the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

`a` and `b` are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, *o*.

Parameterstransform (*Transform*) – Transform to be applied **before** self

Returnstransform (*TransformChain*) – The resulting transform chain.

compose_before(*transform*)

Returns a *TransformChain* that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

a and b are left unchanged.

Parameters **transform** (*Transform*) – Transform to be applied **after** self

Returns **transform** (*TransformChain*) – The resulting transform chain.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns type(self) – A copy of this object

n_dims

The dimensionality of the data the transform operates on.

None if the transform is not dimension specific.

Type *int* or None

n_dims_output

The output of the data from the transform.

None if the output of the transform is not dimension specific.

Type *int* or None

Transformable

class menpo.transform.base.**Transformable**

Bases: *Copyable*

Interface for objects that know how to be transformed by the *Transform* interface.

When Transform.apply_inplace is called on an object, the *_transform_inplace()* method is called, passing in the transforms' _apply() function.

This allows for the object to define how it should transform itself.

_transform_inplace(*transform*)

Apply the given transform function to self inplace.

Parameters **transform** (*function*) – Function that applies a transformation to the transformable object.

Returns **transformed** (type(self)) – The transformed object, having been transformed in place.

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on self will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns type(self) – A copy of this object

ComposableTransform

class menpo.transform.base.composable.**ComposableTransform**

Bases: Transform

Transform subclass that enables native composition, such that the behavior of multiple *Transform* s is composed together in a natural way.

_compose_after_inplace(*transform*)

Specialised inplace composition. This should be overridden to provide specific cases of composition as defined in *composes_inplace_with*.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **before** self

_compose_before_inplace(*transform*)

Specialised inplace composition. This should be overridden to provide specific cases of composition as defined in *composes_inplace_with*.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **after** self

apply(*x*, *batch_size=None*, ***kwargs*)

Applies this transform to x.

If x is Transformable, x will be handed this transform object to transform itself non-destructively (a transformed copy of the object will be returned).

If not, x is assumed to be an *ndarray*. The transformation will be non-destructive, returning the transformed version.

Any kwargs will be passed to the specific transform _apply() method.

Parameters

- **x** (Transformable or (n_points, n_dims) *ndarray*) – The array or object to be transformed.
- **batch_size** (*int*, optional) – If not None, this determines how many items from the numpy array will be passed through the transform at a time. This is useful for operations that require large intermediate matrices to be computed.
- **kwargs** (*dict*) – Passed through to _apply().

Returns **transformed** (type(x)) – The transformed object or array

apply_inplace(*x*, ***kwargs*)

Applies this transform to a Transformable x destructively.

Any kwargs will be passed to the specific transform _apply() method.

Parameters

- **x** (Transformable) – The Transformable object to be transformed.
- **kwargs** (*dict*) – Passed through to _apply().

Returns **transformed** (type(x)) – The transformed object

compose_after(*transform*)

A *Transform* that represents **this** transform composed **after** the given transform:

```
c = a.compose_after(b)
c.apply(p) == a.apply(b.apply(p))
```

a and b are left unchanged.

This corresponds to the usual mathematical formalism for the compose operator, o.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameters **transform** (*Transform*) – Transform to be applied **before** `self`

Returns **transform** (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_after_inplace(*transform*)

Update `self` so that it represents **this** transform composed **after** the given transform:

```
a_orig = a.copy()
a.compose_after_inplace(b)
a.apply(p) == a_orig.apply(b.apply(p))
```

`a` is permanently altered to be the result of the composition. `b` is left unchanged.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **before** `self`

Raises `ValueError` – If `transform` isn't an instance of *composes_inplace_with*

compose_before(*transform*)

A *Transform* that represents **this** transform composed **before** the given transform:

```
c = a.compose_before(b)
c.apply(p) == b.apply(a.apply(p))
```

`a` and `b` are left unchanged.

An attempt is made to perform native composition, but will fall back to a *TransformChain* as a last resort. See *composes_with* for a description of how the mode of composition is decided.

Parameters **transform** (*Transform*) – Transform to be applied **after** `self`

Returns **transform** (*Transform* or *TransformChain*) – If the composition was native, a single new *Transform* will be returned. If not, a *TransformChain* is returned instead.

compose_before_inplace(*transform*)

Update `self` so that it represents **this** transform composed **before** the given transform:

```
a_orig = a.copy()
a.compose_before_inplace(b)
a.apply(p) == b.apply(a_orig.apply(p))
```

`a` is permanently altered to be the result of the composition. `b` is left unchanged.

Parameters **transform** (*composes_inplace_with*) – Transform to be applied **after** `self`

Raises `ValueError` – If `transform` isn't an instance of *composes_inplace_with*

copy()

Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.

Returns `type(self)` – A copy of this object

composes_inplace_with

The *Transform* s that this transform composes inplace with **natively** (i.e. no *TransformChain* will be produced).

An attempt to compose inplace against any type that is not an instance of this property on this class will result in an *Exception*.

Type `Transform` or *tuple* of `Transform` s

composes_with

The `Transform` s that this transform composes with **natively** (i.e. no `TransformChain` will be produced).

If native composition is not possible, falls back to producing a `TransformChain`.

By default, this is the same list as `composes_inplace_with`.

Type `Transform` or *tuple* of `Transform` s

n_dims

The dimensionality of the data the transform operates on.

`None` if the transform is not dimension specific.

Type *int* or `None`

n_dims_output

The output of the data from the transform.

`None` if the output of the transform is not dimension specific.

Type *int* or `None`

Invertible

class `menpo.transform.base.invertible.`**`Invertible`**

Bases: `object`

Mix-in for invertible transforms. Provides an interface for taking the *pseudo* or true inverse of a transform.

Has to be implemented in conjunction with `Transform`.

pseudoinverse`()`

The pseudoinverse of the transform - that is, the transform that results from swapping *source* and *target*, or more formally, negating the transforms parameters. If the transform has a true inverse this is returned instead.

Type `type(self)`

has_true_inverse

`True` if the pseudoinverse is an exact inverse.

Type *bool*

Alignment

class `menpo.transform.base.alignment.`**`Alignment`**(*source*, *target*)

Bases: `Targetable`, `Viewable`

Mix-in for `Transform` that have been constructed from an optimisation aligning a source `PointCloud` to a target `PointCloud`.

This is naturally an extension of the `Targetable` interface - we just augment `Targetable` with the concept of a source, and related methods to construct alignments between a source and a target.

Note that to inherit from `Alignment`, you have to be a `Transform` subclass first.

Parameters

- **source** (`PointCloud`) – A PointCloud that the alignment will be based from
- **target** (`PointCloud`) – A PointCloud that the alignment is targeted towards

aligned_source()
The result of applying `self` to *source*
Type*PointCloud*

alignment_error()
The Frobenius Norm of the difference between the target and the aligned source.
Type*float*

copy()
Generate an efficient copy of this object.

Note that Numpy arrays and other *Copyable* objects on `self` will be deeply copied. Dictionaries and sets will be shallow copied, and everything else will be assigned (no copy will be made).

Classes that store state other than numpy arrays and immutable types should overwrite this method to ensure all state is copied.
Returns`type(self)` – A copy of this object

set_target(*new_target*)
Update this object so that it attempts to recreate the `new_target`.
Parameters`new_target` (*PointCloud*) – The new target that this object should try and regenerate.

n_dims
The number of dimensions of the *target*.
Type*int*

n_points
The number of points on the *target*.
Type*int*

source
The source *PointCloud* that is used in the alignment.

The source is not mutable.
Type*PointCloud*

target
The current *PointCloud* that this object produces.

To change the target, use *set_target()*.
Type*PointCloud*

MultipleAlignment

class `menpo.transform.groupalign.base.`**MultipleAlignment**(*sources*, *target=None*)
Bases: `object`

Abstract base class for aligning multiple *source* shapes to a *target* shape.
Parameters
- `sources` (*list* of *PointCloud*) – List of pointclouds to be aligned.
- `target` (*PointCloud*, optional) – The target *PointCloud* to align each source to. If `None`, then the mean of the sources is used.

Raises`ValueError` – Need at least two sources to align

DiscreteAffine

class `menpo.transform.homogeneous.affine.`**DiscreteAffine**
Bases: `object`

A discrete Affine transform operation (such as a `Scale()`, `Translation` or `Rotation()`). Has to be invertable. Make sure you inherit from `DiscreteAffine` first, for optimal *decompose()* behavior.

decompose()

A `DiscreteAffine` is already maximally decomposed - return a copy of self in a *list*.

Returnstransform (`DiscreteAffine`) – Deep copy of *self*.

2.9.7 Performance Specializations

Mix-ins that provide fast vectorized variants of methods.

VComposable

class menpo.transform.base.composable.**VComposable**

Bases: `object`

Mix-in for `Vectorizable` `ComposableTransform` s.

Use this mix-in with `ComposableTransform` if the `ComposableTransform` in question is `Vectorizable` as this adds `from_vector()` variants to the `ComposableTransform` interface.

These can be tuned for performance.

compose_after_from_vector_inplace(*vector*)

Specialised inplace composition with a vector. This should be overridden to provide specific cases of composition whereby the current state of the transform can be derived purely from the provided vector.

Parametersvector (`(n_parameters,)` *ndarray*) – Vector to update the transform state with.

VInvertible

class menpo.transform.base.invertible.**VInvertible**

Bases: `Invertible`

Mix-in for `Vectorizable` `Invertible` `Transform` s.

Prefer this mix-in over `Invertible` if the `Transform` in question is `Vectorizable` as this adds `from_vector()` variants to the `Invertible` interface. These can be tuned for performance, and are, for instance, needed by some of the machinery of fit.

pseudoinverse()

The pseudoinverse of the transform - that is, the transform that results from swapping *source* and *target*, or more formally, negating the transforms parameters. If the transform has a true inverse this is returned instead.

Type`type(self)`

pseudoinverse_vector(*vector*)

The vectorized pseudoinverse of a provided vector instance. Syntactic sugar for:

```
self.from_vector(vector).pseudoinverse().as_vector()
```

Can be much faster than the explict call as object creation can be entirely avoided in some cases.

Parametersvector (`(n_parameters,)` *ndarray*) – A vectorized version of `self`

Returnspseudoinverse_vector (`(n_parameters,)` *ndarray*) – The pseudoinverse of the vector provided

has_true_inverse
`True` if the pseudoinverse is an exact inverse.
Type*bool*

2.10 menpo.visualize

2.10.1 Abstract Classes

Renderer

class menpo.visualize.**Renderer**(*figure_id*, *new_figure*)
Bases: `object`

Abstract class for rendering visualizations. Framework specific implementations of these classes are made in order to separate implementation cleanly from the rest of the code.

It is assumed that the renderers follow some form of stateful pattern for rendering to Figures. Therefore, the major interface for rendering involves providing a *figure_id* or a *bool* about whether a new figure should be used. If neither are provided then the default state of the rendering engine is assumed to be maintained.

Providing both a `figure_id` and `new_figure == True` is not a valid state.
Parameters
- **figure_id** (*object*) – A figure id. Could be any valid object that identifies a figure in a given framework (*str*, *int*, *float*, etc.).
- **new_figure** (*bool*) – Whether the rendering engine should create a new figure.

Raises`ValueError` – It is not valid to provide a figure id AND request a new figure to be rendered on.

get_figure()
Abstract method for getting the correct figure to render on. Should also set the correct *figure_id* for the figure.
Returnsfigure (*object*) – The figure object that the renderer will render on.

render(***kwargs*)
Abstract method to be overridden by the renderer. This will implement the actual rendering code for a given object class.
Parameterskwargs (*dict*) – Passed through to specific rendering engine.
Returnsviewer (`Renderer`) – Pointer to *self*.

save_figure(***kwargs*)
Abstract method for saving the figure of the current *figure_id* to file. It will implement the actual saving code for a given object class.
Parameterskwargs (*dict*) – Options to be set when saving the figure to file.

Viewable

class menpo.visualize.**Viewable**
Bases: `object`

Abstract interface for objects that can visualize themselves. This assumes that the class has dimensionality as the view method checks the `n_dims` property to wire up the correct view method.

LandmarkableViewable

class menpo.visualize.**LandmarkableViewable**

Bases: object

Mixin for *Landmarkable* and *Viewable* objects. Provides a single helper method for viewing Landmarks and *self* on the same figure.

MatplotlibRenderer

class menpo.visualize.**MatplotlibRenderer**(*figure_id*, *new_figure*)

Bases: Renderer

Abstract class for rendering visualizations using Matplotlib.

Parameters

- **figure_id** (*int* or None) – A figure id or None. None assumes we maintain the Matplotlib state machine and use *plt.gcf()*.
- **new_figure** (*bool*) – If True, it creates a new figure to render on.

get_figure()

Gets the figure specified by the combination of self.figure_id and self.new_figure. If self.figure_id == None then plt.gcf() is used. self.figure_id is also set to the correct id of the figure if a new figure is created.

Returns figure (*Matplotlib figure object*) – The figure we will be rendering on.

render(***kwargs*)

Abstract method to be overridden by the renderer. This will implement the actual rendering code for a given object class.

Parameters kwargs (*dict*) – Passed through to specific rendering engine.

Returns viewer (*Renderer*) – Pointer to *self*.

save_figure(*filename*, *format='png'*, *dpi=None*, *face_colour='w'*, *edge_colour='w'*, *orientation='portrait'*, *paper_type='letter'*, *transparent=False*, *pad_inches=0.1*, *overwrite=False*)

Method for saving the figure of the current *figure_id* to file.

Parameters

- **filename** (*str* or *file*-like object) – The string path or file-like object to save the figure at/into.
- **format** (*str*) – The format to use. This must match the file path if the file path is a *str*.
- **dpi** (*int* > 0 or None, optional) – The resolution in dots per inch.
- **face_colour** (*See Below, optional*) – The face colour of the figure rectangle. Example options

```
{``r``, ``g``, ``b``, ``c``, ``m``, ``k``, ``w``}
or
``(3, )`` `ndarray`
or
`list` of len 3
```

- **edge_colour** (*See Below, optional*) – The edge colour of the figure rectangle. Example options

```
{``r``, ``g``, ``b``, ``c``, ``m``, ``k``, ``w``}
or
``(3, )`` `ndarray`
or
`list` of len 3
```

- **orientation** ({portrait, landscape}, optional) – The page orientation.
- **paper_type** (*See Below, optional*) – The type of the paper. Example options

```
{``letter``, ``legal``, ``executive``, ``ledger``,
 ``a0`` through ``a10``, ``b0` through ``b10``}
```

- **transparent** (*bool*, optional) – If True, the axes patches will all be transparent; the figure patch will also be transparent unless *face_colour* and/or *edge_colour* are specified. This is useful, for example, for displaying a plot on top of a coloured background on a web page. The transparency of these patches will be restored to their original values upon exit of this function.
- **pad_inches** (*float*, optional) – Amount of padding around the figure.
- **overwrite** (*bool*, optional) – If True, the file will be overwritten if it already exists.

save_figure_widget()

Method for saving the figure of the current figure_id to file using menpo.visualize.widgets.base.save_matplotlib_figure() widget.

2.10.2 Widgets

visualize_images

menpo.visualize.**visualize_images**(*images*, *figure_size=(10, 8)*, *style='coloured'*, *browser_style='buttons'*)

Widget that allows browsing through a *list* of Image (or subclass) objects.

The images can have a combination of different attributes, e.g. masked or not, landmarked or not, without multiple landmark groups and labels etc. The widget has options tabs regarding the visualized channels, the landmarks, the renderer (lines, markers, numbering, legend, figure, axes) and saving the figure to file.

Parameters

- **images** (*list* of Image or subclass) – The *list* of images to be visualized.
- **figure_size** ((*int*, *int*), optional) – The initial size of the rendered figure.
- **style** ({'coloured', 'minimal'}, optional) – If 'coloured', then the style of the widget will be coloured. If minimal, then the style is simple using black and white colours.
- **browser_style** ({'buttons', 'slider'}, optional) – It defines whether the selector of the objects will have the form of plus/minus buttons or a slider.

visualize_landmarks

menpo.visualize.**visualize_landmarks**(*landmarks*, *figure_size=(10, 8)*, *style='coloured'*, *browser_style='buttons'*)

Widget that allows browsing through a *list* of LandmarkManager (or subclass) objects.

The landmark managers can have a combination of different attributes, e.g. landmark groups and labels etc. The widget has options tabs regarding the landmarks, the renderer (lines, markers, numbering, legend, figure, axes) and saving the figure to file.

Parameters

- **landmarks** (*list* of LandmarkManager or subclass) – The *list* of landmark managers to be visualized.
- **figure_size** ((*int*, *int*), optional) – The initial size of the rendered figure.

- **style** ({'coloured', 'minimal'}, optional) – If 'coloured', then the style of the widget will be coloured. If minimal, then the style is simple using black and white colours.
- **browser_style** ({'buttons', 'slider'}, optional) – It defines whether the selector of the objects will have the form of plus/minus buttons or a slider.

visualize_landmarkgroups

menpo.visualize.**visualize_landmarkgroups**(*landmarkgroups*, *figure_size=(10, 8)*, *style='coloured'*, *browser_style='buttons'*)

Widget that allows browsing through a *list* of LandmarkGroup (or subclass) objects.

The landmark groups can have a combination of different attributes, e.g. different labels, number of points etc. The widget has options tabs regarding the landmarks, the renderer (lines, markers, numbering, legend, figure, axes) and saving the figure to file.

Parameters

- **landmarkgroups** (*list* of LandmarkGroup or subclass) – The *list* of landmark groups to be visualized.
- **figure_size** ((*int*, *int*), optional) – The initial size of the rendered figure.
- **style** ({'coloured', 'minimal'}, optional) – If 'coloured', then the style of the widget will be coloured. If minimal, then the style is simple using black and white colours.
- **browser_style** ({'buttons', 'slider'}, optional) – It defines whether the selector of the objects will have the form of plus/minus buttons or a slider.

visualize_pointclouds

menpo.visualize.**visualize_pointclouds**(*pointclouds*, *figure_size=(10, 8)*, *style='coloured'*, *browser_style='buttons'*)

Widget that allows browsing through a *list* of PointCloud, PointUndirectedGraph, PointDirectedGraph, PointTree, TriMesh or subclasses. All the above can be combined in the *list*.

The widget has options tabs regarding the renderer (lines, markers, figure, axes) and saving the figure to file.

Parameters

- **pointclouds** (*list*) – The *list* of objects to be visualized. It can contain a combination of PointCloud, PointUndirectedGraph, PointDirectedGraph, PointTree, TriMesh or subclasses of those.
- **figure_size** ((*int*, *int*), optional) – The initial size of the rendered figure.
- **style** ({'coloured', 'minimal'}, optional) – If 'coloured', then the style of the widget will be coloured. If minimal, then the style is simple using black and white colours.
- **browser_style** ({'buttons', 'slider'}, optional) – It defines whether the selector of the objects will have the form of plus/minus buttons or a slider.

features_selection

menpo.visualize.**features_selection**(*style='coloured'*)

Widget that allows selecting a features function and its options. The widget supports all features from *menpo.feature* and has a preview tab. It returns a *list* of length 1 with the selected features function closure.

Parameters

- **style** ({'coloured', 'minimal'}, optional) – If 'coloured', then the style of the widget will be coloured. If minimal, then the style is simple using black and white colours.

Returns

features_function (*list* of length `1`) – The function closure of the features function using *functools.partial*. So the function can be called as:

```
features_image = features_function[0](image)
```

save_matplotlib_figure

`menpo.visualize.`**`save_matplotlib_figure`**(*renderer*, *style='coloured'*)

Widget that allows to save a figure, which was generated with Matplotlib, to file.

Parameters

- **`renderer`** (*`MatplotlibRenderer`*) – The Matplotlib renderer object.
- **`style`** (`{'coloured', 'minimal'}`, optional) – If `'coloured'`, then the style of the widget will be coloured. If `minimal`, then the style is simple using black and white colours.

plot_graph

`menpo.visualize.`**`plot_graph`**(*x_axis*, *y_axis*, *legend_entries=None*, *title=None*, *x_label=None*, *y_label=None*, *x_axis_limits=None*, *y_axis_limits=None*, *figure_size=(10, 6)*, *style='coloured'*)

Widget that allows plotting various curves in a graph using `GraphPlotter`.

The widget has options tabs regarding the graph and the renderer (lines, markers, legend, figure, axes, grid) and saving the figure to file.

Parameters

- **`x_axis`** (*list* of *float*) – The values of the horizontal axis. Note that these values are common for all the curves.
- **`y_axis`** (*list* of *lists* of *float*) – A *list* that stores a *list* of values to be plotted for each curve.
- **`legend_entries`** (*list* or *str* or `None`, optional) – The *list* of names that will appear on the legend for each curve. If `None`, then the names format is `curve {}.format(i)`.
- **`title`** (*str* or `None`, optional) – The title of the graph.
- **`x_label`** (*str* or `None`, optional) – The label on the horizontal axis of the graph.
- **`y_label`** (*str* or `None`, optional) – The label on the vertical axis of the graph.
- **`x_axis_limits`** ((*float*, *float*) or `None`, optional) – The limits of the horizontal axis. If `None`, the limits are set based on the min and max values of *x_axis*.
- **`y_axis_limits`** ((*float*, *float*), optional) – The limits of the vertical axis. If `None`, the limits are set based on the min and max values of *y_axis*.
- **`figure_size`** ((*int*, *int*), optional) – The initial size of the rendered figure.
- **`style`** (`{'coloured', 'minimal'}`, optional) – If `'coloured'`, then the style of the widget will be coloured. If `minimal`, then the style is simple using black and white colours.

2.10.3 Print Utilities

print_progress

`menpo.visualize.`**`print_progress`**(*iterable*, *prefix=''*, *n_items=None*, *offset=0*, *show_bar=True*, *show_count=True*, *show_eta=True*, *end_with_newline=True*)

Print the remaining time needed to compute over an iterable.

To use, wrap an existing iterable with this function before processing in a for loop (see example).

The estimate of the remaining time is based on a moving average of the last 100 items completed in the loop.

Parameters

- **iterable** (*iterable*) – An iterable that will be processed. The iterable is passed through by this function, with the time taken for each complete iteration logged.
- **prefix** (*str*, optional) – If provided a string that will be prepended to the progress report at each level.
- **n_items** (*int*, optional) – Allows for `iterator` to be a generator whose length will be assumed to be *n_items*. If not provided, then `iterator` needs to be *Sizable*.
- **offset** (*int*, optional) – Useful in combination with `n_items` - report back the progress as if *offset* items have already been handled. `n_items` will be left unchanged.
- **show_bar** (*bool*, optional) – If False, The progress bar (e.g. [=========]) will be hidden.
- **show_count** (*bool*, optional) – If False, The item count (e.g. (4/25)) will be hidden.
- **show_eta** (*bool*, optional) – If False, The estimated time to finish (e.g. - 00:00:03 remaining) will be hidden.
- **end_with_newline** (*bool*, optional) – If False, there will be no new line added at the end of the dynamic printing. This means the next print statement will overwrite the dynamic report presented here. Useful if you want to follow up a print_progress with a second print_progress, where the second overwrites the first on the same line.

Raises `ValueError` – `offset` provided without `n_items`

Examples

This for loop:

```
from time import sleep
for i in print_progress(range(100)):
    sleep(1)
```

prints a progress report of the form:

```
[=============       ] 70% (7/10) - 00:00:03 remaining
```

---

print_dynamic

`menpo.visualize.`**`print_dynamic`**(*str_to_print*)

Prints dynamically the provided *str*, i.e. the *str* is printed and then the buffer gets flushed.

Parameters **str_to_print** (*str*) – The string to print.

progress_bar_str

`menpo.visualize.`**`progress_bar_str`**(*percentage*, *bar_length=20*, *bar_marker='='*, *show_bar=True*)

Returns an *str* of the specified progress percentage. The percentage is represented either in the form of a progress bar or in the form of a percentage number. It can be combined with the `print_dynamic()` function.

Parameters

- **percentage** (*float*) – The progress percentage to be printed. It must be in the range `[0, 1]`.
- **bar_length** (*int*, optional) – Defines the length of the bar in characters.
- **bar_marker** (*str*, optional) – Defines the marker character that will be used to fill the bar.

- **show_bar** (*bool*, optional) – If `True`, the *str* includes the bar followed by the percentage, e.g. `'[===== ] 50%'`

  If `False`, the *str* includes only the percentage, e.g. `'50%'`

Returnsprogress_str (*str*) – The progress percentage string that can be printed.

Raises

- `ValueError` – `percentage` is not in the range `[0, 1]`
- `ValueError` – `bar_length` must be an integer >= `1`
- `ValueError` – `bar_marker` must be a string of length 1

Examples

This for loop:

```
n_iters = 2000
for k in range(n_iters):
    print_dynamic(progress_bar_str(float(k) / (n_iters-1)))
```

prints a progress bar of the form:

```
[=============       ] 68%
```

bytes_str

`menpo.visualize.`**`bytes_str`**(*num*)

Converts bytes to a human readable format. For example:

```
print_bytes(12345) returns '12.06 KB'
print_bytes(123456789) returns '117.74 MB'
```

Parametersnum (*int*) – The size in bytes.

Raises`ValueError` – num must be int >= 0

2.10.4 Create Custom Widgets

Collection of widgets that can be used as the main ingredients for creating other custom widgets.

AnimationOptionsWidget

class `menpo.visualize.widgets.`**`AnimationOptionsWidget`**(*index, render_function=None, update_function=None, index_style='buttons', interval=0.5, description='Index: ', minus_description='-', plus_description='+', loop_enabled=True, text_editable=True, style='minimal'*)

Bases: `FlexBox`

Creates a widget for animating through a list of objects. The widget consists of the following parts from *IPython.html.widgets* and *menpo.visualize.widgets.tools*:

No	Object	Variable (*self.*)	Description
1	ToggleButton	*play_stop_toggle*	The play/stop button
2	ToggleButton	*play_options_toggle*	Button that toggles the options menu
3	Checkbox	*loop_checkbox*	Repeat mode
4	FloatText	*interval_text*	Interval (secs)
5	VBox	*loop_interval_box*	Contains 3, 4
6	VBox	*play_options_box*	Contains 2, 5
7	HBox	*animation_box*	Contains 1, 6
8	IndexButtonsWidget IndexSliderWidget	*index_wid*	The index selector widget

Note that:

- The selected values are stored in the `self.selected_values` *dict*.
- To set the styling please refer to the `style()` and `predefined_style()` methods.
- To update the state of the widget, please refer to the `set_widget_state()` method.
- To update the callback function please refer to the `replace_render_function()` and `replace_update_function()` methods.

Parameters

- **`index`** (*dict*) – The dictionary with the initial options. For example

```
index = {'min': 0,
         'max': 100,
         'step': 1,
         'index': 10}
```

- **`render_function`** (*function* or `None`, optional) – The render function that is executed when a widgets' value changes. If `None`, then nothing is assigned.
- **`update_function`** (*function* or `None`, optional) – The update function that is executed when the index value changes. If `None`, then nothing is assigned.
- **`index_style`** (`{'buttons', 'slider'}`, optional) – If `'buttons'`, then *IndexButtonsWidget()* class is called. If `'slider'`, then 'IndexSliderWidget()' class is called.
- **`interval`** (*float*, optional) – The interval between the animation progress.
- **`description`** (*str*, optional) – The title of the widget.
- **`minus_description`** (*str*, optional) – The title of the button that decreases the index.
- **`plus_description`** (*str*, optional) – The title of the button that increases the index.
- **`loop_enabled`** (*bool*, optional) – If `True`, then after reach the minimum (maximum) index values, the counting will continue from the end (beginning). If `False`, the counting will stop at the minimum (maximum) value.
- **`text_editable`** (*bool*, optional) – Flag that determines whether the index text will be editable.
- **`style`** (*See Below, optional*) – Sets a predefined style at the widget. Possible options are

Style	Description
'minimal'	Simple black and white style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	No style

Example

Let's create an animation widget and then update its state. Firstly, we need to import it:

```
>>> from menpo.visualize.widgets import AnimationOptionsWidget
>>> from IPython.display import display
```

Now let's define a render function that will get called on every widget change and will dynamically print the selected index:

```
>>> from menpo.visualize import print_dynamic
>>> def render_function(name, value):
>>>     s = "Selected index: {}".format(wid.selected_values['index'])
>>>     print_dynamic(s)
```

Create the widget with some initial options and display it:

```
>>> index = {'min': 0, 'max': 100, 'step': 1, 'index': 10}
>>> wid = AnimationOptionsWidget(index, index_style='buttons',
>>>                              render_function=render_function,
>>>                              style='info')
>>> display(wid)
```

By pressing the buttons (or simply pressing the Play button), the printed message gets updated. Finally, let's change the widget status with a new dictionary of options:

```
>>> new_options = {'min': 0, 'max': 20, 'step': 2, 'index': 16}
>>> wid.set_widget_state(new_options, allow_callback=False)
```

---

add_render_function(*render_function*)

Method that adds a *render_function()* to the widget. The signature of the given function is also stored in *self._render_function*.

Parameters **render_function** (*function* or `None`, optional) – The render function that behaves as a callback. If `None`, then nothing is added.

add_update_function(*update_function*)

Method that adds an *update_function()* to the widget. The signature of the given function is also stored in *self._update_function*.

Parameters **update_function** (*function* or `None`, optional) – The update function that behaves as a callback. If `None`, then nothing is added.

predefined_style(*style*)

Function that sets a predefined style on the widget.

Parameters **style** (*str* (see below)) – Style options

Style	Description
'minimal'	Simple black and white style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	No style

remove_render_function()

Method that removes the current *self._render_function()* from the widget and sets `self._render_function = None`.

remove_update_function()

Method that removes the current *self._update_function()* from the widget and sets `self._update_function = None`.

replace_render_function(*render_function*)

Method that replaces the current *self._render_function()* of the widget with the given *render_function()*.

Parameters

render_function (*function* or `None`, optional) – The render function that behaves as a callback. If `None`, then nothing is happening.

replace_update_function(*update_function*)

Method that replaces the current *self._update_function()* of the widget with the given *update_function()*.

Parameters

update_function (*function* or `None`, optional) – The update function that behaves as a callback. If `None`, then nothing is happening.

set_widget_state(*index*, *allow_callback=True*)

Method that updates the state of the widget with a new set of values.

Parameters

- **index** (*dict*) – The dictionary with the new options to be used. For example

```
index = {'min': 0,
         'max': 100,
         'step': 1,
         'index': 10}
```

- **allow_callback** (*bool*, optional) – If `True`, it allows triggering of any callback functions.

style(*box_style=None*, *border_visible=False*, *border_color='black'*, *border_style='solid'*, *border_width=1*, *border_radius=0*, *padding=0*, *margin=0*, *font_family=''*, *font_size=None*, *font_style=''*, *font_weight=''*)

Function that defines the styling of the widget.

Parameters

- **box_style** (*See Below, optional*) – Style options

Style	Description
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	Default style
None	No style

- **border_visible** (*bool*, optional) – Defines whether to draw the border line around the widget.
- **border_color** (*str*, optional) – The color of the border around the widget.
- **border_style** (*str*, optional) – The line style of the border around the widget.
- **border_width** (*float*, optional) – The line width of the border around the widget.
- **border_radius** (*float*, optional) – The radius of the corners of the box.
- **padding** (*float*, optional) – The padding around the widget.
- **margin** (*float*, optional) – The margin around the widget.
- **font_family** (*See Below, optional*) – The font family to be used. Example options

```
{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace',
 'helvetica'}
```

- **font_size** (*int*, optional) – The font size.

- **font_style** ({'normal','italic','oblique'}, optional) – The font style.
- **font_weight** (*See Below, optional*) – The font weight. Example options

```
{'ultralight', 'light', 'normal', 'regular', 'book', 'medium',
 'roman', 'semibold', 'demibold', 'demi', 'bold', 'heavy',
 'extra bold', 'black'}
```

ChannelOptionsWidget

class menpo.visualize.widgets.**ChannelOptionsWidget**(*channel_options*, *render_function=None*, *style='minimal'*)

Bases: FlexBox

Creates a widget for selecting channel options when rendering an image. The widget consists of the following parts from *IPython.html.widgets*:

No	Object	Variable (*self.*)	Description
1	RadioButtons	*mode_radiobuttons*	The mode selector 'Single' or 'Multiple'
2	Checkbox	*masked_checkbox*	Controls masked mode
3	IntSlider	*single_slider*	Single channel selector
4	IntRangeSlider	*multiple_slider*	Channels range selector
5	Checkbox	*rgb_checkbox*	View as RGB
6	Checkbox	*sum_checkbox*	View sum of channels
7	Checkbox	*glyph_checkbox*	View glyph
8	BoundedIntText	*glyph_block_size_text*	Glyph block size
9	Checkbox	*glyph_use_negative_checkbox*	Use negative values
10	VBox	*glyph_options_box*	Contains 8, 9
11	VBox	*glyph_box*	Contains 7, 10
12	HBox	*multiple_options_box*	Contains 6, 11, 5
13	Box	*sliders_box*	Contains 3, 4
14	Box	*sliders_and_multiple_options_box*	Contains 13, 12
15	VBox	*mode_and_masked_box*	Contains 1, 2

Note that:

- The selected values are stored in the `self.selected_values` *dict*.
- To set the styling please refer to the `style()` and `predefined_style()` methods.
- To update the state of the widget, please refer to the `set_widget_state()` method.
- To update the callback function please refer to the `replace_render_function()` method.

Parameters

- **channel_options** (*dict*) – The dictionary with the initial options. For example

```
channel_options = {'n_channels': 10,
                   'image_is_masked': True,
                   'channels': 0,
                   'glyph_enabled': False,
                   'glyph_block_size': 3,
                   'glyph_use_negative': False,
                   'sum_enabled': False,
                   'masked_enabled': True}
```

- **render_function** (*function* or None, optional) – The render function that is executed when a widgets' value changes. If None, then nothing is assigned.

- **style** (*See Below, optional*) – Sets a predefined style at the widget. Possible options are

Style	Description
'minimal'	Simple black and white style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	No style

Example

Let's create a channels widget and then update its state. Firstly, we need to import it:

```
>>> from menpo.visualize.widgets import ChannelOptionsWidget
>>> from IPython.display import display
```

Now let's define a render function that will get called on every widget change and will dynamically print the selected channels and masked flag:

```
>>> from menpo.visualize import print_dynamic
>>> def render_function(name, value):
>>>     s = "Channels: {}, Masked: {}".format(
>>>         wid.selected_values['channels'],
>>>         wid.selected_values['masked_enabled'])
>>>     print_dynamic(s)
```

Create the widget with some initial options and display it:

```
>>> channel_options = {'n_channels': 30,
>>>                    'image_is_masked': True,
>>>                    'channels': [0, 10],
>>>                    'glyph_enabled': False,
>>>                    'glyph_block_size': 3,
>>>                    'glyph_use_negative': False,
>>>                    'sum_enabled': True,
>>>                    'masked_enabled': True}
>>> wid = ChannelOptionsWidget(channel_options,
>>>                            render_function=render_function,
>>>                            style='warning')
>>> display(wid)
```

By playing around with the widget, printed message gets updated. Finally, let's change the widget status with a new dictionary of options:

```
>>> new_options = {'n_channels': 10,
>>>                'image_is_masked': True,
>>>                'channels': [7, 8, 9],
>>>                'glyph_enabled': True,
>>>                'glyph_block_size': 3,
>>>                'glyph_use_negative': True,
>>>                'sum_enabled': False,
>>>                'masked_enabled': False}
>>> wid.set_widget_state(new_options, allow_callback=False)
```

add_render_function(*render_function*)

Method that adds a *render_function()* to the widget. The signature of the given function is also stored in *self._render_function*.

Parameters **render_function** (*function* or `None`, optional) – The render function that behaves as a callback. If `None`, then nothing is added.

predefined_style(*style*)

Function that sets a predefined style on the widget.

Parameters **style** (*str* (see below)) – Style options

Style	Description
'minimal'	Simple black and white style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	No style

remove_render_function()

Method that removes the current *self._render_function()* from the widget and sets `self._render_function = None`.

replace_render_function(*render_function*)

Method that replaces the current *self._render_function()* of the widget with the given *render_function()*.

Parameters **render_function** (*function* or `None`, optional) – The render function that behaves as a callback. If `None`, then nothing is happening.

set_widget_state(*channel_options*, *allow_callback=True*)

Method that updates the state of the widget with a new set of values.

Parameters

- **channel_options** (*dict*) – The dictionary with the new options to be used. For example

```
channel_options = {'n_channels': 10,
                   'image_is_masked': True,
                   'channels': 0,
                   'glyph_enabled': False,
                   'glyph_block_size': 3,
                   'glyph_use_negative': False,
                   'sum_enabled': False,
                   'masked_enabled': True}
```

- **allow_callback** (*bool*, optional) – If `True`, it allows triggering of any callback functions.

style(*box_style=None*, *border_visible=False*, *border_color='black'*, *border_style='solid'*, *border_width=1*, *border_radius=0*, *padding=0*, *margin=0*, *font_family=''*, *font_size=None*, *font_style=''*, *font_weight=''*, *slider_width=''*, *slider_colour=''*)

Function that defines the styling of the widget.

Parameters

- **box_style** (*See Below, optional*) – Style options

Style	Description
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	Default style
None	No style

- **border_visible** (*bool*, optional) – Defines whether to draw the border line around the widget.
- **border_color** (*str*, optional) – The color of the border around the widget.
- **border_style** (*str*, optional) – The line style of the border around the widget.
- **border_width** (*float*, optional) – The line width of the border around the widget.
- **border_radius** (*float*, optional) – The radius of the corners of the box.
- **padding** (*float*, optional) – The padding around the widget.
- **margin** (*float*, optional) – The margin around the widget.
- **font_family** (*See Below, optional*) – The font family to be used. Example options

```
{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace',
 'helvetica'}
```

- **font_size** (*int*, optional) – The font size.
- **font_style** ({'normal','italic','oblique'}, optional) – The font style.
- **font_weight** (*See Below, optional*) – The font weight. Example options

```
{'ultralight', 'light', 'normal', 'regular', 'book', 'medium',
 'roman', 'semibold', 'demibold', 'demi', 'bold', 'heavy',
 'extra bold', 'black'}
```

- **slider_width** (*str*, optional) – The width of the slider.
- **slider_colour** (*str*, optional) – The colour of the sliders.

LandmarkOptionsWidget

class menpo.visualize.widgets.**LandmarkOptionsWidget**(*landmark_options*, *render_function=None*, *update_function=None*, *style='minimal'*)

Bases: FlexBox

Creates a widget for animating through a list of objects. The widget consists of the following parts from *IPython.html.widgets*:

No	Object	Variable (*self.*)	Description
1	Latex	*no_landmarks_msg*	Message in case there are no landmarks available.
2	Checkbox	*render_landmarks_checkbox*	Render landmarks
3	Box	*landmarks_checkbox_and_msg_box*	Contains 2, 1
4	Dropdown	*group_dropdown*	Landmark group selector
5	ToggleButtons	*labels_toggles*	*list* of *lists* with the labels per group
6	Latex	*labels_text*	Labels title text
7	HBox	*labels_box*	Contains all 5
8	HBox	*labels_and_text_box*	Contains 6, 7
9	VBox	*group_and_labels_and_text_box*	Contains 4, 8

Note that:

- The selected values are stored in the `self.selected_values` *dict*.
- To set the styling please refer to the `style()` and `predefined_style()` methods.
- To update the state of the widget, please refer to the `set_widget_state()` method.

- To update the callback function please refer to the `replace_render_function()` and `replace_update_function()` methods.

Parameters

- **`landmark_options`** (*dict*) – The dictionary with the initial options. For example

```
landmark_options = {'has_landmarks': True,
                    'render_landmarks': True,
                    'group_keys': ['PTS', 'ibug_face_68'],
                    'labels_keys': [['all'], ['jaw', 'eye']],
                    'group': 'PTS',
                    'with_labels': ['all']}
```

- **`render_function`** (*function* or `None`, optional) – The render function that is executed when a widgets' value changes. If `None`, then nothing is assigned.
- **`update_function`** (*function* or `None`, optional) – The update function that is executed when the index value changes. If `None`, then nothing is assigned.
- **`style`** (*str* (see below)) – Sets a predefined style at the widget. Possible options are

Style	Description
'minimal'	Simple black and white style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	No style

Example

Let's create a landmarks widget and then update its state. Firstly, we need to import it:

```
>>> from from menpo.visualize.widgets import LandmarkOptionsWidget
>>> from IPython.display import display
```

Now let's define a render function that will get called on every widget change and will dynamically print the selected index:

```
>>> from menpo.visualize import print_dynamic
>>> def render_function(name, value):
>>>     s = "Group: {}, Labels: {}".format(
>>>         wid.selected_values['group'],
>>>         wid.selected_values['with_labels'])
>>>     print_dynamic(s)
```

Create the widget with some initial options and display it:

```
>>> landmark_options = {'has_landmarks': True,
>>>                     'render_landmarks': True,
>>>                     'group_keys': ['PTS', 'ibug_face_68'],
>>>                     'labels_keys': [['all'], ['jaw', 'eye', 'mouth']],
>>>                     'group': 'ibug_face_68',
>>>                     'with_labels': ['eye', 'jaw', 'mouth']}
>>> wid = LandmarkOptionsWidget(landmark_options,
>>>                             render_function=render_function,
>>>                             style='danger')
>>> display(wid)
```

By playing around with the widget, the printed message gets updated. Finally, let's change the widget status with a new dictionary of options:

```
>>> new_options = {'has_landmarks': True,
>>>                 'render_landmarks': True,
>>>                 'group_keys': ['new_group'],
>>>                 'labels_keys': [['1', '2', '3']],
>>>                 'group': 'new_group',
>>>                 'with_labels': None}
>>> wid.set_widget_state(new_options, allow_callback=False)
```

---

add_render_function(*render_function*)

Method that adds a *render_function()* to the widget. The signature of the given function is also stored in *self._render_function*.

Parameters **render_function** (*function* or `None`, optional) – The render function that behaves as a callback. If `None`, then nothing is added.

add_update_function(*update_function*)

Method that adds an *update_function()* to the widget. The signature of the given function is also stored in *self._update_function*.

Parameters **update_function** (*function* or `None`, optional) – The update function that behaves as a callback. If `None`, then nothing is added.

predefined_style(*style*)

Function that sets a predefined style on the widget.

Parameters **style** (*str* (see below)) – Style options

Style	Description
'minimal'	Simple black and white style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	No style

remove_render_function()

Method that removes the current *self._render_function()* from the widget and sets `self._render_function = None`.

remove_update_function()

Method that removes the current *self._update_function()* from the widget and sets `self._update_function = None`.

replace_render_function(*render_function*)

Method that replaces the current *self._render_function()* of the widget with the given *render_function()*.

Parameters **render_function** (*function* or `None`, optional) – The render function that behaves as a callback. If `None`, then nothing is happening.

replace_update_function(*update_function*)

Method that replaces the current *self._update_function()* of the widget with the given *update_function()*.

Parameters **update_function** (*function* or `None`, optional) – The update function that behaves as a callback. If `None`, then nothing is happening.

set_widget_state(*landmark_options*, *allow_callback=True*)

Method that updates the state of the widget with a new set of values.

Parameters

- **landmark_options** (*dict*) – The dictionary with the new options to be used. For example

```
landmark_options = {'has_landmarks': True,
                    'render_landmarks': True,
                    'group_keys': ['PTS', 'ibug_face_68'],
                    'labels_keys': [['all'], ['jaw', 'eye']],
                    'group': 'PTS',
                    'with_labels': ['all']}
```

- **allow_callback** (*bool*, optional) – If `True`, it allows triggering of any callback functions.

style(*box_style=None*, *border_visible=False*, *border_color='black'*, *border_style='solid'*, *border_width=1*, *border_radius=0*, *padding=0*, *margin=0*, *font_family=''*, *font_size=None*, *font_style=''*, *font_weight=''*, *labels_buttons_style=''*)

Function that defines the styling of the widget.

Parameters

- **box_style** (*See Below, optional*) – Style options

Style	Description
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	Default style
None	No style

- **border_visible** (*bool*, optional) – Defines whether to draw the border line around the widget.
- **border_color** (*str*, optional) – The color of the border around the widget.
- **border_style** (*str*, optional) – The line style of the border around the widget.
- **border_width** (*float*, optional) – The line width of the border around the widget.
- **border_radius** (*float*, optional) – The radius of the corners of the box.
- **padding** (*float*, optional) – The padding around the widget.
- **margin** (*float*, optional) – The margin around the widget.
- **font_family** (*See Below, optional*) – The font family to be used. Example options

```
{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace',
 'helvetica'}
```

- **font_size** (*int*, optional) – The font size.
- **font_style** ({`'normal','italic','oblique'`}, optional) – The font style.
- **font_weight** (*See Below, optional*) – The font weight. Example options

```
{'ultralight', 'light', 'normal', 'regular', 'book', 'medium',
 'roman', 'semibold', 'demibold', 'demi', 'bold', 'heavy',
 'extra bold', 'black'}
```

- **labels_buttons_style** (*See Below, optional*) – Style options

Style	Description
'primary'	Blue-based style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	Default style
None	No style

RendererOptionsWidget

class `menpo.visualize.widgets.`**`RendererOptionsWidget`**(*renderer_options*, *options_tabs*, *objects_names=None*, *labels_per_object=None*, *selected_object=0*, *object_selection_dropdown_visible=True*, *render_function=None*, *style='minimal'*, *tabs_style='minimal'*)

Bases: `FlexBox`

Creates a widget for selecting rendering options. The widget consists of the following parts from *IPython.html.widgets* and *menpo.visualize.widgets.tools*:

No	Object	Variable (*self.*)	Description
1	Dropdown	*object_selection_dropdown*	The object selector
2	LineOptionsWidget MarkerOptionsWidget ImageOptionsWidget NumberingOptionsWidget FigureOptionsWidget LegendOptionsWidget GridOptionsWidget	*options_widgets*	*list* with the various rendering sub-options widgets
3	Tab	*suboptions_tab*	Contains all 2

Note that:

- The selected values are stored in the `self.selected_values` *dict*.
- To set the styling please refer to the `style()` and `predefined_style()` methods.
- To update the state of the widget, please refer to the `set_widget_state()` method.
- To update the callback function please refer to the `replace_render_function()` methods.

Parameters

- **`renderer_options`** (*list* of *dict*) – The initial rendering options per object. The *list* must have length *n_objects* and contain a *dict* of rendering options per object. For example, in case we had two objects to render

```
lines_options = {'render_lines': True,
                 'line_width': 1,
                 'line_colour': ['b', 'r'],
                 'line_style': '-'}
markers_options = {'render_markers': True,
                   'marker_size': 20,
```

```
                        'marker_face_colour': ['w', 'w'],
                        'marker_edge_colour': ['b', 'r'],
                        'marker_style': 'o',
                        'marker_edge_width': 1}
numbering_options = {'render_numbering': True,
                     'numbers_font_name': 'serif',
                     'numbers_font_size': 10,
                     'numbers_font_style': 'normal',
                     'numbers_font_weight': 'normal',
                     'numbers_font_colour': ['k'],
                     'numbers_horizontal_align': 'center',
                     'numbers_vertical_align': 'bottom'}
legend_options = {'render_legend': True,
                  'legend_title': '',
                  'legend_font_name': 'serif',
                  'legend_font_style': 'normal',
                  'legend_font_size': 10,
                  'legend_font_weight': 'normal',
                  'legend_marker_scale': 1.,
                  'legend_location': 2,
                  'legend_bbox_to_anchor': (1.05, 1.),
                  'legend_border_axes_pad': 1.,
                  'legend_n_columns': 1,
                  'legend_horizontal_spacing': 1.,
                  'legend_vertical_spacing': 1.,
                  'legend_border': True,
                  'legend_border_padding': 0.5,
                  'legend_shadow': False,
                  'legend_rounded_corners': True}
figure_options = {'x_scale': 1.,
                  'y_scale': 1.,
                  'render_axes': True,
                  'axes_font_name': 'serif',
                  'axes_font_size': 10,
                  'axes_font_style': 'normal',
                  'axes_font_weight': 'normal',
                  'axes_x_limits': None,
                  'axes_y_limits': None}
grid_options = {'render_grid': True,
                'grid_line_style': '--',
                'grid_line_width': 0.5}
image_options = {'alpha': 1.,
                 'interpolation': 'bilinear',
                 'cmap_name': 'gray'}
rendering_dict = {'lines': lines_options,
                  'markers': markers_options,
                  'numbering': numbering_options,
                  'legend': legend_options,
                  'figure': figure_options,
                  'grid': grid_options,
                  'image': image_options}
renderer_options = [rendering_dict, rendering_dict]
```

- **options_tabs** (*list* of *str*) – *List* that defines the ordering of the options tabs. Possible values are

Value	Returned class
'lines'	*LineOptionsWidget*
'markers'	*MarkerOptionsWidget*
'numbering'	*NumberingOptionsWidget*
'figure_one'	*FigureOptionsOneScaleWidget*
'figure_two'	*FigureOptionsTwoScalesWidget*
'legend'	*LegendOptionsWidget*
'grid'	*GridOptionsWidget*
'image'	*ImageOptionsWidget*

- **objects_names** (*list* of *str* or `None`, optional) – A *list* with the names of the objects that will be used in the selection dropdown menu. If `None`, then the names will have the format `%d`.
- **labels_per_object** (*list* of *list* or `None`, optional) – A *list* that contains a *list* of labels for each object. Those *labels* are employed by the *ColourSelectionWidget*. An example for which this option is useful is in the case we wish to create rendering options for multiple `LandmarkGroup` objects and each one of them has a different set of *labels*. If `None`, then *labels_per_object* is a *list* of length *n_objects* with `None`.
- **selected_object** (*int*, optional) – The object for which to show the rendering options in the beginning, when the widget is created.
- **object_selection_dropdown_visible** (*bool*, optional) – Controls the visibility of the object selection dropdown (*self.object_selection_dropdown*).
- **render_function** (*function* or `None`, optional) – The render function that is executed when a widgets' value changes. If `None`, then nothing is assigned.
- **style** (*See Below, optional*) – Sets a predefined style at the widget. Possible options are

Style	Description
'minimal'	Simple black and white style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	No style

- **tabs_style** (*See Below, optional*) – Sets a predefined style at the tabs of the widget. Possible options are

Style	Description
'minimal'	Simple black and white style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	No style

Example

Let's create a rendering options widget and then update its state. Firstly, we need to import it:

```
>>> from menpo.visualize.widgets import RendererOptionsWidget
>>> from IPython.display import display
```

Let's set some initial options:

```
>>> options_tabs = ['markers', 'lines', 'grid']
>>> objects_names = ['james', 'patrick']
>>> labels_per_object = [['jaw', 'eyes'], None]
```

```
>>> selected_object = 1
>>> object_selection_dropdown_visible = True
```

Now let's define a render function that will get called on every widget change and will dynamically print the selected marker face colour for both objects:

```
>>> from menpo.visualize import print_dynamic
>>> def render_function(name, value):
>>>     s = "{}: {}, {}: {}".format(
>>>         wid.objects_names[0],
>>>         wid.selected_values[0]['markers']['marker_face_colour'],
>>>         wid.objects_names[1],
>>>         wid.selected_values[1]['markers']['marker_face_colour'])
>>>     print_dynamic(s)
```

Create the widget with some initial options and display it:

```
>>> # 1st dictionary
>>> markers_options = {'render_markers': True, 'marker_size': 20,
>>>                    'marker_face_colour': ['w', 'w'],
>>>                    'marker_edge_colour': ['b', 'r'],
>>>                    'marker_style': 'o', 'marker_edge_width': 1}
>>> lines_options = {'render_lines': True, 'line_width': 1,
>>>                  'line_colour': ['b', 'r'], 'line_style': '-'}
>>> grid_options = {'render_grid': True, 'grid_line_style': '--',
>>>                 'grid_line_width': 0.5}
>>> rendering_dict_1 = {'lines': lines_options, 'grid': grid_options,
>>>                     'markers': markers_options}
>>>
>>> # 2nd dictionary
>>> markers_options = {'render_markers': True, 'marker_size': 200,
>>>                    'marker_face_colour': [[0.1, 0.2, 0.3]],
>>>                    'marker_edge_colour': ['m'], 'marker_style': 'x',
>>>                    'marker_edge_width': 1}
>>> lines_options = {'render_lines': True, 'line_width': 100,
>>>                  'line_colour': [[0.1, 0.2, 0.3]], 'line_style': '-'}
>>> grid_options = {'render_grid': False, 'grid_line_style': '--',
>>>                 'grid_line_width': 0.5}
>>> rendering_dict_2 = {'lines': lines_options, 'grid': grid_options,
>>>                     'markers': markers_options}
>>>
>>> # Final list
>>> rendering_options = [rendering_dict_1, rendering_dict_2]
>>>
>>> # Create and display widget
>>> wid = AnimationOptionsWidget(index, index_style='buttons',
>>>                              render_function=render_function,
>>>                              style='info')
>>> display(wid)
```

By playing around, the printed message gets updated. The style of the widget can be changed as:

```
>>> wid.predefined_style('minimal', 'info')
```

Finally, let's change the widget status with a new dictionary of options:

```
>>> # 1st dictionary
>>> markers_options = {'render_markers': False, 'marker_size': 20,
>>>                    'marker_face_colour': ['k'],
>>>                    'marker_edge_colour': ['c'],
>>>                    'marker_style': 'o', 'marker_edge_width': 1}
>>> lines_options = {'render_lines': False, 'line_width': 1,
>>>                  'line_colour': ['r'], 'line_style': '-'}
>>> grid_options = {'render_grid': True, 'grid_line_style': '--',
>>>                 'grid_line_width': 0.5}
>>> rendering_dict_1 = {'lines': lines_options, 'grid': grid_options,
>>>                     'markers': markers_options}
>>>
>>> # 2nd dictionary
>>> markers_options = {'render_markers': True, 'marker_size': 200,
>>>                    'marker_face_colour': [[0.123, 0.234, 0.345], 'r'],
>>>                    'marker_edge_colour': ['m', 'm'],
>>>                    'marker_style': 'x', 'marker_edge_width': 1}
>>> lines_options = {'render_lines': True, 'line_width': 100,
>>>                  'line_colour': [[0.1, 0.2, 0.3], 'b'], 'line_style': '-'}
>>> grid_options = {'render_grid': False, 'grid_line_style': '--',
>>>                 'grid_line_width': 0.5}
>>> rendering_dict_2 = {'lines': lines_options, 'grid': grid_options,
>>>                     'markers': markers_options}
>>>
>>> # Final list
>>> new_options = [rendering_dict_1, rendering_dict_2]
>>>
>>> # Set new labels per object
>>> labels_per_object = [['1'], ['jaw', 'eyes']]
>>>
>>> # Update widget state
>>> wid.set_widget_state(new_options, labels_per_object,
>>>                      allow_callback=True)
```

---

add_render_function(*render_function*)

Method that adds a *render_function()* to the widget. The signature of the given function is also stored in *self._render_function*.

Parameters **render_function** (*function* or `None`, optional) – The render function that behaves as a callback. If `None`, then nothing is added.

predefined_style(*style*, *tabs_style='minimal'*)

Function that sets a predefined style on the widget.

Parameters

- **style** (*str* (see below)) – Style options

Style	Description
'minimal'	Simple black and white style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	No style

- **tabs_style** (*str* (see below), optional) – Style options

Style	Description
'minimal'	Simple black and white style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	No style

remove_render_function()

Method that removes the current *self._render_function()* from the widget and sets `self._render_function = None`.

replace_render_function(*render_function*)

Method that replaces the current *self._render_function()* of the widget with the given *render_function()*.

Parameters

render_function (*function* or `None`, optional) – The render function that behaves as a callback. If `None`, then nothing is happening.

set_widget_state(*renderer_options*, *labels_per_object*, *selected_object=None*, *object_selection_dropdown_visible=None*, *allow_callback=True*)

Method that updates the state of the widget with a new set of values. Note that the number of objects should not change.

Parameters

- **renderer_options** (*list* of *dict*) – The selected rendering options per object. The *list* must have length *n_objects* and contain a *dict* of rendering options per object. For example, in case we had two objects to render

```
lines_options = {'render_lines': True,
                 'line_width': 1,
                 'line_colour': ['b', 'r'],
                 'line_style': '-'}
markers_options = {'render_markers': True,
                   'marker_size': 20,
                   'marker_face_colour': ['w', 'w'],
                   'marker_edge_colour': ['b', 'r'],
                   'marker_style': 'o',
                   'marker_edge_width': 1}
numbering_options = {'render_numbering': True,
                     'numbers_font_name': 'serif',
                     'numbers_font_size': 10,
                     'numbers_font_style': 'normal',
                     'numbers_font_weight': 'normal',
                     'numbers_font_colour': ['k'],
                     'numbers_horizontal_align': 'center',
                     'numbers_vertical_align': 'bottom'}
legend_options = {'render_legend': True,
                  'legend_title': '',
                  'legend_font_name': 'serif',
                  'legend_font_style': 'normal',
                  'legend_font_size': 10,
                  'legend_font_weight': 'normal',
                  'legend_marker_scale': 1.,
                  'legend_location': 2,
                  'legend_bbox_to_anchor': (1.05, 1.),
                  'legend_border_axes_pad': 1.,
                  'legend_n_columns': 1,
                  'legend_horizontal_spacing': 1.,
                  'legend_vertical_spacing': 1.,
                  'legend_border': True,
```

```
                                 'legend_border_padding': 0.5,
                                 'legend_shadow': False,
                                 'legend_rounded_corners': True}
                figure_options = {'x_scale': 1.,
                                  'y_scale': 1.,
                                  'render_axes': True,
                                  'axes_font_name': 'serif',
                                  'axes_font_size': 10,
                                  'axes_font_style': 'normal',
                                  'axes_font_weight': 'normal',
                                  'axes_x_limits': None,
                                  'axes_y_limits': None}
                grid_options = {'render_grid': True,
                                'grid_line_style': '--',
                                'grid_line_width': 0.5}
                image_options = {'alpha': 1.,
                                 'interpolation': 'bilinear',
                                 'cmap_name': 'gray'}
                rendering_dict = {'lines': lines_options,
                                  'markers': markers_options,
                                  'numbering': numbering_options,
                                  'legend': legend_options,
                                  'figure': figure_options,
                                  'grid': grid_options
                                  'image': image_options}
                renderer_options = [rendering_dict, rendering_dict]
```

- **labels_per_object** (*list* of *list* or `None`, optional) – A *list* that contains a *list* of labels for each object. Those *labels* are employed by the *ColourSelectionWidget*. An example for which this option is useful is in the case we wish to create rendering options for multiple `LandmarkGroup` objects and each one of them has a different set of *labels*. If `None`, then *labels_per_object* is a *list* of lenth *n_objects* with `None`.
- **selected_object** (*int*, optional) – The object for which to show the rendering options in the beginning, when the widget is created.
- **object_selection_dropdown_visible** (*bool*, optional) – Controls the visibility of the object selection dropdown (*self.object_selection_dropdown*).
- **allow_callback** (*bool*, optional) – If `True`, it allows triggering of any callback functions.

style(*box_style=None*, *border_visible=False*, *border_color='black'*, *border_style='solid'*, *border_width=1*, *border_radius=0*, *padding='0.2cm'*, *margin=0*, *tabs_box_style=None*, *tabs_border_visible=True*, *tabs_border_color='black'*, *tabs_border_style='solid'*, *tabs_border_width=1*, *tabs_border_radius=1*, *tabs_padding=0*, *tabs_margin=0*, *font_family=''*, *font_size=None*, *font_style=''*, *font_weight=''*)

Function that defines the styling of the widget.

Parameters

- **box_style** (*See Below, optional*) – Style options

Style	Description
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	Default style
None	No style

- **border_visible** (*bool*, optional) – Defines whether to draw the border line

around the widget.

- **border_color** (*str*, optional) – The color of the border around the widget.
- **border_style** (*str*, optional) – The line style of the border around the widget.
- **border_width** (*float*, optional) – The line width of the border around the widget.
- **border_radius** (*float*, optional) – The radius of the corners of the box.
- **padding** (*float*, optional) – The padding around the widget.
- **margin** (*float*, optional) – The margin around the widget.
- **tabs_box_style** (*See Below, optional*) – Style options

Style	Description
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	Default style
None	No style

- **tabs_border_visible** (*bool*, optional) – Defines whether to draw the border line around the tab widgets.
- **tabs_border_color** (*str*, optional) – The color of the border around the tab widgets.
- **tabs_border_style** (*str*, optional) – The line style of the border around the tab widgets.
- **tabs_border_width** (*float*, optional) – The line width of the border around the tab widgets.
- **tabs_border_radius** (*float*, optional) – The radius of the corners of the box of the tab widgets.
- **tabs_padding** (*float*, optional) – The padding around the tab widgets.
- **tabs_margin** (*float*, optional) – The margin around the tab widgets.
- **font_family** (*See Below, optional*) – The font family to be used. Example options

```
{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace',
 'helvetica'}
```

- **font_size** (*int*, optional) – The font size.
- **font_style** ({'normal','italic','oblique'}, optional) – The font style.
- **font_weight** (*See Below, optional*) – The font weight. Example options

```
{'ultralight', 'light', 'normal', 'regular', 'book', 'medium',
 'roman', 'semibold', 'demibold', 'demi', 'bold', 'heavy',
 'extra bold', 'black'}
```

update_object_names(*objects_names*)

Method that updates the options in the dropdown menu for selecting an object. Note that the number of objects should not change.

Parameters **objects_names** (*list* of *str*) – A *list* with the names of the objects that will be used in the selection dropdown menu.

GraphOptionsWidget

class `menpo.visualize.widgets.`**`GraphOptionsWidget`**(*graph_options*, *x_slider_options*, *y_slider_options*, *renderer_function=None*, *style='minimal'*, *tabs_style='minimal'*, *renderer_tabs_style='minimal'*)

Bases: `FlexBox`

Creates a widget for selecting options for rendering various curves in a graph. The widget consists of the following parts from *IPython.html.widgets* and *menpo.visualize.widgets.tools*:

No	Object	Variable (*self.*)	Description
1	RendererOptionsWidget	*renderer_widget*	The rendering widget
2	FloatRangeSlider	*x_limit*	Sets the x limit
3	FloatRangeSlider	*y_limit*	Sets the y limit
4	Text	*x_label*	Sets the x label
5	Text	*y_label*	Sets the y label
6	Text	*title*	Sets the title
7	Textarea	*legend_entries*	Sets the legend entries
8	VBox	*graph_related_options*	Contains 2 - 7
9	Tab	*options_tab*	Contains 8, 1

Note that:

- The selected values are stored in the `self.selected_values` *dict*.
- To set the styling please refer to the `style()` and `predefined_style()` methods.
- To update the state of the widget, please refer to the `set_widget_state()` method.
- To update the callback function please refer to the `replace_render_function()` methods.

Parameters

- **`graph_options`** (*list* of *str*) – The initial options. For example, in case we had two curves to render

```
graph_options = {'legend_entries': ['Nontas', 'Leda'],
                 'x_label': 'X',
                 'y_label': 'Y',
                 'title': 'TITLE',
                 'x_axis_limits': (2, 7),
                 'y_axis_limits': (-0.2, 0.2),
                 'render_lines': [True, True],
                 'line_colour': ['r', 'b'],
                 'line_style': ['--', '-'],
                 'line_width': [1, 3],
                 'render_markers': [True, False],
                 'marker_style': ['o', 's'],
                 'marker_size': [6, 12],
                 'marker_face_colour': ['k', 'm'],
                 'marker_edge_colour': ['w', 'c'],
                 'marker_edge_width': [1, 4],
                 'render_legend': True,
                 'legend_title': '',
                 'legend_font_name': 'sans-serif',
                 'legend_font_style': 'normal',
                 'legend_font_size': 10,
                 'legend_font_weight': 'normal',
                 'legend_marker_scale': 1.,
                 'legend_location': 2,
```

```
                                        'legend_bbox_to_anchor': (1.05, 1.),
                                        'legend_border_axes_pad': 0.,
                                        'legend_n_columns': 1,
                                        'legend_horizontal_spacing': 0,
                                        'legend_vertical_spacing': 0,
                                        'legend_border': True,
                                        'legend_border_padding': 0,
                                        'legend_shadow': False,
                                        'legend_rounded_corners': False,
                                        'render_axes': True,
                                        'axes_font_name': 'sans-serif',
                                        'axes_font_size': 10,
                                        'axes_font_style': 'normal',
                                        'axes_font_weight': 'normal',
                                        'figure_size': (10, 8),
                                        'render_grid': True,
                                        'grid_line_style': '--',
                                        'grid_line_width': 1}
```

- **x_slider_options** ((*float*, *float*, *float*)) – The attributes of the x limit slider in the form (*min*, *max*, *step*).
- **y_slider_options** ((*float*, *float*, *float*)) – The attributes of the y limit slider in the form (*min*, *max*, *step*).
- **render_function** (*function* or `None`, optional) – The render function that is executed when a widgets' value changes. If `None`, then nothing is assigned.
- **style** (*See Below, optional*) – Sets a predefined style at the widget. Possible options are

Style	Description
'minimal'	Simple black and white style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	No style

- **tabs_style** (*See Below, optional*) – Sets a predefined style at the tabs of the widget. Possible options are

Style	Description
'minimal'	Simple black and white style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	No style

- **renderer_tabs_style** (*See Below, optional*) – Sets a predefined style at the tabs of the renderer widget. Possible options are

Style	Description
'minimal'	Simple black and white style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	No style

add_render_function(*render_function*)

Method that adds a *render_function()* to the widget. The signature of the given function is also stored in

self._render_function.

Parameters **render_function** (*function* or `None`, optional) – The render function that behaves as a callback. If `None`, then nothing is added.

predefined_style(*style*, *tabs_style='minimal'*, *renderer_tabs_style='mininal'*)

Function that sets a predefined style on the widget.

Parameters

- **style** (*str* (see below)) – Style options

Style	Description
'minimal'	Simple black and white style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	No style

- **tabs_style** (*str* (see below), optional) – Style options

Style	Description
'minimal'	Simple black and white style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	No style

- **renderer_tabs_style** (*str* (see below), optional) – Style options

Style	Description
'minimal'	Simple black and white style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	No style

remove_render_function()

Method that removes the current *self._render_function()* from the widget and sets `self._render_function = None`.

replace_render_function(*render_function*)

Method that replaces the current *self._render_function()* of the widget with the given *render_function()*.

Parameters **render_function** (*function* or `None`, optional) – The render function that behaves as a callback. If `None`, then nothing is happening.

style(*box_style=None*, *border_visible=False*, *border_color='black'*, *border_style='solid'*, *border_width=1*, *border_radius=0*, *padding='0.2cm'*, *margin=0*, *tabs_box_style=None*, *tabs_border_visible=True*, *tabs_border_color='black'*, *tabs_border_style='solid'*, *tabs_border_width=1*, *tabs_border_radius=1*, *tabs_padding=0*, *tabs_margin=0*, *renderer_tabs_box_style=None*, *renderer_tabs_border_visible=True*, *renderer_tabs_border_color='black'*, *renderer_tabs_border_style='solid'*, *renderer_tabs_border_width=1*, *renderer_tabs_border_radius=1*, *renderer_tabs_padding=0*, *renderer_tabs_margin=0*, *font_family=''*, *font_size=None*, *font_style=''*, *font_weight=''*)

Function that defines the styling of the widget.

Parameters

- **box_style** (*See Below, optional*) – Style options

Style	Description
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	Default style
None	No style

- **`border_visible`** (*bool*, optional) – Defines whether to draw the border line around the widget.
- **`border_color`** (*str*, optional) – The color of the border around the widget.
- **`border_style`** (*str*, optional) – The line style of the border around the widget.
- **`border_width`** (*float*, optional) – The line width of the border around the widget.
- **`border_radius`** (*float*, optional) – The radius of the corners of the box.
- **`padding`** (*float*, optional) – The padding around the widget.
- **`margin`** (*float*, optional) – The margin around the widget.
- **`tabs_box_style`** (*See Below, optional*) – Style options

Style	Description
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	Default style
None	No style

- **`tabs_border_visible`** (*bool*, optional) – Defines whether to draw the border line around the tab widgets.
- **`tabs_border_color`** (*str*, optional) – The color of the border around the tab widgets.
- **`tabs_border_style`** (*str*, optional) – The line style of the border around the tab widgets.
- **`tabs_border_width`** (*float*, optional) – The line width of the border around the tab widgets.
- **`tabs_border_radius`** (*float*, optional) – The radius of the corners of the box of the tab widgets.
- **`tabs_padding`** (*float*, optional) – The padding around the tab widgets.
- **`tabs_margin`** (*float*, optional) – The margin around the tab widgets.
- **`renderer_tabs_box_style`** (*See Below, optional*) – Style options

Style	Description
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	Default style
None	No style

- **`renderer_tabs_border_visible`** (*bool*, optional) – Defines whether to draw the border line around the tab widgets of the renderer widget.
- **`renderer_tabs_border_color`** (*str*, optional) – The color of the border around the tab widgets of the renderer widget.
- **`renderer_tabs_border_style`** (*str*, optional) – The line style of the border around the tab widgets of the renderer widget.
- **`renderer_tabs_border_width`** (*float*, optional) – The line width of the border around the tab widgets of the renderer widget.

- **renderer_tabs_border_radius** (*float*, optional) – The radius of the corners of the box of the tab widgets of the renderer widget.
- **renderer_tabs_padding** (*float*, optional) – The padding around the tab widgets of the renderer widget.
- **renderer_tabs_margin** (*float*, optional) – The margin around the tab widgets of the renderer widget.
- **font_family** (*See Below, optional*) – The font family to be used. Example options

```
{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace',
 'helvetica'}
```

- **font_size** (*int*, optional) – The font size.
- **font_style** ({'normal','italic','oblique'}, optional) – The font style.
- **font_weight** (*See Below, optional*) – The font weight. Example options

```
{'ultralight', 'light', 'normal', 'regular', 'book', 'medium',
 'roman', 'semibold', 'demibold', 'demi', 'bold', 'heavy',
 'extra bold', 'black'}
```

SaveFigureOptionsWidget

class menpo.visualize.widgets.**SaveFigureOptionsWidget**(*renderer, file_format='png', dpi=None, orientation='portrait', papertype='letter', transparent=False, facecolour='w', edgecolour='w', pad_inches=0.0, overwrite=False, style='minimal'*)

Bases: FlexBox

Creates a widget for saving a figure to file. The widget consists of the following parts from *IPython.html.widgets* and *menpo.visualize.widgets.tools*:

No	Object	Variable (*self.*)	Description
1	Select	*file_format_select*	Image format selector
2	FloatText	*dpi_text*	DPI selector
3	Dropdown	*orientation_dropdown*	Paper orientation selector
4	Select	*papertype_select*	Paper type selector
5	Checkbox	*transparent_checkbox*	Transparency setter
6	ColourSelectionWidget	*facecolour_widget*	Face colour selector
7	ColourSelectionWidget	*edgecolour_widget*	Edge colour selector
8	FloatText	*pad_inches_text*	Padding in inches setter
9	Text	*filename_text*	Path and filename
10	Checkbox	*overwrite_checkbox*	Overwrite flag
11	Latex	*error_latex*	Error message area
12	Button	*save_button*	Save button
13	VBox	*path_box*	Contains 9, 1, 10, 4
14	VBox	*page_box*	Contains 3, 2, 8
15	VBox	*colour_box*	Contains 6, 7, 5
16	Tab	*options_tabs*	Contains 13, 14, 15
17	HBox	*save_box*	Contains 12, 11
18	VBox	*options_box*	Contains 16, 17

To set the styling please refer to the `style()` and `predefined_style()` methods.

Parameters

- **renderer** (*Renderer* class or subclass) – The renderer object that was used to render the figure.
- **file_format** (*str*, optional) – The initial value of the file format.
- **dpi** (*float* or `None`, optional) – The initial value of the dpi. If `None`, then dpi is set to `0`.
- **orientation** (`{'portrait', 'landscape'}`, optional) – The initial value of the orientation.
- **papertype** (*str*, optional) – The initial value of the paper type. Possible options are

```
{'letter', 'legal', 'executive', 'ledger', 'a0', 'a1', 'a2', 'a3',
 'a4', 'a5', 'a6', 'a7', 'a8', 'a9', 'a10', 'b0', 'b1', 'b2', 'b3',
 'b4', 'b5', 'b6', 'b7', 'b8', 'b9', 'b10'}
```

- **transparent** (*bool*, optional) – The initial value of the transparency flag.
- **facecolour** (*str* or *list* of *float*, optional) – The initial value of the face colour.
- **edgecolour** (*str* or *list* of *float*, optional) – The initial value of the edge colour.
- **pad_inches** (*float*, optional) – The initial value of the figure padding in inches.
- **overwrite** (*bool*, optional) – The initial value of the overwrite flag.
- **style** (*See Below, optional*) – Sets a predefined style at the widget. Possible options are

Style	Description
'minimal'	Simple black and white style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	No style

predefined_style(*style*)

Function that sets a predefined style on the widget.

Parameters

style (*str* (see below)) – Style options

Style	Description
'minimal'	Simple black and white style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	No style

style(*box_style=None*, *border_visible=False*, *border_color='black'*, *border_style='solid'*, *border_width=1*, *border_radius=0*, *padding=0*, *margin=0*, *font_family=''*, *font_size=None*, *font_style=''*, *font_weight=''*)

Function that defines the styling of the widget.

Parameters

- **box_style** (*See Below, optional*) – Style options

Style	Description
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	Default style
None	No style

- **border_visible** (*bool*, optional) – Defines whether to draw the border line around the widget.
- **border_color** (*str*, optional) – The color of the border around the widget.
- **border_style** (*str*, optional) – The line style of the border around the widget.
- **border_width** (*float*, optional) – The line width of the border around the widget.
- **border_radius** (*float*, optional) – The radius of the corners of the box.
- **padding** (*float*, optional) – The padding around the widget.
- **margin** (*float*, optional) – The margin around the widget.
- **font_family** (*See Below, optional*) – The font family to be used. Example options

```
{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace',
 'helvetica'}
```

- **font_size** (*int*, optional) – The font size.
- **font_style** ({'normal','italic','oblique'}, optional) – The font style.
- **font_weight** (*See Below, optional*) – The font weight. Example options

```
{'ultralight', 'light', 'normal', 'regular', 'book', 'medium',
 'roman', 'semibold', 'demibold', 'demi', 'bold', 'heavy',
 'extra bold', 'black'}
```

TextPrintWidget

class `menpo.visualize.widgets.`**`TextPrintWidget`**(*n_lines*, *text_per_line*, *style='minimal'*)

Bases: `FlexBox`

Creates a widget for printing text. Specifically, it consists of a *list* of *IPython.html.widgets.Latex* objects, i.e. one per text line.

Note that:

- To set the styling please refer to the `style()` and `predefined_style()` methods.
- To update the state of the widget, please refer to the `set_widget_state()` method.

Parameters

- **n_lines** (*int*) – The number of lines of the text to be printed.
- **text_per_line** (*list* of length *n_lines*) – The text to be printed per line.
- **style** (*See Below, optional*) – Sets a predefined style at the widget. Possible options are

Style	Description
'minimal'	Simple black and white style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	No style

Example

Let's create an text widget and then update its state. Firstly, we need to import it:

```
>>> from menpo.visualize.widgets import TextPrintWidget
>>> from IPython.display import display
```

Create the widget with some initial options and display it:

```
>>> n_lines = 3
>>> text_per_line = ['> The', '> Menpo', '> Team']
>>> wid = TextPrintWidget(n_lines, text_per_line, style='success')
>>> display(wid)
```

The style of the widget can be changed as:

```
>>> wid.predefined_style('danger')
```

Update the widget state as:

```
>>> wid.set_widget_state(5, ['M', 'E', 'N', 'P', 'O'])
```

---

predefined_style (*style*)

Function that sets a predefined style on the widget.

Parameters

style (*str* (see below)) – Style options

Style	Description
'minimal'	Simple black and white style
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	No style

set_widget_state (*n_lines*, *text_per_line*)

Method that updates the state of the widget with a new set of values.

Parameters

- **n_lines** (*int*) – The number of lines of the text to be printed.
- **text_per_line** (*list* of length *n_lines*) – The text to be printed per line.

style (*box_style=None*, *border_visible=False*, *border_color='black'*, *border_style='solid'*, *border_width=1*, *border_radius=0*, *padding=0*, *margin=0*, *font_family=''*, *font_size=None*, *font_style=''*, *font_weight=''*)

Function that defines the styling of the widget.

Parameters

- **box_style** (*See Below, optional*) – Style options

Style	Description
'success'	Green-based style
'info'	Blue-based style
'warning'	Yellow-based style
'danger'	Red-based style
''	Default style
None	No style

- **border_visible** (*bool*, optional) – Defines whether to draw the border line around the widget.
- **border_color** (*str*, optional) – The color of the border around the widget.
- **border_style** (*str*, optional) – The line style of the border around the widget.
- **border_width** (*float*, optional) – The line width of the border around the widget.
- **border_radius** (*float*, optional) – The radius of the corners of the box.
- **padding** (*float*, optional) – The padding around the widget.

- **margin** (*float*, optional) – The margin around the widget.
- **font_family** (*See Below, optional*) – The font family to be used. Example options

```
{'serif', 'sans-serif', 'cursive', 'fantasy', 'monospace',
 'helvetica'}
```

- **font_size** (*int*, optional) – The font size.
- **font_style** ({'normal','italic','oblique'}, optional) – The font style.
- **font_weight** (*See Below, optional*) – The font weight. Example options

```
{'ultralight', 'light', 'normal', 'regular', 'book', 'medium',
 'roman', 'semibold', 'demibold', 'demi', 'bold', 'heavy',
 'extra bold', 'black'}
```

Symbols

_compose_after_inplace() (menpo.transform.base.composable.ComposableTransform method), 265
_compose_before_inplace() (menpo.transform.base.composable.ComposableTransform method), 265
_transform_inplace() (menpo.transform.base.Transformable method), 264
_view_2d() (menpo.image.Image method), 27
_view_2d() (menpo.image.MaskedImage method), 55
_view_2d() (menpo.shape.ColouredTriMesh method), 188
_view_2d() (menpo.shape.PointCloud method), 118
_view_2d() (menpo.shape.PointDirectedGraph method), 155
_view_2d() (menpo.shape.PointTree method), 168
_view_2d() (menpo.shape.PointUndirectedGraph method), 143
_view_2d() (menpo.shape.TexturedTriMesh method), 197
_view_2d() (menpo.shape.TriMesh method), 179
_view_landmarks_2d() (menpo.image.Image method), 28
_view_landmarks_2d() (menpo.image.MaskedImage method), 55
_view_landmarks_2d() (menpo.shape.ColouredTriMesh method), 189
_view_landmarks_2d() (menpo.shape.PointCloud method), 119
_view_landmarks_2d() (menpo.shape.PointDirectedGraph method), 156
_view_landmarks_2d() (menpo.shape.PointTree method), 169
_view_landmarks_2d() (menpo.shape.PointUndirectedGraph method), 144
_view_landmarks_2d() (menpo.shape.TexturedTriMesh method), 198
_view_landmarks_2d() (menpo.shape.TriMesh method), 180

A

add_render_function() (menpo.visualize.widgets.AnimationOptionsWidget method), 278
add_render_function() (menpo.visualize.widgets.ChannelOptionsWidget method), 281
add_render_function() (menpo.visualize.widgets.GraphOptionsWidget method), 296
add_render_function() (menpo.visualize.widgets.LandmarkOptionsWidget method), 285
add_render_function() (menpo.visualize.widgets.RendererOptionsWidget method), 291
add_update_function() (menpo.visualize.widgets.AnimationOptionsWidget method), 278
add_update_function() (menpo.visualize.widgets.LandmarkOptionsWidget method), 285
Affine (class in menpo.transform), 210
aligned_source() (menpo.transform.AlignmentAffine method), 235
aligned_source() (menpo.transform.AlignmentRotation method), 244
aligned_source() (menpo.transform.AlignmentSimilarity method), 240
aligned_source() (menpo.transform.AlignmentTranslation method), 249
aligned_source() (menpo.transform.AlignmentUniformScale method), 253
aligned_source() (menpo.transform.base.alignment.Alignment method), 268
aligned_source() (menpo.transform.ThinPlateSplines method), 233
Alignment (class in menpo.transform.base.alignment), 267
alignment_error() (menpo.transform.AlignmentAffine method), 235
alignment_error() (menpo.transform.AlignmentRotation method), 244
alignment_error() (menpo.transform.AlignmentSimilarity method), 240
alignment_error() (menpo.transform.AlignmentTranslation method), 249

alignment_error() (menpo.transform.AlignmentUniformScale method), 253
alignment_error() (menpo.transform.base.alignment.Alignment method), 268
alignment_error() (menpo.transform.ThinPlateSplines method), 233
AlignmentAffine (class in menpo.transform), 235
AlignmentRotation (class in menpo.transform), 244
AlignmentSimilarity (class in menpo.transform), 240
AlignmentTranslation (class in menpo.transform), 248
AlignmentUniformScale (class in menpo.transform), 252
all_true() (menpo.image.BooleanImage method), 42
AnimationOptionsWidget (class in menpo.visualize.widgets), 276
apply() (menpo.transform.Affine method), 210
apply() (menpo.transform.AlignmentAffine method), 236
apply() (menpo.transform.AlignmentRotation method), 244
apply() (menpo.transform.AlignmentSimilarity method), 240
apply() (menpo.transform.AlignmentTranslation method), 249
apply() (menpo.transform.AlignmentUniformScale method), 253
apply() (menpo.transform.base.composable.ComposableTransform method), 265
apply() (menpo.transform.Homogeneous method), 207
apply() (menpo.transform.NonUniformScale method), 229
apply() (menpo.transform.R2LogR2RBF method), 259
apply() (menpo.transform.R2LogRRBF method), 261
apply() (menpo.transform.Rotation method), 218
apply() (menpo.transform.Similarity method), 214
apply() (menpo.transform.ThinPlateSplines method), 233
apply() (menpo.transform.Transform method), 263
apply() (menpo.transform.TransformChain method), 257
apply() (menpo.transform.Translation method), 222
apply() (menpo.transform.UniformScale method), 226
apply_inplace() (menpo.transform.Affine method), 211
apply_inplace() (menpo.transform.AlignmentAffine method), 236
apply_inplace() (menpo.transform.AlignmentRotation method), 245
apply_inplace() (menpo.transform.AlignmentSimilarity method), 240
apply_inplace() (menpo.transform.AlignmentTranslation method), 249
apply_inplace() (menpo.transform.AlignmentUniformScale method), 253
apply_inplace() (menpo.transform.base.composable.ComposableTransform method), 265
apply_inplace() (menpo.transform.Homogeneous method), 207
apply_inplace() (menpo.transform.NonUniformScale method), 230
apply_inplace() (menpo.transform.R2LogR2RBF method), 260
apply_inplace() (menpo.transform.R2LogRRBF method), 261
apply_inplace() (menpo.transform.Rotation method), 218
apply_inplace() (menpo.transform.Similarity method), 215
apply_inplace() (menpo.transform.ThinPlateSplines method), 234
apply_inplace() (menpo.transform.Transform method), 263
apply_inplace() (menpo.transform.TransformChain method), 257
apply_inplace() (menpo.transform.Translation method), 222
apply_inplace() (menpo.transform.UniformScale method), 226
as_greyscale() (menpo.image.BooleanImage method), 42
as_greyscale() (menpo.image.Image method), 31
as_greyscale() (menpo.image.MaskedImage method), 59
as_histogram() (menpo.image.BooleanImage method), 42
as_histogram() (menpo.image.Image method), 31
as_histogram() (menpo.image.MaskedImage method), 59
as_masked() (menpo.image.BooleanImage method), 43
as_masked() (menpo.image.Image method), 32
as_masked() (menpo.image.MaskedImage method), 60
as_matrix() (in module menpo.math), 96
as_non_alignment() (menpo.transform.AlignmentAffine method), 236
as_non_alignment() (menpo.transform.AlignmentRotation method), 245
as_non_alignment() (menpo.transform.AlignmentSimilarity method), 240
as_non_alignment() (menpo.transform.AlignmentTranslation method), 249
as_non_alignment() (menpo.transform.AlignmentUniformScale method), 253
as_PILImage() (menpo.image.BooleanImage method), 42
as_PILImage() (menpo.image.Image method), 31
as_PILImage() (menpo.image.MaskedImage method), 59
as_pointgraph() (menpo.shape.ColouredTriMesh method), 192
as_pointgraph() (menpo.shape.TexturedTriMesh method), 201
as_pointgraph() (menpo.shape.TriMesh method), 183
as_unmasked() (menpo.image.MaskedImage method), 60
as_vector() (menpo.base.Vectorizable method), 19
as_vector() (menpo.image.BooleanImage method), 43
as_vector() (menpo.image.Image method), 32
as_vector() (menpo.image.MaskedImage method), 60

as_vector() (menpo.shape.base.Shape method), 117
as_vector() (menpo.shape.ColouredTriMesh method), 193
as_vector() (menpo.shape.PointCloud method), 122
as_vector() (menpo.shape.PointDirectedGraph method), 159
as_vector() (menpo.shape.PointTree method), 172
as_vector() (menpo.shape.PointUndirectedGraph method), 147
as_vector() (menpo.shape.TexturedTriMesh method), 202
as_vector() (menpo.shape.TriMesh method), 184
as_vector() (menpo.transform.Affine method), 211
as_vector() (menpo.transform.AlignmentAffine method), 236
as_vector() (menpo.transform.AlignmentRotation method), 245
as_vector() (menpo.transform.AlignmentSimilarity method), 240
as_vector() (menpo.transform.AlignmentTranslation method), 249
as_vector() (menpo.transform.AlignmentUniformScale method), 253
as_vector() (menpo.transform.Homogeneous method), 207
as_vector() (menpo.transform.NonUniformScale method), 230
as_vector() (menpo.transform.Rotation method), 219
as_vector() (menpo.transform.Similarity method), 215
as_vector() (menpo.transform.Translation method), 223
as_vector() (menpo.transform.UniformScale method), 226
axis_and_angle_of_rotation() (menpo.transform.AlignmentRotation method), 245
axis_and_angle_of_rotation() (menpo.transform.Rotation method), 219

B

BooleanImage (class in menpo.image), 42
boundary_tri_index() (menpo.shape.ColouredTriMesh method), 193
boundary_tri_index() (menpo.shape.TexturedTriMesh method), 202
boundary_tri_index() (menpo.shape.TriMesh method), 184
bounding_box() (menpo.shape.ColouredTriMesh method), 193
bounding_box() (menpo.shape.PointCloud method), 123
bounding_box() (menpo.shape.PointDirectedGraph method), 160
bounding_box() (menpo.shape.PointTree method), 172
bounding_box() (menpo.shape.PointUndirectedGraph method), 148
bounding_box() (menpo.shape.TexturedTriMesh method), 202
bounding_box() (menpo.shape.TriMesh method), 184
bounds() (menpo.shape.ColouredTriMesh method), 193
bounds() (menpo.shape.PointCloud method), 123
bounds() (menpo.shape.PointDirectedGraph method), 160
bounds() (menpo.shape.PointTree method), 172
bounds() (menpo.shape.PointUndirectedGraph method), 148
bounds() (menpo.shape.TexturedTriMesh method), 202
bounds() (menpo.shape.TriMesh method), 184
bounds_false() (menpo.image.BooleanImage method), 43
bounds_true() (menpo.image.BooleanImage method), 43
bu3dfe_83() (in module menpo.landmark), 87
build_mask_around_landmarks() (menpo.image.MaskedImage method), 60
bytes_str() (in module menpo.visualize), 276

C

centre() (menpo.image.BooleanImage method), 44
centre() (menpo.image.Image method), 32
centre() (menpo.image.MaskedImage method), 61
centre() (menpo.shape.ColouredTriMesh method), 193
centre() (menpo.shape.PointCloud method), 123
centre() (menpo.shape.PointDirectedGraph method), 160
centre() (menpo.shape.PointTree method), 172
centre() (menpo.shape.PointUndirectedGraph method), 148
centre() (menpo.shape.TexturedTriMesh method), 202
centre() (menpo.shape.TriMesh method), 184
centre_of_bounds() (menpo.shape.ColouredTriMesh method), 193
centre_of_bounds() (menpo.shape.PointCloud method), 123
centre_of_bounds() (menpo.shape.PointDirectedGraph method), 160
centre_of_bounds() (menpo.shape.PointTree method), 173
centre_of_bounds() (menpo.shape.PointUndirectedGraph method), 148
centre_of_bounds() (menpo.shape.TexturedTriMesh method), 202
centre_of_bounds() (menpo.shape.TriMesh method), 184
ChannelOptionsWidget (class in menpo.visualize.widgets), 280
children() (menpo.shape.DirectedGraph method), 132
children() (menpo.shape.PointDirectedGraph method), 160
children() (menpo.shape.PointTree method), 173
children() (menpo.shape.Tree method), 137
clear() (menpo.landmark.LandmarkGroup method), 81
clear() (menpo.landmark.LandmarkManager method), 80
ColouredTriMesh (class in menpo.shape), 188

component() (menpo.model.InstanceLinearModel method), 100
component() (menpo.model.MeanInstanceLinearModel method), 105
component() (menpo.model.PCAModel method), 108
component_vector() (menpo.model.InstanceLinearModel method), 100
component_vector() (menpo.model.LinearModel method), 98
component_vector() (menpo.model.MeanInstanceLinearModel method), 105
component_vector() (menpo.model.MeanLinearModel method), 103
component_vector() (menpo.model.PCAModel method), 108
components (menpo.model.InstanceLinearModel attribute), 102
components (menpo.model.LinearModel attribute), 100
components (menpo.model.MeanInstanceLinearModel attribute), 107
components (menpo.model.MeanLinearModel attribute), 104
components (menpo.model.PCAModel attribute), 116
ComposableTransform (class in menpo.transform.base.composable), 265
compose_after() (menpo.transform.Affine method), 211
compose_after() (menpo.transform.AlignmentAffine method), 236
compose_after() (menpo.transform.AlignmentRotation method), 245
compose_after() (menpo.transform.AlignmentSimilarity method), 241
compose_after() (menpo.transform.AlignmentTranslation method), 249
compose_after() (menpo.transform.AlignmentUniformScale method), 253
compose_after() (menpo.transform.base.composable.ComposableTransform method), 265
compose_after() (menpo.transform.Homogeneous method), 207
compose_after() (menpo.transform.NonUniformScale method), 230
compose_after() (menpo.transform.R2LogR2RBF method), 260
compose_after() (menpo.transform.R2LogRRBF method), 261
compose_after() (menpo.transform.Rotation method), 219
compose_after() (menpo.transform.Similarity method), 215
compose_after() (menpo.transform.ThinPlateSplines method), 234
compose_after() (menpo.transform.Transform method), 263
compose_after() (menpo.transform.TransformChain method), 257
compose_after() (menpo.transform.Translation method), 223
compose_after() (menpo.transform.UniformScale method), 226
compose_after_from_vector_inplace() (menpo.transform.base.composable.VComposable method), 269
compose_after_inplace() (menpo.transform.Affine method), 211
compose_after_inplace() (menpo.transform.AlignmentAffine method), 236
compose_after_inplace() (menpo.transform.AlignmentRotation method), 245
compose_after_inplace() (menpo.transform.AlignmentSimilarity method), 241
compose_after_inplace() (menpo.transform.AlignmentTranslation method), 250
compose_after_inplace() (menpo.transform.AlignmentUniformScale method), 254
compose_after_inplace() (menpo.transform.base.composable.ComposableT method), 266
compose_after_inplace() (menpo.transform.Homogeneous method), 208
compose_after_inplace() (menpo.transform.NonUniformScale method), 230
compose_after_inplace() (menpo.transform.Rotation method), 219
compose_after_inplace() (menpo.transform.Similarity method), 215
compose_after_inplace() (menpo.transform.TransformChain method), 258
compose_after_inplace() (menpo.transform.Translation method), 223
compose_after_inplace() (menpo.transform.UniformScale method), 227
compose_before() (menpo.transform.Affine method), 211
compose_before() (menpo.transform.AlignmentAffine method), 237
compose_before() (menpo.transform.AlignmentRotation method), 246
compose_before() (menpo.transform.AlignmentSimilarity method), 241
compose_before() (menpo.transform.AlignmentTranslation method), 250
compose_before() (menpo.transform.AlignmentUniformScale method), 254
compose_before() (menpo.transform.base.composable.ComposableTransfor method), 266
compose_before() (menpo.transform.Homogeneous method), 208
compose_before() (menpo.transform.NonUniformScale method), 230

compose_before() (menpo.transform.R2LogR2RBF method), 260
compose_before() (menpo.transform.R2LogRRBF method), 261
compose_before() (menpo.transform.Rotation method), 219
compose_before() (menpo.transform.Similarity method), 215
compose_before() (menpo.transform.ThinPlateSplines method), 234
compose_before() (menpo.transform.Transform method), 263
compose_before() (menpo.transform.TransformChain method), 258
compose_before() (menpo.transform.Translation method), 223
compose_before() (menpo.transform.UniformScale method), 227
compose_before_inplace() (menpo.transform.Affine method), 212
compose_before_inplace() (menpo.transform.AlignmentAffine method), 237
compose_before_inplace() (menpo.transform.AlignmentRotation method), 246
compose_before_inplace() (menpo.transform.AlignmentSimilarity method), 241
compose_before_inplace() (menpo.transform.AlignmentTranslation method), 250
compose_before_inplace() (menpo.transform.AlignmentUniformScale method), 254
compose_before_inplace() (menpo.transform.base.composable.ComposableTransform method), 266
compose_before_inplace() (menpo.transform.Homogeneous method), 208
compose_before_inplace() (menpo.transform.NonUniformScale method), 231
compose_before_inplace() (menpo.transform.Rotation method), 220
compose_before_inplace() (menpo.transform.Similarity method), 216
compose_before_inplace() (menpo.transform.TransformChain method), 258
compose_before_inplace() (menpo.transform.Translation method), 223
compose_before_inplace() (menpo.transform.UniformScale method), 227
composes_inplace_with (menpo.transform.Affine attribute), 213
composes_inplace_with (menpo.transform.AlignmentAffine attribute), 238
composes_inplace_with (menpo.transform.AlignmentRotation attribute), 248
composes_inplace_with (menpo.transform.AlignmentSimilarity attribute), 243
composes_inplace_with (menpo.transform.AlignmentTranslation attribute), 251
composes_inplace_with (menpo.transform.AlignmentUniformScale attribute), 255
composes_inplace_with (menpo.transform.base.composable.ComposableTr attribute), 266
composes_inplace_with (menpo.transform.Homogeneous attribute), 209
composes_inplace_with (menpo.transform.NonUniformScale attribute), 232
composes_inplace_with (menpo.transform.Rotation attribute), 221
composes_inplace_with (menpo.transform.Similarity attribute), 217
composes_inplace_with (menpo.transform.TransformChain attribute), 259
composes_inplace_with (menpo.transform.Translation attribute), 225
composes_inplace_with (menpo.transform.UniformScale attribute), 228
composes_with (menpo.transform.Affine attribute), 213
composes_with (menpo.transform.AlignmentAffine attribute), 238
composes_with (menpo.transform.AlignmentRotation attribute), 248
composes_with (menpo.transform.AlignmentSimilarity attribute), 243
composes_with (menpo.transform.AlignmentTranslation attribute), 251
composes_with (menpo.transform.AlignmentUniformScale attribute), 255
composes_with (menpo.transform.base.composable.ComposableTransform attribute), 267
composes_with (menpo.transform.Homogeneous attribute), 210
composes_with (menpo.transform.NonUniformScale attribute), 232
composes_with (menpo.transform.Rotation attribute), 221
composes_with (menpo.transform.Similarity attribute), 217
composes_with (menpo.transform.TransformChain attribute), 259

composes_with (menpo.transform.Translation attribute), 225
composes_with (menpo.transform.UniformScale attribute), 228
constrain_landmarks_to_bounds() (menpo.image.BooleanImage method), 44
constrain_landmarks_to_bounds() (menpo.image.Image method), 32
constrain_landmarks_to_bounds() (menpo.image.MaskedImage method), 61
constrain_mask_to_landmarks() (menpo.image.MaskedImage method), 61
constrain_points_to_bounds() (menpo.image.BooleanImage method), 44
constrain_points_to_bounds() (menpo.image.Image method), 32
constrain_points_to_bounds() (menpo.image.MaskedImage method), 61
constrain_to_landmarks() (menpo.image.BooleanImage method), 44
constrain_to_pointcloud() (menpo.image.BooleanImage method), 44
copy() (menpo.base.Copyable method), 19
copy() (menpo.base.Targetable method), 21
copy() (menpo.base.Vectorizable method), 20
copy() (menpo.image.BooleanImage method), 45
copy() (menpo.image.Image method), 32
copy() (menpo.image.MaskedImage method), 61
copy() (menpo.landmark.Landmarkable method), 79
copy() (menpo.landmark.LandmarkGroup method), 81
copy() (menpo.landmark.LandmarkManager method), 80
copy() (menpo.model.InstanceLinearModel method), 100
copy() (menpo.model.LinearModel method), 98
copy() (menpo.model.MeanInstanceLinearModel method), 105
copy() (menpo.model.MeanLinearModel method), 103
copy() (menpo.model.PCAModel method), 108
copy() (menpo.shape.base.Shape method), 117
copy() (menpo.shape.ColouredTriMesh method), 193
copy() (menpo.shape.PointCloud method), 123
copy() (menpo.shape.PointDirectedGraph method), 160
copy() (menpo.shape.PointTree method), 173
copy() (menpo.shape.PointUndirectedGraph method), 148
copy() (menpo.shape.TexturedTriMesh method), 202
copy() (menpo.shape.TriMesh method), 184
copy() (menpo.transform.Affine method), 212
copy() (menpo.transform.AlignmentAffine method), 237
copy() (menpo.transform.AlignmentRotation method), 246
copy() (menpo.transform.AlignmentSimilarity method), 242
copy() (menpo.transform.AlignmentTranslation method), 250
copy() (menpo.transform.AlignmentUniformScale method), 254
copy() (menpo.transform.base.alignment.Alignment method), 268
copy() (menpo.transform.base.composable.ComposableTransform method), 266
copy() (menpo.transform.base.Transformable method), 264
copy() (menpo.transform.Homogeneous method), 208
copy() (menpo.transform.NonUniformScale method), 231
copy() (menpo.transform.R2LogR2RBF method), 260
copy() (menpo.transform.R2LogRRBF method), 262
copy() (menpo.transform.Rotation method), 220
copy() (menpo.transform.Similarity method), 216
copy() (menpo.transform.ThinPlateSplines method), 234
copy() (menpo.transform.Transform method), 264
copy() (menpo.transform.TransformChain method), 258
copy() (menpo.transform.Translation method), 224
copy() (menpo.transform.UniformScale method), 227
Copyable (class in menpo.base), 19
crop() (menpo.image.BooleanImage method), 45
crop() (menpo.image.Image method), 33
crop() (menpo.image.MaskedImage method), 62
crop_inplace() (menpo.image.BooleanImage method), 45
crop_inplace() (menpo.image.Image method), 33
crop_inplace() (menpo.image.MaskedImage method), 62
crop_to_landmarks() (menpo.image.BooleanImage method), 45
crop_to_landmarks() (menpo.image.Image method), 33
crop_to_landmarks() (menpo.image.MaskedImage method), 62
crop_to_landmarks_inplace() (menpo.image.BooleanImage method), 46
crop_to_landmarks_inplace() (menpo.image.Image method), 33
crop_to_landmarks_inplace() (menpo.image.MaskedImage method), 62
crop_to_landmarks_proportion() (menpo.image.BooleanImage method), 46
crop_to_landmarks_proportion() (menpo.image.Image method), 33
crop_to_landmarks_proportion() (menpo.image.MaskedImage method), 62
crop_to_landmarks_proportion_inplace() (menpo.image.BooleanImage method), 46
crop_to_landmarks_proportion_inplace() (menpo.image.Image method), 34
crop_to_landmarks_proportion_inplace() (menpo.image.MaskedImage method), 63
crop_to_true_mask() (menpo.image.MaskedImage method), 63

D

daisy() (in module menpo.feature), 77
data_dir_path() (in module menpo.io), 26
data_path_to() (in module menpo.io), 26
decompose() (menpo.transform.Affine method), 212
decompose() (menpo.transform.AlignmentAffine method), 237
decompose() (menpo.transform.AlignmentRotation method), 246
decompose() (menpo.transform.AlignmentSimilarity method), 242
decompose() (menpo.transform.AlignmentTranslation method), 250
decompose() (menpo.transform.AlignmentUniformScale method), 254
decompose() (menpo.transform.homogeneous.affine.DiscreteAffine method), 269
decompose() (menpo.transform.NonUniformScale method), 231
decompose() (menpo.transform.Rotation method), 220
decompose() (menpo.transform.Similarity method), 216
decompose() (menpo.transform.Translation method), 224
decompose() (menpo.transform.UniformScale method), 227
depth_of_vertex() (menpo.shape.PointTree method), 173
depth_of_vertex() (menpo.shape.Tree method), 137
diagonal() (menpo.image.BooleanImage method), 46
diagonal() (menpo.image.Image method), 34
diagonal() (menpo.image.MaskedImage method), 63
dilate() (menpo.image.MaskedImage method), 63
DirectedGraph (class in menpo.shape), 130
DiscreteAffine (class in menpo.transform.homogeneous.affine), 268
distance_to() (menpo.shape.ColouredTriMesh method), 194
distance_to() (menpo.shape.PointCloud method), 123
distance_to() (menpo.shape.PointDirectedGraph method), 161
distance_to() (menpo.shape.PointTree method), 173
distance_to() (menpo.shape.PointUndirectedGraph method), 148
distance_to() (menpo.shape.TexturedTriMesh method), 203
distance_to() (menpo.shape.TriMesh method), 185
dot_inplace_left() (in module menpo.math), 96
dot_inplace_right() (in module menpo.math), 96

E

edge_indices() (menpo.shape.ColouredTriMesh method), 194
edge_indices() (menpo.shape.TexturedTriMesh method), 203
edge_indices() (menpo.shape.TriMesh method), 185
edge_lengths() (menpo.shape.ColouredTriMesh method), 194
edge_lengths() (menpo.shape.TexturedTriMesh method), 203
edge_lengths() (menpo.shape.TriMesh method), 185
edge_vectors() (menpo.shape.ColouredTriMesh method), 194
edge_vectors() (menpo.shape.TexturedTriMesh method), 203
edge_vectors() (menpo.shape.TriMesh method), 185
eigenvalue_decomposition() (in module menpo.math), 94
eigenvalues (menpo.model.PCAModel attribute), 116
eigenvalues_cumulative_ratio() (menpo.model.PCAModel method), 108
eigenvalues_ratio() (menpo.model.PCAModel method), 108
erode() (menpo.image.MaskedImage method), 63
es() (in module menpo.feature), 74
export_image() (in module menpo.io), 24
export_landmark_file() (in module menpo.io), 25
export_pickle() (in module menpo.io), 25
extract_channels() (menpo.image.BooleanImage method), 46
extract_channels() (menpo.image.Image method), 34
extract_channels() (menpo.image.MaskedImage method), 63
extract_patches() (menpo.image.BooleanImage method), 46
extract_patches() (menpo.image.Image method), 34
extract_patches() (menpo.image.MaskedImage method), 63
extract_patches_around_landmarks() (menpo.image.BooleanImage method), 47
extract_patches_around_landmarks() (menpo.image.Image method), 34
extract_patches_around_landmarks() (menpo.image.MaskedImage method), 64

F

false_indices() (menpo.image.BooleanImage method), 47
features_selection() (in module menpo.visualize), 273
features_selection_widget() (in module menpo.feature), 78
find_all_paths() (menpo.shape.DirectedGraph method), 132
find_all_paths() (menpo.shape.PointDirectedGraph method), 161
find_all_paths() (menpo.shape.PointTree method), 173
find_all_paths() (menpo.shape.PointUndirectedGraph method), 149
find_all_paths() (menpo.shape.Tree method), 137
find_all_paths() (menpo.shape.UndirectedGraph method), 127

find_all_shortest_paths() (menpo.shape.DirectedGraph method), 132
find_all_shortest_paths() (menpo.shape.PointDirectedGraph method), 161
find_all_shortest_paths() (menpo.shape.PointTree method), 173
find_all_shortest_paths() (menpo.shape.PointUndirectedGraph method), 149
find_all_shortest_paths() (menpo.shape.Tree method), 137
find_all_shortest_paths() (menpo.shape.UndirectedGraph method), 127
find_path() (menpo.shape.DirectedGraph method), 132
find_path() (menpo.shape.PointDirectedGraph method), 161
find_path() (menpo.shape.PointTree method), 174
find_path() (menpo.shape.PointUndirectedGraph method), 149
find_path() (menpo.shape.Tree method), 138
find_path() (menpo.shape.UndirectedGraph method), 127
find_shortest_path() (menpo.shape.DirectedGraph method), 133
find_shortest_path() (menpo.shape.PointDirectedGraph method), 162
find_shortest_path() (menpo.shape.PointTree method), 174
find_shortest_path() (menpo.shape.PointUndirectedGraph method), 149
find_shortest_path() (menpo.shape.Tree method), 138
find_shortest_path() (menpo.shape.UndirectedGraph method), 127
flic_pose() (in module menpo.landmark), 90
from_mask() (menpo.shape.ColouredTriMesh method), 194
from_mask() (menpo.shape.PointCloud method), 124
from_mask() (menpo.shape.PointDirectedGraph method), 162
from_mask() (menpo.shape.PointTree method), 174
from_mask() (menpo.shape.PointUndirectedGraph method), 150
from_mask() (menpo.shape.TexturedTriMesh method), 203
from_mask() (menpo.shape.TriMesh method), 185
from_matrix() (in module menpo.math), 97
from_vector() (menpo.base.Vectorizable method), 20
from_vector() (menpo.image.BooleanImage method), 47
from_vector() (menpo.image.Image method), 35
from_vector() (menpo.image.MaskedImage method), 64
from_vector() (menpo.shape.base.Shape method), 117
from_vector() (menpo.shape.ColouredTriMesh method), 194
from_vector() (menpo.shape.PointCloud method), 124
from_vector() (menpo.shape.PointDirectedGraph method), 162
from_vector() (menpo.shape.PointTree method), 175
from_vector() (menpo.shape.PointUndirectedGraph method), 150
from_vector() (menpo.shape.TexturedTriMesh method), 203
from_vector() (menpo.shape.TriMesh method), 185
from_vector() (menpo.transform.Affine method), 212
from_vector() (menpo.transform.AlignmentAffine method), 237
from_vector() (menpo.transform.AlignmentRotation method), 246
from_vector() (menpo.transform.AlignmentSimilarity method), 242
from_vector() (menpo.transform.AlignmentTranslation method), 250
from_vector() (menpo.transform.AlignmentUniformScale method), 254
from_vector() (menpo.transform.Homogeneous method), 209
from_vector() (menpo.transform.NonUniformScale method), 231
from_vector() (menpo.transform.Rotation method), 220
from_vector() (menpo.transform.Similarity method), 216
from_vector() (menpo.transform.Translation method), 224
from_vector() (menpo.transform.UniformScale method), 228
from_vector_inplace() (menpo.base.Vectorizable method), 20
from_vector_inplace() (menpo.image.BooleanImage method), 48
from_vector_inplace() (menpo.image.Image method), 35
from_vector_inplace() (menpo.image.MaskedImage method), 65
from_vector_inplace() (menpo.shape.base.Shape method), 117
from_vector_inplace() (menpo.shape.ColouredTriMesh method), 195
from_vector_inplace() (menpo.shape.PointCloud method), 124
from_vector_inplace() (menpo.shape.PointDirectedGraph method), 162
from_vector_inplace() (menpo.shape.PointTree method), 175
from_vector_inplace() (menpo.shape.PointUndirectedGraph method), 150
from_vector_inplace() (menpo.shape.TexturedTriMesh method), 204
from_vector_inplace() (menpo.shape.TriMesh method), 186
from_vector_inplace() (menpo.transform.Affine method), 212
from_vector_inplace() (menpo.transform.AlignmentAffine method), 238

from_vector_inplace() (menpo.transform.AlignmentRotation method), 246
from_vector_inplace() (menpo.transform.AlignmentSimilarity method), 242
from_vector_inplace() (menpo.transform.AlignmentTranslation method), 251
from_vector_inplace() (menpo.transform.AlignmentUniformScale method), 255
from_vector_inplace() (menpo.transform.Homogeneous method), 209
from_vector_inplace() (menpo.transform.NonUniformScale method), 231
from_vector_inplace() (menpo.transform.Rotation method), 220
from_vector_inplace() (menpo.transform.Similarity method), 216
from_vector_inplace() (menpo.transform.Translation method), 224
from_vector_inplace() (menpo.transform.UniformScale method), 228

G

gaussian_filter() (in module menpo.feature), 73
gaussian_pyramid() (menpo.image.BooleanImage method), 48
gaussian_pyramid() (menpo.image.Image method), 35
gaussian_pyramid() (menpo.image.MaskedImage method), 65
GeneralizedProcrustesAnalysis (class in menpo.transform), 256
get() (menpo.landmark.LandmarkGroup method), 81
get() (menpo.landmark.LandmarkManager method), 80
get_adjacency_list() (menpo.shape.DirectedGraph method), 133
get_adjacency_list() (menpo.shape.PointDirectedGraph method), 162
get_adjacency_list() (menpo.shape.PointTree method), 175
get_adjacency_list() (menpo.shape.PointUndirectedGraph method), 150
get_adjacency_list() (menpo.shape.Tree method), 138
get_adjacency_list() (menpo.shape.UndirectedGraph method), 128
get_figure() (menpo.visualize.MatplotlibRenderer method), 271
get_figure() (menpo.visualize.Renderer method), 270
glyph() (in module menpo.feature.visualize), 77
gradient() (in module menpo.feature), 73
gradient() (menpo.image.BooleanImage method), 48
gradient() (menpo.image.Image method), 36
gradient() (menpo.image.MaskedImage method), 65
GraphOptionsWidget (class in menpo.visualize.widgets), 295
group_labels (menpo.landmark.LandmarkManager attribute), 81

H

h_matrix (menpo.transform.Affine attribute), 213
h_matrix (menpo.transform.AlignmentAffine attribute), 239
h_matrix (menpo.transform.AlignmentRotation attribute), 248
h_matrix (menpo.transform.AlignmentSimilarity attribute), 243
h_matrix (menpo.transform.AlignmentTranslation attribute), 252
h_matrix (menpo.transform.AlignmentUniformScale attribute), 255
h_matrix (menpo.transform.Homogeneous attribute), 210
h_matrix (menpo.transform.NonUniformScale attribute), 232
h_matrix (menpo.transform.Rotation attribute), 221
h_matrix (menpo.transform.Similarity attribute), 217
h_matrix (menpo.transform.Translation attribute), 225
h_matrix (menpo.transform.UniformScale attribute), 229
h_matrix_is_mutable (menpo.transform.Affine attribute), 213
h_matrix_is_mutable (menpo.transform.AlignmentAffine attribute), 239
h_matrix_is_mutable (menpo.transform.AlignmentRotation attribute), 248
h_matrix_is_mutable (menpo.transform.AlignmentSimilarity attribute), 243
h_matrix_is_mutable (menpo.transform.AlignmentTranslation attribute), 252
h_matrix_is_mutable (menpo.transform.AlignmentUniformScale attribute), 256
h_matrix_is_mutable (menpo.transform.Homogeneous attribute), 210
h_matrix_is_mutable (menpo.transform.NonUniformScale attribute), 232
h_matrix_is_mutable (menpo.transform.Rotation attribute), 221
h_matrix_is_mutable (menpo.transform.Similarity attribute), 217
h_matrix_is_mutable (menpo.transform.Translation attribute), 225
h_matrix_is_mutable (menpo.transform.UniformScale attribute), 229
h_points() (menpo.shape.ColouredTriMesh method), 195
h_points() (menpo.shape.PointCloud method), 124
h_points() (menpo.shape.PointDirectedGraph method), 162
h_points() (menpo.shape.PointTree method), 175
h_points() (menpo.shape.PointUndirectedGraph method), 150
h_points() (menpo.shape.TexturedTriMesh method), 204

h_points() (menpo.shape.TriMesh method), 186
has_cycles() (menpo.shape.DirectedGraph method), 133
has_cycles() (menpo.shape.PointDirectedGraph method), 163
has_cycles() (menpo.shape.PointTree method), 175
has_cycles() (menpo.shape.PointUndirectedGraph method), 150
has_cycles() (menpo.shape.Tree method), 138
has_cycles() (menpo.shape.UndirectedGraph method), 128
has_isolated_vertices() (menpo.shape.DirectedGraph method), 133
has_isolated_vertices() (menpo.shape.PointDirectedGraph method), 163
has_isolated_vertices() (menpo.shape.PointTree method), 175
has_isolated_vertices() (menpo.shape.PointUndirectedGraph method), 150
has_isolated_vertices() (menpo.shape.Tree method), 138
has_isolated_vertices() (menpo.shape.UndirectedGraph method), 128
has_landmarks (menpo.image.BooleanImage attribute), 53
has_landmarks (menpo.image.Image attribute), 41
has_landmarks (menpo.image.MaskedImage attribute), 71
has_landmarks (menpo.landmark.Landmarkable attribute), 79
has_landmarks (menpo.landmark.LandmarkManager attribute), 81
has_landmarks (menpo.shape.base.Shape attribute), 118
has_landmarks (menpo.shape.ColouredTriMesh attribute), 196
has_landmarks (menpo.shape.PointCloud attribute), 125
has_landmarks (menpo.shape.PointDirectedGraph attribute), 166
has_landmarks (menpo.shape.PointTree attribute), 178
has_landmarks (menpo.shape.PointUndirectedGraph attribute), 153
has_landmarks (menpo.shape.TexturedTriMesh attribute), 206
has_landmarks (menpo.shape.TriMesh attribute), 187
has_landmarks_outside_bounds (menpo.image.BooleanImage attribute), 53
has_landmarks_outside_bounds (menpo.image.Image attribute), 41
has_landmarks_outside_bounds (menpo.image.MaskedImage attribute), 71
has_nan_values() (menpo.base.Vectorizable method), 20
has_nan_values() (menpo.image.BooleanImage method), 48
has_nan_values() (menpo.image.Image method), 36
has_nan_values() (menpo.image.MaskedImage method), 65
has_nan_values() (menpo.landmark.LandmarkGroup method), 81
has_nan_values() (menpo.shape.base.Shape method), 118
has_nan_values() (menpo.shape.ColouredTriMesh method), 195
has_nan_values() (menpo.shape.PointCloud method), 124
has_nan_values() (menpo.shape.PointDirectedGraph method), 163
has_nan_values() (menpo.shape.PointTree method), 175
has_nan_values() (menpo.shape.PointUndirectedGraph method), 151
has_nan_values() (menpo.shape.TexturedTriMesh method), 204
has_nan_values() (menpo.shape.TriMesh method), 186
has_nan_values() (menpo.transform.Affine method), 212
has_nan_values() (menpo.transform.AlignmentAffine method), 238
has_nan_values() (menpo.transform.AlignmentRotation method), 246
has_nan_values() (menpo.transform.AlignmentSimilarity method), 242
has_nan_values() (menpo.transform.AlignmentTranslation method), 251
has_nan_values() (menpo.transform.AlignmentUniformScale method), 255
has_nan_values() (menpo.transform.Homogeneous method), 209
has_nan_values() (menpo.transform.NonUniformScale method), 231
has_nan_values() (menpo.transform.Rotation method), 220
has_nan_values() (menpo.transform.Similarity method), 216
has_nan_values() (menpo.transform.Translation method), 224
has_nan_values() (menpo.transform.UniformScale method), 228
has_true_inverse (menpo.transform.Affine attribute), 213
has_true_inverse (menpo.transform.AlignmentAffine attribute), 239
has_true_inverse (menpo.transform.AlignmentRotation attribute), 248
has_true_inverse (menpo.transform.AlignmentSimilarity attribute), 243
has_true_inverse (menpo.transform.AlignmentTranslation attribute), 252
has_true_inverse (menpo.transform.AlignmentUniformScale attribute), 256
has_true_inverse (menpo.transform.base.invertible.Invertible attribute), 267

has_true_inverse (menpo.transform.base.invertible.VInvertible attribute), 269
has_true_inverse (menpo.transform.Homogeneous attribute), 210
has_true_inverse (menpo.transform.NonUniformScale attribute), 232
has_true_inverse (menpo.transform.Rotation attribute), 221
has_true_inverse (menpo.transform.Similarity attribute), 217
has_true_inverse (menpo.transform.ThinPlateSplines attribute), 234
has_true_inverse (menpo.transform.Translation attribute), 225
has_true_inverse (menpo.transform.UniformScale attribute), 229
height (menpo.image.BooleanImage attribute), 53
height (menpo.image.Image attribute), 41
height (menpo.image.MaskedImage attribute), 71
hog() (in module menpo.feature), 75
Homogeneous (class in menpo.transform), 207

I

ibug_close_eye_points() (in module menpo.landmark), 89
ibug_close_eye_trimesh() (in module menpo.landmark), 88
ibug_face_49() (in module menpo.landmark), 83
ibug_face_51() (in module menpo.landmark), 84
ibug_face_65_closed_mouth() (in module menpo.landmark), 85
ibug_face_66() (in module menpo.landmark), 84
ibug_face_68() (in module menpo.landmark), 85
ibug_face_68_trimesh() (in module menpo.landmark), 85
ibug_hand() (in module menpo.landmark), 89
ibug_open_eye() (in module menpo.landmark), 88
ibug_open_eye_trimesh() (in module menpo.landmark), 88
ibug_tongue() (in module menpo.landmark), 94
igo() (in module menpo.feature), 73
Image (class in menpo.image), 27
image_paths() (in module menpo.io), 26
ImageBoundaryError (class in menpo.image), 72
imm_face() (in module menpo.landmark), 86
import_builtin_asset() (in module menpo.io), 24
import_image() (in module menpo.io), 21
import_images() (in module menpo.io), 22
import_landmark_file() (in module menpo.io), 23
import_landmark_files() (in module menpo.io), 23
import_pickle() (in module menpo.io), 23
import_pickles() (in module menpo.io), 24
increment() (menpo.model.PCAModel method), 109
indices() (menpo.image.BooleanImage method), 48
indices() (menpo.image.Image method), 36
indices() (menpo.image.MaskedImage method), 65
init_blank() (menpo.image.BooleanImage class method), 48
init_blank() (menpo.image.Image class method), 36
init_blank() (menpo.image.MaskedImage class method), 65
init_from_2d_ccw_angle() (menpo.transform.AlignmentRotation method), 247
init_from_2d_ccw_angle() (menpo.transform.Rotation class method), 220
init_from_edges() (menpo.shape.DirectedGraph method), 133
init_from_edges() (menpo.shape.PointDirectedGraph method), 163
init_from_edges() (menpo.shape.PointTree class method), 175
init_from_edges() (menpo.shape.PointUndirectedGraph class method), 151
init_from_edges() (menpo.shape.Tree method), 138
init_from_edges() (menpo.shape.UndirectedGraph class method), 128
init_identity() (menpo.transform.Affine class method), 212
init_identity() (menpo.transform.AlignmentAffine method), 238
init_identity() (menpo.transform.AlignmentRotation method), 247
init_identity() (menpo.transform.AlignmentSimilarity method), 242
init_identity() (menpo.transform.AlignmentTranslation method), 251
init_identity() (menpo.transform.AlignmentUniformScale method), 255
init_identity() (menpo.transform.Homogeneous class method), 209
init_identity() (menpo.transform.NonUniformScale class method), 231
init_identity() (menpo.transform.Rotation class method), 221
init_identity() (menpo.transform.Similarity class method), 217
init_identity() (menpo.transform.Translation class method), 224
init_identity() (menpo.transform.UniformScale class method), 228
init_with_all_label() (menpo.landmark.LandmarkGroup class method), 81
instance() (menpo.model.InstanceLinearModel method), 101
instance() (menpo.model.MeanInstanceLinearModel method), 105
instance() (menpo.model.PCAModel method), 109

instance_vector() (menpo.model.InstanceLinearModel method), 101
instance_vector() (menpo.model.LinearModel method), 99
instance_vector() (menpo.model.MeanInstanceLinearModel method), 105
instance_vector() (menpo.model.MeanLinearModel method), 103
instance_vector() (menpo.model.PCAModel method), 109
instance_vectors() (menpo.model.InstanceLinearModel method), 101
instance_vectors() (menpo.model.LinearModel method), 99
instance_vectors() (menpo.model.MeanInstanceLinearModel method), 106
instance_vectors() (menpo.model.MeanLinearModel method), 103
instance_vectors() (menpo.model.PCAModel method), 109
InstanceLinearModel (class in menpo.model), 100
inverse_noise_variance() (menpo.model.PCAModel method), 109
invert() (menpo.image.BooleanImage method), 49
invert_inplace() (menpo.image.BooleanImage method), 49
Invertible (class in menpo.transform.base.invertible), 267
ipca() (in module menpo.math), 95
is_edge() (menpo.shape.DirectedGraph method), 134
is_edge() (menpo.shape.PointDirectedGraph method), 164
is_edge() (menpo.shape.PointTree method), 176
is_edge() (menpo.shape.PointUndirectedGraph method), 152
is_edge() (menpo.shape.Tree method), 140
is_edge() (menpo.shape.UndirectedGraph method), 129
is_leaf() (menpo.shape.PointTree method), 176
is_leaf() (menpo.shape.Tree method), 140
is_tree() (menpo.shape.DirectedGraph method), 135
is_tree() (menpo.shape.PointDirectedGraph method), 164
is_tree() (menpo.shape.PointTree method), 176
is_tree() (menpo.shape.PointUndirectedGraph method), 152
is_tree() (menpo.shape.Tree method), 140
is_tree() (menpo.shape.UndirectedGraph method), 129
isolated_vertices() (menpo.shape.DirectedGraph method), 135
isolated_vertices() (menpo.shape.PointDirectedGraph method), 164
isolated_vertices() (menpo.shape.PointTree method), 176
isolated_vertices() (menpo.shape.PointUndirectedGraph method), 152
isolated_vertices() (menpo.shape.Tree method), 140
isolated_vertices() (menpo.shape.UndirectedGraph method), 129
items() (menpo.landmark.LandmarkGroup method), 82
items() (menpo.landmark.LandmarkManager method), 80
items_matching() (menpo.landmark.LandmarkManager method), 80
iteritems() (menpo.landmark.LandmarkGroup method), 82
iteritems() (menpo.landmark.LandmarkManager method), 80
iterkeys() (menpo.landmark.LandmarkGroup method), 82
iterkeys() (menpo.landmark.LandmarkManager method), 80
itervalues() (menpo.landmark.LandmarkGroup method), 82
itervalues() (menpo.landmark.LandmarkManager method), 80

K

keys() (menpo.landmark.LandmarkGroup method), 82
keys() (menpo.landmark.LandmarkManager method), 80
keys_matching() (menpo.landmark.LandmarkManager method), 80

L

labeller() (in module menpo.landmark), 83
LabellingError (class in menpo.landmark), 79
labels (menpo.landmark.LandmarkGroup attribute), 82
landmark_file_paths() (in module menpo.io), 26
Landmarkable (class in menpo.landmark), 79
LandmarkableViewable (class in menpo.visualize), 271
LandmarkGroup (class in menpo.landmark), 81
LandmarkManager (class in menpo.landmark), 79
LandmarkOptionsWidget (class in menpo.visualize.widgets), 283
landmarks (menpo.image.BooleanImage attribute), 53
landmarks (menpo.image.Image attribute), 41
landmarks (menpo.image.MaskedImage attribute), 72
landmarks (menpo.landmark.Landmarkable attribute), 79
landmarks (menpo.shape.base.Shape attribute), 118
landmarks (menpo.shape.ColouredTriMesh attribute), 196
landmarks (menpo.shape.PointCloud attribute), 125
landmarks (menpo.shape.PointDirectedGraph attribute), 166
landmarks (menpo.shape.PointTree attribute), 178
landmarks (menpo.shape.PointUndirectedGraph attribute), 153
landmarks (menpo.shape.TexturedTriMesh attribute), 206
landmarks (menpo.shape.TriMesh attribute), 187
lbp() (in module menpo.feature), 74
leaves (menpo.shape.PointTree attribute), 178
leaves (menpo.shape.Tree attribute), 141

lfpw_face() (in module menpo.landmark), 86
linear_component (menpo.transform.Affine attribute), 213
linear_component (menpo.transform.AlignmentAffine attribute), 239
linear_component (menpo.transform.AlignmentRotation attribute), 248
linear_component (menpo.transform.AlignmentSimilarity attribute), 243
linear_component (menpo.transform.AlignmentTranslation attribute), 252
linear_component (menpo.transform.AlignmentUniformScale attribute), 256
linear_component (menpo.transform.NonUniformScale attribute), 232
linear_component (menpo.transform.Rotation attribute), 222
linear_component (menpo.transform.Similarity attribute), 217
linear_component (menpo.transform.Translation attribute), 225
linear_component (menpo.transform.UniformScale attribute), 229
LinearModel (class in menpo.model), 98
lms (menpo.landmark.LandmarkGroup attribute), 83
log_gabor() (in module menpo.math), 97
ls_builtin_assets() (in module menpo.io), 26
lsp_pose() (in module menpo.landmark), 90

M

mask (menpo.image.BooleanImage attribute), 53
masked_pixels() (menpo.image.MaskedImage method), 66
MaskedImage (class in menpo.image), 54
MatplotlibRenderer (class in menpo.visualize), 271
maximum_depth (menpo.shape.PointTree attribute), 178
maximum_depth (menpo.shape.Tree attribute), 141
mean() (menpo.model.MeanInstanceLinearModel method), 106
mean() (menpo.model.PCAModel method), 109
mean_aligned_shape() (menpo.transform.GeneralizedProcrustesAnalysis method), 257
mean_alignment_error() (menpo.transform.GeneralizedProcrustesAnalysis method), 257
mean_edge_length() (menpo.shape.ColouredTriMesh method), 195
mean_edge_length() (menpo.shape.TexturedTriMesh method), 204
mean_edge_length() (menpo.shape.TriMesh method), 186
mean_pointcloud() (in module menpo.shape), 206
mean_tri_area() (menpo.shape.ColouredTriMesh method), 195
mean_tri_area() (menpo.shape.TexturedTriMesh method), 204
mean_tri_area() (menpo.shape.TriMesh method), 186
MeanInstanceLinearModel (class in menpo.model), 105
MeanLinearModel (class in menpo.model), 103
menpo_src_dir_path() (in module menpo.base), 21
minimum_spanning_tree() (menpo.shape.PointUndirectedGraph method), 152
minimum_spanning_tree() (menpo.shape.UndirectedGraph method), 129
MultipleAlignment (class in menpo.transform.groupalign.base), 268

N

n_active_components (menpo.model.PCAModel attribute), 117
n_centres (menpo.transform.R2LogR2RBF attribute), 260
n_centres (menpo.transform.R2LogRRBF attribute), 262
n_channels (menpo.image.BooleanImage attribute), 54
n_channels (menpo.image.Image attribute), 41
n_channels (menpo.image.MaskedImage attribute), 72
n_children() (menpo.shape.DirectedGraph method), 135
n_children() (menpo.shape.PointDirectedGraph method), 164
n_children() (menpo.shape.PointTree method), 176
n_children() (menpo.shape.Tree method), 140
n_components (menpo.model.InstanceLinearModel attribute), 102
n_components (menpo.model.LinearModel attribute), 100
n_components (menpo.model.MeanInstanceLinearModel attribute), 107
n_components (menpo.model.MeanLinearModel attribute), 104
n_components (menpo.model.PCAModel attribute), 117
n_dims (menpo.base.Targetable attribute), 21
n_dims (menpo.image.BooleanImage attribute), 54
n_dims (menpo.image.Image attribute), 41
n_dims (menpo.image.MaskedImage attribute), 72
n_dims (menpo.landmark.LandmarkGroup attribute), 83
n_dims (menpo.landmark.LandmarkManager attribute), 81
n_dims (menpo.shape.ColouredTriMesh attribute), 196
n_dims (menpo.shape.PointCloud attribute), 125
n_dims (menpo.shape.PointDirectedGraph attribute), 166
n_dims (menpo.shape.PointTree attribute), 178
n_dims (menpo.shape.PointUndirectedGraph attribute), 153
n_dims (menpo.shape.TexturedTriMesh attribute), 206
n_dims (menpo.shape.TriMesh attribute), 187
n_dims (menpo.transform.Affine attribute), 213

n_dims (menpo.transform.AlignmentAffine attribute), 239
n_dims (menpo.transform.AlignmentRotation attribute), 248
n_dims (menpo.transform.AlignmentSimilarity attribute), 243
n_dims (menpo.transform.AlignmentTranslation attribute), 252
n_dims (menpo.transform.AlignmentUniformScale attribute), 256
n_dims (menpo.transform.base.alignment.Alignment attribute), 268
n_dims (menpo.transform.base.composable.ComposableTransform attribute), 267
n_dims (menpo.transform.Homogeneous attribute), 210
n_dims (menpo.transform.NonUniformScale attribute), 232
n_dims (menpo.transform.R2LogR2RBF attribute), 260
n_dims (menpo.transform.R2LogRRBF attribute), 262
n_dims (menpo.transform.Rotation attribute), 222
n_dims (menpo.transform.Similarity attribute), 218
n_dims (menpo.transform.ThinPlateSplines attribute), 234
n_dims (menpo.transform.Transform attribute), 264
n_dims (menpo.transform.TransformChain attribute), 259
n_dims (menpo.transform.Translation attribute), 225
n_dims (menpo.transform.UniformScale attribute), 229
n_dims() (menpo.landmark.Landmarkable method), 79
n_dims() (menpo.shape.base.Shape method), 118
n_dims_output (menpo.transform.Affine attribute), 214
n_dims_output (menpo.transform.AlignmentAffine attribute), 239
n_dims_output (menpo.transform.AlignmentRotation attribute), 248
n_dims_output (menpo.transform.AlignmentSimilarity attribute), 243
n_dims_output (menpo.transform.AlignmentTranslation attribute), 252
n_dims_output (menpo.transform.AlignmentUniformScale attribute), 256
n_dims_output (menpo.transform.base.composable.ComposableTransform attribute), 267
n_dims_output (menpo.transform.Homogeneous attribute), 210
n_dims_output (menpo.transform.NonUniformScale attribute), 232
n_dims_output (menpo.transform.R2LogR2RBF attribute), 261
n_dims_output (menpo.transform.R2LogRRBF attribute), 262
n_dims_output (menpo.transform.Rotation attribute), 222
n_dims_output (menpo.transform.Similarity attribute), 218
n_dims_output (menpo.transform.ThinPlateSplines attribute), 235
n_dims_output (menpo.transform.Transform attribute), 264
n_dims_output (menpo.transform.TransformChain attribute), 259
n_dims_output (menpo.transform.Translation attribute), 225
n_dims_output (menpo.transform.UniformScale attribute), 229
n_edges (menpo.shape.DirectedGraph attribute), 135
n_edges (menpo.shape.PointDirectedGraph attribute), 166
n_edges (menpo.shape.PointTree attribute), 178
n_edges (menpo.shape.PointUndirectedGraph attribute), 153
n_edges (menpo.shape.Tree attribute), 141
n_edges (menpo.shape.UndirectedGraph attribute), 130
n_elements (menpo.image.BooleanImage attribute), 54
n_elements (menpo.image.Image attribute), 41
n_elements (menpo.image.MaskedImage attribute), 72
n_false() (menpo.image.BooleanImage method), 49
n_false_elements() (menpo.image.MaskedImage method), 66
n_false_pixels() (menpo.image.MaskedImage method), 66
n_features (menpo.model.InstanceLinearModel attribute), 102
n_features (menpo.model.LinearModel attribute), 100
n_features (menpo.model.MeanInstanceLinearModel attribute), 107
n_features (menpo.model.MeanLinearModel attribute), 104
n_features (menpo.model.PCAModel attribute), 117
n_groups (menpo.landmark.LandmarkManager attribute), 81
n_labels (menpo.landmark.LandmarkGroup attribute), 83
n_landmark_groups (menpo.image.BooleanImage attribute), 54
n_landmark_groups (menpo.image.Image attribute), 41
n_landmark_groups (menpo.image.MaskedImage attribute), 72
n_landmark_groups (menpo.landmark.Landmarkable attribute), 79
n_landmark_groups (menpo.shape.base.Shape attribute), 118
n_landmark_groups (menpo.shape.ColouredTriMesh attribute), 196
n_landmark_groups (menpo.shape.PointCloud attribute), 125
n_landmark_groups (menpo.shape.PointDirectedGraph attribute), 166
n_landmark_groups (menpo.shape.PointTree attribute), 179

n_landmark_groups (menpo.shape.PointUndirectedGraph attribute), 153
n_landmark_groups (menpo.shape.TexturedTriMesh attribute), 206
n_landmark_groups (menpo.shape.TriMesh attribute), 187
n_landmarks (menpo.landmark.LandmarkGroup attribute), 83
n_leaves (menpo.shape.PointTree attribute), 179
n_leaves (menpo.shape.Tree attribute), 141
n_neighbours() (menpo.shape.PointUndirectedGraph method), 152
n_neighbours() (menpo.shape.UndirectedGraph method), 129
n_parameters (menpo.base.Vectorizable attribute), 20
n_parameters (menpo.image.BooleanImage attribute), 54
n_parameters (menpo.image.Image attribute), 41
n_parameters (menpo.image.MaskedImage attribute), 72
n_parameters (menpo.shape.base.Shape attribute), 118
n_parameters (menpo.shape.ColouredTriMesh attribute), 197
n_parameters (menpo.shape.PointCloud attribute), 125
n_parameters (menpo.shape.PointDirectedGraph attribute), 166
n_parameters (menpo.shape.PointTree attribute), 179
n_parameters (menpo.shape.PointUndirectedGraph attribute), 153
n_parameters (menpo.shape.TexturedTriMesh attribute), 206
n_parameters (menpo.shape.TriMesh attribute), 188
n_parameters (menpo.transform.Affine attribute), 214
n_parameters (menpo.transform.AlignmentAffine attribute), 239
n_parameters (menpo.transform.AlignmentSimilarity attribute), 243
n_parameters (menpo.transform.AlignmentTranslation attribute), 252
n_parameters (menpo.transform.AlignmentUniformScale attribute), 256
n_parameters (menpo.transform.Homogeneous attribute), 210
n_parameters (menpo.transform.NonUniformScale attribute), 232
n_parameters (menpo.transform.Similarity attribute), 218
n_parameters (menpo.transform.Translation attribute), 225
n_parameters (menpo.transform.UniformScale attribute), 229
n_parents() (menpo.shape.DirectedGraph method), 135
n_parents() (menpo.shape.PointDirectedGraph method), 165
n_parents() (menpo.shape.PointTree method), 177
n_parents() (menpo.shape.Tree method), 140
n_paths() (menpo.shape.DirectedGraph method), 135
n_paths() (menpo.shape.PointDirectedGraph method), 165
n_paths() (menpo.shape.PointTree method), 177
n_paths() (menpo.shape.PointUndirectedGraph method), 152
n_paths() (menpo.shape.Tree method), 140
n_paths() (menpo.shape.UndirectedGraph method), 130
n_pixels (menpo.image.BooleanImage attribute), 54
n_pixels (menpo.image.Image attribute), 41
n_pixels (menpo.image.MaskedImage attribute), 72
n_points (menpo.base.Targetable attribute), 21
n_points (menpo.shape.ColouredTriMesh attribute), 197
n_points (menpo.shape.PointCloud attribute), 125
n_points (menpo.shape.PointDirectedGraph attribute), 166
n_points (menpo.shape.PointTree attribute), 179
n_points (menpo.shape.PointUndirectedGraph attribute), 153
n_points (menpo.shape.TexturedTriMesh attribute), 206
n_points (menpo.shape.TriMesh attribute), 188
n_points (menpo.transform.AlignmentAffine attribute), 239
n_points (menpo.transform.AlignmentRotation attribute), 248
n_points (menpo.transform.AlignmentSimilarity attribute), 244
n_points (menpo.transform.AlignmentTranslation attribute), 252
n_points (menpo.transform.AlignmentUniformScale attribute), 256
n_points (menpo.transform.base.alignment.Alignment attribute), 268
n_points (menpo.transform.ThinPlateSplines attribute), 235
n_tris (menpo.shape.ColouredTriMesh attribute), 197
n_tris (menpo.shape.TexturedTriMesh attribute), 206
n_tris (menpo.shape.TriMesh attribute), 188
n_true() (menpo.image.BooleanImage method), 49
n_true_elements() (menpo.image.MaskedImage method), 66
n_true_pixels() (menpo.image.MaskedImage method), 66
n_vertices (menpo.shape.DirectedGraph attribute), 135
n_vertices (menpo.shape.PointDirectedGraph attribute), 166
n_vertices (menpo.shape.PointTree attribute), 179
n_vertices (menpo.shape.PointUndirectedGraph attribute), 153
n_vertices (menpo.shape.Tree attribute), 141
n_vertices (menpo.shape.UndirectedGraph attribute), 130
n_vertices_at_depth() (menpo.shape.PointTree method), 177
n_vertices_at_depth() (menpo.shape.Tree method), 141
neighbours() (menpo.shape.PointUndirectedGraph method), 152

neighbours() (menpo.shape.UndirectedGraph method), 130
no_op() (in module menpo.feature), 73
noise_variance() (menpo.model.PCAModel method), 110
noise_variance_ratio() (menpo.model.PCAModel method), 110
NonUniformScale (class in menpo.transform), 229
norm() (menpo.shape.ColouredTriMesh method), 195
norm() (menpo.shape.PointCloud method), 124
norm() (menpo.shape.PointDirectedGraph method), 165
norm() (menpo.shape.PointTree method), 177
norm() (menpo.shape.PointUndirectedGraph method), 153
norm() (menpo.shape.TexturedTriMesh method), 204
norm() (menpo.shape.TriMesh method), 186
normalize_norm_inplace() (menpo.image.BooleanImage method), 49
normalize_norm_inplace() (menpo.image.Image method), 36
normalize_norm_inplace() (menpo.image.MaskedImage method), 66
normalize_std_inplace() (menpo.image.BooleanImage method), 49
normalize_std_inplace() (menpo.image.Image method), 36
normalize_std_inplace() (menpo.image.MaskedImage method), 66

O

original_variance() (menpo.model.PCAModel method), 110
orthonormalize_against_inplace() (menpo.model.InstanceLinearModel method), 101
orthonormalize_against_inplace() (menpo.model.LinearModel method), 99
orthonormalize_against_inplace() (menpo.model.MeanInstanceLinearModel method), 106
orthonormalize_against_inplace() (menpo.model.MeanLinearModel method), 103
orthonormalize_against_inplace() (menpo.model.PCAModel method), 110
orthonormalize_inplace() (menpo.model.InstanceLinearModel method), 101
orthonormalize_inplace() (menpo.model.LinearModel method), 99
orthonormalize_inplace() (menpo.model.MeanInstanceLinearModel method), 106
orthonormalize_inplace() (menpo.model.MeanLinearModel method), 104
orthonormalize_inplace() (menpo.model.PCAModel method), 110

P

parent() (menpo.shape.PointTree method), 177
parent() (menpo.shape.Tree method), 141
parents() (menpo.shape.DirectedGraph method), 135
parents() (menpo.shape.PointDirectedGraph method), 165
parents() (menpo.shape.PointTree method), 177
parents() (menpo.shape.Tree method), 141
pca() (in module menpo.math), 95
PCAModel (class in menpo.model), 107
PiecewiseAffine (in module menpo.transform), 235
plot_eigenvalues() (menpo.model.PCAModel method), 110
plot_eigenvalues_cumulative_ratio() (menpo.model.PCAModel method), 111
plot_eigenvalues_cumulative_ratio_widget() (menpo.model.PCAModel method), 113
plot_eigenvalues_ratio() (menpo.model.PCAModel method), 113
plot_eigenvalues_ratio_widget() (menpo.model.PCAModel method), 114
plot_eigenvalues_widget() (menpo.model.PCAModel method), 114
plot_graph() (in module menpo.visualize), 274
PointCloud (class in menpo.shape), 118
PointDirectedGraph (class in menpo.shape), 154
PointTree (class in menpo.shape), 167
PointUndirectedGraph (class in menpo.shape), 142
pop() (menpo.landmark.LandmarkGroup method), 82
pop() (menpo.landmark.LandmarkManager method), 80
popitem() (menpo.landmark.LandmarkGroup method), 82
popitem() (menpo.landmark.LandmarkManager method), 80
predefined_style() (menpo.visualize.widgets.AnimationOptionsWidget method), 278
predefined_style() (menpo.visualize.widgets.ChannelOptionsWidget method), 282
predefined_style() (menpo.visualize.widgets.GraphOptionsWidget method), 297
predefined_style() (menpo.visualize.widgets.LandmarkOptionsWidget method), 285
predefined_style() (menpo.visualize.widgets.RendererOptionsWidget method), 291
predefined_style() (menpo.visualize.widgets.SaveFigureOptionsWidget method), 300
predefined_style() (menpo.visualize.widgets.TextPrintWidget method), 302
print_dynamic() (in module menpo.visualize), 275
print_progress() (in module menpo.visualize), 274

progress_bar_str() (in module menpo.visualize), 275
project() (menpo.model.InstanceLinearModel method), 101
project() (menpo.model.MeanInstanceLinearModel method), 106
project() (menpo.model.PCAModel method), 115
project_out() (menpo.model.InstanceLinearModel method), 101
project_out() (menpo.model.MeanInstanceLinearModel method), 106
project_out() (menpo.model.PCAModel method), 115
project_out_vector() (menpo.model.InstanceLinearModel method), 101
project_out_vector() (menpo.model.LinearModel method), 99
project_out_vector() (menpo.model.MeanInstanceLinearModel method), 106
project_out_vector() (menpo.model.MeanLinearModel method), 104
project_out_vector() (menpo.model.PCAModel method), 115
project_out_vectors() (menpo.model.InstanceLinearModel method), 102
project_out_vectors() (menpo.model.LinearModel method), 99
project_out_vectors() (menpo.model.MeanInstanceLinearModel method), 106
project_out_vectors() (menpo.model.MeanLinearModel method), 104
project_out_vectors() (menpo.model.PCAModel method), 115
project_vector() (menpo.model.InstanceLinearModel method), 102
project_vector() (menpo.model.LinearModel method), 99
project_vector() (menpo.model.MeanInstanceLinearModel method), 107
project_vector() (menpo.model.MeanLinearModel method), 104
project_vector() (menpo.model.PCAModel method), 115
project_vectors() (menpo.model.InstanceLinearModel method), 102
project_vectors() (menpo.model.LinearModel method), 99
project_vectors() (menpo.model.MeanInstanceLinearModel method), 107
project_vectors() (menpo.model.MeanLinearModel method), 104
project_vectors() (menpo.model.PCAModel method), 115
project_whitened() (menpo.model.PCAModel method), 115
project_whitened_vector() (menpo.model.PCAModel method), 115
proportion_false() (menpo.image.BooleanImage method), 49
proportion_true() (menpo.image.BooleanImage method), 49
pseudoinverse() (menpo.transform.Affine method), 213
pseudoinverse() (menpo.transform.AlignmentAffine method), 238
pseudoinverse() (menpo.transform.AlignmentRotation method), 247
pseudoinverse() (menpo.transform.AlignmentSimilarity method), 242
pseudoinverse() (menpo.transform.AlignmentTranslation method), 251
pseudoinverse() (menpo.transform.AlignmentUniformScale method), 255
pseudoinverse() (menpo.transform.base.invertible.Invertible method), 267
pseudoinverse() (menpo.transform.base.invertible.VInvertible method), 269
pseudoinverse() (menpo.transform.Homogeneous method), 209
pseudoinverse() (menpo.transform.NonUniformScale method), 231
pseudoinverse() (menpo.transform.Rotation method), 221
pseudoinverse() (menpo.transform.Similarity method), 217
pseudoinverse() (menpo.transform.ThinPlateSplines method), 234
pseudoinverse() (menpo.transform.Translation method), 224
pseudoinverse() (menpo.transform.UniformScale method), 228
pseudoinverse_vector() (menpo.transform.Affine method), 213
pseudoinverse_vector() (menpo.transform.AlignmentAffine method), 238
pseudoinverse_vector() (menpo.transform.AlignmentRotation method), 247
pseudoinverse_vector() (menpo.transform.AlignmentSimilarity method), 242
pseudoinverse_vector() (menpo.transform.AlignmentTranslation method), 251
pseudoinverse_vector() (menpo.transform.AlignmentUniformScale method), 255
pseudoinverse_vector() (menpo.transform.base.invertible.VInvertible method), 269
pseudoinverse_vector() (menpo.transform.Homogeneous method), 209
pseudoinverse_vector() (menpo.transform.NonUniformScale method), 232
pseudoinverse_vector() (menpo.transform.Rotation method), 221
pseudoinverse_vector() (menpo.transform.Similarity method), 217

pseudoinverse_vector() (menpo.transform.Translation method), 224
pseudoinverse_vector() (menpo.transform.UniformScale method), 228
pyramid() (menpo.image.BooleanImage method), 49
pyramid() (menpo.image.Image method), 36
pyramid() (menpo.image.MaskedImage method), 66

R

R2LogR2RBF (class in menpo.transform), 259
R2LogRRBF (class in menpo.transform), 261
range() (menpo.shape.ColouredTriMesh method), 195
range() (menpo.shape.PointCloud method), 124
range() (menpo.shape.PointDirectedGraph method), 165
range() (menpo.shape.PointTree method), 177
range() (menpo.shape.PointUndirectedGraph method), 153
range() (menpo.shape.TexturedTriMesh method), 204
range() (menpo.shape.TriMesh method), 186
reconstruct() (menpo.model.InstanceLinearModel method), 102
reconstruct() (menpo.model.MeanInstanceLinearModel method), 107
reconstruct() (menpo.model.PCAModel method), 115
reconstruct_vector() (menpo.model.InstanceLinearModel method), 102
reconstruct_vector() (menpo.model.LinearModel method), 100
reconstruct_vector() (menpo.model.MeanInstanceLinearModel method), 107
reconstruct_vector() (menpo.model.MeanLinearModel method), 104
reconstruct_vector() (menpo.model.PCAModel method), 116
reconstruct_vectors() (menpo.model.InstanceLinearModel method), 102
reconstruct_vectors() (menpo.model.LinearModel method), 100
reconstruct_vectors() (menpo.model.MeanInstanceLinearModel method), 107
reconstruct_vectors() (menpo.model.MeanLinearModel method), 104
reconstruct_vectors() (menpo.model.PCAModel method), 116
relative_location_edge() (menpo.shape.PointDirectedGraph method), 165
relative_location_edge() (menpo.shape.PointTree method), 177
relative_locations() (menpo.shape.PointDirectedGraph method), 166
relative_locations() (menpo.shape.PointTree method), 178
remove_render_function() (menpo.visualize.widgets.AnimationOptionsWidget method), 278
remove_render_function() (menpo.visualize.widgets.ChannelOptionsWidget method), 282
remove_render_function() (menpo.visualize.widgets.GraphOptionsWidget method), 297
remove_render_function() (menpo.visualize.widgets.LandmarkOptionsWidget method), 285
remove_render_function() (menpo.visualize.widgets.RendererOptionsWidget method), 292
remove_update_function() (menpo.visualize.widgets.AnimationOptionsWidget method), 278
remove_update_function() (menpo.visualize.widgets.LandmarkOptionsWidget method), 285
render() (menpo.visualize.MatplotlibRenderer method), 271
render() (menpo.visualize.Renderer method), 270
Renderer (class in menpo.visualize), 270
RendererOptionsWidget (class in menpo.visualize.widgets), 287
replace_render_function() (menpo.visualize.widgets.AnimationOptionsWidget method), 279
replace_render_function() (menpo.visualize.widgets.ChannelOptionsWidget method), 282
replace_render_function() (menpo.visualize.widgets.GraphOptionsWidget method), 297
replace_render_function() (menpo.visualize.widgets.LandmarkOptionsWidget method), 285
replace_render_function() (menpo.visualize.widgets.RendererOptionsWidget method), 292
replace_update_function() (menpo.visualize.widgets.AnimationOptionsWidget method), 279
replace_update_function() (menpo.visualize.widgets.LandmarkOptionsWidget method), 285
rescale() (menpo.image.BooleanImage method), 49
rescale() (menpo.image.Image method), 36
rescale() (menpo.image.MaskedImage method), 67
rescale_landmarks_to_diagonal_range() (menpo.image.BooleanImage method), 50
rescale_landmarks_to_diagonal_range() (menpo.image.Image method), 37

rescale_landmarks_to_diagonal_range() (menpo.image.MaskedImage method), 67
rescale_pixels() (menpo.image.BooleanImage method), 50
rescale_pixels() (menpo.image.Image method), 37
rescale_pixels() (menpo.image.MaskedImage method), 67
rescale_to_diagonal() (menpo.image.BooleanImage method), 50
rescale_to_diagonal() (menpo.image.Image method), 38
rescale_to_diagonal() (menpo.image.MaskedImage method), 68
rescale_to_reference_shape() (menpo.image.BooleanImage method), 51
rescale_to_reference_shape() (menpo.image.Image method), 38
rescale_to_reference_shape() (menpo.image.MaskedImage method), 68
resize() (menpo.image.BooleanImage method), 51
resize() (menpo.image.Image method), 38
resize() (menpo.image.MaskedImage method), 68
rolled_channels() (menpo.image.BooleanImage method), 51
rolled_channels() (menpo.image.Image method), 38
rolled_channels() (menpo.image.MaskedImage method), 69
rotate_ccw_about_centre() (menpo.image.BooleanImage method), 51
rotate_ccw_about_centre() (menpo.image.Image method), 39
rotate_ccw_about_centre() (menpo.image.MaskedImage method), 69
Rotation (class in menpo.transform), 218
rotation_matrix (menpo.transform.AlignmentRotation attribute), 248
rotation_matrix (menpo.transform.Rotation attribute), 222

S

sample() (menpo.image.BooleanImage method), 52
sample() (menpo.image.Image method), 39
sample() (menpo.image.MaskedImage method), 69
save_figure() (menpo.visualize.MatplotlibRenderer method), 271
save_figure() (menpo.visualize.Renderer method), 270
save_figure_widget() (menpo.visualize.MatplotlibRenderer method), 272
save_matplotlib_figure() (in module menpo.visualize), 274
SaveFigureOptionsWidget (class in menpo.visualize.widgets), 299
scale (menpo.transform.AlignmentUniformScale attribute), 256
scale (menpo.transform.NonUniformScale attribute), 233
scale (menpo.transform.UniformScale attribute), 229
Scale() (in module menpo.transform), 225
set_boundary_pixels() (menpo.image.MaskedImage method), 69
set_h_matrix() (menpo.transform.Affine method), 213
set_h_matrix() (menpo.transform.AlignmentAffine method), 238
set_h_matrix() (menpo.transform.AlignmentRotation method), 247
set_h_matrix() (menpo.transform.AlignmentSimilarity method), 243
set_h_matrix() (menpo.transform.AlignmentTranslation method), 251
set_h_matrix() (menpo.transform.AlignmentUniformScale method), 255
set_h_matrix() (menpo.transform.Homogeneous method), 209
set_h_matrix() (menpo.transform.NonUniformScale method), 232
set_h_matrix() (menpo.transform.Rotation method), 221
set_h_matrix() (menpo.transform.Similarity method), 217
set_h_matrix() (menpo.transform.Translation method), 224
set_h_matrix() (menpo.transform.UniformScale method), 228
set_masked_pixels() (menpo.image.MaskedImage method), 70
set_rotation_matrix() (menpo.transform.AlignmentRotation method), 247
set_rotation_matrix() (menpo.transform.Rotation method), 221
set_target() (menpo.base.Targetable method), 21
set_target() (menpo.transform.AlignmentAffine method), 238
set_target() (menpo.transform.AlignmentRotation method), 247
set_target() (menpo.transform.AlignmentSimilarity method), 243
set_target() (menpo.transform.AlignmentTranslation method), 251
set_target() (menpo.transform.AlignmentUniformScale method), 255
set_target() (menpo.transform.base.alignment.Alignment method), 268
set_target() (menpo.transform.ThinPlateSplines method), 234
set_widget_state() (menpo.visualize.widgets.AnimationOptionsWidget method), 279
set_widget_state() (menpo.visualize.widgets.ChannelOptionsWidget method), 282
set_widget_state() (menpo.visualize.widgets.LandmarkOptionsWidget method), 285

set_widget_state() (menpo.visualize.widgets.RendererOptionsWidget method), 292
set_widget_state() (menpo.visualize.widgets.TextPrintWidget method), 302
setdefault() (menpo.landmark.LandmarkGroup method), 82
setdefault() (menpo.landmark.LandmarkManager method), 80
Shape (class in menpo.shape.base), 117
shape (menpo.image.BooleanImage attribute), 54
shape (menpo.image.Image attribute), 41
shape (menpo.image.MaskedImage attribute), 72
Similarity (class in menpo.transform), 214
source (menpo.transform.AlignmentAffine attribute), 239
source (menpo.transform.AlignmentRotation attribute), 248
source (menpo.transform.AlignmentSimilarity attribute), 244
source (menpo.transform.AlignmentTranslation attribute), 252
source (menpo.transform.AlignmentUniformScale attribute), 256
source (menpo.transform.base.alignment.Alignment attribute), 268
source (menpo.transform.ThinPlateSplines attribute), 235
stickmen_pose() (in module menpo.landmark), 89
streetscene_car_view_0() (in module menpo.landmark), 91
streetscene_car_view_1() (in module menpo.landmark), 91
streetscene_car_view_2() (in module menpo.landmark), 91
streetscene_car_view_3() (in module menpo.landmark), 92
streetscene_car_view_4() (in module menpo.landmark), 92
streetscene_car_view_5() (in module menpo.landmark), 93
streetscene_car_view_6() (in module menpo.landmark), 93
streetscene_car_view_7() (in module menpo.landmark), 93
style() (menpo.visualize.widgets.AnimationOptionsWidget method), 279
style() (menpo.visualize.widgets.ChannelOptionsWidget method), 282
style() (menpo.visualize.widgets.GraphOptionsWidget method), 297
style() (menpo.visualize.widgets.LandmarkOptionsWidget method), 286
style() (menpo.visualize.widgets.RendererOptionsWidget method), 293
style() (menpo.visualize.widgets.SaveFigureOptionsWidget method), 300
style() (menpo.visualize.widgets.TextPrintWidget method), 302
sum_channels() (in module menpo.feature.visualize), 78

T

target (menpo.base.Targetable attribute), 21
target (menpo.transform.AlignmentAffine attribute), 239
target (menpo.transform.AlignmentRotation attribute), 248
target (menpo.transform.AlignmentSimilarity attribute), 244
target (menpo.transform.AlignmentTranslation attribute), 252
target (menpo.transform.AlignmentUniformScale attribute), 256
target (menpo.transform.base.alignment.Alignment attribute), 268
target (menpo.transform.ThinPlateSplines attribute), 235
Targetable (class in menpo.base), 20
tcoords_pixel_scaled() (menpo.shape.TexturedTriMesh method), 204
TextPrintWidget (class in menpo.visualize.widgets), 301
TexturedTriMesh (class in menpo.shape), 197
ThinPlateSplines (class in menpo.transform), 233
tojson() (menpo.landmark.LandmarkGroup method), 82
tojson() (menpo.shape.ColouredTriMesh method), 195
tojson() (menpo.shape.PointCloud method), 124
tojson() (menpo.shape.PointDirectedGraph method), 166
tojson() (menpo.shape.PointTree method), 178
tojson() (menpo.shape.PointUndirectedGraph method), 153
tojson() (menpo.shape.TexturedTriMesh method), 205
tojson() (menpo.shape.TriMesh method), 186
Transform (class in menpo.transform), 262
Transformable (class in menpo.transform.base), 264
TransformChain (class in menpo.transform), 257
Translation (class in menpo.transform), 222
translation_component (menpo.transform.Affine attribute), 214
translation_component (menpo.transform.AlignmentAffine attribute), 239
translation_component (menpo.transform.AlignmentRotation attribute), 248
translation_component (menpo.transform.AlignmentSimilarity attribute), 244
translation_component (menpo.transform.AlignmentTranslation attribute), 252
translation_component (menpo.transform.AlignmentUniformScale attribute), 256
translation_component (menpo.transform.NonUniformScale attribute), 233
translation_component (menpo.transform.Rotation attribute), 222

translation_component (menpo.transform.Similarity attribute), 218
translation_component (menpo.transform.Translation attribute), 225
translation_component (menpo.transform.UniformScale attribute), 229
Tree (class in menpo.shape), 136
tri_areas() (menpo.shape.ColouredTriMesh method), 195
tri_areas() (menpo.shape.TexturedTriMesh method), 205
tri_areas() (menpo.shape.TriMesh method), 186
tri_normals() (menpo.shape.ColouredTriMesh method), 195
tri_normals() (menpo.shape.TexturedTriMesh method), 205
tri_normals() (menpo.shape.TriMesh method), 186
trim_components() (menpo.model.PCAModel method), 116
TriMesh (class in menpo.shape), 179
true_indices() (menpo.image.BooleanImage method), 52

U

UndirectedGraph (class in menpo.shape), 125
UniformScale (class in menpo.transform), 226
unique_edge_indicies() (menpo.shape.ColouredTriMesh method), 196
unique_edge_indicies() (menpo.shape.TexturedTriMesh method), 205
unique_edge_indicies() (menpo.shape.TriMesh method), 187
unique_edge_lengths() (menpo.shape.ColouredTriMesh method), 196
unique_edge_lengths() (menpo.shape.TexturedTriMesh method), 205
unique_edge_lengths() (menpo.shape.TriMesh method), 187
unique_edge_vectors() (menpo.shape.ColouredTriMesh method), 196
unique_edge_vectors() (menpo.shape.TexturedTriMesh method), 205
unique_edge_vectors() (menpo.shape.TriMesh method), 187
update() (menpo.landmark.LandmarkGroup method), 82
update() (menpo.landmark.LandmarkManager method), 80
update_object_names() (menpo.visualize.widgets.RendererOptionsWidget method), 294

V

values() (menpo.landmark.LandmarkGroup method), 82
values() (menpo.landmark.LandmarkManager method), 80
variance() (menpo.model.PCAModel method), 116
variance_ratio() (menpo.model.PCAModel method), 116
VComposable (class in menpo.transform.base.composable), 269
Vectorizable (class in menpo.base), 19
vertex_normals() (menpo.shape.ColouredTriMesh method), 196
vertex_normals() (menpo.shape.TexturedTriMesh method), 205
vertex_normals() (menpo.shape.TriMesh method), 187
vertices (menpo.shape.DirectedGraph attribute), 135
vertices (menpo.shape.PointDirectedGraph attribute), 166
vertices (menpo.shape.PointTree attribute), 179
vertices (menpo.shape.PointUndirectedGraph attribute), 154
vertices (menpo.shape.Tree attribute), 141
vertices (menpo.shape.UndirectedGraph attribute), 130
vertices_at_depth() (menpo.shape.PointTree method), 178
vertices_at_depth() (menpo.shape.Tree method), 141
view_widget() (menpo.image.BooleanImage method), 52
view_widget() (menpo.image.Image method), 39
view_widget() (menpo.image.MaskedImage method), 70
view_widget() (menpo.landmark.LandmarkGroup method), 82
view_widget() (menpo.landmark.LandmarkManager method), 80
view_widget() (menpo.shape.ColouredTriMesh method), 196
view_widget() (menpo.shape.PointCloud method), 124
view_widget() (menpo.shape.PointDirectedGraph method), 166
view_widget() (menpo.shape.PointTree method), 178
view_widget() (menpo.shape.PointUndirectedGraph method), 153
view_widget() (menpo.shape.TexturedTriMesh method), 205
view_widget() (menpo.shape.TriMesh method), 187
Viewable (class in menpo.visualize), 270
VInvertible (class in menpo.transform.base.invertible), 269
visualize_images() (in module menpo.visualize), 272
visualize_landmarkgroups() (in module menpo.visualize), 273
visualize_landmarks() (in module menpo.visualize), 272
visualize_pointclouds() (in module menpo.visualize), 273

W

warp_to_mask() (menpo.image.BooleanImage method), 52
warp_to_mask() (menpo.image.Image method), 39
warp_to_mask() (menpo.image.MaskedImage method), 70
warp_to_shape() (menpo.image.BooleanImage method), 53
warp_to_shape() (menpo.image.Image method), 40

warp_to_shape() (menpo.image.MaskedImage method), 71
whitened_components() (menpo.model.PCAModel method), 116
width (menpo.image.BooleanImage attribute), 54
width (menpo.image.Image attribute), 41
width (menpo.image.MaskedImage attribute), 72
with_labels() (menpo.landmark.LandmarkGroup method), 82
without_labels() (menpo.landmark.LandmarkGroup method), 82

Z

zoom() (menpo.image.BooleanImage method), 53
zoom() (menpo.image.Image method), 40
zoom() (menpo.image.MaskedImage method), 71